

DÉTECTION DES RADIATIONS

Table of contents

Moniteurs de zone	13
SE International	13
AM-2x2 Contrôleur de zone de rayonnement	15
AM-71313 Contrôleur de zone de rayonnement	16
AM-7128 Contrôleur de zone de rayonnement	17
AM-1X1 Contrôleur de zone de rayonnement	18
Ludlum Measurements	18
Modèle 375 Contrôleur d'ambiance	21
Modèle 375/1 Moniteur numérique de surface	22
Model 375/2 Digital Area Monitor - Ludlum	23
Model 375/4 Gamma Area Monitor - Ludlum	24
Model 375-10 Digital Area Monitor - Ludlum	25
Model 375-9 Digital Area Monitor - Ludlum	26
Model 375-Dual Digital Area Monitor - Ludlum	27
Model 375-20 Monitoring System	28
Model 375-30	29
Model 375/31H	30
Model 3276 - Area Monitor Controller	32
Model 3277/1 Alpha-Beta Frisker	34
Model 375P-1000	35
Model 375P-2000	36
Model 375P-336 Series	37
Model 240 Series Alpha-Beta Floor and Wall Monitor	38
Model 3002/FM Series Alpha-Beta Floor Monitor	40
Model 239-1F Series Alpha-Beta Floor Contamination Monitor	41
Model 375P-336 Surface Contamination Monitor - Ludlum	42
Moniteurs portables	43
BSI	43
Hand-held Integrated Gamma Spectrometer	45
Ludlum Measurements	45
Model 26 - Frisker with Geiger Mueller Pancake	50
Model 26-1 Frisker with integrated GM Pancake - Ludlum	52
Model 26-3 - High Range Frisker	54
Model 26S - Integrated Scintillator Frisker	56
Model 3000 Digital Survey Meter - Ludlum	57
Model 3001 Multi-Detector Survey Meter - Ludlum	59
Model 3002 Alpha-Beta Digital Survey Meter	60
Model 3003 Series Multi-Detector Ratemeter / SCA	61
Model 3014 Dual-Detector Digital Survey Meter / SCA	63
Model 9DP Pressurized Ion Chamber	64
Model 9DP-1 Pressurized Ion Chamber	67
Model 9DP* Ambient Dose Ion Chamber	69

Model 9DP-1* Ambient Dose Ion Chamber	71
Model 3-IS-1 Intrinsically Safe Gamma Ratemeter	73
Model 3-IS Intrinsically Safe Survey Meter	74
Model 12-4 Neutron Dose Survey Meter	75
Model 30-4 Digital Neutron Survey Meter	76
Model 12-4-7 Neutron Dose Survey Meter	77
Model 3007 Series Neutron Dose Survey Meter With Optional Internal Gamma Detector	78
Model 30-7 Series Lightweight Digital Neutron Survey Meter	80
Model 12 General Purpose Survey Meter	81
Model 14C General Purpose Survey Meter	82
Model 16 General Purpose Survey Meter	83
Model 18 General Purpose Survey Meter	84
Model 3 General Purpose Survey Meter	85
Model 3A General Purpose Survey Meter with Alarm	86
Model 3-97 Gamma Survey Meter	87
Model 195 with Model 43-132 High Range Alpha Ion Chamber	88
Model 3-98 125I & Alpha-Beta-Gamma Survey Meter	89
Model 194 Dose Equivalent Rate Meter	90
Model 2403 Pocket-Size Survey Meter	91
Model 2402 Pocket-Size Survey Meter with Alarm	92
Model 35 Vehicle-Mounted Digital Survey Meter	93
Model 30 Digital Survey Meter - Ludlum	94
Model 44-9 Pancake GM Detector - Ludlum	95
Model 3001-MERK response kit	96
Model 3001-2RK Emergency Response & NORM Kit	97
Model 2241-3RK2 Emergency Response Kit	98
Model 26-2 - Integrated Frisker with Timed Frisk	99
Model 3019 Digital Background Survey Meter - Ludlum	100
Model 133-6 GM Detector - Ludlum	101
Model 133-4 GM Detector - Ludlum	102
Model 133-2 GM Detector - Ludlum	103
Model 44-3 NAL Low Energy Gamma Scintillator - Ludlum	104
Model 44-2 NAL Gamma Scintillator - Ludlum	105
Model 44-1 Beta Scintillator - Ludlum	106
Model 44-38 Energy Compensated GM Detector - Ludlum	107
Model 44-9 Ambient Dose Equivalent Filter - Ludlum	108
Model 44-9 Exposure Filter Kit - Ludlum	109
Model 44-7 Alpha Beta Gamma Detector - Ludlum	110
Model 43-92 Alpha Scintillator - Ludlum	111
Model 43-65 Alpha Scintillator - Ludlum	112
Model 43-5 Alpha Scintillator - Ludlum	113
Model 9DP Ambient Dose Ion Chamber Survey Meter - Ludlum	114
Model 9DP-1 Ion Chamber Survey Meter - Ludlum	116
Tracerco	117
Contamination Monitor T401 - Tracerco	119
Dose Rate Monitor T402 & T402HR - Tracerco	120
Contamination Monitor T403 - Tracerco	121
T406 X-ray Monitor	122
Intrinsically Safe Radiation Dose Rate Monitor (T202) Tracerco™	123
NORM Monitor-IS - Tracerco	124

Polimaster	124
PM1401K-3M Multipurpose Hand-Held Radiation Monitor/Identifier	126
PM1401K-3P Multipurpose Hand-Held Radiation Monitor/Identifier	127
PoliPack® G-S Backpack Radiation Detector	128
PoliPack® GN Backpack Radiation Detector	129
PoliPack® G Backpack Radiation Detector	130
PoliPack® GN-S Backpack Radiation Detector	131
Bertin Instruments	131
MINITRACE CSDF – Bertin Instruments	133
MiniTRACE S5 – Saphymo	136
MiniTRACE γ	137
SaphyRAD S	138
SaphyRAD C	139
AlphaE – Bertin Instruments	140
SaphyRAD E Multiprobe – Bertin Instruments	141
SaphyRAD MS Dom-420 – Bertin Instruments	142
SE International	142
Radiation Alert Monitor 200	145
Radiation Alert MC1K	146
Radiation Alert Frisker	147
Radiation Alert Ranger	148
Radiation Alert Monitor 4EC	150
Radiation Alert® Ranger EXP	151
Radiation Alert Monitor 1000EC	153
Radiation Alert® GammaView	155
Radiation Alert Monitor 4	156
GEORADIS s.r.o.	156
RT-20 Compact handheld Radiation Detector – Georadis	158
RT-21 Handheld Radiation Detector – Georadis	159
RT-22 Handheld Radiation Detector with GeoView Software – Georadis	160
RT-30 Mk II – Georadis	161
Kromek	162
D5 RIID	164
D3S ID	165
RayMon 10	166
Radiation Solutions Inc.	166
RS-230 BGO Handheld Spectrometer – Radiation Solutions	168
RS-125 Handheld Spectrometer – Radiation Solutions	169
RS-125 Handheld Spectrometer – Radiation Solutions	170
Dosimètres électroniques personnels	171
Tracerco	171
PED2 (Personal Electronic Dosimeter) – Tracerco	173
PED2 – ER (Personal Electronic Dosimeter) – Tracerco	176
PED2-IS (Personal Electronic Dosimeter) – Tracerco	177
PED-Blue (Personal Electronic Dosimeter) – Tracerco	178
PED+ (Personal Electronic Dosimeter) – Tracerco	180
PED-ER (Personal Electronic Dosimeter) – Tracerco	181
PED-ER+ (Personal Electronic Dosimeter) – Tracerco	183
Dosimeter software DoseVision™ and DoseVision™ Tracerco	184

Polimaster	184
PM1703GNA-II MBT Personal Radiation Detector/Dosimeter	187
PM1703GNA-II/BT Personal Radiation Detector	188
PM1703MO-II BT Personal Radiation Detector/Dosimeter	189
PM1703MA-II/BT Personal Radiation Detector	190
PM1610B X-Ray and Gamma Radiation Personal Dosimeter	191
PM1610 X-Ray and Gamma Radiation Personal Dosimeter	192
PM1605BT Personal Radiation Monitor/Dosimeter	193
PoliSimeter™ ERB Electronic Personal Dosimeter	194
PoliSimeter™ ER Electronic Personal Dosimeter	195
PoliSimeter™ Electronic Personal Dosimeter	196
RadFlash® Electronic Personal Dosimeter	197
Bertin Instruments	197
Saphydose gamma i	199
SE International	199
Radiation Alert® Sentry EC	201
Rad-60 Alarming Dosimeter	202
Ludlum Measurements	202
Model 23-1 Electronic Personal Dosimeter – Ludlum	204
Caméras CZT et Gamma	205
BSI	205
Hand-held Integrated Gamma Spectrometer	207
3D Plus	207
Spid-X	209
Kromek	209
GR Series Gamma Spectrometers	211
Quant GR1	213
TN15	214
Sigma 25/50	215
RayMon 10	216
K102	217
Identificateurs d'isotopes portables	218
BSI	218
Hand-held Integrated Gamma Spectrometer	220
Else Nuclear	220
B-RAD	222
FOOMON	223
THYMON	224
HERMES GSU	225
Kromek	225
GR Series Gamma Spectrometers	227
D5 RIID	229
D3S ID	230
RayMon 10	231
AARM	232
Polimaster	232
PM1401K-3M Multipurpose Hand-Held Radiation Monitor/Identifier	234
PM1401K-3P Multipurpose Hand-Held Radiation Monitor/Identifier	235

GEORADIS s.r.o.	235
RT-30 Gamma-Ray Spectrometer with Nuclide ID Capability – Georadis	237
Surveillance Environnementale	238
Else Nuclear	238
GSU – GAMMA SPECTROMETRY UNIT WITH NaI(Tl)	241
SP2 – SINGLE-SPHERE NEUTRON SPECTROMETER	242
LUPIN BF3	243
SATURN I, SATURN II	244
SATURN 5702	245
NAUSICAA IC-T, ICP-T	246
GM-1, MERCURY	247
NAUSICAA 2IC	248
MISTRAL XM	249
HERMES	250
FOOMON	251
THYMON	252
HERMES GSU	253
BSI	253
Gamma analysis software SpectraLineGP	256
Calibration software EffMaker	257
Calibration software MCC-MT	259
Nuclide Master Plus	260
Quality Assurance package	261
Alpha analysis software SpectraLineADA	262
AirTrack Aerosol Monitoring Station	263
AirTrack-i Iodine Monitoring Station	264
WaterTrack Online Water Monitoring Station	265
Spectrometer WaterSPEC	266
Spectrometer AirSPEC	267
Mobile Radiation Monitor GammaCART	268
Alpha analysis software AlphaPRO	269
SpectraLineGIS software package	270
Gamma analysis software GammaPRO	271
Radiation Analysis and Visualization Environment Network RAVEN software	272
Hybrid cooling for the HPGe detector Nicole	274
Bertin Instruments	274
GammaTRACER Spider Autonomous Gamma Monitor for Emergencies – Saphymo	277
AlphaGUARD-Radon Monitor – Bertin Instruments	278
ShortLINK Short-Range Environmental Radiation Monitoring Network – Bertin/ Saphymo	280
GammaTRACER Autonomous Radiation Monitoring Probe – Saphymo	281
BAB E Air Monitoring Beacon	284
SkyLINK Wide-Range Environmental Radiation Monitoring Network – Bertin/ Saphymo	285
AlphaE – Bertin Instruments	286
SpectroTRACER Environmental Radiation Monitor – Saphymo	287
Skydose Dosimetry System – Bertin Instruments	288
Coriolis RECON – Bertin Instruments	290
Coriolis Micro – Bertin Instruments	291
Ludlum Measurements	291
Model 3101 Portable Tritium in Air Monitor	293

Model 334AB-G Alpha-Beta Particulate Monitor	295
Model 334A Alpha Air Monitor	297
Model 3100 Portable Tritium in Air Monitor	299
SDEC France	299
AM 3000 N - Air Sampler for Asbestos Diagnosis in Nuclear Environments - NF43-050 version 2021 , NF X43-269, NF EN ISO 13137	301
AM 3000 - Air Sampler for Asbestos Diagnosis - NF43-050 version 2021, NF X43-269, NF EN ISO 13137	302
Battery Operated Field Electric Vacuum Pump PAV 2000 : For soil sampling	303
AS 5000 Aerosol & Iodine Sampler - SDEC	304
AS 3000 AEROSOL & IODINE SAMPLER - SDEC	305
GEORADIS s.r.o.	305
GT-40 Gamma Ray Spectrometer	307
Centronic Nuclear	308
Alpha, Beta & Gamma Detectors - Centronic	310
Beta & Gamma Detectors - Centronic	311
Ultra Electronics	311
CMS Gamma - Lab Impex	313
HPGE portable	314
BSI	314
MONOLITH Gamma & X-ray HPGe Spectrometer	316
HPGe Spectrometer with Lead Shield	317
Portable HPGe Gamma- & X-ray Spectrometer	318
Robotic Gamma Spectrometer	319
Ultra Low-background HPGe Detectors	321
PHDS	321
GeGI: Imaging HPGe Detector	323
NP Radiochemistry Imager	324
Fulcrum: HPGe Detector	325
Fulcrum-40h: 40% HPGe Detector	326
LoPro HPGe Detector	327
Autre	327
Spectromètre d'analyse rapide par activation neutronique gamma (PGNAA)	329
Équipement de laboratoire	330
BSI	330
Gamma analysis software GammaPRO	333
MONOLITH Gamma & X-ray HPGe Spectrometer	334
HPGe Spectrometer with Lead Shield	335
Hybrid cooling for the HPGe detector Nicole	336
Robotic Gamma Spectrometer	337
HPGe Spectrometer with Shield	339
Flowing HPGe Spectrometer	341
HPGe Infrared Detectors	342
Ultra Low-background HPGe Detectors	343
LN2 storage and transfer system	344
Multi Channel Analyzer BOSON	345
Digital Miniature Multi Channel Analyzer MCA 527	346
Quality Assurance package	347

Free Release Monitor HERCULES-FRM	348
Gamma-, beta- and alpha- spectrometer-radiometer TRIO	350
Else Nuclear	350
BSS – BONNER SPHERE SPECTROMETER	352
SP2 – SINGLE-SPHERE NEUTRON SPECTROMETER	353
W-PIE – WIDE ENERGY ACTIVE NEUTRON SPECTROMETER	354
GSU – GAMMA SPECTROMETRY UNIT WITH NaI(Tl)	355
SATURN I, SATURN II	356
WDMS NT-VK	357
LEM – LIQUID EFFLUENT MONITORING SYSTEM	358
Ludlum Measurements	358
Model 3030E Alpha-Beta Scaler	361
Model 2000 General Purpose Scaler	362
Model 2200 Scaler-Ratemeter	363
Model 2100-1 Sample Counter	364
Model 2100 Conveyorized Sample Counter	365
Model 3030E with 43-10-1 Alpha-Beta Sample Counter	366
Model 3030-2 Simultaneous Alpha-Beta Sample Counter	367
Model 3030 Alpha-Beta Sample Counter	368
Model 3030P Alpha-Beta Sample Counter	369
Probes (Ludlum)	370
SDEC France	370
EDP 9002 – Double Mast Electrodeposition Equipment	373
PRC 14: Maintenance Pump – For Cleaning Pipes for HAGUE 7000 CARBON 14 Bubbler	374
MARC 7000 – Tritium Bubbler: Atmospheric Monitoring System with 4 Pots (With Oven)	375
Aerosol and Iodine Sampling Heads	376
AS 5000 Portable Aerosol & Iodine Sampler DPRC Type for Air Flow Regulation – Maintenance-Free Design	377
EDP 7000 – Electrodeposition Equipment – Monostation	378
DPM 7001 Liquid Scintillation Counter – SDEC	379
H3R 7000 Airborne Tritium Condenser – SDEC	380
Single Mast Electrodeposition Equipment – EDP 7000 – SDEC	381
Tritium sampler 4 vials MARC 7000 – SDEC	382
Spectrum Techniques	382
Advanced Spectroscopy System	384
SCINTILLATION WELL COUNTING SYSTEM	385
Intermediate Nuclear Laboratory System	386
GEORADIS s.r.o.	386
RT-50 Laboratory Gamma-Ray Spectrometer – Georadis	388
Kromek	388
Quant GR1	390
Ultra Electronics	390
CMS Iodine Monitor – Lab Impex Systems	392
Simulateurs de formation	393
Argon Electronics	393
RADSIM 44-9-SIM Radiation Safety Training Probe Simulator	397
PlumeSIM®	398
PlumeSIM-SMART	399
RS340 Back Pack	400

UDR-13 & UDR-14 SIM	401
Radsim DS3 Mini 900	402
Nuvia CoMo 170 Contamination Training Simulator	403
AN/PDR 77 APLHA & BETA SIM PROBES	404
GMP-11 Radiation Safety Training Simulator Probe	405
M4A1 JCAD Chemical Hazard Detection Simulator	406
6150AD-K Contamination Simulator	407
RADSIM GS4	408
MultiGAS SIM	409
RDS Beta Photon Probe Simulator	410
Ludlum 133-6 and 44-2 Radiation Simulation Probes	411
RDS-100 / PDR-77 / CDV 718 SIM Probes	412
AN/VDR 2 DT616-SIM Radiation Safety Training Simulator	413
ADM300A-SIM Radiation Training Simulator	414
GID-3 Chemical Warfare Detection Simulator	415
MCAD-SIM Chemical Warfare Detection Simulator	416
CAMSIM Chemical Hazard Detection Simulator	417
AccuRad PRD Simulator	418
Nuvia DoImo Radiation Hazard Detection Simulator	419
HRM Radiation Hazard Simulator	420
SP4E Chemical Hazard Detection Simulator	421
AP4C-SIM Chemical Detector Simulator	422
D-tect SYSTEMS RDS Radiation Training Simulator	423
SVG-2 Radiation Hazard Detection Simulator	424
RadEye GF-10 SIM	425
RADSIM-SS3	427
LCD3.3-SIM Chemical Hazard Detection Simulator	428
FH 40 GSIM Survey Meter Simulator	429
Raid-100M Training Simulator	430
Dräger X-am Series Simulator	431
Tracerco PED+ Simulator	432

Moniteurs corporels 435

Ludlum Measurements	435
Model 215 Alpha Frisker Station	438
Model 177HFM Low Cost Hand & Foot Monitor	439
Model HFC-8 Hand, Foot, and Clothing Monitor	440
Model 4906P Alpha-Beta-Gamma Hand & Foot Monitor	441
Model 4906AB Alpha-Beta Hand & Foot Monitor	442
Model 4906A Alpha Hand & Foot Monitor	443
Model 4901P Beta-Gamma Hand & Foot Monitor	444
Model 3276HFM Low Cost Hand & Foot Monitor	445
Model 3277HFM Compact Alpha-Beta Hand & Foot Monitor	446
Model 53 Gamma Portal Monitor	448
Model 52-1, 52-5 & 52-6 Series Portable Portal Monitors	449
Model 52 Portable Portal Monitor	451
Model HBP-22 Body Contamination Monitor	453
Model HBP-29 Body Contamination Monitor	454
Model 375P-1000 Outdoor Radiation Contamination Monitor – Ludlum	455
Helgeson Scientific Services (HSS)	455

HS-BEXA – Alpha Beta hand feet monitor	457
HS-BEX – Beta gamma hand feet monitor	458
DIYS – Bed type whole body counter for internal dosimetry	459
HS-ABOMO – Alpha beta gamma portal for personnel monitoring	460
HS-BOMO – Beta gamma portal for personnel monitoring	461
HS-RAM – Gamma portal for personnel monitoring	462
QUICKY – Whole body counter for internal dosimetry	463
Moniteurs de portail	464
Polimaster	464
Poligate Light G1 RPM	467
PoliGate™ Vehicle G4 RPM	468
PoliGate™ Pedestrian G1 RPM	469
PoliGate™ Pedestrian GN2 RPM	470
Poligate Light G2 RPM	471
Poligate Light G4 RPM	472
Poligate Pedestrian GN1 RPM	473
Poligate Deployable RPM	474
Poligate Pedestrian G2 RPM	475
Poligate Vehicle G4N4 RPM	476
Poligate Vehicle G2 RPM	477
Radiation Solutions Inc.	477
RS-200 / 3000 Radiation Portal Monitoring Systems (Radiation Solutions)	479
RS-200 / 6000 Radiation Portal Monitoring Systems (Radiation Solutions)	481
RS-200 / 10000 Radiation Portal Monitoring Systems (Radiation Solutions)	483
RS-300 Radiation Portal Monitoring Systems (Radiation Solutions)	485
RS-400 Radiation Portal Monitoring Systems (Radiation Solutions)	487
Ludlum Measurements	488
Model 4525 Series Radiation Portal Monitor	490
Model 4525-5000 Radiation Portal Monitor – Ludlum	492
Model 4525-7000 Radiation Portal Monitor – Ludlum	493
Model 4530 Series Radiation Portal Monitor	494
Model 375P-3500 Conveyor Monitor – Ludlum	496
Model 52-8 Series Outdoor Portal Monitor	497
Helgeson Scientific Services (HSS)	497
HS-VGAM – Portal vehicle for scrap yards	499
HS-PORT – Portable Gamma Portal monitor for personnel and vehicles	500
HS-PoNaI	501
Systèmes de détection mobile des rayonnements	502
Else Nuclear	502
SATURN 5702	504
Polimaster	504
PoliGate™ Mobile MDS	506
PoliPack® G-S Backpack Radiation Detector	507
PoliPack® GN Backpack Radiation Detector	508
PoliPack® G Backpack Radiation Detector	509
PoliPack® GN-S Backpack Radiation Detector	510
Équipement de radioprotection	511

RADsafe	511
Comfortwear Aprons	513
Urology Aprons	514
Surgical Drop-Away Aprons	515
Maternity Aprons	516
RadShield – Apex Series	517
RadShield – Zenith Series	518
RadShield – Zenith – X Base	519
RadShield – Zenith – H Base	520
Sources	521
Spectrum Techniques	521
RSS3 Source Set – Spectrum Techniques	523
RSS-5 Source Set – Spectrum Techniques	524
RSS-8 Source Set – Spectrum Techniques	525
Laminated Sources – Spectrum Techniques	526
Disc Sources – Spectrum Techniques	528
Isotope Generator – Spectrum Techniques	529
Tube Sources – Spectrum Techniques	530
Needle Sources – Spectrum Techniques	531
Gestion des déchets et du recyclage	532
Else Nuclear	532
LEM – LIQUID EFFLUENT MONITORING SYSTEM	534
WDMS NT-VK	535
BSI	535
Free Release Monitor HERCULES-FRM	537
Hybrid cooling for the HPGe detector Nicole	539
Ludlum Measurements	539
HLM-6GP Laundry Monitor	542
Model 375-600 Digital Area Monitor for Small Areas	543
Model 2100-1 Sample Counter	544
Model 329-32 Laundry Contamination Monitor	545
Model 2100 Conveyorized Sample Counter	546
Model 375P-3500 Conveyor Monitor	547
Model 375P-1000 Outdoor Monitoring System	548
Model 375P-2000 Outdoor Monitoring System	549
HLM-22, HLM-3G Laundry Monitor	550
Helgeson Scientific Services (HSS)	550
HS-DRUM – Waste characterization system for drums	552
HS-FRM – Free release monitor for drums, containers and big bags	553
HS-OTM – Object and tool monitors for objects monitoring	554
Complete storage and treatment plant for NORM wastes	555
Descaling system for NORM waste	556
Soil segregation unit	557
SDEC France	557
Isokinetic Sampling Probes – SDEC	559
Carbon 14 Sampler with 2 Vials – SDEC	560
Carbon 14 Sampler with 4 Vials – SDEC	561
Tritium Sampler with 2 Vials – SDEC	562

Bertin Instruments 562
Coriolis Consumables - Bertin Instruments 564

MONITEURS DE ZONE





Partner **SE International**



S.E. International, Inc. est un fabricant américain de confiance d'instruments de détection de radiations sous la marque Radiation Alert®. Sa gamme de produits comprend des détecteurs de zone, des radiamètres portables et des dosimètres électroniques personnels, tous conçus pour une surveillance précise et en temps réel des radiations dans un large éventail d'applications.

Product offering

AM-2x2 Contrôleur de zone de rayonnement



AM-71313 Contrôleur de zone de rayonnement



AM-7128 Contrôleur de zone de rayonnement



AM-1X1 Contrôleur de zone de rayonnement






Détection des radiations > Moniteurs de zone

AM-2x2 Contrôleur de zone de rayonnement

Le Radiation Alert® AM-2X2 est un moniteur de zone de pointe conçu pour une utilisation facile et des performances fiables. Doté d'une interface tactile intelligente, d'un écran LED et d'un détecteur de scintillation externe, il est idéal pour la surveillance des salles, des portiques et des sources dans les environnements médicaux, de recherche et industriels. Avec ses alertes intégrées, son logiciel de surveillance à distance et ses options de boîtier robuste, l'AM-2X2 est votre solution tout-en-un pour la radioprotection.



Vue d'ensemble :

Le moniteur de zone Radiation Alert® est l'un des moniteurs de zone de rayonnement les plus conviviaux, les plus complets et les plus modernes du marché. L'interface facile à utiliser est un écran tactile résistif intelligent doté d'un grand affichage LED à cinq chiffres.

Caractéristiques :

L'AM-2X2 est livré avec un détecteur de scintillation à l'iodure de sodium externe. Des sondes à l'iodure de césium sont disponibles. Des options de boîtier robuste à montage mural sont disponibles pour les zones à forte fréquentation. Surveillez chaque Radiation Alert® Area Monitor sur votre réseau à l'aide du logiciel gratuit. Comprend des indicateurs d'avertissement sélectionnables par l'utilisateur pour les niveaux d'alarme de rayonnement faibles et élevés, ainsi que pour les défaillances du détecteur. Configurez des alertes par e-mail et par SMS pour recevoir les alarmes lorsque vous êtes en déplacement. Tous les paramètres sont stockés en interne, même lorsque l'alimentation est coupée. Tous les appareils sont accompagnés d'un certificat de conformité. Des étalonnages à la source NIST sont disponibles sur demande.

Applications et utilisations :


Surveillance des salles dans les hôpitaux, les machines à rayons X, les accélérateurs, les laboratoires, etc. Surveillance des portails, tels que les portes et les allées, surveillance des sources, alarmes en présence de rayonnements ou en l'absence de sources.



Détection des radiations > Moniteurs de zone

AM-71313 Contrôleur de zone de rayonnement

Un moniteur de zone de rayonnement à la pointe de la technologie et convivial, doté d'un écran tactile intelligent et d'un grand affichage LED. Choisissez entre des détecteurs internes ou externes et surveillez l'ensemble de votre réseau grâce au logiciel gratuit fourni. Définissez des alarmes personnalisées, recevez des alertes mobiles et bénéficiez d'un stockage interne sécurisé des paramètres. Idéal pour les hôpitaux, les laboratoires, les accélérateurs et les points d'accès contrôlés. Certificat de conformité inclus ; étalonnage NIST disponible sur demande.



Vue d'ensemble :

Le moniteur de zone Radiation Alert® est l'un des moniteurs de zone de rayonnement les plus conviviaux, les plus complets et les plus modernes du marché. L'interface facile à utiliser est un écran tactile résistif intelligent doté d'un grand affichage LED à cinq chiffres.

Caractéristiques :

Il est livré avec un détecteur interne ou externe et un logiciel gratuit pour surveiller chaque Radiation Alert® Area Monitor sur votre réseau. Comprend des indicateurs d'avertissement sélectionnables par l'utilisateur pour les niveaux d'alarme de rayonnement faibles et élevés, ainsi que pour les défaillances du détecteur. Configurez des alertes par e-mail et par SMS pour recevoir les alarmes lorsque vous êtes en déplacement. Tous les paramètres sont stockés en interne, même lorsque l'alimentation est coupée. Tous les appareils sont accompagnés d'un certificat de conformité. Des étalonnages à la source NIST sont disponibles sur demande.

Options de sondes internes ou externes disponibles.

Applications et utilisations :

Surveillance des salles dans les hôpitaux, les machines à rayons X, les accélérateurs, les laboratoires, etc. Surveillance des portails, tels que les portes et les allées


← Back to partner



Détection des radiations > Moniteurs de zone

AM-7128 Contrôleur de zone de rayonnement

Le moniteur de zone Radiation Alert® est l'un des moniteurs de zone de rayonnement les plus conviviaux, les plus complets et les plus modernes du marché. L'interface facile à utiliser est un écran tactile résistif intelligent doté d'un grand affichage LED à cinq chiffres.



Caractéristiques :

Le produit est livré avec un détecteur interne ou externe et un logiciel gratuit pour surveiller chaque Radiation Alert® Area Monitor sur votre réseau. Comprend des indicateurs d'alerte sélectionnables par l'utilisateur pour les niveaux d'alarme de rayonnement faibles et élevés, ainsi que pour les défaillances du détecteur. Configurez des alertes par e-mail et par SMS pour recevoir les alarmes lorsque vous êtes en déplacement. Tous les paramètres sont stockés en interne, même lorsque l'alimentation est coupée. Tous les appareils sont accompagnés d'un certificat de conformité. Des étalonnages à la source NIST sont disponibles sur demande.

Options de sondes internes ou externes disponibles

Applications et utilisations :

Surveillance des salles dans les hôpitaux, les machines à rayons X, les accélérateurs, les laboratoires, etc. Surveillance des portails, tels que les portes et les allées



Détection des radiations > Moniteurs de zone

AM-1X1 Contrôleur de zone de rayonnement

Le moniteur de zone Radiation Alert® est l'un des moniteurs de zone de rayonnement les plus conviviaux, les plus complets et les plus modernes du marché. L'interface facile à utiliser est un écran tactile résistif intelligent doté d'un grand affichage LED à cinq chiffres.



Caractéristiques :

Le AM1X1 est livré avec un détecteur de scintillation à iodure de sodium interne ou externe. Des sondes à l'iodure de césium sont également disponibles. Des options de boîtier robuste à montage mural sont disponibles pour les zones à forte fréquentation. Surveillez chaque Radiation Alert® Area Monitor sur votre réseau à l'aide du logiciel gratuit. Comprend des indicateurs d'avertissement sélectionnables par l'utilisateur pour les niveaux d'alarme de rayonnement faibles et élevés, ainsi que pour les défaillances du détecteur. Configurez des alertes par e-mail et par SMS pour recevoir les alarmes lorsque vous êtes en déplacement. Tous les paramètres sont stockés en interne, même lorsque l'alimentation est coupée. Tous les appareils sont accompagnés d'un certificat de conformité. Des étalonnages à la source NIST sont disponibles sur demande.

Options de sondes internes ou externes disponibles.

Applications et utilisations :

Surveillance des salles dans les hôpitaux, les machines à rayons X, les accélérateurs, les laboratoires, etc. Surveillance des portails, tels que les portes et les allées, surveillance des sources, alarmes en présence de rayonnements ou en l'absence de sources.



Partner Ludlum Measurements




Ludlum Measurements, Inc. conçoit et fabrique des instruments et des technologies de détection des rayonnements. Fondée en 1962, elle propose une large gamme d'instruments de détection de rayonnements, développés pour aider à surveiller la sécurité du personnel et de l'environnement. Les instruments sont utilisés dans des applications telles que la surveillance de routine du personnel et du matériel, la sécurité des frontières et les situations d'intervention d'urgence.

Product offering

<p>Modèle 375 Contrôleur d'ambiance</p> 	<p>Modèle 375/1 Moniteur numérique de surface</p> 	<p>Model 375/2 Digital Area Monitor - Ludlum</p> 	<p>Model 375/4 Gamma Area Monitor - Ludlum</p> 
<p>Model 375-10 Digital Area Monitor - Ludlum</p> 	<p>Model 375-9 Digital Area Monitor - Ludlum</p> 	<p>Model 375-Dual Digital Area Monitor - Ludlum</p> 	<p>Model 375-20 Monitoring System</p> 
<p>Model 375-30</p> 	<p>Model 375/31H</p> 	<p>Model 3276 - Area Monitor Controller</p> 	<p>Model 3277/1 Alpha- Beta Frisker</p>  <p>Model 3277/1 with Desktop Mount (PN 4519-435) and Model 43-93 (PN 47-2556)</p>


Model 375P-1000



Model 375P-2000



Model 375P-336 Series



**Model 240 Series
Alpha-Beta Floor and
Wall Monitor**



**Model 3002/FM Series
Alpha-Beta Floor
Monitor**



**Model 239-1F Series
Alpha-Beta Floor
Contamination
Monitor**



**Model 375P-336
Surface
Contamination
Monitor - Ludlum**





Détection des radiations > Moniteurs de zone

Modèle 375 Contrôleur d'ambiance

Le modèle 375 est un contrôleur électronique numérique polyvalent, compact et très abordable, conçu pour la surveillance des rayonnements dans les locaux. Sa conception simple permet d'utiliser de nombreux détecteurs différents pour une grande variété d'applications et offre une lecture locale et des alarmes. Ces unités polyvalentes peuvent également être connectées à un indicateur/annonceur auxiliaire optionnel pour alerter le personnel dans des endroits éloignés.



Caractéristiques :

- Contrôleur numérique abordable
- S'adapte à une grande variété de détecteurs
- Alarmes et unités de mesure programmables
- Possibilité de mise en réseau (nécessite l'option d'interface Ethernet ou de page Web)
- Batterie de secours

Vue d'ensemble :

Le modèle 375 est un contrôleur de zone numérique pour la mesure ou la détection des rayonnements. Sa conception simple permet d'utiliser de nombreux détecteurs différents, ce qui convient à une grande variété d'applications. Il est équipé d'un grand écran numérique à LED et d'alarmes. Cet instrument polyvalent peut également être connecté à des indicateurs/annonceurs auxiliaires optionnels pour alerter le personnel à distance. La conception numérique conviviale facilite la configuration et l'utilisation. Cet appareil peut également être mis en réseau avec une station centrale sur PC où les données sont enregistrées et les alarmes affichées.

Applications et utilisations :

Ce système abordable et flexible peut être utilisé dans de nombreuses applications différentes. Au fil des ans, Ludlum Measurements a développé une large gamme de détecteurs, d'accessoires et d'options qui peuvent être inclus dans la configuration d'un système modèle 375. Ceux-ci comprennent des indicateurs d'alarme à distance, des imprimantes, des sorties relais, des boîtiers résistants aux intempéries, des logiciels de réseau Ethernet, des caméras industrielles, et bien plus encore.



Détection des radiations > Moniteurs de zone

Modèle 375/1 Moniteur numérique de surface

Le moniteur numérique 375/1 est conçu pour être visible et facile à utiliser. Le moniteur est équipé d'un scintillateur CsI de 18 mm logé à l'intérieur avec une sensibilité d'environ 120 cpm/R/h. Le moniteur est doté d'un châssis mural et d'un écran LED à quatre chiffres.

Le moniteur est doté d'un châssis mural et d'un écran LED à quatre chiffres que vous pouvez lire à une distance de 9 mètres (20 pieds).

Les indicateurs émettent une alarme lorsqu'ils détectent un faible rayonnement (en jaune), un rayonnement élevé (en rouge), une défaillance de l'instrument (également en rouge) ou une batterie faible (en jaune).



Caractéristiques :

- Moniteur de zone abordable
- Plage de mesure : 0,1 à 9999 $\mu\text{R/hr}$
- Conception compacte et intégrée
- Faible sensibilité à l'arrière-plan
- Alarmes sonores et visuelles
- Possibilité de mise en réseau (nécessite l'option d'interface Ethernet ou de page Web)

Vue d'ensemble :

Le moniteur numérique mural 375/1 est conçu pour être visible et facile à utiliser. Ce moniteur intègre un scintillateur CsI de 18 mm avec une sensibilité d'environ 120 cpm par $\mu\text{R/hr}$. Il est doté d'un châssis mural et d'un écran LED à quatre chiffres lisible à une distance de 9 mètres (30 pieds). Des indicateurs rétroéclairés signalent un faible rayonnement (jaune), un rayonnement élevé (rouge), une défaillance de l'instrument (rouge) et une batterie faible (jaune), ainsi qu'une alarme. Un voyant d'état vert indique que l'instrument fonctionne correctement.

Les paramètres sont protégés par un couvercle d'étalonnage qui permet de régler la constante d'étalonnage, la correction du temps mort et les paramètres du point d'alarme. Les paramètres sont stockés dans une mémoire non volatile (conservée même lorsque l'alimentation est coupée). Une sortie analogique logarithmique à cinq décades est fournie.



Détection des radiations > Moniteurs de zone

Model 375/2 Digital Area Monitor - Ludlum

The Model 375/2 Digital Wall-Mount Area Monitor is designed for visibility and ease of use. This monitor incorporates an internally-housed energy compensated GM detector with a range from 1 μ Sv/h to 10 mSv/h (0.1 mR/hr to 1 R/hr). It features a wall-mount chassis and a four-digit LED display that is readable from 9 meters (30 feet) away. Backlit indicators warn of low radiation (yellow), high radiation (red), instrument failure (red), and low battery (yellow), along with an alarm. A green status light indicates the instrument is functioning properly.



Features

- Affordable Area Monitor
- 1 μ Sv/h to 10 mSv/h (0.1 mR/hr to 1 R/hr)
- Integrated Design
- Battery Backup
- Networkable (Requires Ethernet or Webpage Interface Option)
- Audio & Visual Alarms

Overview:

The Model 375/2 Digital Wall-Mount Area Monitor is designed for visibility and ease of use. This monitor incorporates an internally-housed energy compensated GM detector with a range from 1 μ Sv/h to 10 mSv/h (0.1 mR/hr to 1 R/hr). It features a wall-mount chassis and a four-digit LED display that is readable from 9 meters (30 feet) away. Backlit indicators warn of low radiation (yellow), high radiation (red), instrument failure (red), and low battery (yellow), along with an alarm. A green status light indicates the instrument is functioning properly.

Parameters are protected under a calibration cover. Calibration is easily accomplished by moving the cal dipswitch to the right, and using the pushbuttons to increment or decrement the calibration constant, dead time correction, and alarm point parameters. Parameters are stored in non-volatile memory (retained even with power disconnected). A five-decade logarithmic analog output is provided. A battery backup provides 48 hours of additional use after the primary power is removed.



Détection des radiations > Moniteurs de zone

Model 375/4 Gamma Area Monitor - Ludlum

The Model 375/4 Digital Wall-Mount Area Monitor is designed for visibility and ease of use. This monitor incorporates an internally housed energy compensated GM detector with a range from 0.01 mSv/h to 100 mSv/h (1.0 mR/hr to 10 R/hr). It features a wall-mount chassis and a four-digit LED display that is readable from 9 meters (30 feet) away. Backlit indicators warn of low radiation (yellow), high radiation (red), instrument failure (red), and low battery (yellow), along with an audible alarm. A green status light indicates the instrument is functioning properly.



Features:

- Affordable Area Monitor
- 0.01 mSv/h to 100 mSv/h (1.0 mR/hr to 10 R/hr)
- Integrated Design
- Battery Backup
- Networkable (Requires Ethernet or Webpage Interface Option)
- Audio & Visual Alarms

Overview:

The Model 375/4 Digital Wall-Mount Area Monitor is designed for visibility and ease of use. This monitor incorporates an internally housed energy compensated GM detector with a range from 0.01 mSv/h to 100 mSv/h (1.0 mR/hr to 10 R/hr). It features a wall-mount chassis and a four-digit LED display that is readable from 9 meters (30 feet) away. Backlit indicators warn of low radiation (yellow), high radiation (red), instrument failure (red), and low battery (yellow), along with an audible alarm. A green status light indicates the instrument is functioning properly.

Parameters are protected under a calibration cover. Calibration is easily accomplished by moving the “cal” dipswitch to the right, and using the pushbuttons to increment or decrement the calibration constant, dead time correction, and alarm point parameters. Parameters are stored in non-volatile memory (retained even with power disconnected). A five-decade logarithmic analog output is provided. A battery backup provides 48 hours of additional use after the primary power is removed.



Détection des radiations > Moniteurs de zone

Model 375-10 Digital Area Monitor - Ludlum

This wall-mounted area monitor with an internal NaI scintillation detector is simple to set up, use, and calibrate. The four-digit LED display is readable from 9 meters (30 feet) away. User-configurable alarm setpoints are easy to configure. Parameters are protected under a calibration cover, and further protected by an eight-hour battery backup. They are also stored in non-volatile memory that retains the information even if primary power is disconnected. The controller supplies local alarms but can be connected to external alarms, strobes, camera, or other recording and monitoring devices, or put onto an Ethernet network, if desired.



Features:

- Range: 0.1 to 20 $\mu\text{Sv/hr}$ (1 to 2000 $\mu\text{R/hr}$)
- Encased Shielded Sodium Iodide (NaI) Detector
- User-Programmable Alarms
- Networkable (Requires Ethernet or Webpage Interface Option)
- 8-Hour Battery Backup

Overview:

This wall-mounted area monitor with an internal NaI scintillation detector is simple to set up, use, and calibrate. The four-digit LED display is readable from 9 meters (30 feet) away. User-configurable alarm setpoints are easy to configure. Parameters are protected under a calibration cover, and further protected by an eight-hour battery backup. They are also stored in non-volatile memory that retains the information even if primary power is disconnected. The controller supplies local alarms but can be connected to external alarms, strobes, camera, or other recording and monitoring devices, or put onto an Ethernet network, if desired. The Model 375-10 includes the Model 375 Ethernet hardware option. It is also preprogrammed to use the Model 375 Webpage & Service Software that is available separately (Part Number 1370-077).

An optional lead shield can be included with the detector for applications that need to prevent alarms from low-energy sources. (**Note:** The lead shield option should not be used in applications that need to monitor low-energy sources, such as medical isotopes.)



Détection des radiations > Moniteurs de zone

Model 375-9 Digital Area Monitor - Ludlum

The Model 375-9 Digital Wall-Mount Area Monitor is designed for visibility and ease of use. This monitor provides a fast response to pulsed fields by utilizing an external ion chamber covering any four consecutive decades between 1 $\mu\text{Sv/h}$ and 1000 mSv/h (0.1 mR/hr and 100 R/hr). It features a wall-mount chassis and a four-digit LED display that is readable from 9 meters (30 feet) away. Backlit indicators warn of low radiation (yellow), high radiation (red), instrument failure (red), and low battery (yellow), along with an audible alarm. A green status light indicates the instrument is functioning properly.



Features:

- Integrated Measurement System
- External Ion Chamber Detector
- User-Programmable Alarm Settings
- Audible & Visual Alarms
- Networkable (Requires Ethernet or Webpage Interface Option)

Overview:

The Model 375-9 Digital Wall-Mount Area Monitor is designed for visibility and ease of use. This monitor provides a fast response to pulsed fields by utilizing an external ion chamber covering any four consecutive decades between 1 $\mu\text{Sv/h}$ and 1000 mSv/h (0.1 mR/hr and 100 R/hr). It features a wall-mount chassis and a four-digit LED display that is readable from 9 meters (30 feet) away. Backlit indicators warn of low radiation (yellow), high radiation (red), instrument failure (red), and low battery (yellow), along with an audible alarm. A green status light indicates the instrument is functioning properly.

Parameters are protected under a calibration cover. Calibration is easily accomplished by moving the cal dipswitch to the right, and using the pushbuttons to increment or decrement the calibration constant and alarm point parameters. Parameters are stored in non-volatile memory (retained even with power disconnected). A five-decade logarithmic analog output is provided. A battery backup provides 48 hours of additional use after the primary power is removed.



Model 375-Dual Digital Area Monitor - Ludlum

The Model 375-Dual is a dual-channel digital area monitor controller based on the legacy version of the Model 375. It consists of two Model 375 controllers in one wall-mount chassis, each with its own detector connection. A common application is gamma and neutron monitoring: one controller monitors gamma radiation and the other monitors neutron radiation. This instrument may also be used to monitor radiation in two separate locations when used in conjunction with appropriate external detectors.



Features:

- Dual LED Digital Display
- Low and High Alarm Indicators
- Programmable Alarm Indicators
- Optional Remote
- Detector Fail Indicators
- Battery Backup
- Data Output/RS-232

Overview:

The Model 375-Dual is a dual-channel digital area monitor controller based on the legacy version of the Model 375. It consists of two Model 375 controllers in one wall-mount chassis, each with its own detector connection. A common application is gamma and neutron monitoring: one controller monitors gamma radiation and the other monitors neutron radiation. This instrument may also be used to monitor radiation in two separate locations when used in conjunction with appropriate external detectors.

Each controller features a four-digit LED display that is readable from 9 meters (30 feet) away. Backlit indicators on each instrument warn of low radiation alarm (yellow), high radiation alarm (red), instrument failure (red), and low battery (yellow). A green status light indicates the instrument is functioning properly. Calibration parameters are stored in non-volatile memory and protected under calibration covers on each controller.



Model 375-20 Monitoring System

Features:

- Affordable Digital Controller
- Weatherproof Encased-Shielded NaI Detectors
- Programmable Alarms
- Networkable (Requires Ethernet or Webpage Interface Option)
- Battery Backup



The Model 375-20 is a Digital Model 375 Controller coupled to two shielded 5.1 cm (2 in.) diameter by 5.1 cm (2 in.) thick NaI(Tl) scintillation detectors. The detectors are encased in weathertight enclosures suitable for the outdoor environment, but the Model 375 Controller is normally mounted to a wall indoors near an operator. This is a simple, cost-effective system, easy to operate and maintain. The controller supplies local alarms but can also be connected to external alarms or put onto an Ethernet network if desired. Additionally, it has a 48-hour battery backup to keep the system operational in the event power is lost.

Options:

This device can be complemented with a variety of optional features to suit different operational needs. Available options include enclosures for added protection, remote displays for convenient monitoring, and alarm annunciators to enhance safety and response time. Additionally, signal outputs can be integrated for connection with external systems, while software and networking options allow for advanced data management and remote access capabilities.



Interested in Model 375-20? Contact us for more details!

Order now

Ask a question



Détection des radiations > Moniteurs de zone

Model 375-30

The Model 375-30 pairs a digital controller with two rugged, weatherproof NaI(Tl) detectors for reliable outdoor gamma detection. Simple, cost-effective, and easy to maintain, it features local and remote alarm options, Ethernet connectivity, and 48-hour battery backup for continuous operation.



Features:

- Affordable Digital Controller
- Weatherproof Encased-Shielded NaI Detectors
- Programmable Alarms
- Networkable (Requires Ethernet or Webpage Interface Option)
- Battery Backup

Overview:

The Model 375-30 is a digital Model 375 Controller coupled to two shielded 7.6 cm (3 in.) diameter by 2.5 cm (1 in.) thick NaI(Tl) scintillation detectors. The detectors are encased in NEMA 4X rated weathertight enclosures suitable for the outdoor environment, but the 375 Controller is normally mounted to a wall indoors near an operator. This cost-effective system is simple, making it easy to operate and maintain. The controller supplies local alarms but can also be connected to external alarms or put onto an Ethernet network if desired. It additionally has a 48-hour battery backup to keep the system operational in the event power is lost.



Détection des radiations > Moniteurs de zone

Model 375/31H

The Model 375 is a compact, digital controller designed for flexible radiation monitoring across diverse environments. Paired with a high-performance neutron detector, it offers accurate thermal and fast neutron detection with excellent gamma rejection. With local and remote alarms, Ethernet connectivity, and optional real-time data logging and imaging, the Model 375 is an ideal solution for centralized, networked radiation safety.



Features:

- Perfect for Temporary Jobsites
- Easy Setup and Use
- Versatile Controller with Highly Visible Display
- User-Programmable Alarms
- Network and Relay Options
- 48-Hour Battery Backup
- CE Certified

Overview:

The Model 375 is a versatile, compact, and easy-to-use digital electronic controller designed for monitoring radiation in areas. Its simple design accommodates many different detectors to suit a wide variety of applications, and it is equipped with a local readout and alarms. These versatile units may also be connected to an optional auxiliary indicator/annunciator to alert personnel at remote locations. The user-friendly, digital design enhances setup and operation. The Model 375 units may also be networked to a central PC-based station where data are logged and alarms posted.

Applications & Uses:

This affordable and very flexible system has found its way into many applications resulting in a full complement of detectors, accessories, and options that include remote indicator alarms, printers, relay outputs, weather-proof enclosures, Ethernet networking software, industrial cameras, and more.

Sites requiring centralization of their data can link multiple 375 systems together via Ethernet and view them using a common web browser with the purchase of Ludlum's Webpage & Service Software. This program collects all data in real time, logs data, and annunciates any alarms. The system can also send intelligent email alerts to responsible personnel and capture a picture of whatever triggered an

alarm if optional Ethernet cameras are employed.



Détection des radiations > Moniteurs de zone

Model 3276 - Area Monitor Controller

The Model 3276 is a lightweight, versatile radiation detection unit designed for both area monitoring and frisking applications. Compatible with alpha, beta, and gamma detectors, it features a large backlit display, audible alarms, and intuitive controls. Ideal for indoor use, the Model 3276 supports multiple measurement modes and units, offering precision and flexibility in a compact, rugged design.



Features:

- Uses Either an Internal or External Detector to Measure Alpha, Beta, or Gamma Radiation
- Versatile - Can Operate as an Area Monitor or a Frisker
- Simple Setup and Use
- User-Adjustable Alarms
- User-Programmable Units of Measurement, Either U.S. or SI Units
- Power: Standard Alkaline (4) "AA" Batteries or 9 Vdc Wall Mount Transformer

Overview:

The Model 3276 is a versatile instrument that can be used for multiple radiation detection or measurement purposes. It is used with either an internal or an external radiation detector to detect alpha, beta, or gamma radiation in applications such as frisking or area monitoring.

It features a large, backlit, easy-to-read LCD screen and audible alarms and is controlled using a simple four-button interface. The unit body is made of lightweight, rugged aluminum. It is not intended for outdoor use and should be protected from splashing water. The attached metal handle facilitates transportation between sites. The instrument can be wall-mounted for area monitoring applications or mounted to a stand for desktop applications such as frisking.

Applications & Uses:

The Model 3276 can measure radiation in count rate, exposure rate, exposure rate/dose, activity rate, integrated exposure/dose, time-averaged rates, and scaler counts. When used as a frisker, three modes of operation are available - RATE, MAX, and COUNT - which can be selected by pressing the MODE button. When used as an area monitor, only RATE mode is available by default. Measurements can be collected in two sets of units (primary and secondary) for RATE and MAX modes in cps, cpm, Bq, dpm, R/hr, or Sv/h units. The user can

switch between the two sets of units by pressing the UNITS button. When used as a frisker with a scintillation detector, a sigma audio mode can be enabled that allows the user to find small increases above the background radiation level.

Instrument setup can be done either through the front-panel controls or via the Lumin Calibration Kit (PN: 4498-1018). Power is supplied by either four alkaline "AA" batteries or a 9 Vdc wall mount transformer. The Model 3276 is shipped ready to use with batteries, a wall transformer, and a calibration certificate.



Model 3277/1 Alpha-Beta Frisker



Features:

- 7-inch Colour Touch-Screen Display Shows All Readings Simultaneously in a Large, Simple Layout
- Simple Setup and Use
- Can Be Used with Various Scintillation or Proportional Detectors
- Either Imperial or SI Units
- Rechargeable Backup Battery
- Automatic Background Subtraction During Measurements

Overview:

The Model 3277/1 is a wall-mount or desktop instrument that can be used for frisking personnel or objects for alpha and beta contamination. A large, colour touch-screen displays alpha and beta readings simultaneously, and dual tone click-audio enables the user to easily distinguish between alpha and beta contamination. Power is supplied by either an internal, rechargeable battery or a 100 – 240 Vdc wall transformer. Battery life is approximately 8 hours under normal usage.



Model 375P-1000



Features:

- Checks for Surface Contamination Entering/Exiting Facilities
- Affordable Digital Controller
- Weatherproof Encased-Shielded Plastic Scintillator Detectors
- Programmable Alarms
- Networkable (Requires Ethernet or Webpage Interface Option)
- Battery Backup

Overview:

The Model 375P-1000 is a digital Model 375 Controller coupled to two shielded 7866 cm³ (480 in³) plastic scintillator detectors. The detectors are encased in weathertight enclosures suitable for the outdoor environment. The Model 375 Controller is not weatherproof and must be mounted either indoors or within an environmental enclosure (available separately, see Options). This cost-effective solution offers a simple system that is easy to operate and maintain.

The system continuously monitors background levels and will alert the user when the infrared sensors detect a contaminated object. Once the object is removed, the system will return to normal (background) monitoring.

The controller supplies local alarms, but can also be connected to external alarms or even put onto an Ethernet network if desired. In addition, a 24-hour battery backup keeps the system operational in the event power is lost.



Détection des radiations > Moniteurs de zone

Model 375P-2000

The Model 375P-2000 features a digital controller with four large, lead-shielded plastic scintillator detectors in rugged, weatherproof housings—ideal for monitoring objects entering or exiting facilities. With infrared-triggered detection, programmable alarms, network capability, and 24-hour battery backup, it delivers dependable, automated contamination control in a user-friendly, cost-effective system.



Features:

- Checks for Surface Contamination Entering/Exiting Facilities
- Affordable Digital Controller
- Weatherproof Encased-Shielded Plastic Scintillator Detectors
- Programmable Alarms
- Networkable (Requires Ethernet or Webpage Interface Option)
- Battery Backup

Overview:

The Model 375P-2000 is a digital Model 375 Controller coupled to four lead-shielded 7866 cm³ (480 in³) plastic scintillator detectors. The detectors are encased in weather-tight enclosures suitable for the outdoor environment. The Model 375P Controller is not weatherproof and must be mounted either indoors or within an environmental enclosure. This cost-effective solution offers a simple system that is easy to operate and maintain.


The system continuously monitors background levels and will alert the user when the infrared sensors detect a contaminated object. Once the object is removed, the system will return to normal (background) monitoring.

The controller supplies local alarms, but can also be connected to external alarms or put onto an Ethernet network if desired. In addition, a 24-hour battery backup keeps the system operational in the event power is lost.



Model 375P-336 Series

The Model 375P-336 Series combines a digital controller with two lead-shielded plastic scintillation detectors for reliable surface contamination monitoring. Available in both indoor (375P-336) and outdoor (375P-336-1L) configurations, these user-friendly, cost-effective systems offer local and remote alarms, Ethernet connectivity, and 24-hour battery backup for uninterrupted operation.



Features:

- Excellent Surface Contamination Screening Tool for Small Articles, Baggage, Packages, and Medical Waste
- Affordable Digital Controller
- 2 Large Plastic Scintillator Detectors
- Programmable Alarms
- Networkable (Requires Ethernet or Webpage Interface Option)
- Includes Check Source for Calibration
- 24-Hour Battery Backup

Overview:

The Model 375P-336 Series are monitoring systems that consist of a Model 375P digital controller coupled with two lead shielded 2753 cm³ (168 in³) plastic scintillation detectors. The Model 375P-336 is designed for indoor applications, while the Model 375P-336-1L has detectors housed in waterproof enclosures that can be mounted outdoors. The Model 375P controller is not weatherproof and must be mounted either indoors or within an environmental enclosure.

These simple and cost-effective solutions offer a system that is easy to operate and maintain. The controller supplies local alarms but can also be connected to external alarms or put onto an Ethernet network if desired. Each system has a 24-hour battery backup to keep it operational in the event power is lost.



Détection des radiations > Moniteurs de zone

Model 240 Series Alpha-Beta Floor and Wall Monitor

The Model 240 is a portable, high-efficiency alpha-beta contamination monitor designed for fast, accurate scanning of floors and walls. Featuring an array of low-background detectors, real-time alarms, and USB connectivity for streamlined data logging and reporting, it delivers precise, user-friendly performance—ideal for labs, cleanrooms, and decontamination zones.



Features:

- Quickly Surveys and Datalogs Large Areas with 173 cm (68 in.) Wide Path
- Hinged Array Can Be Folded for Easy Transportation
- 12 Alpha-Beta Detector Capability
- Can Use Either Gas Proportional or Scintillation Detectors
- Measures and Warns Operator About Excessive Speed

Overview:

The Model 240 Alpha-Beta Floor and Wall Monitor allows a user to quickly survey large areas for alpha-beta contamination. Compatible with either gas-proportional or scintillation detectors, the Model 240 cart comes in a floor-style only version, or a version that supports both floor and wall monitoring. Detector-to-surface spacing is adjustable and detectors are positioned for no “dead” zones when scanning. Gas proportional models come with a gas regulator, flowmeters, and gas lines, but a P-10 gas bottle is not included. The cart also provides two holders for spare detectors, to provide for replacement if a detector becomes damaged.

Utilizing an array of detectors instead of a single detector provides several advantages: 1) smaller detectors have lower backgrounds and thus lower minimum detectable activity (MDA); 2) smaller detectors allow the user to pinpoint the contamination; and 3) smaller detectors make it easier to maintain and replace fragile metallized polyester windows necessary for alpha detection.

The array of detectors is connected to an electronics box, which has a USB connection to a laptop. The electronics has 12 separate detector boards, each with its own settable high voltage, lower and upper thresholds, and alpha-beta count channels. The laptop display makes it easy to view all 12 detectors simultaneously, and provides setup wizards to help with establishing operating points for the detectors.

The system initially measures radiation background from the detector array, allowing the operator to see net counts during scanning. While scanning, a rolling average is checked on all 24 channels (12 each, alpha and beta) every half-second, and a momentary audible and visual alarm activates if any alarm points are exceeded. Measurements are also automatically logged to a file for subsequent reports.

← Back to partner



Détection des radiations > Moniteurs de zone

Model 3002/FM Series Alpha-Beta Floor Monitor

The Model 3002/FM Series Alpha-Beta Floor Monitors allow a user to quickly survey large areas for alpha-beta contamination. They combine the dependable [Model 3002 Alpha-Beta Survey Meter](#) with two alpha-beta scintillation detectors in configurations ideal for floor monitoring. The use of scintillation detectors creates an instrument that requires much less maintenance than traditional gas flow proportional detectors.



Features:

- Large Backlit and Auto-Ranging LCD
- Simultaneous Alpha-Beta Counting
- Gasless - Uses Scintillators and PMTs
- Dual-Tone Audio: Low-Pitch Beta Clicks and High-Pitch Alpha Beeps
- 4-Button Interface for Easy Operation
- Height Above Floor Easily Adjusted
- Rate, Max, and Count Modes



Model 239-1F Series Alpha-Beta Floor Contamination Monitor



Features:

- 594 cm² or 821 cm² Active Area Gas Proportional Detector
- Adjustable Detector Height
- Compatible with Multiple Survey Meters

Overview:

The Model 239-1F Floor Monitor is a gas proportional floor monitor detector mounted on a roll-around cart. The instrument features a flow system, quick-connects, a gas bottle mount, and a means to adjust the height of the detector from the floor for optimum performance. A nuclear counting gas bottle, gas regulator, and a survey instrument are required for the operation of the floor monitor.



Model 375P-336 Surface Contamination Monitor - Ludlum



Features:

- Excellent Surface Contamination Screening Tool for Small Articles, Baggage, Packages, and Medical Waste
- Affordable Digital Controller
- 2 Large Plastic Scintillator Detectors
- Programmable Alarms
- Networkable (Requires Ethernet or Webpage Interface Option)
- Includes Check Source for Calibration
- 24-Hour Battery Backup

Overview:

The Model 375P-336 Series are monitoring systems that consist of a Model 375P digital controller coupled with two lead shielded 2753 cm³ (168 in³) plastic scintillation detectors. The Model 375P-336 is designed for indoor applications, while the Model 375P-336-1L has detectors housed in waterproof enclosures that can be mounted outdoors. The Model 375P controller is not weatherproof and must be mounted either indoors or within an environmental enclosure (available separately).

These simple and cost-effective solutions offer a system that is easy to operate and maintain. The controller supplies local alarms but can also be connected to external alarms or put onto an Ethernet network if desired. Each system has a 24-hour battery backup to keep it operational in the event power is lost.

MONITEURS PORTABLES





Partner **BSI**



Baltic Scientific Instruments (BSI) is an OEM manufacturer based in Riga, Latvia, dedicated to the development and production of advanced spectrometric and detection equipment. With decades of experience and roots in the former Research Institute for Radioisotope Apparatus (RNIIRP), BSI provides cutting-edge technologies for nuclear power, environmental monitoring, security, medicine, and scientific research.

The company specializes in HPGe, Si, CdZnTe/CdTe, and scintillation detector systems, known for their accuracy, stability, and performance in demanding analytical environments.

Through continuous innovation, strict quality assurance (ISO 9001:2015), and strong international collaboration, BSI supports customers worldwide in achieving precise and reliable radiation measurement and analysis.

Product offering

Hand-held Integrated Gamma Spectrometer





Hand-held Integrated Gamma Spectrometer

Hand-held Integrated Gamma Spectrometer with an integrated HPGe detector, preamplifier, multichannel analyzer, batteries, and software offers relatively compact, portable solution for high-resolution gamma-ray analysis. Its all-in-one design enhances field usability, requiring no external components for setup.



Application

Hand-held Integrated Gamma Spectrometer is ideal for nuclear safety, environmental monitoring, radiological emergency response, CBRN and waste characterization, it ensures rapid deployment and reliable data acquisition. The integrated system minimizes cabling, reduces noise, and simplifies operation, making it highly efficient for both laboratory and on-site measurements.

Features

- Integrated HPGe Detector - High-purity germanium detector ensures excellent energy resolution for precise gamma spectroscopy
- Embedded Digital Multichannel Analyzer (MCA) - Enables real-time spectrum acquisition and processing without external electronics
- Internal Battery Operation - Offers several hours of autonomous use for field measurements
- Compact All-in-One Design - Reduces cabling and simplifies deployment in any environment
- On-board ruggedized display - large and bright to fit the whole spectrum or a part of it since software is adopted for "mobile view mode"
- Analytical Spectroscopy Software - Supports spectrum analysis, nuclide identification, and reporting
- Advanced Spectroscopy Software - allows applying Monte-Carlo simulation results to the analytical software to make sure correct measurement result in case of complex geometry of the measured object



Partner Ludlum Measurements



Ludlum Measurements, Inc. conçoit et fabrique des instruments et des technologies de détection des rayonnements. Fondée en 1962, elle propose une large gamme d'instruments de détection de rayonnements, développés pour aider à surveiller la sécurité du personnel et de l'environnement. Les instruments sont utilisés dans des applications telles que la surveillance de routine du personnel et du matériel, la sécurité des frontières et les situations d'intervention d'urgence.

Product offering

Model 26 - Frisker with Geiger Mueller Pancake



Model 26-1 Frisker with integrated GM Pancake - Ludlum



Model 26-3 - High Range Frisker



Model 26S - Integrated Scintillator Frisker



Model 3000 Digital Survey Meter - Ludlum



Model 3001 Multi-Detector Survey Meter - Ludlum



Model 3002 Alpha-Beta Digital Survey Meter



Model 3003 Series Multi-Detector Ratemeter / SCA



Model 3014 Dual-Detector Digital Survey Meter / SCA



Model 9DP Pressurized Ion Chamber



Model 9DP-1 Pressurized Ion Chamber



Model 9DP* Ambient Dose Ion Chamber



**Model 9DP-1*
Ambient Dose Ion
Chamber**



**Model 3-IS-1
Intrinsically Safe
Gamma Ratemeter**



**Model 3-IS
Intrinsically Safe
Survey Meter**



**Model 12-4 Neutron
Dose Survey Meter**



**Model 30-4 Digital
Neutron Survey Meter**



**Model 12-4-7 Neutron
Dose Survey Meter**



**Model 3007 Series
Neutron Dose Survey
Meter With Optional
Internal Gamma
Detector**



**Model 30-7 Series
Lightweight Digital
Neutron Survey Meter**



**Model 12 General
Purpose Survey Meter**



**Model 14C General
Purpose Survey Meter**



**Model 16 General
Purpose Survey Meter**



**Model 18 General
Purpose Survey Meter**



**Model 3 General
Purpose Survey Meter**



**Model 3A General
Purpose Survey Meter
with Alarm**



**Model 3-97 Gamma
Survey Meter**



**Model 195 with Model
43-132 High Range
Alpha Ion Chamber**



Model 3-98 125I & Alpha-Beta-Gamma Survey Meter



Model 194 Dose Equivalent Rate Meter



Model 2403 Pocket-Size Survey Meter



Model 2402 Pocket-Size Survey Meter with Alarm



Model 35 Vehicle-Mounted Digital Survey Meter



Model 30 Digital Survey Meter - Ludlum



Model 44-9 Pancake GM Detector - Ludlum



Model 3001-MERK response kit



Model 3001-2RK Emergency Response & NORM Kit



Model 2241-3RK2 Emergency Response Kit



Model 26-2 - Integrated Frisker with Timed Frisk



Model 3019 Digital Background Survey Meter - Ludlum



Model 133-6 GM Detector - Ludlum



Model 133-4 GM Detector - Ludlum



Model 133-2 GM Detector - Ludlum



Model 44-3 NAL Low Energy Gamma Scintillator - Ludlum



**Model 44-2 NAL
Gamma Scintillator -
Ludlum**



**Model 44-1 Beta
Scintillator - Ludlum**



**Model 44-38 Energy
Compensated GM
Detector - Ludlum**



**Model 44-9 Ambient
Dose Equivalent Filter
- Ludlum**



**Model 44-9 Exposure
Filter Kit - Ludlum**



**Model 44-7 Alpha
Beta Gamma Detector
- Ludlum**



**Model 43-92 Alpha
Scintillator - Ludlum**



**Model 43-65 Alpha
Scintillator - Ludlum**



**Model 43-5 Alpha
Scintillator - Ludlum**



**Model 9DP Ambient
Dose Ion Chamber
Survey Meter -
Ludlum**



**Model 9DP-1 Ion
Chamber Survey
Meter - Ludlum**





Détection des radiations > Moniteurs portables

Model 26 - Frisker with Geiger Mueller Pancake

This Frisker with Geiger Mueller (GM) 26 is the simpler version of Ludlum's model 26-1.

Ludlum designed this device especially for frisking people and objects for alpha, beta and gamma contamination. This cable-less device consolidates the electronics and the detector into one ergonomic device. The frisker has a standard 15,51 cm² GM pancake detector and a large LCD display.



Features:

- Integrated, Lightweight Design Simplifies Frisking
- Protective Rubber Covering Enhances Ruggedness, Water Resistance, and Non-Slip Comfort
- Employs Standard 15.51 cm² GM Pancake Detector
- Ratemeter, MAX Hold, and Scaler Operating Modes
- Simple Two-Button Operation
- Count Rate and Scaler Alarms
- Automatic LCD Backlight Activation
- Wrist Cuff and Lanyard Included

Services supplémentaires

Afin d'assurer des performances optimales et la conformité aux normes réglementaires, PEO propose les services suivants pour cet appareil :

Service

✓ Inspections périodiques effectuées par des techniciens qualifiés afin d'évaluer le bon fonctionnement, d'identifier l'usure et de détecter rapidement les problèmes potentiels.

Entretien

✓ Mesures préventives, remplacement de pièces et contrôles de performance visant à prolonger la durée de vie opérationnelle de l'appareil et à maintenir une fiabilité constante.

Étalonnage

✓ Services d'étalonnage, effectués par des techniciens qualifiés. Chaque appareil reçoit un certificat d'étalonnage confirmant sa précision et sa conformité.

Tests d'étanchéité

✗ Test de fuite de rayonnement pour confirmer la sécurité du détecteur et sa conformité aux exigences applicables en matière de santé et de sécurité.

Ces services sont disponibles via PEO.

Pour prendre rendez-vous ou connaître les options contractuelles, veuillez contacter votre représentant PEO.

Acheter le produit

Demander un service

Posez une question

Trouver plus de produits



Détection des radiations > Moniteurs portables

Model 26-1 Frisker with integrated GM Pancake - Ludlum



Présentation :

Le détecteur intégré modèle 26-1 permet un contrôle rapide de la contamination d'une seule main grâce à sa conception tout-en-un pratique. Équipé d'un détecteur GM pancake, de commandes intuitives et d'un écran LCD rétroéclairé, il fournit des mesures de rayonnement fiables dans plusieurs unités et modes. Robuste, léger et résistant à l'eau, il est idéal pour une utilisation en intérieur comme en extérieur.

Caractéristiques :

- Conception ergonomique intégrée et légère
- Plastique résistant aux chocs avec joints en caoutchouc résistants à l'eau
- Utilise un détecteur GM Pancake standard de 15,51 cm²
- Affichage en mR/h, μ Sv/h, dpm, Bq, cpm ou cps
- Correction du temps mort (DTC) permettant des mesures gamma jusqu'à 500 mR/h ou jusqu'à 1999 μ Sv/h
- Fonctionnement simple à trois boutons
- Alarmes de taux de comptage, d'exposition, de dose et de comptage
- Rétroéclairage automatique de l'écran
- LED d'alarme rouge vif clignotante
- Comprend un bracelet, un couvercle de détecteur et une lanière



Services supplémentaires

Afin d'assurer des performances optimales et la conformité aux normes réglementaires, PEO propose les services suivants pour cet appareil :

Service

✓ Inspections périodiques effectuées par des techniciens qualifiés afin d'évaluer le bon fonctionnement, d'identifier l'usure et de détecter rapidement les problèmes potentiels.

Entretien

✓ Mesures préventives, remplacement de pièces et contrôles de performance visant à prolonger la durée de vie opérationnelle de l'appareil et à maintenir une fiabilité constante.

Étalonnage

✓ Services d'étalonnage, effectués par des techniciens qualifiés. Chaque appareil reçoit un certificat d'étalonnage confirmant sa précision et sa conformité.

Tests d'étanchéité

✗ Test de fuite de rayonnement pour confirmer la sécurité du détecteur et sa conformité aux exigences applicables en matière de santé et de sécurité.

Ces services sont disponibles via PEO.

Pour prendre rendez-vous ou connaître les options contractuelles, veuillez contacter votre représentant PEO.

Acheter le produit

Demander un service

Posez une question

Trouver plus de produits



Model 26-3 - High Range Frisker



Caractéristiques

- Conception ergonomique intégrée et légère
- Plastique résistant aux chocs avec joints en caoutchouc résistants à l'eau
- Utilise un détecteur GM Pancake standard de 15,51 cm²
- Affichage en mR/h, μ Sv/h, dpm, Bq, cpm ou cps
- Correction du temps mort (DTC) permettant des mesures gamma jusqu'à 1999 μ Sv/h (1000 mR/h)
- Fonctionnement simple à trois boutons
- Taux de comptage, taux de dose/d'exposition et alarmes de comptage
- Rétroéclairage automatique de l'écran
- LED d'alarme rouge clignotante
- Comprend un bracelet, un couvercle transparent pour le détecteur Pancake et une lanière

Compact, puissant et sans fil

Le modèle Ludlum 26-3 offre une détection rapide et fiable des rayonnements dans un boîtier robuste, résistant à l'eau et sans fil, idéal pour fouiller les personnes et inspecter les objets en toute simplicité.

Détection haute performance, affichage clair

Équipé d'un pancake GM de 15,51 cm², d'un signal sonore puissant et d'un grand écran LCD rétroéclairé à plage automatique, il fournit un retour d'information instantané. Passez de mR/h à μ Sv/h, dpm et Bq d'une simple pression sur un bouton.

Utilisation simple d'une seule main

Trois modes intuitifs (RATE, MAX et COUNT) offrent un contrôle précis pour la surveillance en temps réel, la capture des valeurs maximales et les relevés chronométrés. Le tout dans un outil durable et ergonomique.



Options de mesure polyvalentes

Affichez les mesures en nombre, en activité, en taux moyens ou en dose cumulée, selon vos besoins. Ajoutez le filtre de dose ambiante en option pour améliorer la réponse énergétique dans les mesures de dose.



Longue durée de vie des piles, configuration intelligente

Alimenté par seulement deux piles AA, le modèle 26-3 fonctionne pendant des centaines d'heures. Les paramètres peuvent être verrouillés ou ajustés en fonction des préférences de l'utilisateur ou du calibrateur.

Fonctionnalités conviviales

Un rétroéclairage réactif s'active en cas de faible luminosité, et le clic sonore peut être désactivé pour une utilisation discrète, ce qui est parfait pour les enquêtes de routine et les enquêtes sensibles.

Services supplémentaires

Afin d'assurer des performances optimales et la conformité aux normes réglementaires, PEO propose les services suivants pour cet appareil :

Service

✓ Inspections périodiques effectuées par des techniciens qualifiés afin d'évaluer le bon fonctionnement, d'identifier l'usure et de détecter rapidement les problèmes potentiels.

Entretien

✓ Mesures préventives, remplacement de pièces et contrôles de performance visant à prolonger la durée de vie opérationnelle de l'appareil et à maintenir une fiabilité constante.

Étalonnage

✓ Services d'étalonnage, effectués par des techniciens qualifiés. Chaque appareil reçoit un certificat d'étalonnage confirmant sa précision et sa conformité.

Tests d'étanchéité

✗ Test de fuite de rayonnement pour confirmer la sécurité du détecteur et sa conformité aux exigences applicables en matière de santé et de sécurité.

Ces services sont disponibles via PEO.

Pour prendre rendez-vous ou connaître les options contractuelles, veuillez contacter votre représentant PEO.

Acheter le produit

Demander un service

Posez une question

Trouver plus de produits

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 26S - Integrated Scintillator Frisker

- Lightweight Design - Only 0.35 kg (0.75 lb)
- Employs 1 x 1 Equivalent Scintillator Detector
- Sigma Audio (or Click Audio Possible) & Alarm Beep
- Displays in mR/hr, $\mu\text{Sv/h}$, dpm, Bq, cpm, or cps
- Simple Three-Button Operation
- Count Rate, Exposure, Dose, and Counting Alarms
- Automatic Display Backlight
- Bright Red Flashing ALARM LED





Détection des radiations > Moniteurs portables

Model 3000 Digital Survey Meter - Ludlum

Overview:

The Ludlum Model 3000 is a lightweight, durable radiation survey meter designed for alpha, beta, and gamma detection using external probes. It features a large LCD, audible alarms, and three operating modes (RATE, MAX, COUNT), with dual-unit readout capability. Built for field use with a splash-resistant, high-impact plastic housing, it supports data logging (up to 1000 points) and calibration via front panel or optional Lumic kits. Supplied ready-to-use with batteries and calibration certificate.



Features:

- Large, Backlit, Easy-To-Read LCD Screen
- Auto-Ranging
- RATE, MAX, and COUNT Modes of Operation
- Splash-Resistant Construction for Outdoor Use
- All-Digital Calibration
- USB Port
- Lightweight Yet Ruggedly Built
- Simple 5-Button Interface

Options:

- **Calibration & Configuration Kits** - Software packages for setup, calibration, and detector optimization, each with required USB cables
- **Data Logging Solutions** - Includes data logger kit and retrofit handle for enabling or upgrading internal data logging
- **Wireless & Serial Connectivity** - Bluetooth® linker for mobile devices; RS-232 and TTL serial port options for external interfacing
- **Audio Kit** - Headphone jack with adjustable stereo/mono headset for audible alerts
- **Carrying Solutions** - Rugged transport case and adjustable shoulder strap (case modification required)





Additional Services

To support optimal performance and compliance with regulatory standards, PEO offers the following services for this device:

✓ Service

✓ Maintenance

✓ Calibration

> Leakage Tests

These services are available through PEO.

For service appointments or contract options, please contact your PEO representative.

[Purchase Product](#)

[Request Service](#)

[Ask a question](#)

[Find more products](#)

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 3001 Multi-Detector Survey Meter - Ludlum

The Model 3001 Multi-Detector Survey Meter (Ludlum) is an ergonomically-designed, versatile, lightweight instrument which can support up to 4 external detectors. Each detector with its own user parameters and set of calibration.



Choose from a wide range of probes for any application: [Ludlum probes](#)

Model 3001 Multi-Detector Survey Meter features:

- max, rate and count modes of operation
- datalogging and headphone options
- large backlit LCD for ease of reading
- USB port
- ruggedly built and lighter weight
- splash-resistant construction for outdoor use
- Geiger-Mueller (GM), scintillator or proportional detector

Read more about the Model 3001 Multi-Detector Survey Meter on the [Ludlum website](#)

← **Back to partner**



Détection des radiations > Moniteurs portables

Model 3002 Alpha-Beta Digital Survey Meter

The Model 3002 is a durable, lightweight instrument designed for alpha and beta radiation survey with an external detector. It features a large, easy-to-read LCD screen and audible alarms and is controlled using a simple five-button interface. The unit body is made of high-impact plastic and splash resistant construction allows the instrument to be used outdoors.

Three modes of operation are available - RATE, MAX, and COUNT - which can be selected by pressing the MODE button. Measurements can be collected in cps, cpm, Bq, or dpm units. Pressing the α - β button switches between alpha, beta, or alpha+beta measurements. When enabled with the optional Lumic Data Logger Kit (see Options), data can be logged in any of the operational modes using the LOG button on the handle. Up to 1000 data points can be stored internally.

Instrument setup can be done either through the front-panel controls or via the Lumic Calibration Kit (see Options). The Model 3002 is shipped ready to use with batteries and calibration certificate.

Features

- Large Backlit LCD for Ease of Reading
- Auto Ranging, Dual Tone Audio Clicks
- All-Digital Calibration
- Alpha, Beta, or Alpha + Beta Measurements
- Rate, Max, and Count Modes of Operation
- 4-Button Intuitive Interface for Easy Operation
- Lighter Weight Yet Ruggedly Built
- Splash-Resistant Construction for Outdoor Use





Détection des radiations > Moniteurs portables

Model 3003 Series Multi-Detector Ratemeter / SCA

The Model 3003 is a durable, lightweight instrument designed for alpha, beta, gamma, or neutron radiation survey. It can support up to four external detectors, each with its own set of calibration and user parameters. The Model 3003i is a version that includes an internal GM or scintillation detector. The instrument features a large, easy-to-read LCD screen and audible alarms and is controlled using a simple seven-button interface. The unit body is made of high-impact plastic and splash resistant construction allows the instrument to be used outdoors.



Four modes of operation are available – RATE, MAX, INTG, and COUNT – which can be selected by pressing the MODE button. Measurements can be collected in two sets of units (primary and secondary) for RATE, MAX, and DOSE modes, unless alpha-beta detection is selected. The user can switch between the two sets of units by pressing the UNITS button. The DETECTOR button is used to switch between the active detector settings, indicated by the colored LEDs above the control buttons. When enabled with the Lumatic Data Logger Kit (see Options), data can be logged in any of the operational modes using the LOG button on the handle. Up to 1000 data points can be stored internally. The SCA ability allows a scintillator or proportional detector to be set up with an upper window, giving it higher sensitivity to a specific isotope or region. This instrument can be used with external alpha-beta detectors to display alpha, beta, or alpha+beta counts.

Instrument setup can be done either through the front-panel controls or via the Lumatic Calibration Kit (see Options). The Model 3003 is shipped ready to use with batteries and calibration certificate.

Features

- 4 Selectable & Configurable Detector Settings
- Single Channel Analyzer (SCA)
- Alpha, Beta, or Alpha+Beta Measurements
- 3003i: Internal Detector Option for Dose Measurements
- Rate, Max, Integrated Dose, and Count Modes
- 4-Button Intuitive Interface for Easy Operation
- 3-Button Handle Interface for One Handed Control
- Digital Calibration, Datalogging, Auto-Ranging, USB
- Bluetooth®, True RS-232, and Headphone Options

- Lightweight and Ruggedly Built
- Large Backlit LCD for Ease of Reading
- Alternative to Ludlum Models 18 and 2221



Détection des radiations > Moniteurs portables

Model 3014 Dual-Detector Digital Survey Meter / SCA

The Ludlum Model 3014 is a durable, lightweight instrument with both an internal energy-compensated gamma detector and a connection for an external detector. It features a large, easy-to-read LCD screen and audible alarms and is controlled using a simple five-button interface. The unit body is made of high-impact plastic and splash-resistant construction allows the instrument to be used outdoors.



Four modes of operation are available - RATE, MAX, INTG, and COUNT - which can be selected by pressing the MODE button. Measurements can be collected in two sets of units (primary and secondary) for RATE and MAX modes. The user can switch between the two sets of units by pressing the UNITS button. Pressing the DETECTOR button toggles the display between the internal and external detector readings. When enabled with the Lumatic Data Logger Kit (see Options), data can be logged in any of the operational modes using the LOG button on the handle. Up to 1000 data points can be stored internally. The SCA ability allows a scintillator or proportional detector to be set up with an upper window, giving it higher sensitivity to a specific isotope or region. This instrument can be used with external alpha-beta detectors to display alpha, beta, or alpha+beta counts.

Instrument setup can be done either through the front-panel controls or via the Lumatic Calibration Kit (see Options). The Model 3014 is shipped ready to use with batteries and calibration certificate.

Features

- Internal Gamma Detector for Survey / Accumulated Dose
- Can Be Used with a Variety of External Detectors
- General Purpose Survey Meter
- Rate, Max, Integrated Dose, and Count Modes
- Alpha, Beta, or Alpha+Beta Capable
- Single Channel Analyzer (SCA) Capable
- Large Backlit LCD for Ease of Reading
- 4-Button Intuitive Interface for Easy Operation
- 1-Button Handle Interface for Data Logging
- Digital Calibration, Data Logging, Auto-Ranging, USB
- Bluetooth, True RS-232, and Headphone Options
- Alternative to Ludlum Models 14C and 2221



Model 9DP Pressurized Ion Chamber

Overview:

The Ludlum Model 9DP is a compact, hand-held instrument engineered for reliable radiation monitoring in field environments. Designed for professionals across medical, industrial, and emergency response sectors, it ensures accurate assessment of radiological conditions with minimal operational complexity.



Features:

- **Measurement Range:** Background to 50 mSv/h (5 R/hr)
- **Display Modes:** Real-time Exposure Rate & user-selectable Integrated or Peak Exposure Rate
- **Display:** Sunlight-readable color screen
- **Detection Performance:** Auto-zeroing and auto-ranging functionality
- **Power Supply:** Rechargeable battery pack for extended field operations
- **Alarms:** Integrated audio and visual alarms for threshold breaches
- **Quality-of-Life:** Data logging, USB connectivity, and free firmware updates via the manufacturer's website

Optional additions:

- Software and USB cable for Dimension instrument setup.
- Log real-time data to Excel; available with or without USB cable.
- Adds headphone jack to the instrument.
- Adjustable stereo/mono headphones.
- Rechargeable AA battery pack (8x NiMH).
- Alkaline AA battery pack (8x standard).
- 10 μ Ci Cs-137 plastic check source.
- Rugged, waterproof medium transport case.
- 1.8 m nylon shoulder strap (case modification required).
- Mini USB keyboard for instrument setup.





Services supplémentaires

Afin d'assurer des performances optimales et la conformité aux normes réglementaires, PEO propose les services suivants pour cet appareil :

Service

✓ Inspections périodiques effectuées par des techniciens qualifiés afin d'évaluer le bon fonctionnement, d'identifier l'usure et de détecter rapidement les problèmes potentiels.

Entretien

✓ Mesures préventives, remplacement de pièces et contrôles de performance visant à prolonger la durée de vie opérationnelle de l'appareil et à maintenir une fiabilité constante.

Étalonnage

✓ Services d'étalonnage, effectués par des techniciens qualifiés. Chaque appareil reçoit un certificat d'étalonnage confirmant sa précision et sa conformité.

Tests d'étanchéité

✓ Test de fuite de rayonnement pour confirmer la sécurité du détecteur et sa conformité aux exigences applicables en matière de santé et de sécurité.

Ces services sont disponibles via PEO.

Pour prendre rendez-vous ou connaître les options contractuelles, veuillez contacter votre représentant PEO.

Acheter le produit

Demander un service



Posez une question

Trouver plus de produits



Détection des radiations > Moniteurs portables

Model 9DP-1 Pressurized Ion Chamber

The Model 9DP-1 is a digital, hand-held pressurized ion chamber that provides highly sensitive exposure measurements of gamma and x-ray radiation at energies above 25 keV and beta radiation at energies above 1 MeV. This meter is specially designed for radiography work where pulsed fields are being measured. It correctly integrates 50 ns pulses (and wider) that other systems typically miss or measure inaccurately. Another feature of this instrument is that the detector chamber is only pressurized to 2.5 atm (22 psig), thus avoiding all (USA) HAZMAT concerns for shipping and handling. However, this reduced pressure also reduces sensitivity, so the minimum “good” measurement point is 2 $\mu\text{Sv/h}$ (200 $\mu\text{R/hr}$).



Measurements and instrument status are displayed on a large 232K-color, backlit LCD screen. The screen displays the current exposure rate as well as simultaneously displaying either the integrated exposure rate or the peak exposure rate in Sv, R, Gy, or rem units. An additional mode, Pulsed Mode, locks the instrument in the highest measurement range in order to improve pulsed radiation response while sacrificing low radiation reading resolution.

The instrument is operated using the four push-buttons below the screen (ON/OFF, FUNCTION, AUDIO, ACK/RESET). In addition to the visual display, click audio proportional to the current exposure rate audibly indicates the exposure rate level. Two alarm levels can be set to alert the user whenever the pre-programmed level has been exceeded. Alarms are indicated on the display and by an audio tone. The instrument can also be configured for data logging. Logged data can either be stored in CSV format and written to a standard USB drive inserted in the instrument’s USB port, or written directly to a Microsoft Excel spreadsheet by connecting the instrument to a computer running Ludlum’s Model 9DP Logging Spreadsheet Software.

The Model 9DP parameter settings can be edited by connecting the instrument to a basic USB keyboard. Instrument setup and calibration can also be configured using the Ludlum Dimension Interface Kit, which includes the Dimension Configuration Manager Software and the required USB cable.

Features

- Range: 2 $\mu\text{Sv/h}$ to 500 mSv/h (200 $\mu\text{R/hr}$ to 50 R/hr)
- Special Design for Measuring Pulsed Fields
- Low Pressure Chamber is Non-Hazmat
- Shows Exposure Rate & Either Integrated Exposure or Peak Exposure Rate
- Pulsed Mode for Measuring Pulsed Radiation
- Sunlight Readable Color Display
- Auto-Zeroing & -Ranging
- Rechargeable Batteries
- Audio & Visual Alarms
- Data Logging
- USB Connectivity
- Free Firmware Updates Through Website



Détection des radiations > Moniteurs portables

Model 9DP* Ambient Dose Ion Chamber

Overview:

The Model 9DP* is a digital, hand-held ion chamber for measuring ambient dose equivalent from gamma, x-ray, and high-energy beta radiation. It features ICRU-compliant dose readings, a color LCD display, audio-visual alarms, and supports data logging via USB or Excel. Settings and calibration are configurable via USB keyboard or software.



Features:

- Provides ICRU-Based Ambient Dose Equivalent Measurements
- Range: Background to 50 mSv/h (5 rem/h)
- Shows Dose Rate & Either Integrated Dose or Peak Dose Rate
- Ambient Equivalent Dose or Dose Rate is Flat within 20% from 40 keV to 1.3 MeV
- Sunlight Readable Color Display
- Auto-Zeroing & -Ranging
- Rechargeable Batteries
- Audio & Visual Alarms
- Data Logging
- USB Connectivity
- Free Firmware Updates Through Website

Optional additions:

- Calibration and setup kit with software and USB cable
- Real-time data logging to Excel
- Headphone jack add-on
- Stereo/mono headphones
- Rechargeable battery pack (8x AA NiMH)
- Alkaline battery pack (8x AA)
- 10 μ Ci Cs-137 check source
- Rugged, waterproof transport case
- Adjustable shoulder strap (requires case modification)
- USB keyboard for configuration





Additional Services

To support optimal performance and compliance with regulatory standards, PEO offers the following services for this device:

- > Service
- > Maintenance
- > Calibration
- > Leakage Tests

These services are available through PEO.

For service appointments or contract options, please contact your PEO representative.

[Purchase Product](#)

[Request Service](#)

[Ask a question](#)

[Find more products](#)



Détection des radiations > Moniteurs portables

Model 9DP-1* Ambient Dose Ion Chamber

The Model 9DP-1* is a digital, hand-held pressurized ion chamber that provides highly sensitive ambient dose equivalent measurements of gamma and x-ray radiation at energies above 25 keV and beta radiation at energies above 1 MeV. Ambient dose equivalent is defined as the dose equivalent readout that would be measured at a (human) tissue depth of 10 mm. The Model 9DP-1* measures and displays the ambient dose equivalent in accordance with the ICRU (International Commission on Radiation Units) 30 cm tissue equivalent sphere. This requires a special ion chamber that can provide a conversion of the (air kerma) exposure rate to provide the ambient dose and dose rate.

This meter is also specially designed to measure pulsed radiation fields, correctly integrating 50 ns pulses (and wider) that other systems typically miss or measure inaccurately. Another feature is a detector chamber that is only pressurized to 2.5 atm (22 psig), eliminating (USA) shipping and handling HAZMAT concerns. However, this reduced pressure also decreases sensitivity, reducing the minimum measurement point to 2 $\mu\text{Sv/h}$ (200 $\mu\text{R/hr}$).

Measurements and instrument status are displayed on a large 232K-color, backlit LCD screen. The screen displays the current dose rate as well as simultaneously displaying either the integrated dose rate or the peak dose rate in Sv, R, Gy, or rem units. An additional mode, Pulsed Mode, locks the instrument in the highest measurement range in order to improve pulsed radiation response while sacrificing low radiation reading resolution.

The instrument is operated using the four push-buttons below the screen (ON/OFF, FUNCTION, AUDIO, ACK/RESET). In addition to the visual display, click audio proportional to the current dose rate audibly indicates the dose rate level. Two alarm levels can be set to alert the user whenever the pre-programmed level has been exceeded. Alarms are indicated on the display and by an audio tone. The instrument can also be configured for data logging. Logged data can either be stored in CSV format and written to a standard USB drive inserted in the instrument's USB port, or written directly to a Microsoft Excel spreadsheet by connecting the instrument to a computer running Ludlum's Model 9DP Logging Spreadsheet Software.



The Model 9DP parameter settings can be edited by connecting the instrument to a basic USB keyboard. Instrument setup and calibration can also be configured using the Ludlum Dimension Interface Kit, which includes the Dimension Configuration Manager Software and the required USB cable.

Features

- Provides ICRU-Based Ambient Dose Measurements
- Range: 2 $\mu\text{Sv/h}$ to 500 mSv/h (200 $\mu\text{R/hr}$ to 50 R/hr)
- Special Design for Measuring Pulsed Fields
- Low Pressure Chamber is Non-Hazmat
- Shows Dose Rate & Either Integrated Dose or Peak Dose Rate
- Ambient Equivalent Dose or Dose Rate Is Flat Within 30% from 60 keV to 1.3 MeV
- Sunlight Readable Color Display
- Auto-Zeroing & -Ranging
- Rechargeable Batteries
- Audio & Visual Alarms
- Data Logging
- USB Connectivity
- Free Firmware Updates Through Website



Model 3-IS-1 Intrinsically Safe Gamma Ratemeter

This intrinsically safe general purpose ratemeter is patterned after Ludlum's best-selling Model 3. It was designed and tested to USA standards for intrinsic safety, permitting it to be used in potentially explosive atmospheres.

This instrument includes an internally housed, energy compensated GM detector with a gamma detection range of 0.1 mR/hr to 1.0 R/hr. The Model 3 type instruments are well known for their accuracy and long-lasting dependability. The cast aluminum instrument housing, with its separate battery compartment and accompanying metal handle, offer an industrial robustness and quality that promote long-lasting protection and instrument life. The front panel controls include a rotary switch for selecting the four-decade range, instrument shut-off, and battery test, an audio on/off switch, a fast/slow response switch, and a count reset button.



Features

- Intrinsically Safe Gamma Survey Meter
- Rugged
- 4-Range Analog Ratemeter
- Built-in Energy Compensated GM Detector
- 0.1 mR/hr to 1.0 R/hr Detector Range

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 3-IS Intrinsically Safe Survey Meter

This intrinsically safe general purpose ratemeter is patterned after Ludlum's best-selling Model 3. It was designed and tested to USA standards for intrinsic safety, permitting it to be used in potentially explosive atmospheres. The Model 3-IS can only be used with select detectors to sustain the intrinsic safety rating. Click the tab below to view compatible detectors.

Like the Model 3 before it, the 3-IS retains the well-deserved reputation for accuracy and long-lasting dependability. The cast aluminum instrument housing, with its separate battery compartment and accompanying metal handle, offer an industrial robustness and quality that promote long-lasting protection and instrument life. The front-panel controls include a rotary switch for selecting the four-decade range, instrument shut-off, and battery test, an audio on/off switch, a fast/slow response switch, and a count reset button. The analog meter comes in a variety of measurement ranges and units to support the external radiation detector selected.

A one meter (39 in.) straight type detector cable equipped with special connectors designed to prevent quick or accidental disconnection in the field is included in the price of the instrument.

Features

- Intrinsically Safe
- Rugged
- 4-Range Analog Ratemeter
- Supports GM & Scintillation Type Detectors





Model 12-4 Neutron Dose Survey Meter

The Model 12-4 is an industry standard neutron dose rate instrument that conforms to the RPG curve with a measuring range of 0 to 100 mSv/h (0 to 10,000 mrem/hr) from thermal to 12 MeV.

The detector is a 22.9 cm (9 in.) moderated ^3He tube with a gamma background rejection up to 100 mSv/h (10 R/hr). The ratemeter is a four-decade analog meter, designed with a cast aluminum instrument housing incorporating a separate battery compartment, and accompanying metal handle. This design delivers industrial robustness and quality, promoting long-lasting protection and instrument life.

The front-panel controls include a rotary switch for selecting the four-decade range, instrument shut-off, and battery test; an audio on/off switch; a fast/slow response switch; a count reset; and high-voltage test push-button. The Model 12-4 is a complete turn-key system and includes two "D" cell batteries.



Features

- Moderated Neutron Detector
- Range: 0 to 100 mSv/h (0 to 10,000 mrem/hr)
- Gamma Rejection up to 0.1 Sv/h (10 R/hr)
- Rugged
- 4-Range Analog Meter



Détection des radiations > Moniteurs portables

Model 30-4 Digital Neutron Survey Meter

The Ludlum Model 30-4 joins the Model 30 digital display unit with a 22.9 cm (9 in.) REM ball containing a ^3He detector, thereby providing a significant weight reduction and more compact, maneuverable instrument for determining neutron dose rates. Three modes of operation – RATE, MAX, and COUNT – are available for the user. Measurements can be collected in two sets of units (primary and secondary) for RATE and MAX modes in cps, cpm, rem/hr, or Sv/h units. An internal switch is used to enable or disable the front-panel setup feature to protect desired settings from inadvertent modification. Setup is also available via software from Ludlum Measurements.



This instrument features a large, easily-readable LCD (liquid crystal display) that may be rotated for maximum ease of use for the operator. The connecting cable is threaded through the rugged carrying handle to simplify use. In addition the display unit may be detached from REM ball permitting the operator to position the detector and the display unit to best advantage within the limits of the cable length. Other features are an audio warning tone and easy, intuitive, user-friendly design. Splash-resistant construction allows the Model 30 to be used in outdoor environments. The instrument body is constructed of lightweight, durable, high-impact plastic.

Features

- Multi-Function Digital Display Unit
- Low-Weight Device Substitutes for Ratemeter
- Simple Switching Between Two Sets of Measurement Units
- Moderated Neutron Detector
- Range: 0 to 99.9 mSv/h (0 to 9.99 rem/hr)
- Display Unit Detaches for Greater Versatility



Model 12-4-7 Neutron Dose Survey Meter

The Model 12-4-7 is a neutron dose rate instrument that conforms to the RPG curve with a measuring range of 0 to 100 mSv/h (0 to 10,000 mrem/hr) from thermal to 12 MeV neutrons.

The detector is a 19.5 cm (7.7 in.), moderated ^3He tube with a gamma background rejection up to 100 mSv/h (10 R/hr). The ratemeter is a four-decade analog meter, designed with a cast aluminum instrument housing incorporating a separate battery compartment, and accompanying metal handle. This design delivers industrial robustness and quality, promoting long-lasting protection and instrument life.

The front-panel controls include a rotary switch for selecting the four-decade range, instrument shut-off, and battery test; an audio on/off switch; a fast/slow response switch; a count reset; and high-voltage test push-button. The Model 12-4-7 is a complete turn-key system and includes two "D" cell batteries.

Features

- Smaller, Lighter 7-inch Polyethylene Ball
- Moderated Neutron Detector
- Range: 0 to 100 mSv/h (0 to 10,000 mrem/hr)
- Gamma Rejection up to 0.1 Sv/h (10 R/hr)
- Rugged
- 4-Range Analog Meter
- Complete Turn-Key System





Détection des radiations > Moniteurs portables

Model 3007 Series Neutron Dose Survey Meter With Optional Internal Gamma Detector

The Model 3007 Series of neutron dose survey meters combines a handheld digital meter with a 19.5 cm (7.7 in.) diameter REM ball containing a ^3He detector to measure and monitor neutron radiation. Several versions of these instruments are available. The Model 3007 and Model 3007B use similar detectors that only differ by the boron concentration in the internal borated layer. The Model 3007 has a lower boron concentration and offers a typical sensitivity of 10 cpm per $\mu\text{Sv/h}$ (100 cpm per mrem/hr), but tends to overrespond in the 5 keV range. The Model 3007B has a higher boron concentration and a lower sensitivity, typically 4.5 cpm per $\mu\text{Sv/h}$ (45 cpm per mrem/hr), but does not have the same overresponse issue. The Model 3007-1 has a higher pressure detector that offers greater sensitivity, typically 17 cpm per $\mu\text{Sv/h}$ (170 cpm per mrem/hr), but falls under shipping regulations due to the pressure. “i” versions include an internal gamma detector in the meter for exposure or dose measurements.



Each instrument features a large, easy-to-read LCD screen and is controlled using a simple five-button interface. The meter body is made of high-impact plastic, and splash resistant construction allows the instruments to be used outdoors.

Four modes of operation are available – RATE, MAX, COUNT, and DOSE – which can be selected by pressing the MODE button. Measurements can be collected in two sets of units (primary and secondary) for RATE and MAX modes in cps, cpm, Bq, dpm, mR/hr, mrem/hr, or $\mu\text{Sv/h}$ units. The user can switch between two sets of units by pressing the UNITS button. Audible alarms can be set in all modes of operation. When enabled with the optional Lumic Data Logger Kit, data can be logged in any of the operational modes using the LOG button on the handle. Up to 1000 data points can be stored internally.

Instrument setup can be done either through the front-panel controls or via the Lumic Calibration Kit. The Model 3007 is shipped ready to use with batteries and a calibration certificate.

Features

- Small & Light 19.5 cm (7.7 in.) REM Ball
- Moderated Neutron Detector
- Range: 0 - 100 mSv/h (0 - 10,000 mrem/hr)
- Gamma Rejection up to 0.1 Sv/h (10 R/hr)
- "i" Versions: Internal Gamma Detector Option for Exposure/Dose Measurements
- Rate, Max, Integrated Dose & Count Modes
- Digital Calibration, Data Logging, Auto-Ranging, USB
- Large, Backlit, Easy-to-Read LCD Screen
- Simple 5-Button Interface



Détection des radiations > Moniteurs portables

Model 30-7 Series Lightweight Digital Neutron Survey Meter

The Model 30-7 Series are handheld, lightweight neutron dose detectors that join the Model 30 digital meter with a 19.5 cm (7.7 in) diameter REM ball containing a ^3He detector. The instruments use similar detectors that only differ by the boron concentration in the internal borated layer. The Model 30-7 detector has a lower boron concentration and offers a greater sensitivity, typically 10 cpm per $\mu\text{Sv/h}$ (100 cpm per mrem/hr), but tends to overrespond in the 5 keV range. The Model 30-7B detector has a higher boron concentration and a lower sensitivity, typically 4.5 cpm per $\mu\text{Sv/h}$ (45 cpm per mrem/hr), but does not have the same overresponse issue as the Model 30-7.



Three modes of operation - RATE, MAX, and COUNT - are available for the user. Measurements can be collected in two sets of units (primary and secondary) for RATE and MAX modes in cps, cpm, rem/hr, or Sv/h units. An internal switch is used to enable or disable the front-panel setup feature to protect desired settings from inadvertent modification. Setup is also available via the Lumic calibration software (see Options tab).

Each instrument features a large, easily-readable LCD (liquid crystal display) that may be rotated for maximum ease of use by the operator. The connecting cable is threaded through the rugged carrying handle to simplify use. In addition, the display unit may be detached from REM ball, permitting the operator to position the detector and the display unit to best advantage within the limits of the cable length. Other features are an audio warning tone and easy, intuitive, user-friendly design. Splash-resistant construction allows the Model 30-7 Series to be used in outdoor environments. The display body is constructed of lightweight, durable, high-impact plastic.

Features

- Small & Light 19.5 cm (7.7 in.) REM Ball
- Moderated Neutron Detector
- Digital Display with Adjustable Viewing Angle
- Range: 0 to 99.9 mSv/h (0 to 9.99 rem/hr)
- Low-Weight Unit Provides Same Readings as Standard REM-ball from Bare AmBe and Lower Energies
- Includes Adjustable Shoulder Strap

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 12 General Purpose Survey Meter

This general purpose, handheld analog ratemeter supports GM, proportional, and scintillation type detectors. The analog meter face comes in a variety of options to support the measurement units and ranges for the optional external detector selected.

The cast aluminum instrument housing with its separate battery compartment and accompanying metal handle offer an industrial robustness and quality that promote long lasting protection and instrument life. The front panel controls include a rotary switch for selecting the four-decade range, instrument shut-off and battery test, an audio on/off switch, a fast/slow response switch, a high voltage display button, and a count reset button.

A one-meter (39 in.) straight type detector cable with "C" style connector and batteries are included in the price of the instrument.

Features

- Low Price
- Rugged
- 4-Range Analog Ratemeter
- Supports GM, Proportional, and Scintillation Type Detectors
- Greater Than 2000 Hour Battery Life





Model 14C General Purpose Survey Meter

This general purpose, handheld analog ratemeter supports operating two separate radiation detectors. A switch allows the user to select between the internally mounted GM detector with an exposure range of 0 - 20 mSv/h (0 - 2000 mR/hr) or an external GM or scintillator detector of choice (see table below).

The cast aluminum instrument housing, with its separate battery compartment and accompanying metal handle, offer an industrial robustness and quality that promote long-lasting protection and instrument life. The front-panel controls include a rotary switch for selecting the five-decade range and instrument shut-off, an audio on/off switch, a fast/slow response switch, a high voltage display button, and a battery test button.

The analog meter face comes in a variety of options to support the measurement units and ranges for the additional external detector selected. A one meter (39 in.) straight type detector cable with "C" style connector is included in the price of the instrument.



Features

- Low Price
- Rugged
- 5-Range Analog Ratemeter
- Operates Two Detectors
 - Built-in Internal GM Detector (0 to 2000 mR/hr)
 - External GM or Scintillation Detector

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 16 General Purpose Survey Meter

This general purpose, handheld analog ratemeter supports GM, proportional, and scintillation type detectors. The cast aluminum instrument housing, with its separate battery compartment and accompanying metal handle, offers an industrial robustness and quality that promotes long-lasting protection and instrument life.

The front-panel controls include a rotary switch for selecting the four-decade range, instrument shut-off, and battery test, an audio on/off switch, a fast/slow response switch, a high-voltage display button, a count reset button, and a window in/out switch. The analog meter face comes in a variety of options to support the measurement units and ranges for the additional external detector selected.

A one-meter (39 in.) long straight type detector cable with “C” style connector is included in the price of the instrument.

Features

- Low Price
- Rugged
- 4-Range Analog Ratemeter
- Supports GM, Proportional, & Scintillation Type Detectors
- Adjustable Window





Détection des radiations > Moniteurs portables

Model 18 General Purpose Survey Meter

This general purpose, handheld analog ratemeter supports GM, proportional, and scintillation type detectors. The analog meter face comes in a variety of options to support the measurement units and ranges for the optional external detector(s) selected.

The unique capability this instrument offers is its ability to select between three different detector setups. This feature facilitates switching detectors in the field without requiring calibration adjustments. In addition to the three-position detector selector switch, the front panel also provides the user with the capability to switch the operating window between an open (gross) channel and a pre-selected narrower setting when targeting specific energies. Other front-panel controls include a rotary switch for selecting the four-decade range, instrument shut-off and battery test, an audio on/off switch, a fast/slow response switch, a high-voltage display button, and a count reset button.

The cast aluminum instrument housing with its separate battery compartment and accompanying metal handle offer an industrial robustness and quality that promote long-lasting protection and instrument life. A one meter (39 in.) straight type detector cable with "C" style connector is included in the price of the instrument.

Features

- Low Price
- Rugged
- 4-Range Analog Ratemeter
- Supports GM, Proportional & Scintillation Type Detectors
- Adjustable Window
- 3-Detector, High-Voltage Setups



← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 3 General Purpose Survey Meter

The Model 3 is Ludlum's best selling, general purpose, handheld, analog ratemeter known for accuracy and long-lasting dependability. It comes in a variety of measurement ranges and units to support the external radiation detector selected.

The cast aluminum instrument housing with a separate battery compartment and metal handle offer an industrial robustness and quality that promote long-lasting protection and instrument life. The front-panel controls include a rotary switch for selecting the four-decade range, instrument shut-off, and battery test, an audio on/off switch, a fast/slow response switch, and a count reset button.

A one meter (39 in.) straight type detector cable with "C" style connector is included in the price of the instrument.

Features

- Low price
- Rugged
- 4-Range Analog Ratemeter
- Supports GM & Scintillation Type Detectors
- Greater than 2000 Hour Battery Life



← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 3A General Purpose Survey Meter with Alarm

The Model 3A is identical to Ludlum's best selling, general purpose, Model 3 handheld analog ratemeter with the addition of an audible alarm. It is likewise known for its accuracy and long-lasting dependability. The cast aluminum instrument housing with its separate battery compartment and accompanying metal handle offer an industrial robustness and quality that promote long-lasting protection and instrument life.



The front-panel controls include a rotary switch for selecting the four-decade range, instrument shut-off, and battery test, an audio on/off switch, a fast/slow response switch, and a count reset button. The analog meter comes in a variety of measurement ranges and units to support the external radiation detector selected.

A one meter (39 in.) long straight type detector cable with "C" style connector is included in the price of the instrument..

Features

- Low Price
- Rugged
- 4-Range Analog Ratemeter
- Alarms
- Supports GM & Scintillation Type Detectors



Détection des radiations > Moniteurs portables

Model 3-97 Gamma Survey Meter

The Model 3-97 provides a great solution for locating potential contamination and then accurately measuring the exposure rate, or for simply measuring the ambient exposure levels over a wide range. The instrument is equipped with an internal 2.5 x 2.5 cm (1 x 1 in.) NaI detector that is highly sensitive to gamma, with readings in the μR range between 0 to 3000 $\mu\text{R/hr}$ (0 to 3 mR/hr). The instrument is additionally equipped with an external Model 44-38 energy-compensated GM to extend the detection range up to 200 mR/hr. The ratemeter is Ludlum's venerable Model 3-series, which employs a robust cast aluminum instrument housing with a separate battery compartment for long-lasting protection and instrument life. The front-panel controls include a rotary switch for selecting the 4-decade range, instrument shut-off and battery test, audio on/off switch, fast/slow response switch, count reset button, and internal/external detector switch. The Model 3-97 is a complete turn-key system with the detector cable and two "D" cell batteries.



Features

- Wide Range from $\mu\text{R/hr}$ to 200 mR/hr
- High-Sensitivity Gamma
- Rugged
- 4-Range Analog Ratemeter

[← Back to partner](#)



Détection des radiations > Moniteurs portables

Model 195 with Model 43-132 High Range Alpha Ion Chamber

The high-range alpha ion chamber system uses the Model 43-132 Ion Chamber and the Model 195 readout unit. The Model 43-132 is designed to enhance alpha detection, although it is also sensitive to beta-gamma radiation. The Model 195 has a rugged cast aluminum instrument housing with sealed battery compartment that offer an industrial robustness and quality that promote long-lasting protection and instrument life.





Détection des radiations > Moniteurs portables

Model 3-98 ¹²⁵I & Alpha-Beta-Gamma Survey Meter

Ludlum's Model 3-98 is uniquely configured to optimize measurements for ¹²⁵I and any alpha, beta, or gamma contamination. The dual detector design allows the user to select the detector for the task at hand. The internally-housed GM pancake detector can be used to measure gamma. This detector's face can be exposed via a slide located along the bottom of the instrument, thus making it sensitive to alpha and beta as well. The external NaI detector, Ludlum Model 44-3, is optimized for low-energy gamma from ¹²⁵I.



The ratemeter is Ludlum's venerable Model 3-series, which employs a robust, cast aluminum instrument housing with a separate battery compartment for long-lasting protection and long instrument life. The front-panel controls include a rotary switch for selecting the 4-decade range, instrument shut-off and battery test, audio on/off switch, fast/slow response switch, count reset button, and internal/external detector switch. Also included are a standard 1-meter (39 inch) cable with series "C" connector (others available), detector clip, and two "D" cell batteries.

Features

- Dual Purpose Detection
- ¹²⁵I & Alpha-Beta-Gamma Contamination
- 4-Range Analog Ratemeter
- Rugged Construction
- 0 to 500 kcpm
- User-Selectable Internal and External Detectors



Model 194 Dose Equivalent Rate Meter

Features

- Accurate (Energy-Flat) Ambient Dose Equivalent Rate Measurements
- Eliminates High False Readings of Typical microR Meters
- Rugged Scintillator, Will Not Leak
- Low Range: Background to 19.99 $\mu\text{Sv/h}$ (1999 $\mu\text{rem/hr}$)
- High Range: 1 to 1999 $\mu\text{Sv/h}$ (0.1 to 199.9 mrem/hr)
- Improved Replacement for Bicron Microrem
- “/E” Extended Version Has Low-Energy, 3.2 mg/cm^2 Window for Operation Below 50 keV



← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 2403 Pocket-Size Survey Meter

The Model 2403 is a pocket-size ratemeter with an analog display that may be connected to a number of detectors. This unit supports mR/hr exposure and cpm count-rate measurements. The metallic case and convenient size make this a nice tool to for a wide variety of applications.

Features

- Pocket-Size Ratemeter
- Accommodates a Variety of Detectors
- Metallic Case
- Easy to Use



← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 2402 Pocket-Size Survey Meter with Alarm

The Model 2402 is a pocket-sized ratemeter with an analog display that may be connected to a number of available detectors. This unit supports mR/hr exposure and cpm count-rate measurements. It also has a built-in audio and visual alarm. The metallic case and convenient size make this a nice tool to for a wide variety of applications.

Features

- Pocket-Size Ratemeter
- Accommodates a Variety of Detectors
- Audio & Visual Alarm
- Metallic Case
- Easy to Use





Détection des radiations > Moniteurs portables

Model 35 Vehicle-Mounted Digital Survey Meter

The Ludlum Model 35 is a versatile, lightweight, vehicle mounted instrument with an external detector used for alpha, beta, or gamma radiation survey. It remains unobtrusive until an alarm is reached. At that point the monitor can be quickly removed from the mount for closer inspection. Three modes of operation – RATE, MAX, and COUNT – are available for the user. Measurements can be collected in two sets of units (primary and secondary) for RATE and MAX modes in cps, cpm, Bq, dpm, R/hr, rem, or Sv/h units. The user can switch between two sets of chosen units by simply pressing the Units button.



An internal switch is used to enable or disable the front-panel setup feature to protect desired settings from inadvertent modification. Setup is also available via software available from Ludlum Measurements.

This instrument features a large, easily-readable LCD (liquid crystal display), an audio warning tone, and easy, intuitive, user-friendly design. Splash-resistant construction allows the Model 35 to be used outdoors. The instrument body is made of lightweight, durable, high-impact plastic. The Model 35 is shipped ready to use with batteries and calibration certificate.

Features

- Includes Rotatable Ball-Mount Stand
- Optional Windshield and Under-Dash Mounts Available
- Powered by Connected Vehicle or Internal Batteries
- Large Backlit Auto Ranging LCD with Adjustable Viewing Angle
- Simple Green, Yellow, and Red Status Lights
- 3-Button Intuitive Interface for Easy Operation
- USB Port and All-Digital Calibration

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 30 Digital Survey Meter - Ludlum

The Ludlum Model 30 is a versatile, lightweight, instrument used with an external detector for alpha, beta, or gamma radiation survey. Three modes of operation – RATE, MAX, and COUNT – are available for the user. Measurements can be collected in two sets of units (primary and secondary) for RATE and MAX modes in cps, cpm, Bq, dpm, R/hr, rem, or Sv/h units.



The user can switch between two sets of chosen units by simply pressing the Units button. An internal switch is used to enable or disable the front-panel setup feature to protect desired settings from inadvertent modification. Setup is also available via software available from Ludlum Measurements.

This instrument features a large, easily-readable LCD (liquid crystal display), a piercing audio warning tone, and easy, intuitive, user-friendly design. Splash-resistant construction allows the Model 30 to be used outdoors. The unit body is made of lightweight, durable, high-impact plastic.

The Model 30 is shipped ready to use with batteries and calibration certificate.

Model 30 Digital Survey Meter features

- attaches to detector allowing one-handed operation
- large backlit auto-ranging LCD with adjustable viewing angle
- simple green, yellow, and red status indicators
- 3-button intuitive interface for easy operation
- USB port and all-digital calibration
- available in stretch scope configuration

View compatible probes [here](#)

Download the datasheets below or contact our product specialist.

← **Back to partner**



Détection des radiations > Moniteurs portables

Model 44-9 Pancake GM Detector - Ludlum

The Model 44-9 Pancake GM Detector (Ludlum) is proven to be the most popular radiation detector used throughout the world. This detector is sensitive to alpha, beta and gamma radiation. The Model 44-9 Pancake GM Detector is enclosed within a rough metal cage but sized and shaped very convenient. It is ideal for checking contamination on people and objects.



Model 44-9 Pancake GM Detector features:

- window area: 15.51 cm² (2.4 in²) active, 12.26 cm² (1.9 in²) open
- pancake-type, halogen-quenched GM detector
- efficiency (4π): 5% for 14C; 22% for 90Sr/90Y; 19% for 99Tc; 32% for 32P; 15% for 239Pu, ≤ 1% for 99mTc; 0.2% for 125I
- sensitivity (137Cs gamma): 3300 cpm/mR/hr
- weight: 0,5 kg

Read more about the Model 44-9 Pancake GM Detector on the [Ludlum website](#)

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 3001-MERK response kit

Medical Environment Response Kit

This response kit is an ideal tool for any nuclear medicine department or emergency department. It offers a detector complement optimized for medical isotopes and includes personal radiation monitoring. The kit fits securely in a foam-padded, padlockable, rugged storage and transport case, and will easily meet the radiation requirements of the emergency response plan.



The Model 3001-MERK Medical Environment Response Kit includes:

- Model 3001 Multi-Detector Digital Survey Meter
- Model 44-9, Alpha-Beta-Gamma Detector
- Model 44-2, Gamma Scintillator Detector
- Model 44-142, Beta Scintillator Detector
- Model 25 or Model 25-1 Personal Radiation Monitor
- 1 μCi (^{137}Cs) check source
- 1 m (39 in.) long detector cable
- Carrying case for easy transportation of the kit to the affected site

Ludlum offers several versions of pre-packaged response kits suitable for a wide variety of applications. If you desire more or different detectors, or other changes to our standard kits, please contact us regarding a customized kit.



Détection des radiations > Moniteurs portables

Model 3001-2RK Emergency Response & NORM Kit

The Model 3001-2RK is composed of two dependable, high-quality detectors matched with the versatile Model 3001 survey meter and packaged in a rugged transport and storage case.

The Model 3001 can be configured with up to four detector setups, enabling the user to quickly exchange detectors in the field. Once the detector system is configured, a user can select a detector's parameters with a press of a button and choose the desired measurement units and operation mode.

The kit includes the Model 44-9 alpha-beta-gamma detector for general survey measurements and the Model 44-2 high-sensitivity gamma detector for locating the source of high readings. The case is cushioned with dense foam padding, and has a large, comfortable grip, a manual pressure relief valve, and padlockable hasps. The kit also includes a 1 μCi (^{137}Cs) check source, check source holder, cable, and batteries, making this kit ready-to-go for emergency response or NORM applications.

Ludlum offers several versions of pre-packaged response kits suitable for a wide variety of applications. If you desire more or different detectors, or other changes to our standard kits, please contact us regarding a customized kit.

Features

- Ready-to-Go Kit in Rugged Case
- Ergonomic Survey Meter with 4 Selectable and Configurable Detector Settings
- Measures Alpha, Beta, and Gamma Contamination
- Convenient In-Field Detector Switching
- For Emergency Response or NORM Applications
- Includes:
 - Model 3001 Multi-Detector Survey Meter
 - Model 44-9 Alpha-Beta-Gamma Detector
 - Model 44-2 High Energy Gamma Detector
 - Check Source, Cable, Batteries
 - Transport & Storage Case with dense foam padding





Détection des radiations > Moniteurs portables

Model 2241-3RK2 Emergency Response Kit

All of the basic radiation measurement tools likely required to rapidly react to a radiological emergency are conveniently assembled in the Model 2241-3RK2 Response Kit. The digital, auto-ranging Model 2241-3 scaler-ratemeter stores 4 parameter setups to allow for quick detector changes in the field.

The Model 2241-3 has a backlit LCD and user-adjustable alert and alarm for both scaler and ratemeter modes. The rugged transport and storage case is foam-padded with custom cutouts for the instruments and gives air- and watertight, corrosion-proof, and padlockable protection. A check source with mountable holder is included to ensure instruments are functioning properly.

Ludlum offers several versions of pre-packaged response kits suitable for a wide variety of applications. If you desire more or different detectors, or other changes to our standard kits, please contact us regarding a customized kit.

Features

- Ready-to-Go Response Kit in Rugged Case
- Digital Scaler-Ratemeter with User-Adjustable Audible & Visual Alarms
- Includes Check Source and Cable
- Measures Alpha, Beta, and Gamma Contamination
- Convenient In-Field Detector Switching



← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 26-2 - Integrated Frisker with Timed Frisk

- Integrated, Lightweight Design
- High-Impact Plastic with Water-Resistant Rubber Seals
- GM Pancake Detector
- Ratemeter, Peak, and Timed Frisk Operating Modes
- Simple Two-Button Operation
- Automatic LCD Backlight
- Comfortable Non-Slip Grip, Includes Lanyard & Adjustable Wrist Strap
- Daylight-Visible Green & Red Status LEDs



← Back to partner



Détection des radiations > Moniteurs portables

Model 3019 Digital Background Survey Meter - Ludlum

The Model 3019 Digital Background Survey Meter (Ludlum) is a device with an internal scintillation detector used for gamma radiation survey for background to 500 $\mu\text{Sv/hr}$.



Model 3019 Digital Background Survey Meter features:

- internal CsI, scintillator with 175 cpm/ $\mu\text{R/hr}$ sensitivity detector
- count, rate and max
- 4-button intuitive interface for easy operation
- ruggedly built and light weight
- splash-resistant construction
- bright LED and sigma audio simplifies searching
- large backlit LCD for ease of reading
- USB port
- autoranging

Read more about the Model 3019 Digital Background Survey Meter on the [Ludlum website](#)

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 133-6 GM Detector - Ludlum

The Model 133-6 GM Detector (Ludlum) is a gamma survey detector (GM) that can be used with any scaler instrument, ratemeter or area monitor that delivers the appropriate amount of voltage (see datasheet below) with an input sensitivity of $30 \pm 10\text{mV}$.



Model 133-6 GM Detector features:

- waterproof (optional)
- halogen quenched
- stainless steel tube
- range: $40 \mu\text{Sv/h}$ to 10Sv/h
- energy compensated GM

Read more about the Model 133-6 GM Detector on the [Ludlum Website](#)

← Back to partner



Détection des radiations > Moniteurs portables

Model 133-4 GM Detector - Ludlum

The Model 133-4 GM Detector (Ludlum) is a gamma survey detector (GM) that can be used with any scaler instrument, portable ratemeter or area monitor that delivers the appropriate amount of voltage (see datasheet below) with an input sensitivity of $30 \pm 10\text{mV}$.



Model 133-4 GM Detector features:

- waterproof (optional)
- halogen quenched
- stainless steel tube
- range: 0.01 mSv/h to 100 mSv/h
- energy compensated GM

Read more about the Model 133-4 GM Detector on the [Ludlum Website](#)

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 133-2 GM Detector - Ludlum

The Model 133-2 GM Detector (Ludlum) is a gamma survey detector (GM) that can be used with any scaler instrument, portable ratemeter or area monitor that delivers the appropriate amount of voltage (see datasheet below) with an input sensitivity of $30 \pm 10\text{mV}$.



Model 133-2 GM Detector features:

- stainless steel tube
- energy compensated GM
- waterproof (optional)
- halogen quenched
- range: $1 \mu\text{Sv/h}$ – 10mSv/h

Read more about the Model 133-2 GM Detector on the [Ludlum Website](#)

← Back to partner



Détection des radiations > Moniteurs portables

Model 44-3 NAL Low Energy Gamma Scintillator - Ludlum

The Model 44-3 NAL Low Energy Gamma Scintillator (Ludlum) is a detector for 125I and low energy gamma radiation survey.



Model 44-3 NAL Low Energy Gamma Scintillator features:

- entry window: 18.4 mg/cm²
- weight: 0.5 kg
- sensitivity: 675 cpm/μR/hr (125I)
- window area: 5 cm² open and active
- efficiency (4π): 33.5%–125I (based on 129I efficiency of 18%)
- detector: scintillator, 2.5 cm diameter x 1 mm thick NaI(Tl) crystal
- photomultiplier tube: 3.8 cm diameter

Read more about the Model 44-3 NAL Low Energy Gamma Scintillator on the [Ludlum website](#)

← Back to partner



Détection des radiations > Moniteurs portables

Model 44-2 NAL Gamma Scintillator - Ludlum

The Model 44-2 NAL Gamma Scintillator (Ludlum) is a detector for low-level, wide-energy gamma radiation survey.



Model 44-2 NAL Gamma Scintillator features:

- detector: scintillator, 2.5 x 2.5 cm (1 x 1 in.) (Dia x L) thick NaI
- efficiency: 125I for 7%; 57Co for 10%; 137Cs for 3%; 60Co for 3%
- sensitivity: 175 cpm/ μ R/hr (137Cs gamma)
- background: 1800 cpm
- photomultiplier tube: 2.86 cm (1.125 in.) diameter, magnetically shielded

Read more about the Model 44-2 NAL Gamma Scintillator on the [Ludlum website](#)

← **Back to partner**



Détection des radiations > Moniteurs portables

Model 44-1 Beta Scintillator - Ludlum

The Model 44-1 Beta Scintillator (Ludlum) is a detector for beta radiation survey.



Model 44-1 Beta Scintillator features:

- window area: 9.7 cm² active and open
- efficiency (4π): 7% for 14C
- background (10 μR/hr): 100 cpm
- weight: 0.3 kg
- detector type: 4.3 x 0.03 cm (1.7 x 0.01 in.) (Dia x L) plastic scintillator

Read more about the Model 44-1 Beta Scintillator on the [Ludlum website](#)

← Back to partner



Détection des radiations > Moniteurs portables

Model 44-38 Energy Compensated GM Detector - Ludlum

The Model 44-38 Energy Compensated GM Detector (Ludlum) is a device for beta and gamma radiation survey.



Model 44-38 Energy Compensated GM Detector features:

- weight: 0.5 kg
- detector: 30–45 mg/cm² stainless steel wall halogen quenched GM
- sensitivity: 1200 cpm per mR/hr (137Cs gamma) with window closed
- range: $\pm 10\%$ up to 50 mR/hr without DTC and up to 500 mR/hr with DTC
- background: 25 cpm open, 20 cpm closed
- gamma energy response (window closed): within 20% of 137Cs (662 keV) from 60 keV to 1.3 MeV

Read more about the Model 44-38 Energy Compensated GM Detector on the [Ludlum website](#)

← Back to partner



Détection des radiations > Moniteurs portables

Model 44-9 Ambient Dose Equivalent Filter - Ludlum

The Model 44-9 Ambient Dose Equivalent Filter (Ludlum) is an expansion on the Model 44-9 Pancake GM Detector. It is an energy compensation filter that flattens the energy response to facilitate measuring Ambient Equivalent Dose.



Model 44-9 Ambient Dose Equivalent Filter features:

- can be purchased separately or together with a Model 44-9 Pancake GM Detector
- flattens the response to within $\pm 20\%$ referenced to ^{137}Cs (662 keV) over an energy range of 20 keV to 1.2 MeV
- easy to mount and remove

Dose Equivalent Filter Response (green line):

Read more about the Model 44-9 Ambient Dose Equivalent Filter on the [Ludlum website](#)

← Back to partner



Détection des radiations > Moniteurs portables

Model 44-9 Exposure Filter Kit - Ludlum

The Model 44-9 Exposure Filter Kit (Ludlum) is an expansion on the Model 44-9 Pancake GM Detector. It is an energy compensation filter that flattens the energy response to facilitate measuring exposure.



Model 44-9 Exposure Filter Kit features:

- flattens the response to within $\pm 20\%$ referenced to ^{137}Cs (662 keV) over an energy range of 33 keV to 1.2 MeV
- easy to mount and remove
- filter can be purchased separately or together with a Model 44-9 Pancake GM Detector

Exposure Filter Response (blue line):

Read more about the Model 44-9 Exposure Filter Kit on the [Ludlum website](#)

← Back to partner



Détection des radiations > Moniteurs portables

Model 44-7 Alpha Beta Gamma Detector - Ludlum

The Model 44-7 Alpha Beta Gamma Detector (Ludlum) is a device for alpha, beta and gamma survey (sample counting).



Model 44-7 Alpha Beta Gamma Detector features:

- end window, halogen-quenched GM detector
- 6 cm² (0.93 in²) active; 5 cm² (0.78 in²) open window area
- 1.7 ± 0.3 mg/cm² mica window
- 2% for 14C; 10% for 90Sr/90Y; 7% for 99Tc; 7% for 239Pu; 0.1% for 125I efficiency (4π)
- 2100 cpm/mR/hr sensitivity (137Cs gamma)
- anodized aluminum housing
- 0.5 kg weight

Read more about the Model 44-7 Alpha Beta Gamma Detector on the [Ludlum website](#)

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 43-92 Alpha Scintillator - Ludlum

The Model 43-92 Alpha Scintillator (Ludlum) is a device for alpha contamination survey.



Model 43-92 Alpha Scintillator features:

- window area: active: 100 cm² (15.5 in²) open: 88 cm² (13.6 in²)
- weight: 0.5 kg
- window: 0.8 mg/cm² metalized polyester (1.2 mg/cm² recommended for outdoor use)
- scintillator: ZnS(Ag)
- efficiency (4π): typically 20% for ²³⁹Pu
- removable protective screen
- background radiation: 3 cpm or less
- photomultiplier tube: 2.9 cm (1.13 in.) diameter

Read more about the Model 43-92 Alpha Scintillator on the [Ludlum website](#)

← Back to partner



Détection des radiations > Moniteurs portables

Model 43-65 Alpha Scintillator - Ludlum

The Model 43-65 Alpha Scintillator (Ludlum) is a detector designed for alpha radiation survey when used in combination with a general purpose survey meter, ratemeter or scaler instrument.



Model 43-65 Alpha Scintillator features:

- 63 cm² active; 50 cm² open (window area)
- ZnS(Ag) scintillator
- 0.8 mg/cm² metalized polyester window
- 3.8 cm (1.5 in.) diameter photomultiplier tube
- efficiency (4π): 17% for ²³⁹Pu; 17% for ²³⁰Th

Read more about the Model 43-65 Alpha Scintillator on the [Ludlum website](#)

← **Back to partner**



Détection des radiations > Moniteurs portables

Model 43-5 Alpha Scintillator - Ludlum

The Model 43-5 Alpha Scintillator (Ludlum) is a detector developed for alpha radiation survey when used with a common purpose survey meter, ratemeter or scaler instrument. The detector housing is assembled of aluminum alloy with beige powder coat for easy maintenance and durability.



Model 43-5 Alpha Scintillator features:

- efficiency (4π): 13% for ^{239}Pu
- scintillator: ZnS(Ag)
- 0.8 mg/cm² metalized polyester window
- background: 3 cpm or less
- weight: 0.9 kg
- window area: 76 cm² (11.9 in²) active, 50 cm² (7.8 in²) open

Read more about the Model 43-5 Alpha Scintillator on the [Ludlum website](#)

← Back to partner



Détection des radiations > Moniteurs portables

Model 9DP Ambient Dose Ion Chamber Survey Meter - Ludlum

The Model 9DP Ion Chamber Survey Meter is a highly sensitive pressurised ion chamber meter. It doesn't only provide a measurement of exposure, but also of exposure rate. The meter measures and displays data conform the ICRU (International Commission on Radiation Units) tissue equivalent.

AMBIENT DOSE EQUIVALENT

Ambient dose equivalent, is the dose equivalent readout that would be measured at a tissue depth of 10 mm. To measure this, the device requires a special ion chamber to provide a conversion of the exposure rate.

This model can simultaneously display the rate, integrated value and highest rate seen by the instrument. If desired, the user can reset the integrated value.



FEATURES

This chamber survey meter has a nice 256K colour, bit-mapped display, which provides an optimised presentation of the data. The screen is also accompanied with icons that inform the user of the active functions and instrument status. The device can write all logged data in csv format.

When the device's alarms go off, the display will flash colours and, if the user wants, it can also make an acknowledgeable sound.

If you want more information about this Ion chamber survey meter, go to [our partner's website!](#)

BENEFITS

- Provides ICRU-Based ambient dose measures
- The colour display is also readable in sunlight
- Auto zeroing and ranging
- Rechargeable batteries
- Alarm function
- USB Connectivity
- Data logging
- Chamber volume of 230 cc volume pressurised to 8 atmospheres (117 psi)

- 4-button control



Model 9DP Overview https://youtu.be/UYPJQNVeC_I



Model 9DP* overview

9DP Control Panel Overview <https://youtu.be/HusnR4e90yA>



Model 9DP Control Panel Overview



SCAN TO VIEW
VIDEO



SCAN TO VIEW
VIDEO

If you want to know more about this model...

Read our article!

Or contact PEO!

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Model 9DP-1 Ion Chamber Survey Meter - Ludlum

Ludlum designed the Model 9DP-1 Ion Chamber Survey Meter for radiography work where pulsed fields are being measured. This instrument correctly integrates 50 nanosecond pulses (and wider) that other systems typically miss or measure incorrectly.

The detector chamber is only pressurised to 1,36 atm (20 psi). The device has a nice 256-colour, bit mapped display, which provides an optimised presentation of the data. The instrument also has with icons that inform the user of the active functions and instrument status and which make it simple to use.



FEATURES

This chamber survey meter has an alarm that uses colour changes in the screen and an acknowledgeable audio output. It also has a rechargeable battery that delivers up to 30 hours of operation between charges.


The instrument writes the data in csv format for convenient retrieval.

The device measures both exposure and exposure rate, and can simultaneously display the exposure rate, integrated value and highest rate seen by the instrument.

BENEFITS

- Special design for measuring pulsed fields
- Low pressure chamber is non-hazmat
- Range from 0-500 mGy/h
- Sunlight readable colour display
- Auto zeroing & rangin
- Rechargeable batteries
- Alarming capability
- Data logging

If you want to know more, read [our article](#), or take a look at [our partner's website](#)!



Model 9DP Overview https://youtu.be/UYPJQNVeC_I



SCAN TO VIEW VIDEO

9DP instrument overview

9DP Control Panel Overview <https://youtu.be/HusnR4e90yA>



SCAN TO VIEW VIDEO

9DP control panel overview

How To Decompress the Model 9DP <https://youtu.be/JzbUaH9kfjU>



SCAN TO VIEW VIDEO

Decompressing the Ion Chamber



Partner **Tracerco**



Tracerco est un leader mondial de la détection et de la mesure des radiations. Il propose une gamme complète de moniteurs portables et de dosimètres électroniques personnels. Ses instruments sont conçus pour une surveillance précise et en temps réel des niveaux de radiation, garantissant ainsi la sécurité et la conformité dans divers secteurs.

Product offering

Contamination Monitor T401 - Tracerco



Dose Rate Monitor T402 & T402HR - Tracerco



Contamination Monitor T403 - Tracerco



T406 X-ray Monitor



Intrinsically Safe Radiation Dose Rate Monitor (T202) Tracerco™



NORM Monitor-IS - Tracerco





Détection des radiations > Moniteurs portables

Contamination Monitor T401 - Tracerco

The Tracerco™ T401 contamination monitors are suitable for those working in oil and gas, medical and life sciences, nuclear, CBRNe and emergency services, NDT, manufacturing, and environmental and waste management industries.

These monitor benefit from high-level functionality with added environmental tolerance, and they are a highly cost-effective monitor where intrinsic safety is not a concern.

Tracerco™ T401 contamination monitor is particularly suited to the detection of radioactive contamination, and this typically arises where man-made or naturally occurring isotopes are processed. This includes nuclear power, land remediation, research and development and medicine applications.

They also offer a number of additional key features, such as operational reliability, a direct surface ability mode and peak reading to make life easier for the worker.

The Tracerco™ T401 provides excellent sensitivity for the detection of alpha and beta radiation.

Other benefits include:

- Dual bar graph meter display: 0-1000cps
- Digital numeric display provides automatic direct translation to Bq/cm² for 14+ pre-programmed nuclides, natural and man-made
- Detachable radiation probe with up to 1.5 metres of extendable cable
- Optional extension arm for surveying contaminated pipework, drains, laboratory floors and so on
- Probe stepwise rotatable through 90° for internal surface measurements
- Backlight facility
- Audible response with adjustable alarm thresholds
- Ruggedised nylon 6/6 construction and modular integrated electronics provide an all-weather instrument



[← Back to partner](#)



Détection des radiations > Moniteurs portables

Dose Rate Monitor T402 & T402HR - Tracerco

The non-intrinsically safe radiation (contamination) Dose Rate Monitors T402 & T402HR offers an alternative to the Tracerco™ T202 Dose Rate Monitor. The instrument is designed for use in a wide range of industrial applications where radioactive substances are present.



Specifications Dose Rate Monitor T402 & T402HR Tracerco

Contamination Dose Rate Monitor T402 & T402HR

[← Back to partner](#)



Détection des radiations > Moniteurs portables

Contamination Monitor T403 - Tracerco

The Tracerco™ T403 Radiation Contamination Monitor is designed to meet the challenge of combining the operational reliability under adverse conditions with excellent sensitivity and robust construction.



Specifications Contamination Monitor T403 from Tracerco

Contamination Monitor T403 - Tracerco



Détection des radiations > Moniteurs portables

T406 X-ray Monitor

The Tracerco™ T406 X-ray radiation monitor is an advanced radiation monitoring device designed for professionals in oil and gas, medical and life sciences, nuclear, CBRNe and emergency services, NDT, manufacturing and industrial, and/collections/monitors/products/tracerco-t406-x-ray-monitor environmental and waste management industries.

Unlike other radiation survey meters on the market, the Tracerco™ T406 enables rapid radiation level detection, helping users identify peak radiation measurements and minimise exposure to potential radiation leaks during operations.

Benefits of the Tracerco™ T406 X-ray monitor:

- Hygienic design - smooth lines and an easy-to-clean finish make it ideal for environments with a risk of disease transmission through hand contact, such as food processing, airport security, and hospital settings.
- Easy and safe to use - designed to be lightweight and easy to carry, with the ability to be operated remotely in demanding environments.
- Audible response - with alarm set thresholds for enhanced radiation safety.



← [Back to partner](#)



Détection des radiations > Moniteurs portables

Intrinsically Safe Radiation Dose Rate Monitor (T202) Tracerco™

The Tracerco T202 dose rate monitor provides key operational features like peak dose rate memory and personal dose integration. Tracerco designed the monitor specifically to combine intrinsic safety with robust and reliable characteristics.

The monitor is suitable for all kinds of markets like:

- Oil and gas
- First responders
- Military
- Life sciences
- Mining
- Nuclear
- Medical
- Environmental agencies



TRACERCO DOSE RATE MONITOR BENEFITS

- Intrinsically safe, so no need for a hot work permit
- Reads and records peak measurements so you can measure radiation levels remotely
- It can be used in every weather
- Adjustable alarm thresholds
- Lightweight
- Digital bar graph display and dose rate integration
- Easy to decontamination

If you want to know more about Tracerco Dose rate monitors, take a look at [our partner's site!](#)



Need advice or do you have a question?

Contact PEO!



NORM Monitor-IS - Tracerco

Overview:

The Tracerco™ NORM Monitor-IS is a groundbreaking, ATEX-approved radiation monitoring device with dual probe capabilities. Using either a Geiger Muller (GM) detector or a scintillator probe, it enables users to monitor naturally occurring radioactive material (NORM) in all conditions for the first time.

It is lightweight and easy to use, yet also robust and reliable. It comes complete with a practical and secure carrying holster for ease of use.

The Tracerco™ NORM Monitor-IS is available with different combinations of handset and probes depending on your requirements.

Benefits of the Scintillation Probe:

- Robust and suitable for use in challenging conditions
- Enables radiation surveys of external walls for internal NORM deposits
- 360° detection capability for comprehensive radiation monitoring
- $\mu\text{R/h}$ option available for USA

Benefits of the GM Probe:

- Detects alpha and beta radiation
- High sensitivity to lead-210 NORM
- Provides Bq/cm^2 output for typical NORM isotopes
- Measurement modes: CPS, $\mu\text{Sv/h}$ (Scintillator), CPS, Bq/cm^2 (GM)
- All modes have background subtraction option CPM

Additional Key Features:

- One-touch integrate function for detecting very low radiation levels with increased accuracy.
- Live background subtraction and multiple measurement modes, including counts per second (CPS), counts per minute (CPM), dose rate, and surface activity.
- Easy recalibration - recalibration can be performed without the handset (spare probes can be supplied to eliminate downtime).
- Adjustable alarm thresholds for enhanced radiation safety.
- Easy to clean and decontaminate - Scintillator: IP67, GM: IP34, Handset: IP65.
- Large, easy-to-read LCD screen with bar graph and backlight for improved usability in low-light environments.



Partner **Polimaster**



Polimaster est un leader mondial des solutions de détection et de surveillance des rayonnements. Il propose une gamme complète d'instruments conçus pour détecter, identifier et mesurer les rayonnements ionisants dans divers environnements. Sa gamme de produits comprend des détecteurs portables, des dosimètres électroniques personnels, des identificateurs isotopiques portables, des portiques de détection et des systèmes de détection mobiles, tous conçus pour répondre aux exigences rigoureuses des secteurs de la sécurité, des interventions d'urgence et des applications industrielles.

Product offering

PM1401K-3M
Multipurpose Hand-
Held Radiation
Monitor/Identifier



PM1401K-3P
Multipurpose Hand-
Held Radiation
Monitor/Identifier



PoliPack® G-S
Backpack Radiation
Detector



PoliPack® GN
Backpack Radiation
Detector



PoliPack® G
Backpack Radiation
Detector



PoliPack® GN-S
Backpack Radiation
Detector



← [Back to partner](#)



Détection des radiations > Identificateurs d'isotopes portables

PM1401K-3M Multipurpose Hand-Held Radiation Monitor/Identifier

PM1401K-3M model is a gamma-only radiation monitor without a neutron detector which is designed for quick and reliable measurement of gamma dose rate, detection of alpha, beta, and gamma sources, measurement of alpha and beta radiation flux density, acquisition of gamma spectra, identification of radioisotopes, and measurement of food/soil contamination with ^{137}Cs

Features

- Storage of up to 10000 events and 1000 spectra
- Audible, visual and external vibration alarm
- Categorization of identified radionuclides
- Shock and water resistant IP65 case
- Adjustable radionuclide libraries
- USB communication with PC
- Built-in GPS module

Applications

- Customs and border control
- HAZMAT and CBRNe teams
- Emergency services
- Police and security
- Industrial facilities
- First responders





Détection des radiations > Identificateurs d'isotopes portables

PM1401K-3P Multipurpose Hand-Held Radiation Monitor/Identifier

Gamma-neutron model suitable for various radiation control tasks.

The **PM1401K-3 series** of radiation monitors comprises a wide range of all-in-one devices for radiation detection, dose rate, contamination measurements, spectrometry, and radionuclide identification.

The **PM1401K-3P model** is the **gamma-neutron model** suitable for various radiation control tasks, including measurement of ambient dose equivalent rate, detection of alpha, beta, gamma, and neutron sources, measurement of alpha and beta radiation flux density, acquisition of gamma spectra, identification of radioisotopes, and measurement of food/soil contamination with ^{137}Cs .



Features

- Storage of up to 10000 events and 1000 spectra
- Audible, visual, and external vibration alarm
- Categorization of identified radionuclides
- Shock and water-resistant IP65 case
- Adjustable radionuclide libraries
- USB communication with PC
- Built-in GPS module

Operation principle

The PM1401K-3P continuously measures ambient dose equivalent rate $\dot{H}^*(10)$ of photon radiation in the wide energy range, detects alpha, beta, gamma, and neutron radiation, measures alpha and beta radiation flux density, operates as a gamma radiation spectrometer and radioisotope identifier, and measures food/soil contamination with ^{137}Cs radionuclide.

← [Back to partner](#)



Détection des radiations > Moniteurs portables

PoliPack® G-S Backpack Radiation Detector

Spectroscopic Gamma-only Backpack Radiation Detector.

The **PoliPack® G-S** is a **gamma-only** Backpack-Based Radiation Detection System (BRD) equipped with spectroscopic gamma detectors for identifying radionuclides. It is carried in a compact backpack and controlled remotely via the wired control unit or a smartphone with the free Polismart® iOS and Android App.

The **PoliPack® BRDs** are rugged, lightweight, and fast-deploying devices that provide prompt and reliable detection, location, and identification of multiple and masked isotopes. The device is ideal for undercover radiation surveys in crowded areas, addressing the problems of orphaned and maliciously introduced sources and ensuring security before and during mass events. Radionuclides libraries are uploaded in the BRD and can be customized by users.



← [Back to partner](#)



Détection des radiations > Moniteurs portables

PoliPack® GN Backpack Radiation Detector

Gamma-Neutron Backpack Radiation Detector.

The **PoliPack® GN** is a **gamma-neutron** Backpack-Based Radiation Detection System (BRD) equipped with a highly sensitive portable radiation monitor carried in a compact backpack and controlled remotely via the wired control unit or a smartphone with the free Polismart® iOS and Android App.

The **PoliPack® BRDs** are rugged, lightweight, and fast deployable devices that provide prompt and reliable detection, location, and identification of multiple and masked isotopes. The device is ideal for undercover radiation surveys in crowded areas, addressing the problems of orphaned and maliciously introduced sources and ensuring security before and during mass events.



← [Back to partner](#)



Détection des radiations > Moniteurs portables

PoliPack® G Backpack Radiation Detector

Gamma-only Backpack Radiation Detector.

The **PoliPack® G** is a **gamma-only** Backpack-Based Radiation Detection System (BRD) equipped with a highly sensitive portable radiation monitor carried in a compact backpack and controlled remotely via the wired control unit or a smartphone with the free Polismart® iOS and Android App.

The **PoliPack® BRDs** are rugged, lightweight, and fast-deploying devices that provide prompt and reliable detection, location, and identification of multiple and masked isotopes. The device is ideal for undercover radiation surveys in crowded areas, addressing the problems of orphaned and maliciously introduced sources and ensuring security before and during mass events.



← [Back to partner](#)



Détection des radiations > Moniteurs portables

PoliPack® GN-S Backpack Radiation Detector

Spectroscopic Gamma-Neutron Backpack Radiation Detector.

The **PoliPack® GN-S** is a **gamma-neutron** Backpack-Based Radiation Detection System (BRD) equipped with **spectroscopic** gamma detectors for identifying radionuclides. It is carried in a compact backpack and controlled remotely via the wired control unit or a smartphone with the free Polismart® iOS and Android App.

The **PoliPack® BRDs** are rugged, lightweight, and fast deployable devices that provide prompt and reliable detection, location, and identification of multiple and masked isotopes. The device is ideal for undercover radiation surveys in crowded areas, addressing the problems of orphaned and maliciously introduced sources and ensuring security before and during mass events. Radionuclides libraries are uploaded in the BRD and can be customized by users.





Partner Bertin Instruments



Bertin Instruments est un fournisseur mondial de solutions avancées de détection des radiations et de surveillance environnementale, spécialisé dans les détecteurs portables, les dosimètres électroniques personnels, les systèmes de surveillance environnementale et les technologies de gestion des déchets et du recyclage. Ses instruments sont conçus pour répondre aux exigences rigoureuses des installations nucléaires, des équipes d'intervention d'urgence et des agences environnementales.

Product offering

<p>MINITRACE CSDF - Bertin Instruments</p> 	<p>MiniTRACE S5 - Saphymo</p> 	<p>MiniTRACE γ</p> 	<p>SaphyRAD S</p> 
<p>SaphyRAD C</p> 	<p>AlphaE - Bertin Instruments</p> 	<p>SaphyRAD E Multiprobe - Bertin Instruments</p> 	<p>SaphyRAD MS Dom-420 - Bertin Instruments</p> 



MINITRACE CSDF - Bertin Instruments

MiniTRACE CSDF is a unique multipurpose meter for contamination control, survey, dose rate and X Rays radiation measurement.

The MiniTRACE CSDF is a multipurpose instrument fulfilling the functions of a contamination, survey and dose rate meter. It is designed to improve the detection and the quantification of radiation contamination, making this a frontline tool in the protection against uncontrolled distribution of radioactive material. MiniTRACE CSDF provides several functions and measurement modes such as the dose rate, the activity or the count rate.

With the activity and surface contamination modes, different nuclides can be selected from the inbuilt library. The surface contamination mode is calibrated according to ISO 7503-1. Combined with the right accessories, wipe tests (surface contamination) and food tests (food contamination) can be performed. A mean value mode and a count up mode are provided to increase instrument accuracy.



Datasheet

Radiation type

- Alpha, beta and gamma

Detector type

- Geiger-Mueller pancake, active counter area 15.5 cm², active diameter 44.5 mm, window 2.0 mg/cm², energy compensated

Display unit

- $\mu\text{Sv/h}$, cps, Bq, Bq/cm² and Bq/L

Measurement range

- Dose rate: up to 5,000 $\mu\text{Sv/h}$ (100 mR/h)
- Pulses: up to 10,000 cps (300,000 cpm)
- Activity (depends on the radionuclide): up to 100 000 Bq (999,000 dpm)
- Surface contamination (depends on the radionuclide): up to 5,000 Bq/cm² (30,000 dm/cm²)
- Food: up to 100,000 Bq/l (1,000,000 pCi/l)

Gamma sensitivity

- 4.3 cps/ $\mu\text{Sv/h}$

Energy Range

- 26 keV to 1.25 MeV, lid has to be closed

Sensitivity

- Co60: 0.41 cps/Bq/cm²; C14: 1.65 cps/Bq/cm²; Sr90+: 10.65 cps/Bq/cm²; Am-14: 4.19 cps/Bq/cm²; Cl36: 9.57 cps/Bq/cm²; Cs137: 11.15 cps/Bq/cm²; U238: 4.19 cps/Bq/cm²; I131: 9.71 cps/Bq/cm²

Display

- 6-digit LCD display, plus 5-digit alpha numeric display for alarm- and status messages

Grid

- 0.8 stainless steel, 80% transparency, easily removable

Integration time

- Automatic, with count up mode adjustable

Energy supply

- 2 Mignon batteries (type: LR6, AA, MN 1500) 1.5V

Battery autonomy

- Up to 2,000 h

Built-in sensors

- IR-interface for software communication



Benefits

Easy and fast monitoring

- MiniTRACE CSDF is easy to use (2 buttons interface) and provides a very fast response time (1sec.). It can also be set up with the optional DataVIEW software.

All-in-one survey meter

- MiniTRACE CSDF allows multipurpose measurements for dose rate H*(10) (μSv/h), count rate (cps), activity (Bq), surface contamination (Bq/cm²) and food contamination (Bq/L). Radionuclide can also be selected.

Designed for harsh environments

- MiniTRACE CSDF is compact and robust with its strong housing protected with a rubber boot. It is suitable for long time operations (battery lifetime: 2,000 h).

Technologies

MiniTRACE CSDF is a unique multipurpose meter for contamination, survey, dose rate, X Rays, food and wipe test measurements. It is equipped with a 15.55 cm² Geiger-Mueller pancake detector and a 0.8 mm stainless steel grid. In addition to the verification of contamination, it is ideally suited to measuring the environmental dose rate equivalent (H*(10)).

MiniTRACE CSDF displays values in cps, µSv/h, Bq, Bq/cm² and Bq/L. For the Bq and Bq/cm² modes, the user can select different nuclides with built in nuclide specific calibration library (Cs137, Am241, I131, Sr90, U238, C14, Cl36, Co60).

The Bq/cm² mode (for surface contamination) is calibrated according to ISO 7503-1. MiniTRACE CSDF offers a special mode for food measurement: it measures the activity level found in the liquid or smashed food, with a state-of-the-art food measuring kit.

Accessories

- Protective rubber cover (included)
- Communication kit (incl. DataVIEW software and IR transceiver)
- Transparent plastic protection

- Belt pouch
- Suitcase (Pelicase)
- Wipe test kit

- Food measuring kit
- Emergency case
- Pressure-tight container for air transport

← **Back to partner**



Détection des radiations > Moniteurs portables

MiniTRACE S5 - Saphymo

The MiniTRACE S5 is a contamination meter designed to improve the safety of workers in all different kinds of fields. It's very sensitive and responds within a second.

Because the device is very user-friendly, it's very easy to detect possible spots of contamination in the controlling areas. The 6-digit display shows the activity value with a fixed decimal point.

The MiniTRACE has four pre-programmed alarm thresholds, but users can also adjust these to their personal needs.



This contamination meter is not only easy to use, but it's also very fast. If the device detects something, it will respond within a second. The device is applicable to many fields, like nuclear power plants, research centers, hospitals, police, fire brigades and the army.

BENEFITS OF THE MINITRACE S5

- High sensitivity
- Fast response time
- Compact and robust
- Ergonomic design
- Easy two-button operation
- 4 alarm thresholds
- Visual and audible alarm output
- Infrared interface
- X-ray sensitivity of >5 keV

If you want to read more about dose rate meters from Bertin, visit [their website!](#)

If you are in doubt about what MiniTRACE suits you best...

Read this!



Détection des radiations > Moniteurs portables

MiniTRACE γ

Light & sturdy, the MiniTRACE γ survey meter measures personal exposure, along with X & Gamma radiations, to improve workers' safety in hazardous environments.

The MiniTRACE γ is available in 2 versions - S10S & S100S - each with its own energy & measurement range.

In accordance with the ALARA principle (As Low As Reasonably Achievable), the MiniTRACE γ allows for the assessment of personal exposure hazard faced by workers in controlled zones of nuclear power plants, reprocessing facilities, treatment centers & hospitals, etc. to help them better adapt their daily work according to the risk.

Ergonomic & easy to use, it also meets the operational needs of public service's units, such as firefighters, first responders, HAZardous MATerial teams, early warning & rapid response cells, radiation protection specialists (PCR), etc.

Fitted with fast response time (≈ 1 second), the MiniTRACE γ survey meter measures instantaneously the ambient dose equivalent rate $H^*(10)$ or the gamma radiation exposure levels, with a high level of autonomy (approximately 2,000 hours).

The MiniTRACE γ is also equipped with a built-in memory able to save up to 650 measured values of instant & accumulated radiation dose.

Both MiniTRACE γ S10S & S100S are available in radio version (S10R & S100R), allowing for survey meters to be integrated into a ShortLINK/SkyLINK communication network, with a maximum reach of 20 kilometers.





Détection des radiations > Moniteurs portables

SaphyRAD S

The SaphyRAD S is a multiprobe survey meter developed to cover the needs of the nuclear and security market. This rugged, sensitive, and functional survey meter includes a wide and bright LCD display monitors and measures dose and Gamma dose rates in harsh environments even by non-specialists. Equipped with a full range of external probes, this versatile survey meter can discriminate Alpha/Beta radiation, monitor surface contamination, with reliability and accuracy, it can also measure dose rate in hard-to-reach areas and be used to research radioactive sources. In addition, the SaphyRAD S has an integrated simulator that is perfectly suited for training purposes. By utilizing a simulation probe, the user can recreate an Alpha/Beta contamination, enabling training in authentic conditions without the need for radioactive sources.



Benefits

- Robust: designed for use in harsh environments
- Large, high-resolution colour display
- Integrated simulation mode for training
- Designed for use with CBRN personal protective clothing
- Integrated GPS
- Specific algorithm for fast and reactive detection
- Large dose rate range: from 0.05 $\mu\text{Sv/h}$ to 10 Sv/h
- Complete range of external probes for source tracking and measuring multiple contamination, specially designed for use by non-radiation specialists.

← **Back to partner**



Détection des radiations > Moniteurs portables

SaphyRAD C

The SaphyRAD C is a versatile multiprobe contamination meter used for monitoring Alpha and Beta contamination in harsh environments. It has been developed to meet all needs of contamination control for multiple markets such as the nuclear and NORM industries, medical structures & first responders, thanks to its integrated nuclide library.

It is equipped with a powerful algorithm to allow very fast and reliable detection of ionising radiation in a variety of civil applications. The SaphyRAD C has been designed ergonomically to be held with gloves on. Its large colour display makes the results perfectly easy to read. The SaphyRAD C possesses a wide range of contamination probe and it is compatible with all analogue probes on the market.



Ruggedized for harsh environment

The SaphyRAD C has a robust housing with 6 large buttons designed for use with gloves. This device is adapted to meet the needs of the Nuclear industry, but also of the NORM industry, first responders & medical structures.

Versatility

SaphyRAD C is designed for the detection & measurement of Alpha and/or Beta radiation sources with the use of external connected measuring probes. It has a wide dose rate range from 0.05 $\mu\text{Gy/h}$ to 10Gy/h.

It is also compatible with external analog probes of other systems.

Ease of use

SaphyRAD C is an ergonomic handheld device with a high image quality color screen. Some probes also include an embedded alarm & a distance control indicator.

Efficiency

SaphyRAD C works with a specific algorithm which was developed for a very fast and reactive detection of radiation sources.

← [Back to partner](#)



Détection des radiations > Moniteurs portables

AlphaE - Bertin Instruments

AlphaE is an electronic handheld device for fast and time-resolved radon monitoring in buildings, outdoors and mines. Typically, 80 % of the final result is achieved after 2 hours (faster response for higher values). Due to its ultra-lightweight design and sophisticated features, AlphaE is highly suitable also for surveying the personal radon exposure and dose at workplaces.



The AlphaE's favourable price-performance ratio makes it also interesting for service companies engaged in radon assessment and mitigation as well as for users in private homes. Up to 6 months battery life allows long-term measurement without mains power. Permanent operations via mains supply are possible via USB port.

Advantages AlphaE

- ultra-lightweight design
- sophisticated features
- wide measuring range for professional use
- up to 6 months autonomy
- suitable software included

Download the datasheet or contact our product specialist.



SaphyRAD E Multiprobe - Bertin Instruments

SaphyRAD multiprobe alpha & beta contamination meter has been developed to meet all needs of contamination control for multiple markets such as the nuclear and NORM industries, medical structures & first responders, thanks to its integrated nuclide library. Its ergonomic interface and design have been especially conceived for use even by non-specialists.



SaphyRAD's wide range of contamination probes combined with its specific algorithm allow for a very fast and reactive detection. Depending on the probe, the operator can either assess small or large areas to detect alpha, beta/gamma or alpha & beta/gamma radioactive contamination. All data can be stored on an SD card for measurement recordings.

SaphyRAD E advantages

- user friendly embedded alarm & distance control indicator
- wide range of compatible probes
- adaptative nuclide library
- versatile for contamination & measurement operations
- ruggedized for harsh environment

[SaphyRAD E](#)

← **Back to partner**



Détection des radiations > Moniteurs portables

SaphyRAD MS Dom-420 - Bertin Instruments

SaphyRAD MS is the latest multiprobe survey meter designed for operation in harsh environments such as military fields and first responders.



Together with the probes, SaphyRAD MS allows to cover most of the needs of first responders. SaphyRAD MS associates a wide range dose rate meter and external smart probes for source and hot spot search and contamination measurement. SaphyRAD MS includes a simulation mode which allows to train the users with high reality without the use of radioactive sources. Special care has been taken in the design of man machine interface for quick use by non radiation specialists.

SaphyRAD MS features

- designed for operation in harsh environments
- high resolution and large color LCD display
- built in simulation function for training
- designed for use with CBRN protective clothing
- built in GPS
- specific algorithm for very fast and reactive detection
- wide dose rate range 0.05 $\mu\text{Gy/h}$ to 10Gy/h
- comprehensive external smart probes for source search and multiple contamination measurement specially designed for use by non radiation specialists

[SaphyRAD MS](#)

[SaphyRAD MS probes](#)

Contact our PEO product specialist.



Partner **SE International**



S.E. International, Inc. est un fabricant américain de confiance d'instruments de détection de radiations sous la marque Radiation Alert®. Sa gamme de produits comprend des détecteurs de zone, des radiamètres portables et des dosimètres électroniques personnels, tous conçus pour une surveillance précise et en temps réel des radiations dans un large éventail d'applications.

Product offering

Radiation Alert Monitor 200



Radiation Alert MC1K



Radiation Alert Frisker



Radiation Alert Ranger



Radiation Alert Monitor 4EC



Radiation Alert® Ranger EXP



Radiation Alert Monitor 1000EC



Radiation Alert® GammaView



**Radiation Alert
Monitor 4**



← [Back to partner](#)



Détection des radiations > Moniteurs portables

Radiation Alert Monitor 200

The Monitor 200, your go-to solution for precise and versatile radiation detection. This state-of-the-art device measures alpha, beta, gamma, and x-rays providing accurate readings displayed in your preferred unit of measurement. Choose from CPM, CPS, $\mu\text{Sv/hr}$, mR/hr, or in accumulated counts.

Featuring a digital backlit display, the Monitor 200 ensures easy readability in any environment. The addition of a red count light and an audible beeper accompanying each count detected enhances your awareness during radiation monitoring. With an adjustable timer and customizable loud alert, this radiation detector is tailored to meet your specific needs, offering both accuracy and user-friendly functionality.

The Monitor 200 doesn't just stop at on-the-spot readings- it's equipped with internal memory and Included with your purchase is the Free Observer USB Software (compatible with Windows only), enabling you to effortlessly download and manage your data while setting up computer alarms for added convenience.

For an enhanced experience, the optional Bluetooth module opens up a world of possibilities. The Radiation Alert® Monitor 200 seamlessly integrates with the free Radiation Alert® Observer BLE app available for download from the Google App Store. This app empowers you to display real-time readings with descriptions, conduct timed counts, append GPS data, and send your saved survey files. What's more, any alarms set on the instrument will be mirrored on your android device, ensuring you stay informed and in control.



← [Back to partner](#)



Détection des radiations > Moniteurs portables

Radiation Alert MC1K

The MC1K is an ergonomic handheld survey meter using a built-in energy compensated GM detector. It detects gamma and x-rays up to 1000 mR/hr over 4 selectable ranges. The energy compensated Geiger counter affords the detector a more linear response to gammas and x-rays over the full range. A beep sounds and a count light flashes with each event detected.

Applications & Uses: Expanded Range up to 1000 mR/hr, Linear Response needs with Energy Compensation, Checking accelerator & x-ray shielding for leakage, Checking industrial gauges; such as moisture, density, or level gauges containing Cesium-137, Locating lost sources, Personal protection, General surveying



← [Back to partner](#)



Détection des radiations > Moniteurs portables

Radiation Alert Frisker

Tired of dealing with cumbersome cables? Need a free hand? Frustrated with carrying around bulky meters? Introducing The Radiation Alert® Frisker. This compact device detects alpha, beta, gamma, and X-ray radiation. It features multiple units of measure, customizable alarm levels, and a backlit display for easy reading.



The Frisker is a lightweight, single-handed radiation contamination instrument designed to meet the needs of today's radiation professionals. Perfect for leak testing, surface monitoring, sample screening, and personnel screening, it integrates the latest electronics with a reliable Geiger-Mueller detector. S.E. International has crafted a durable, ergonomic Geiger counter that excels in various radiological applications.

Applications & Uses: Screening personnel and objects, such as packages, surfaces, and clothing, Surveying for NORM (Naturally Occurring Radioactive Material) contamination, Gross wipe counting, Contamination surveys of packages, equipment, people, etc., Regulatory inspections, Low energy radionuclide detection.



Détection des radiations > Moniteurs portables

Radiation Alert Ranger

Introducing the Radiation Alert Ranger®, the pinnacle of nuclear radiation detection technology that seamlessly combines performance with unparalleled portability. Whether you're surveying facility or venturing into the field, the Radiation Alert Ranger® stands as a reliable companion, designed with industrial environments in mind while retaining all the features cherished in laboratory settings.



Compact and lightweight, the Radiation Alert Ranger® is a handheld digital survey meter that sets the bar for sensitivity across alpha, beta, gamma, and x-rays ensuring comprehensive coverage for your radiation detection needs. Equipped with built-in efficiencies for common isotopes, this model goes the extra mile by calculating activity in Becquerels (Bq) and Disintegrations Per Minute (DPM).

The Radiation Alert Ranger® boasts a user-friendly interface featuring a backlit digital display, a red count light, and a distinctive beeper that signals each count detected, enhancing your ability to respond promptly to radiation levels. Selectable alert levels, an adjustable timer, and an optional wipe test plate for swipes provide further flexibility, allowing you to tailor the device to your specific requirements.

- Free Observer USB Software
- Free Observer BLE Software
- For Use With The Optional Bluetooth Module

But the Radiation Alert Ranger® doesn't stop there. Included with your purchase is the Free Observer USB Software (compatible with Windows only), enabling you to effortlessly download and manage your data while setting up computer alarms for added convenience.

For an enhanced experience, the optional Bluetooth module opens up a world of possibilities. The Radiation Alert Ranger® seamlessly integrates with the free Radiation Alert® Observer BLE app available for download from the Google App Store. This app empowers you to display real-time readings with descriptions, conduct timed counts, append GPS data, and send your saved survey files. What's more, any alarms set on the instrument will be mirrored on your android device, ensuring you stay informed and in control.

Elevate your radiation detection capabilities with the Radiation Alert Ranger® - where cutting-edge technology

meets user-friendly design, providing peace of mind whether in the lab, facility, or in the field.

Applications & Uses: Surveying for NORM (Naturally Occurring Radioactive Material) contamination, Gross wipe counting, Contamination surveys of packages, equipment, people, etc., Regulatory inspections, Scrap Metal Screening, Low energy radionuclide detection

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Radiation Alert Monitor 4EC

The Monitor 4EC is an energy compensated, ergonomic radiation survey meter capable of detecting alpha, beta, gamma, and x-rays over 3 selectable ranges. A red count light flashes and a beep sounds with each event detected. The Monitor 4EC offers a linear response for gamma and x-rays (above 40 keV).

Applications & Uses: Checking accelerator & x-ray shielding for leakage, Checking industrial gauges, such as moisture, density, or level gauges containing Cesium-137, Locating sources, Personal protection, General surveying



← [Back to partner](#)



Détection des radiations > Moniteurs portables

Radiation Alert® Ranger EXP



The Radiation Alert Ranger® EXP, seamlessly combines performance with unparalleled portability. Whether you're surveying facility or venturing into the field, the Radiation Alert Ranger® EXP stands as a reliable companion, designed with industrial environments in mind while retaining all the features cherished in laboratory settings.

Compact and lightweight, the Radiation Alert Ranger® EXP is a handheld digital survey meter that sets the bar for sensitivity to NORM and low levels of alpha, beta, gamma, and x-rays ensuring comprehensive coverage for your radiation detection needs. Equipped with built-in efficiencies for common isotopes, this model goes the extra mile by calculating activity in Becquerels (Bq) and Disintegrations Per Minute (DPM).

The Radiation Alert Ranger® EXP has a user-friendly interface featuring a backlit digital display, a red count light, and a beeper that signals each count detected, enhancing your ability to respond promptly to radiation levels. Selectable alert levels, an adjustable timer further flexibility. allowing you to tailor the device to you specific requirements.

- Free Observer USB Software
- Free Observer BLE Software
- For Use With The Optional Bluetooth Module

But the Radiation Alert Ranger® EXP doesn't stop there. Included with your purchase is the Free Observer USB Software(compatible with Windows only), enabling you to effortlessly download and manage your data while setting up computer alarms for added convenience.

For an enhanced experience, the optional Bluetooth module opens up a world of possibilities. The Radiation Alert Ranger® EXP seamlessly integrates with the free Radiation Alert® Observer BLE app available for download from the Google App Store. This app empowers you to display real-time readings with descriptions, conduct timed counts, append GPS data, and send your saved survey files. What's more, any alarms set on the instrument will be mirrored on you android device, ensuring you stay informed and in control.

Applications & Uses: Surveying for NORM (Naturally Occurring Radioactive Material) contamination, Gross wipe counting, Contamination surveys of packages, equipment, people, etc.,

Regulatory inspections, Scrap Metal Screening, Low energy radionuclide detection



Détection des radiations > Moniteurs portables

Radiation Alert Monitor 1000EC

The Monitor 1000EC is an energy compensated radiation detector that measures gamma, and x-rays. Perfect for most applications requiring an energy compensated detector. Users can choose from readings of CPM, CPS, $\mu\text{Sv/hr}$, mR/hr, or in accumulated counts. It has a red count light, a beeper that sounds with each count detected, and includes an adjustable timer, and selectable alert.

- Free Observer USB Software
- Free Observer BLE Software For Use With The
- Optional Bluetooth Module

The Radiation Alert® Monitor 1000EC doesn't stop there. Included with your purchase is the Free Observer USB Software(compatible with Windows only), reads in Total Counts, CPM, $\mu\text{R/hr}$, mR/hr, CPS, $\mu\text{Sv/hr}$, and has the ability to collect and log data, set alarms, set timed counts, set the calibration date and settings, and generate reports, enabling you to effortlessly download and manage your data while setting up computer alarms for added convenience.

For an enhanced experience, the optional Bluetooth module opens up a world of possibilities. The Radiation Alert® seamlessly integrates with the free Radiation Alert® Observer BLE app available for download from the Google App Store. This app empowers you to display real-time readings with descriptions, conduct timed counts, append GPS data, and send your saved survey files. What's more, any alarms set on the instrument will be mirrored on you android device, ensuring you stay informed and in control.

Free Radiation Alert® Observer BLE app from the Google App Store, where you can display the readings from your detector, label sample readings and descriptions, take timed counts, append GPS data and send your saved survey file. This radiation detector helps you to set alarms which will also activate if you sync it with your android device. .

This radiation detector device include Free Observer USB software (Windows® only) reads in Total Counts, CPM, $\mu\text{R/hr}$, mR/hr, CPS, $\mu\text{Sv/hr}$, and has the ability to collect and log data, set alarms, set timed counts, set the calibration date and settings, and generate reports.

Applications & Uses: X-ray chamber inspection, Expanded Range up to 1000 mR/hr, Linear Response needs with Energy



Compensation, Checking accelerator & x-ray shielding for leakage, Checking industrial gauges, such as moisture, density, or level gauges containing Cesium-137, Locating lost sources, Personal protection, Linear response detection applications, General surveying

← [Back to partner](#)



Détection des radiations > Moniteurs portables

Radiation Alert® GammaView

The compact GammaView is light, easy to carry and operate with a 1×1 NaI scintillation detector that accurately measures gamma contamination and exposure. Perfect for use in the lab, facility, and in the field.

The GammaView boasts a user-friendly interface featuring a backlit digital display, a red count light, and a distinctive beeper that signals each count detected, enhancing your ability to respond promptly to radiation levels. Selectable alert levels, an adjustable timer, allowing you to tailor the device to you specific requirements.

The GammaView can also be used as a single-channel analyzer (SCA). This function allows a “window” to be set to focus on a specific energy region of the gamma spectrum, effectively reducing the background count.

Specific Applications Include: Compliance monitoring, environmental monitoring, remote monitoring, health physics, homeland defense.



← [Back to partner](#)



Détection des radiations > Moniteurs portables

Radiation Alert Monitor 4

The Radiation Alert® Monitor 4 is a compact, analog radiation detector designed for versatility and reliability. This general-purpose survey meter can detect alpha, beta, gamma, and X-ray radiation across three selectable ranges. With decades of proven performance in the industry, the Monitor 4 has become one of the leading analog radiation detectors available today. Its simple, ergonomic design features a red count light that flashes and an audible beep for each detected count. A quick flick of your thumb allows for an easy battery check and silent operation.

Applications & Uses: Checking industrial gauges, such as moisture, density, or level gauges containing Cesium-137, Locating Sources, Personal protection, General surveying





Partner **GEORADIS s.r.o.**



Georadis s.r.o. est un fabricant spécialisé d'instruments avancés de détection et de surveillance des radiations, proposant une gamme complète de solutions pour les applications de terrain et de laboratoire. Sa gamme de produits comprend des moniteurs portables, des identificateurs d'isotopes portables, des appareils de surveillance environnementale et des équipements de laboratoire, tous conçus pour répondre aux exigences rigoureuses des professionnels des secteurs de la surveillance environnementale, de la sécurité industrielle et de la sécurité publique.

Product offering

RT-20 Compact handheld Radiation Detector - Georadis



RT-21 Handheld Radiation Detector - Georadis



RT-22 Handheld Radiation Detector with GeoView Software - Georadis



RT-30 Mk II - Georadis





Détection des radiations > Moniteurs portables

RT-20 Compact handheld Radiation Detector - Georadis

The RT-20 Compact handheld Radiation Detector is a robust and compact hand held radiation detector specifically designed to quickly scan for radioactive materials. The ruggedness, small size and light weight of the RT-20, combined with its sensitive Gamma Ray scintillation detector makes it a versatile instrument for quick measurements in a large variety of applications.



RT-20 Compact handheld Radiation Detector features:

- 1,3 kg; balanced and lightweight
- reads in counts per second, sampling rate 4 per second
- high sensitivity, NaI/Tl crista
- adjustable audio threshold
- audio output and numeric LCD display maximum 19999 cps
- automated warning of high dose rate
- protection boot with carrying straps
- supplied in aluminium suitcase with moulded insert
- automatic charger integrated in unit
- dust and sprinkling water resistant (IP66)
- available with telescope (RS-111T)

Read more about the RT-20 Compact handheld Radiation Detector on the [Georadis website](#)

← [Back to partner](#)



Détection des radiations > Moniteurs portables

RT-21 Handheld Radiation Detector - Georadis

The RT-21 (Georadis) is the most sensitive of numerous manufactured handheld radiation detectors. Its robust design allows it to operate even in the most demanding climatic conditions. Our bestseller at the time of the uranium panic. Popular with scrap yard owners.



RT-21 Handheld Radiation Detector features:

- one button operation
- highest sensitivity
- weather protected
- lightweight, rugged and compact design
- graphical display
- with telescope available (RS-21T)
- sampling period: 20/sec
- detector: NaI(Tl) 2×2" or BGO 2×2", 103 ccm
- gamma ray energy range: 30 - 3000 keV

Read more about the RT-21 Handheld Radiation Detector on the [Georadis website](#)

← [Back to partner](#)



Détection des radiations > Moniteurs portables

RT-22 Handheld Radiation Detector with GeoView Software - Georadis

The RT-22 model is based on the RT-21 series, the most sensitive from the range of manufactured hand-held radiation detectors. Compared to its predecessor, it comes with an internal memory for storing measurement data, and Bluetooth connectivity allowing the use of an external GPS module. Its robust design makes it suitable for hostile climatic conditions. Our bestseller at the time of the uranium panic. Popular with scrap yard owners.



GeoView provides specified views on accumulated data such as survey in both dose rate or cps. The RT-22 Handheld Radiation Detector can be connected with the software through USB or Bluetooth.

RT-22 Handheld Radiation Detector with GeoView Software features:

- graphical display
- with telescope available (RT-22T)
- sampling period: 20/sec
- detector: NaI(Tl) 2×2" or BGO 2×2", 103 ccm
- gamma ray energy range: 30 - 3000 keV
- highest sensitivity
- weather protected
- lightweight, rugged and compact design

Read more about the RT-22 Handheld Radiation Detector with GeoView Software on the [Georadis website](#)



Détection des radiations > Moniteurs portables

RT-30 Mk II - Georadis

Handheld Isotope Identification Instrument RIID

The RT-30 Mk II is the second generation of popular handheld gamma ray spectrometer RT-30. Strengths of the first generation were copied in the new model. There has to be highlighted a strong alloy body sealed against dust and water, protective removable rubber boot, comfortable grip and low weight.

The Mk II learned of the limitations of the first generation and features a large colored transreflectible sun readable display, improved user's interface with five operation buttons, removable but well-sealed battery pack and clear and loud audio.



The instrument is built as an open platform with potential of fast and simple implementation of special features required by customers. Wide fleet of detectors is supported. The Mk II bridges traditional scintillation detection probes using common vacuum photomultiplier tube with up-to-date silicon photomultipliers technology. Saved significant volume of vacuum tubes is next occupied by larger size of detector.

A heart of gamma ray spectrometer is FPGA (programmable array) plus fast speed and low consumption ARM type processor. The combination of FPGA with ARM is taken of preceding larger instrument and has been tested for years. Beside gamma ray section the FPGA is capable to handle other sensors at the same time. A Geiger-Mueller counter and a Neutron detector make a standard offer.

Thanks to latest electronic the Mk II opens a platform for supporting most modern existing communication standards. Sharing new and traditional communication standards is guaranteed wide compatibility with older as well as new communication devices. The existing USB was upgraded to level C and beside communication it is used also for unit's battery charging. GPS system is built in the front part of the instrument and is used for localization of the unit and also for time synchronization.

Quickly determining the location of lost radioactive sources in the environment or scrap, monitoring of waste in hospitals or waste incinerators, scanning people or baggage to disclose illicit trafficking of nuclear materials; all are typical applications for the RT-30 Mk II series.

Features:

- Ergonomic, lightweight handheld well balanced, compact;
- Comfortable grip with five buttons operable in glows;
- Removable protective rubber boot;
- Detectors fully build in the housing, protected by rubber foam;
- Large, transreflectible colored display – sharp and high contrast in sunlight, backlighted in dark;
- Loudspeaker with plastic membrane watertight;
- Four status indication LEDs – indication of alarms and health status;
- USB standard C for data transfer and charging;

- Wide fleet of scintillation detectors NaI/Tl, CsI/Tl, CsI/Eu, LaHalide, BGO, GAGG, Srl, Plastic scintillation detectors PVT;
- Maximum detector size: Diameter 2" and height 2" with standard vacuum PMT or max 5" with Silicon PMT (SiPM or MPPC).

See the full details in the RT-30 Mk II datasheet.





Partner **Kromek**



Kromek Group plc est un leader mondial des technologies avancées de détection des radiations, spécialisé dans les solutions compactes et haute résolution pour les applications de sécurité, de défense, de nucléaire et de recherche. S'appuyant sur sa technologie brevetée de semi-conducteurs au tellure de cadmium-zinc (CZT), Kromek propose une gamme polyvalente comprenant des moniteurs portables, des identificateurs d'isotopes portables, des gamma-caméras CZT et des spectromètres de laboratoire.

Product offering



← Back to partner



Détection des radiations > Identificateurs d'isotopes portables

D5 RIID

Le D5 RIID fournit un dispositif unique de détection de rayonnements hautes performances et polyvalent dans un boîtier portable pour le personnel militaire, de la sécurité intérieure et industriel.



Le D5 RIID est un petit dispositif d'identification de radio-isotopes (RIID) portable, léger, d'une résolution de 3,5 %, doté d'une vaste bibliothèque de radio-isotopes et d'un taux de fausses alarmes ultra faible. Il analyse en permanence et identifie avec précision les menaces radiologiques en temps réel, même dans des environnements à sources mixtes.

Le D5 RIID combine un petit format avec de puissantes performances radiométriques et une sensibilité améliorée à une résolution moyenne de 3,5 %. Le D5 RIID a une efficacité de surface 62 % supérieure à celle des RIID conventionnels.

D5 RIID Overview <https://youtu.be/yi-uvo05nFg>



SCAN TO VIEW
VIDEO

Le D5 RIID est le plus petit, le plus léger et offre les performances de détection ultimes. Il a une résolution de 3,5 %, avec une vaste bibliothèque de radio-isotopes et un taux de fausses alarmes ultra faible. Il analyse en permanence et identifie avec précision les menaces radiologiques en temps réel, même dans des environnements à sources mixtes.

← **Back to partner**



Détection des radiations > Identificateurs d'isotopes portables

D3S ID

Un détecteur gamma et neutronique portable et dissimulable qui met la puissance d'un RIID dans un boîtier de la taille d'un détecteur de rayonnement personnel (PRD). D3S ID est la nouvelle norme en matière de détecteurs de rayonnement portables.

Le D3S ID est un appareil puissant, portable, discret et mains libres qui recherche en permanence les menaces de rayonnement gamma et neutronique.



Le D3S de Kromek répond aux attentes en matière de sécurité des données des gouvernements, des services de renseignement et des autorités de sécurité. Le D3S est livré en standard avec un smartphone sécurisé (contrôle Android), qui contient le logiciel de détection Kromek exclusif et sécurisé. Le D3S est déjà fréquemment utilisé aux États-Unis, par exemple sur les camions de pompiers et les ambulances ou comme système de cartographie de zone avec 1 000 détecteurs lors d'une « chasse au trésor ». En Europe, le D3S a été déployé lors de visites d'État et de consultations de l'OTAN ces dernières années, pour détecter les menaces radioactives précoces pouvant être présentes dans les marchandises, les véhicules, les bâtiments, d'autres objets et dans l'environnement.

Caractéristiques:

Identifie 37 isotopes (17 de plus que la norme ANSI actuelle)

S'identifie plus rapidement qu'un RIID

Économique par rapport aux autres produits du marché

Petite taille, portable, s'adapte à la ceinture

Connectable en réseau



RayMon 10

RayMon 10

Un détecteur gamma portable puissant et robuste pour l'identification des isotopes radioactifs à haute résolution. Le RayMon10 est l'un des moniteurs de rayonnement portables les plus puissants et les plus robustes au monde. Il peut être utilisé pour détecter, mesurer et identifier avec précision les radionucléides émetteurs de rayons gamma, fournissant une identification isotopique à haute résolution à l'aide de la dernière technologie de détecteur à semi-conducteurs CZT. C'est une solution tout-en-un à vos besoins d'identification des radionucléides gamma

Il peut produire une variété de rapports, notamment la date/heure, l'identifiant de l'utilisateur, les notes photo et audio, le positionnement GPS, les spectres de rayonnement et l'identification des isotopes.

Les variations des conditions normales de fonctionnement peuvent souvent affecter les performances de l'identification des radio-isotopes. Le détecteur avancé à grille coplanaire CZT d'un centimètre cube du RayMon10 offre des performances plus stables que les détecteurs de type à scintillation.





Partner **Radiation Solutions Inc.**



Radiation Solutions Inc. (RSI) est une entreprise canadienne spécialisée dans les systèmes avancés de détection et de surveillance des rayonnements, notamment les portiques de surveillance pour diverses applications. Ses technologies sont conçues pour garantir la sécurité et la conformité dans des secteurs tels que l'acier, la ferraille, le recyclage et la sécurité frontalière.

Product offering

RS-230 BGO Handheld Spectrometer - Radiation Solutions



RS-125 Handheld Spectrometer - Radiation Solutions



RS-125 Handheld Spectrometer - Radiation Solutions



← [Back to partner](#)



Détection des radiations > Moniteurs portables

RS-230 BGO Handheld Spectrometer - Radiation Solutions

The RS-230 BGO Handheld Spectrometer (Radiations Solutions) is a portable handheld radiation survey search device for use in the geophysical industry. Using a BGO give very significant increase in performance over the normally used NaI detector (3x).



RS-230 BGO Handheld Spectrometer features:

- single button operation
- high countrate: 65, 535
- protection: IP67
- rugged design
- digital LCD display
- analyses single channel and multichannel
- PC connectivity: USB or Bluetooth
- detector: BGO 2×2", 103 ccm

Read more about the RS-230 BGO Handheld Spectrometer on the [Radiation Solutions website](#)

← [Back to partner](#)



Détection des radiations > Moniteurs portables

RS-125 Handheld Spectrometer - Radiation Solutions

The RS-125 Handheld Spectrometer (Radiation Solutions) is an advanced mobile instrument for radiation survey. The device is mainly used for spectral analyses in the geophysical industry. The RS-125 has the highest sensitivity in the market of spectrometers and is simple in use. There are no test sources required, the spectrometer stabilizes automatically on the different forms of radioactivity (K, U and Th).



RS-125 Handheld Spectrometer features:

- single button operation
- digital LCD display
- detector: NaI(Tl) 2×2"
- analyses single channel and multichannel
- PC connectivity: USB or Bluetooth
- high countrate: 65, 535
- protection: IP67
- rugged design

Read more about the RS-125 Handheld Spectrometer on the [Radiation Solutions website](#)

← Back to partner



Détection des radiations > Moniteurs portables

RS-125 Handheld Spectrometer - Radiation Solutions

The RS-125 Handheld Spectrometer (Radiation Solutions) is an advanced mobile instrument for radiation survey. The device is mainly used for spectral analyses in the geophysical industry. The RS-125 has the highest sensitivity in the market of spectrometers and is simple in use. There are no test sources required, the spectrometer stabilizes automatically on the different forms of radioactivity (K, U and Th).



RS-125 Handheld Spectrometer features:

- single button operation
- digital LCD display
- detector: NaI(Tl) 2×2"
- analyses single channel and multichannel
- PC connectivity: USB or Bluetooth
- high countrate: 65, 535
- protection: IP67
- rugged design

Read more about the RS-125 Handheld Spectrometer on the [Radiation Solutions website](#)

DOSIMÈTRES ÉLECTRONIQUES PERSONNELS





Partner **Tracerco**



Tracerco est un leader mondial de la détection et de la mesure des radiations. Il propose une gamme complète de moniteurs portables et de dosimètres électroniques personnels. Ses instruments sont conçus pour une surveillance précise et en temps réel des niveaux de radiation, garantissant ainsi la sécurité et la conformité dans divers secteurs.

Product offering

<p>PED2 (Personal Electronic Dosimeter) - Tracerco</p> 	<p>PED2 - ER (Personal Electronic Dosimeter) - Tracerco</p> 	<p>PED2-IS (Personal Electronic Dosimeter) - Tracerco</p> 	<p>PED-Blue (Personal Electronic Dosimeter) - Tracerco</p> 
<p>PED+ (Personal Electronic Dosimeter) - Tracerco</p> 	<p>PED-ER (Personal Electronic Dosimeter) - Tracerco</p> 	<p>PED-ER+ (Personal Electronic Dosimeter) - Tracerco</p> 	<p>Dosimeter software DoseVision™ and DoseVision™ Tracerco</p> 

← Back to partner



Détection des radiations > Dosimètres électroniques personnels **PED2 (Personal Electronic Dosimeter) - Tracerco**

A flexible personal electronic dosimeter for general radiation protection applications.

Flexible radiation protection

Instantaneously measures, records and displays dose rate and accumulated dose in real time

Up to four configurable dose and dose rate alarm settings

Optional extended range calibration up to 1 Sv/h where potential exists for emergency situations



Features:

- Clear and readable
- Simple and intuitive
- Reliable and accurate
- Flexible radiation protection
- IS certification

Easy to use and understand

Large, easy-to-read color display ensures vital information is clear, simple to understand and visible in any lighting scenario

A single button is used to navigate an intuitive carousel menu

Alarm settings trigger audible, visual, textual and haptic alerts

IS certification

PED2-IS and PED2-IS+ are ATEX certified. This European certification is given to equipment that is tested and approved to be intrinsically safe.



Giving you the peace of mind that the IS certified PED2 range is able to safely measure radiation exposure in potentially explosive environments.



Additional Services

To support optimal performance and compliance with regulatory standards, PEO offers the following services for this device:

- > Service
- > Maintenance
- > Calibration
- > Leakage Tests

These services are available through PEO.

For service appointments or contract options, please contact your PEO representative.

Purchase Product

Request Service

Ask a question

Find more products



Détection des radiations > Dosimètres électroniques personnels

PED2 - ER (Personal Electronic Dosimeter) - Tracerco

An intrinsically safe certified personal electronic dosimeter, with handheld survey mode and enhanced features such as Bluetooth, GPS and pop-up message alarms

Features:

- Clear and readable
- Simple and intuitive
- Reliable and accurate
- Flexible radiation protection
- IS certification



Easy to use and understand

Large, easy-to-read colour display ensures vital information is clear, simple to understand and visible in any lighting scenario

A single button is used to navigate an intuitive carousel menu

Alarm settings trigger audible, visual, textual and haptic alerts

Flexible radiation protection

Instantaneously measures, records and displays dose rate and accumulated dose in real time

Up to four configurable dose and dose rate alarm settings

Optional extended range calibration up to 1 Sv/h where potential exists for emergency situations

IS certification

PED2-IS and PED2-IS+ are ATEX certified. This European certification is given to equipment that is tested and approved to be intrinsically safe. Giving you the peace of mind that the IS certified PED2 range is able to safely measure radiation exposure in potentially explosive environments.

← Back to partner



Détection des radiations > Dosimètres électroniques personnels **PED2-IS (Personal Electronic Dosimeter) - Tracerco**

Flexible radiation protection

Instantaneously measures, records and displays dose rate and accumulated dose in real time

Up to four configurable dose and dose rate alarm settings

Optional extended range calibration up to 1 Sv/h where potential exists for emergency situations



Features:

- Clear and readable transfective display enables use in dimly lit or sun-glare scenarios
- Responds promptly to small changes in radiation whilst also being capable of making accurate and reliable readings
- Intuitive single button operation
- Intrinsically safe for use in hazardous areas
- DoseVision™ companion software with optional cloud ecosystem

Easy to use and understand

Large, easy-to-read colour display ensures vital information is clear, simple to understand and visible in any lighting scenario

A single button is used to navigate an intuitive carousel menu

Alarm settings trigger audible, visual, textual and haptic alerts

IS certification

PED2-IS and PED2-IS+ are ATEX certified. This European certification is given to equipment that is tested and approved to be intrinsically safe. Giving you the peace of mind that the IS certified PED2 range is able to safely measure radiation exposure in potentially explosive environments.



← Back to partner



Détection des radiations > Dosimètres électroniques personnels

PED-Blue (Personal Electronic Dosimeter) - Tracerco


PED-BLUE FROM TRACERCO

Personal Electronic Dosimeter

The PED-Blue is a lightweight, non-IS PED. The device can be charged with a direct micro USB connection, so it's more flexible. This dosimeter can also be configured to use either two or four dose alarm levels and is customisable through DoseVision™ software.


The PED Blue also has a task function where you can start and finish a task. After a task is finished you can look back by using DoseVision. This dosimeter is also perfect for clinical environments for example, because of its discreet alarm function.

The dosimeter gives the user immediate feedback so you'll know when the ambient dose is heightened.



BENEFITS OF THE PED BLUE:

- Robust and easy to use
- Direct micro USB connection for greater flexibility
- Large, clear, easy-to-read AMOLED display
- Light weight
- Used with DoseVision™ software ensures ease of use
- IP67 rated
- Simple one-button operation
- Four adjustable alarms
- Immediate detection



Tracerco Radiation Monitors <https://youtu.be/Rm907FOKeX0>



SCAN TO VIEW VIDEO



For more info from Tracerco, take a look at [this page](#).

Would you like more information on PED's?

Contact PEO!

← Back to partner



Détection des radiations > Dosimètres électroniques personnels **PED+ (Personal Electronic Dosimeter) - Tracerco**

Radiation safety - simplified

Tracerco's range of personal electronic dosimeters (PEDs) are suitable for oil and gas, medical and life sciences, nuclear, CBRNe and emergency services, NDT, manufacturing and industrial, and environmental and waste management industries. We offer both intrinsically safe and non-intrinsically safe options for all needs.

PED+ (Personal Electronic Dosimeter) from Tracerco

The PED+ can be used as both a personal dosimeter and a handheld dose rate survey meter. It has a number of additional features, such as Bluetooth, GPS and pop-up message alarms.



Benefits of the PED+ include:

- Handheld mode allows the device to be used as a handheld survey meter
- Shows readings in dose rate (Sv or rem) and displays a live trend graph to show activity in real time
- Measurement is corrected for use off-body, so personal accumulated dose is not recorded
- Dose rate data is logged in off-body mode, allowing data review with DoseVision™
- Pop-up alert messages display clear instructions at alarm threshold
- Allows location data to be logged to the device alongside dose and dose rate data, that can be viewed using DoseVision™

Would you like to receive more information?

Contact PEO!



Détection des radiations > Dosimètres électroniques personnels **PED-ER (Personal Electronic Dosimeter) - Tracerco**

PED-ER FROM TRACERCO

Personal Electronic Dosimeter with extended range

The PED-ER is a robust, light and user-friendly personal electronic dosimeter. You can use it to effectively monitor, measure and manage radiation exposure. This PED is the same as the PED-Blue from Tracerco, only the ER stands for Extended Range, so the range is bigger.


This personal electronic dosimeter has both audio and visual alarms with vibration. The dosimeter will alarm you when you reach your personally set radiation dose. Because of the extended dose range from the PED-ER, it can detect radiation up to 1 Sv/h.

This dosimeter is not only designed to be robust and lightweight, it's also designed to keep it simple. The device has a large and clear AMOLED display which is very user-friendly. When you use this dosimeter in combination with the accompanying software DoseVison, you can easily manage radiation doses.



BENEFITS OF THIS DOSIMETER:

- The dosimeter has an extended dose range of up to 1 Sv/h
- Large easily readable display and intuitive graphical user interface
- A reliable dosimeter, even for the most challenging radiation monitoring situations
- User-friendly design because of one-button operation
- The user can easily operate it without any training
- You can choose between audio and/or visual alarms, with optional vibration



Tracerco Radiation Monitors <https://youtu.be/Rm907FOKeX0>



For more information from Tracerco, take a look at [this page](#).

Would you like more information on PED's?

Contact PEO!

← Back to partner



Détection des radiations > Dosimètres électroniques personnels **PED-ER+ (Personal Electronic Dosimeter) - Tracerco**

Radiation safety - simplified

Tracerco's range of personal electronic dosimeters (PEDs) are suitable for oil and gas, medical and life sciences, nuclear, CBRNe and emergency services, NDT, manufacturing and industrial, and environmental and waste management industries. We offer both intrinsically safe and non-intrinsically safe options for all needs.

PED-ER+ (Personal Electronic Dosimeter) from Tracerco

The PED-ER+ provides the ultimate in radiation monitoring, measurement and management for those working in challenging environments. Ideal for use by industrial NDT workers, emergency services and first response teams (CBRNe).



Benefits of the PED-ER+ include:

- An extended dose rate range of up to 1Sv/h
- Weather, shock and drop-proof housing - ideal for rugged environments
- Large clear display
- Portable - can be used as both a personal dosimeter, and a handheld dose rate survey meter
- Pop-up message alarms when dose limits are reached

Would you like to receive more information?

Contact PEO!

← [Back to partner](#)



Détection des radiations > Dosimètres électroniques personnels

Dosimeter software DoseVision™ and DoseVision™ Tracerco

The dosimeter PC software interface for the PED-IS PED Blue and PED+ is specifically designed for simplicity and interactivity. DoseVision™ allows users to set alarms and reports. This is to assign users to the PED, and download and analyze data.



advantages of DoseVision:

- cumulative dose rate data analysis
- peak dose rates
- data export and easily generate reports
- password protection
- software and firmware updates available for free
- easy management of PED users
- GPS data logging using the PED+

advantages of DoseVison Live™ :

- Bluetooth connectivity
- live dose rate data
- management control for up to 7 devices
- live status updates

DoseVision Live dosimeter software Tracerco



Partner **Polimaster**



Polimaster est un leader mondial des solutions de détection et de surveillance des rayonnements. Il propose une gamme complète d'instruments conçus pour détecter, identifier et mesurer les rayonnements ionisants dans divers environnements. Sa gamme de produits comprend des détecteurs portables, des dosimètres électroniques personnels, des identificateurs isotopiques portables, des portiques de détection et des systèmes de détection mobiles, tous conçus pour répondre aux exigences rigoureuses des secteurs de la sécurité, des interventions d'urgence et des applications industrielles.

Product offering

**PM1703GNA-II MBT
Personal Radiation
Detector/Dosimeter**



**PM1703GNA-II/BT
Personal Radiation
Detector**



**PM1703MO-II BT
Personal Radiation
Detector/Dosimeter**



**PM1703MA-II/BT
Personal Radiation
Detector**



**PM1610B X-Ray and
Gamma Radiation
Personal Dosimeter**



**PM1610 X-Ray and
Gamma Radiation
Personal Dosimeter**



**PM1605BT Personal
Radiation
Monitor/Dosimeter**



**PoliSimeter™ ERB
Electronic Personal
Dosimeter**



**PoliSimeter™ ER
Electronic Personal
Dosimeter**



**PoliSimeter™
Electronic Personal
Dosimeter**



**RadFlash® Electronic
Personal Dosimeter**





Détection des radiations > Dosimètres électroniques personnels **PM1703GNA-II MBT Personal Radiation Detector/Dosimeter**

Gamma-neutron Personal Radiation Detector/Dosimeter.

The **PM1703GNA-II MBT** is a **gamma-neutron** modification equipped with a **Bluetooth** module and a **Geiger-Mueller counter** for extended measurement of the **personal dose rate up to 200 mSv/h** and **personal dose up to 10 Sv**.

The **PM1703@-II series** of personal radiation detectors are extremely sensitive and robust devices that detect and locate even trace amounts of radioactive materials.

Equipped with a clip for multiple wearing options and easy to operate even for non-specialists, the PRDs became the perfect fit as Radiation Pagers for public security agencies, including border control, rescue teams, police, and anti-terrorist units, and first responders that need to quickly search for radioactive materials before and during public mass events.

Features

- ANSI N42.32-2016 and IEC 62401:2017 compliance
- NORM-suppression algorithm for differentiating color-coded alarms triggered by natural or man-made radiation materials
- Dedicated 0-9 scale mode with unitless dose rate indication allowing for ease of use and minimal training
- Personal dose accumulation up to 10 Sv
- Extended dose rate measurement ranges up to 200 mSv/h
- Operation in extreme temperatures from -40 °C to 50 °C
- Long-life alkaline or rechargeable battery for 800 hours
- Shockproof hermetic case IP65
- Audible, visual, and vibration alarms
- Free Polismart® iOS and Android app for advanced operation
- USB and Bluetooth communication





PM1703GNA-II/BT Personal Radiation Detector

Gamma-neutron Personal Radiation Detector.

The **PM1703GNA-II** is a **gamma-neutron** modification equipped with a high-sensitive scintillator for measurement of the **personal dose rate up to 300 μ Sv/h**.

The **PM1703®-II series** of personal radiation detectors are extremely sensitive and robust devices that detect and locate even trace amounts of radioactive materials.

Equipped with a clip for multiple wearing options and easy to operate even for non-specialists, the PRDs became the perfect fit as Radiation Pagers for public security agencies, including border control, rescue teams, police, and anti-terrorist units, and first responders that need to quickly search for radioactive materials before and during public mass events.

Features

- ANSI N42.32-2016 and IEC 62401:2017 compliance
- NORM-suppression algorithm for differentiating color-coded alarms triggered by natural or man-made radiation materials
- Dedicated 0-9 scale mode with unitless dose rate indication allowing for ease of use and minimal training
- Operation in extreme temperatures from -40 °C to 50 °C
- Long-life alkaline or rechargeable battery for 800 hours
- Shockproof hermetic case IP65
- Audible, visual, and vibration alarms
- Free Polismart® iOS and Android app for advanced operation
- USB and Bluetooth (PM1703GNA-II BT) communication





Détection des radiations > Dosimètres électroniques personnels

PM1703MO-II BT Personal Radiation Detector/Dosimeter



Gamma-only Personal Radiation Detector/Dosimeter.

The **PM1703MO-II BT** is a **gamma-only** modification equipped with a **Bluetooth** module and a **Geiger-Mueller counter** for extended measurement of the **personal dose rate up to 200 mSv/h** and **personal dose up to 10 Sv**.

The **PM1703®-II series** of personal radiation detectors (PRD) are extremely sensitive and robust devices that detect and locate even trace amounts of radioactive materials.

Equipped with a clip for multiple wearing options and easy to operate even for non-specialists, the PRDs became the perfect fit as Radiation Pagers for public security agencies, including border control, rescue teams, police, and anti-terrorist units, and first responders that need to quickly search for radioactive materials before and during public mass events.

Features

- ANSI N42.32-2016 and IEC 62401:2017 compliance
- NORM-suppression algorithm for differentiating color-coded alarms triggered by natural or man-made radiation materials
- Dedicated 0-9 scale mode with unitless dose rate indication allowing for ease of use and minimal training
- Personal dose accumulation up to 10 Sv
- Extended dose rate measurement ranges up to 200 mSv/h
- Operation in extreme temperatures from -40 °C to 50 °C
- Long-life alkaline or rechargeable battery for 1000 hours
- Shockproof hermetic case IP65
- Audible, visual, and vibration alarms
- Free Polismart® iOS and Android app for advanced operation
- USB and Bluetooth communication

← Back to partner



Détection des radiations > Dosimètres électroniques personnels

PM1703MA-II/BT Personal Radiation Detector

Gamma-only Personal Radiation Detector.

The **PM1703MA-II** is a **gamma-only** Personal Radiation Detector (PRD) equipped with a high-sensitive scintillator for measurement of the **personal dose rate up to 300 μ Sv/h**.

The **PM1703®-II series** of PRDs are extremely sensitive and robust devices that detect and locate even trace amounts of radioactive materials.

Equipped with a clip for multiple wearing options and easy to operate even for non-specialists, the PRDs became the perfect fit as Radiation Pagers for public security agencies, including border control, rescue teams, police, and anti-terrorist units, and first responders that need to quickly search for radioactive materials before and during public mass events.

Features

- ANSI N42.32-2016 and IEC 62401:2017 compliance
- NORM-suppression algorithm for differentiating color-coded alarms triggered by natural or man-made radiation materials
- Dedicated 0-9 scale mode with unitless dose rate indication allowing for ease of use and minimal training
- Operation in extreme temperatures from -40 °C to 50 °C
- Long-life alkaline or rechargeable battery for 1000 hours
- Shockproof hermetic case IP65
- Audible, visual, and vibration alarms
- Free Polismart® iOS and Android app for advanced operation
- USB and Bluetooth (PM1703MA-II BT) communication





Détection des radiations > Dosimètres électroniques personnels **PM1610B X-Ray and Gamma Radiation Personal Dosimeter**

Extended range X-ray (continuous/pulsed) and gamma radiation personal dosimeter with replaceable battery.

The **PM1610B** model has an extended dose measurement range of up to 20 Sv and improved accuracy of the dose rate measurement. Instead of a rechargeable battery, this model is **powered by an AAA (LR03) battery** which is easy to replace, affordable, and safe to handle.

The **PM1610 series** of electronic personal dosimeters (**EPDs**) are intended for measurement of the personal dose equivalent $H_p(10)$ and personal dose equivalent rate $\dot{H}_p(10)$. The dosimeters are suitable for multiple applications providing the measurement of X-ray (continuous and pulsed) and gamma radiation in the wide energy range.

The **PM1610** dosimeters have unique features for operation in workplaces requiring the use of personal protective equipment or in a harsh environment, including a shockproof rubberized case, a high contrast display with a fluorescent backlight, and two big buttons for easy use even while wearing protective gloves.

- Easily replaceable long-life AAA battery: at least 480 hours
- Extended energy range: from 20 keV to 10 MeV
- Wide dose and dose rate measurement ranges
- Measurement of pulsed photon radiation
- Simple navigation with two large buttons
- Audible, visual, and vibration alarms
- USB communication with PC
- Shockproof hermetic case
- Small and lightweight





PM1610 X-Ray and Gamma Radiation Personal Dosimeter

X-ray (continuous/pulsed) and gamma radiation personal dosimeter.

The **PM1610 series** of electronic personal dosimeters (**EPDs**) are intended for measurement of the personal dose equivalent $H_p(10)$ and personal dose equivalent rate $\dot{H}_p(10)$. The dosimeters are suitable for multiple applications providing the measurement of X-ray (continuous and pulsed) and gamma radiation in the wide energy range.

The **PM1610** dosimeters have unique features for operation in workplaces requiring the use of personal protective equipment or in a harsh environment, including a shockproof rubberized case, a high contrast display with a fluorescent backlight, and two big buttons for easy use even while wearing protective gloves.



Features

- Long-life rechargeable battery: at least 650 hours
- Extended energy range: from 20 keV to 10 MeV
- Wide dose and dose rate measurement ranges
- Measurement of pulsed photon radiation
- Simple navigation with two large buttons
- Audible, visual, and vibration alarms
- USB communication with PC
- Shockproof hermetic case
- Small and lightweight



PM1605BT Personal Radiation Monitor/Dosimeter

Ambient dosimeter for use in extreme environments.


The **PM1605BT** electronic dosimeter is equipped with a Geiger-Mueller counter for extended measurement of the **ambient dose equivalent** and **ambient dose equivalent rate**. Instruments can search, detect, and locate radioactive sources, alert the user with audible, visual, and vibration alarms, and transmit stored data to a PC or smartphone.

The dosimeter is designed to withstand **extreme environmental conditions** such as limited visibility, raised noise, high temperatures, exposure to seawater, shock, and falls. Its control panel with two big buttons allows using protective gloves while operating the instrument.

The instruments are recommended for personal radiation protection of first responders, HAZMAT teams, civil defense, firefighters, and the other divisions that deal with radiological emergencies.

Features

- IP68 case for operation in extreme environmental conditions
- Highly visible LEDs on the front and top panels for alarm indication
- Removable clip for secure fastening to a belt or a pocket
- Large buttons suitable for use with protective gloves
- Operating temperature from -30 °C to 65 °C
- Ambient dose equivalent rate up to 10 Sv/h
- Ambient dose equivalent up to 100 Sv
- Bluetooth and USB communication
- Battery lifetime of at least 9 months
- Large and easy-to-read LCD





Détection des radiations > Dosimètres électroniques personnels

PoliSimeter™ ERB Electronic Personal Dosimeter

X-ray (continuous/pulsed) and gamma radiation personal dosimeter with an **extended range** of dose measurement and a replaceable **battery**.

PoliSimeter™ series of electronic personal dosimeters (EPDs) is the **next generation** of the well-known **PM1610 series** by Polimaster, which was a trusted solution on the market for nearly 15 years, with over 20,000 dosimeters sold. Building on the legacy of the PM1610, the PoliSimeter offers enhanced capabilities for the extended measurement of **personal dose Hp(10)** and **dose rate $\dot{H}_p(10)$** of both continuous and pulsed X-ray and gamma radiation. The PoliSimeter is designed to meet the latest industry requirements and features a USB-C port for convenient connectivity and data transfer.

PoliSimeter ERB model has an **extended range** of dose measurement of **up to 20 Sv** for use in high-radiation environments, providing critical safety and monitoring functionality. Instead of a rechargeable battery, this model is powered by an **AAA battery**, which is easy to replace, affordable and safe to handle.

Features

- Wide dose and dose rate measurement ranges
- Easily replaceable long-life AAA battery: 500 hours
- Measurement of pulsed photon radiation
- Simple navigation with two large buttons
- Audible, visual, and vibration alarms
- USB-C communication with PC
- Shockproof hermetic case
- Small and lightweight





PoliSimeter™ ER Electronic Personal Dosimeter

X-ray (continuous/pulsed) and gamma radiation personal dosimeter with an **extended range** of dose measurement.

PoliSimeter™ series of electronic personal dosimeters (EPDs) is the **next generation** of the well-known **PM1610 series** by Polimaster, which was a trusted solution on the market for nearly 15 years, with over 20,000 dosimeters sold. Building on the legacy of the PM1610, the PoliSimeter offers enhanced capabilities for the extended measurement of **personal dose Hp(10)** and **dose rate $\dot{H}_p(10)$** of both continuous and pulsed X-ray and gamma radiation. The PoliSimeter is designed to meet the latest industry requirements and features a USB-C port for convenient connectivity and data transfer.

PoliSimeter ER model has an **extended range** of dose measurement of **up to 20 Sv** for use in high-radiation environments, providing critical safety and monitoring functionality.

Features

- Wide dose and dose rate measurement ranges
- Long-life rechargeable battery: 500 hours
- Measurement of pulsed photon radiation
- Simple navigation with two large buttons
- Audible, visual, and vibration alarms
- USB-C communication with PC
- Shockproof hermetic case
- Small and lightweight



← [Back to partner](#)



Détection des radiations > Dosimètres électroniques personnels

PoliSimeter™ Electronic Personal Dosimeter

X-ray (continuous/pulsed) and gamma radiation personal dosimeter.

PoliSimeter™ series of electronic personal dosimeters (EPDs) is the **next generation** of the well-known **PM1610 series** by Polimaster, which was a trusted solution on the market for nearly 15 years, with over 20,000 dosimeters sold. Building on the legacy of the PM1610, the PoliSimeter offers enhanced capabilities for the extended measurement of **personal dose Hp(10)** and **dose rate $\dot{H}_p(10)$** of both continuous and pulsed X-ray and gamma radiation. The PoliSimeter is designed to meet the latest industry requirements and features a USB-C port for convenient connectivity and data transfer.



Features

- Wide dose and dose rate measurement ranges
- Long-life rechargeable battery: 500 hours
- Measurement of pulsed photon radiation
- Simple navigation with two large buttons
- Audible, visual, and vibration alarms
- USB-C communication with PC
- Shockproof hermetic case
- Small and lightweight

← [Back to partner](#)



Détection des radiations > Dosimètres électroniques personnels

RadFlash® Electronic Personal Dosimeter



With RadFlash, the instant your radiation exposure increases, you know it. Continuous monitoring and custom alerts provide immediate, precise feedback, empowering you to react in-the-moment to changes in your exposure environment.

The dosimeter is capable of solving a wide range of personal dose monitoring tasks, including measurement of personal dose equivalent $H_p(10)$ and personal dose equivalent rate $\dot{H}_p(10)$ of X-ray (continuous and pulsed) and gamma radiation.

Only the best instant monitoring and alerts provide the safety professionals deserve. The RadFlash electronic personal dosimeter gives you immediate feedback, high precision, and unmatched flexibility. It's the perfect tool for minimizing risk and maximizing confidence.

Features

- Independent alarm thresholds for both dose and dose rate
- Automatic calculation of the safe stay time in the Polismart® app
- Compatible with real-time dosimetry systems
- Miniature, lightweight design
- Intuitive single-control button
- Bluetooth integration
- Wireless charging



Partner Bertin Instruments



Bertin Instruments est un fournisseur mondial de solutions avancées de détection des radiations et de surveillance environnementale, spécialisé dans les détecteurs portables, les dosimètres électroniques personnels, les systèmes de surveillance environnementale et les technologies de gestion des déchets et du recyclage. Ses instruments sont conçus pour répondre aux exigences rigoureuses des installations nucléaires, des équipes d'intervention d'urgence et des agences environnementales.

Product offering

Saphydose gamma i



← [Back to partner](#)



Détection des radiations > Dosimètres électroniques personnels

Saphydose gamma i

Saphydose Gamma i is an operational dosimeter measuring radiation in real time (Hp (10) X and γ dose).

This dosimeter is designed for people working in a controlled area (nuclear power plant, fuel reprocessing plant, research center, hospital, non-destructive testing service, etc.) or likely to be exposed (army, police, fire brigade, etc.).

It is compliant with the IEC 61526 standard for measurement of personal dose equivalents. Reliable and ergonomic, the Saphydose Gamma i is appreciated for its sturdy aluminum housing, its high resistance to electromagnetic fields and its long time battery life. It can be used individually or as part of our dosimetry management system.





Partner **SE International**



S.E. International, Inc. est un fabricant américain de confiance d'instruments de détection de radiations sous la marque Radiation Alert®. Sa gamme de produits comprend des détecteurs de zone, des radiamètres portables et des dosimètres électroniques personnels, tous conçus pour une surveillance précise et en temps réel des radiations dans un large éventail d'applications.

Product offering

**Radiation Alert®
Sentry EC**



**Rad-60 Alarming
Dosimeter**



← [Back to partner](#)



Détection des radiations > Dosimètres électroniques personnels

Radiation Alert® Sentry EC

The Radiation Alert® Sentry EC is a personal alarming radiation dosimeter and rate meter, designed to safeguard personnel working in environments with potential X-ray or gamma exposure.

This pocket-sized unit features an energy-compensated tube for a linear gamma response and built-in memory for tracking accumulated exposure data. With the free SentryCom Software, you can easily generate incident reconstructions for analysis and set custom vibrating and audio alerts for dose (>1.0 mR/10 µSv) and dose rate (>1.0 mR/hr/10 µSv/hr).

An audio switch allows you to choose between audible clicks with each detected count or a discreet silent mode.



[← Back to partner](#)



Détection des radiations > Dosimètres électroniques personnels

Rad-60 Alarming Dosimeter

The RAD-60 is a Personal Alarming Radiation Dosimeter. It's a precise and reliable instrument for ensuring the safety of personnel. Ideally, the RAD-60 is used in stand-alone conditions for everyday radiation monitoring . The RAD-60 can also be switched into System Mode, for the purpose of tracking Personnel Dose records and generating compliance reports.

The design includes state-of-the-art technology with built in memory for retrieving dose, even during power-down. It eliminates outside interference from shock and RF. The RAD-60 is easily programmed by the user, has a digital display, and operates with a single AAA alkaline battery.

With the push of a button, you can turn the unit on/off, change the digital display to read dose or dose rate, select from several dose and dose rate alarm levels, turn the chirp function on/off, reset the integrated dose, and perform battery tests. The large digital display gives instant dose or dose rate readings with a loud audible alarm.





Partner **Ludlum Measurements**



Ludlum Measurements, Inc. conçoit et fabrique des instruments et des technologies de détection des rayonnements. Fondée en 1962, elle propose une large gamme d'instruments de détection de rayonnements, développés pour aider à surveiller la sécurité du personnel et de l'environnement. Les instruments sont utilisés dans des applications telles que la surveillance de routine du personnel et du matériel, la sécurité des frontières et les situations d'intervention d'urgence.

Product offering

**Model 23-1 Electronic
Personal Dosimeter -
Ludlum**



← [Back to partner](#)



Détection des radiations > Dosimètres électroniques personnels

Model 23-1 Electronic Personal Dosimeter - Ludlum

The Model 23-1 Electronic Personal Dosimeter (Ludlum) is a solid and lightweight (55.9 g/2 oz) pen-type personal dosimeter. It can be used for measuring gamma or X-ray radiation in medical and laboratory environments or other areas where personal radiation monitoring is desired or required.



Model 23-1 Electronic Personal Dosimeter features:

- 600 record data logging option available
- low weight and slim design
- audio alarm
- silicon semiconductor detector
- gamma and X-ray (35 keV to 3 MeV)

Read more about the Model 23-1 Electronic Personal Dosimeter on the [Ludlum website](#)

CAMÉRAS CZT ET GAMMA





Partner **BSI**



Baltic Scientific Instruments (BSI) is an OEM manufacturer based in Riga, Latvia, dedicated to the development and production of advanced spectrometric and detection equipment. With decades of experience and roots in the former Research Institute for Radioisotope Apparatus (RNIIRP), BSI provides cutting-edge technologies for nuclear power, environmental monitoring, security, medicine, and scientific research.

The company specializes in HPGe, Si, CdZnTe/CdTe, and scintillation detector systems, known for their accuracy, stability, and performance in demanding analytical environments.

Through continuous innovation, strict quality assurance (ISO 9001:2015), and strong international collaboration, BSI supports customers worldwide in achieving precise and reliable radiation measurement and analysis.

Product offering

Hand-held Integrated Gamma Spectrometer





Hand-held Integrated Gamma Spectrometer

Hand-held Integrated Gamma Spectrometer with an integrated HPGe detector, preamplifier, multichannel analyzer, batteries, and software offers relatively compact, portable solution for high-resolution gamma-ray analysis. Its all-in-one design enhances field usability, requiring no external components for setup.



Application

Hand-held Integrated Gamma Spectrometer is ideal for nuclear safety, environmental monitoring, radiological emergency response, CBRN and waste characterization, it ensures rapid deployment and reliable data acquisition. The integrated system minimizes cabling, reduces noise, and simplifies operation, making it highly efficient for both laboratory and on-site measurements.

Features

- Integrated HPGe Detector - High-purity germanium detector ensures excellent energy resolution for precise gamma spectroscopy
- Embedded Digital Multichannel Analyzer (MCA) - Enables real-time spectrum acquisition and processing without external electronics
- Internal Battery Operation - Offers several hours of autonomous use for field measurements
- Compact All-in-One Design - Reduces cabling and simplifies deployment in any environment
- On-board ruggedized display - large and bright to fit the whole spectrum or a part of it since software is adopted for "mobile view mode"
- Analytical Spectroscopy Software - Supports spectrum analysis, nuclide identification, and reporting
- Advanced Spectroscopy Software - allows applying Monte-Carlo simulation results to the analytical software to make sure correct measurement result in case of complex geometry of the measured object



Partner **3D Plus**



3D PLUS est un fournisseur de premier plan de systèmes d'imagerie compacts et performants basés sur la technologie CZT (tellurure de cadmium et de zinc). Conçues pour des applications exigeantes dans les secteurs de l'espace, de la défense et du nucléaire, ses gamma-caméras offrent une imagerie précise et en temps réel des rayonnements dans des formats compacts et robustes.

Product offering

Spid-X





Détection des radiations > Caméras CZT et Gamma Spid-X

In collaboration with the French Atomic Energy Commission (CEA), the Spectro Imager Spid-X has been designed for nuclear safety applications such as radioactive waste monitoring, decommissioning, decontamination or emergency situations.

The device offers fine spectroscopic capabilities embedding ultra-low noise ASICs and CdTe crystal thanks to 3D PLUS electronic components miniaturization technology.

The Spid-X gamma camera allows locating, identifying and measuring the dose intensity of the various radioactive sources that can be found in a nuclear environment. Combined with the small size and lightweight of the device, it brings a fast and efficient diagnostic on site, and can help the decontamination process.

Features

- Identifies and locates the radioactive sources
- Measures the dose of the sources
- Small dimensions : 323 x 110 x 180 mm³
- Light Weight : < 3,5 kg
- Covers large range of energy
- Fine spectroscopic capabilities





Partner **Kromek**



Kromek Group plc est un leader mondial des technologies avancées de détection des radiations, spécialisé dans les solutions compactes et haute résolution pour les applications de sécurité, de défense, de nucléaire et de recherche. S'appuyant sur sa technologie brevetée de semi-conducteurs au tellure de cadmium-zinc (CZT), Kromek propose une gamme polyvalente comprenant des moniteurs portables, des identificateurs d'isotopes portables, des gamma-caméras CZT et des spectromètres de laboratoire.

Product offering

GR Series Gamma Spectrometers



Quant GR1



TN15



Sigma 25/50



RayMon 10



K102





GR Series Gamma Spectrometers

A family of small and light CZT-based Gamma detector spectrometers!



The Kromek GR family is a range of CZT-based high-performance Gamma spectrometers. They are completely self-contained, with built-in preamplifier, shaping amplifier, baseline restorer, pulse height digitizer and HV supply. The digitised pulse heights of detected Gamma signals are sent to a computer via the USB. The unit is powered entirely from the USB bus, so no external power supply is needed.

Can be used for all Gamma radiation detection needs either straight out of the box or built into your own devices. The GR Gamma detectors can be mounted side by side in an array to give you coverage of a large area.

GR1/GR1+ Gamma spectrometer

- Perfect for most uses
- Energy resolution: < 2.5% FWHM @ 662 KeV
- USB output only
- 1 cm cubed CZT detector
- The plus model is available for those that need higher resolution:
- Energy resolution: <2.0% FWHM @ 662 KeV

GR1-A/GR1-A+ Gamma spectrometer

- For those that need extra outputs channels
- Energy resolution: < 2.5% FWHM @ 662 keV
- USB output
- Three MCX connectors that provide energy and timing outputs and gate inputs
- MultiSpect Analysis spectroscopy software included in the price
- 1 cm cubed CZT detector
- The plus model is available for those that need higher resolution:
- Energy resolution: <2.0% FWHM @ 662 KeV

GR05 Gamma spectrometer

- For use in a high-flux environment
- Energy resolution: < 2.5% FWHM @ 662 keV
- Max dose rate approximately 10mSv/hr
- USB output
- Smaller 0.125 cm cubed CZT detector

- For use in high-count (high-flux) environments



← [Back to partner](#)



Détection des radiations > Caméras CZT et Gamma

Quant GR1

The Quant GR1 is a complete mobile or benchtop solution for quantifying doses of Gamma radiation released by radionuclides. Its high resolution of <math><2\%</math> and count spectrum range of 4096 channels enables any isotope to be identified and its associated dose quantified, even from complex mixtures.

The ability to quantify radiation doses in real time eliminates the need for further analysis in the lab, as data can both be collected and processed on site, saving time and costs.



← [Back to partner](#)



Détection des radiations > Caméras CZT et Gamma

TN15

The Kromek TN15 is a robust, cost effective, self-contained, room temperature Neutron detector without Helium3. The detector surpasses the performance of a 100mm long 13mm³ He tube at 4 atmospheres and does not need cooling as it operates at room temperature.

This highly compact device is completely self-contained, with a built-in preamplifier, shaping amplifier, pulse discrimination, and HV supply.

The digitized neutron data is sent to a computer via the mini-USB which also powers the unit, so no external power supply is required; making the TN15 portable, creating a host of new ways to use and deploy neutron detectors.



← [Back to partner](#)



Détection des radiations > Caméras CZT et Gamma

Sigma 25/50

Available in two variations, Kromek's Sigma 25/50 Gamma ray detectors are highly sensitive, fast, and lightweight replacing conventional photomultiplier technology with state-of-the-art silicon photomultipliers (SiPMs).



The Sigma 25/50 Gamma detectors offer up to 32.8cm³ of detection volume, delivered in a package providing significant benefits in cost, size, weight, power consumption and temperature stability.

CsI(Tl) has a light output of 54 photons/keV and is one of the brightest scintillators known. As well as good Gamma photon stopping power this makes CsI(Tl) well suited for Gamma radiation detection.

Robust, Small & Lightweight

The Sigma 25/50 Caesium Iodide Scintillator Radiation detectors are perfect for radiation detection in the field and in the lab owing to their small size. If you need fast detection in an easy to use package this is what you need.

K-Spect & MultiSpect Analysis Integration

Kromek's Sigma 25/50 are available with both K-Spect and MultiSpect Analysis software which provide the spectrum acquisition, display, analysis, and storage functions.

Integration

Due to the discreet nature of the Sigma 25/50, these can be integrated into other systems. We've had them flying on drones and built into larger detector arrays.



RayMon 10

RayMon 10

Un détecteur gamma portable puissant et robuste pour l'identification des isotopes radioactifs à haute résolution. Le RayMon10 est l'un des moniteurs de rayonnement portables les plus puissants et les plus robustes au monde. Il peut être utilisé pour détecter, mesurer et identifier avec précision les radionucléides émetteurs de rayons gamma, fournissant une identification isotopique à haute résolution à l'aide de la dernière technologie de détecteur à semi-conducteurs CZT. C'est une solution tout-en-un à vos besoins d'identification des radionucléides gamma

Il peut produire une variété de rapports, notamment la date/heure, l'identifiant de l'utilisateur, les notes photo et audio, le positionnement GPS, les spectres de rayonnement et l'identification des isotopes.

Les variations des conditions normales de fonctionnement peuvent souvent affecter les performances de l'identification des radio-isotopes. Le détecteur avancé à grille coplanaire CZT d'un centimètre cube du RayMon10 offre des performances plus stables que les détecteurs de type à scintillation.



← [Back to partner](#)



Détection des radiations > Caméras CZT et Gamma **K102**

The Kromek K102 accepts amplified shaped pulses from detectors, digitizes the pulse heights, and sends the data to PC via the USB bus.

The Analyser is available with either Kromek's Windows based (7/8/10) K-Spect or MultiSpect Analysis software, which provide the spectrum acquisition, display, analysis, and storage functions.

It is powered through the USB bus so no external power supply is required.



IDENTIFICATEURS D'ISOTOPES PORTABLES





Partner **BSI**



Baltic Scientific Instruments (BSI) is an OEM manufacturer based in Riga, Latvia, dedicated to the development and production of advanced spectrometric and detection equipment. With decades of experience and roots in the former Research Institute for Radioisotope Apparatus (RNIIRP), BSI provides cutting-edge technologies for nuclear power, environmental monitoring, security, medicine, and scientific research.

The company specializes in HPGe, Si, CdZnTe/CdTe, and scintillation detector systems, known for their accuracy, stability, and performance in demanding analytical environments.

Through continuous innovation, strict quality assurance (ISO 9001:2015), and strong international collaboration, BSI supports customers worldwide in achieving precise and reliable radiation measurement and analysis.

Product offering

Hand-held Integrated Gamma Spectrometer





Hand-held Integrated Gamma Spectrometer

Hand-held Integrated Gamma Spectrometer with an integrated HPGe detector, preamplifier, multichannel analyzer, batteries, and software offers relatively compact, portable solution for high-resolution gamma-ray analysis. Its all-in-one design enhances field usability, requiring no external components for setup.



Application

Hand-held Integrated Gamma Spectrometer is ideal for nuclear safety, environmental monitoring, radiological emergency response, CBRN and waste characterization, it ensures rapid deployment and reliable data acquisition. The integrated system minimizes cabling, reduces noise, and simplifies operation, making it highly efficient for both laboratory and on-site measurements.

Features

- Integrated HPGe Detector - High-purity germanium detector ensures excellent energy resolution for precise gamma spectroscopy
- Embedded Digital Multichannel Analyzer (MCA) - Enables real-time spectrum acquisition and processing without external electronics
- Internal Battery Operation - Offers several hours of autonomous use for field measurements
- Compact All-in-One Design - Reduces cabling and simplifies deployment in any environment
- On-board ruggedized display - large and bright to fit the whole spectrum or a part of it since software is adopted for "mobile view mode"
- Analytical Spectroscopy Software - Supports spectrum analysis, nuclide identification, and reporting
- Advanced Spectroscopy Software - allows applying Monte-Carlo simulation results to the analytical software to make sure correct measurement result in case of complex geometry of the measured object




Partner **Else Nuclear**



ELSE NUCLEAR S.r.l. is an Italian OEM company specializing in advanced radiation-detection and environmental-monitoring systems for nuclear safety, industry and research.

Product offering



← [Back to partner](#)



Détection des radiations > Identificateurs d'isotopes portables

B-RAD

B-RAD is a hand-held radio-isotope identifier (RIID) for gamma dose rate survey and spectrometry measurements, specifically designed to work in magnetic fields up to 3 T. For comparison, conventional devices fail to operate at intensities as low as 0.1 T.



Light and compact, B-RAD is ideal for radiation surveys and for local measurements of contamination or residual radioactivity in hot spots. The built-in software and algorithm allow performing accurate gamma spectrometry and dose rate measurement with a single instrument.

B-RAD employs a high sensitivity $\text{LaBr}_3(\text{Ce}^{3+})$ crystal directly coupled to a SiPM matrix. Its excellent scintillation properties, high energy resolution (3.3% FWHM at 662 keV) and fast response, together with the built-in pile-up and dead-time correction algorithms, allow the device to cover an extremely wide dose rate range (100 nSv/h to > 20 mSv/h).

This technology has been originally developed at CERN (*) and has become the standard for radiation surveys in the Large Hadron Collider (LHC) experiments. It is commercialized under an official license granted by CERN, with the “CERN Technology” label.



FOOMON

FOOMON is a portable fully-integrated instrument specifically conceived for screening of I-131, Cs-134 and Cs-137 accumulated in food samples. Its “on-the-field” design allows deploying the device in any kind of situation, such as routine campaigns or emergency procedures.



The whole device is self-contained in a portable high-IP-grade technical case, for an overall weight < 25 kg. The food samples are to be placed in 500 ml Marinelli beakers, which then are lodged inside a 1 cm thick lead shielding well upon the detector’s end cap. The complete setup and deployment of the system requires less than 5 minutes.

The User can manage FOOMON through the user-friendly control and analysis software installed on the embedded panel PC, automatically calculating the specific activity and the Minimum Detectable Concentration (MDC) of the sample (in Bq/kg). Data are stored locally and can be analysed and downloaded with dedicated software routines.

The measured activity concentration is compared with isotope-specific and food-group-specific alarms. In the case of an alarm, the measurement output is clearly labelled and the alarm status is clearly displayed on the software, which also activates the acoustic alarm.

The counts-to-activity-concentration conversion coefficients are calculated by means of dedicated Monte Carlo calculations.

The MDC achievable in 1 minute, with an average indoor background (150 nSv/h), is as low as about 150 Bq/kg for Cs-137 and Cs-134, and about 90 Bq/kg for I-131. Under the same conditions, MDC as low as about 30 Bq/kg for I-131, and about 40 Bq/kg for Cs-134 and Cs-137, can be achieved in about 10 minutes.

If enabled, the automatic background subtraction subroutine allows further lowering MDC and measurement uncertainty without increasing the counting time.



THYMON

THYMON is a compact NaI(Tl)-based detector specifically conceived to fast, yet reliably, measure I-131 contamination in thyroid. Its compactness, ruggedness, light-weight, together with its simple and intuitive built-in software interface, make the device perfectly suited for emergency screening applications. The instrument can be used either hand-held or hands-free. The instrument is composed by three main subparts:



- Detector probe: a 1.5" x 1.5" collimated NaI(Tl) crystal coupled to a SiPM matrix and extremely compact readout electronics and MCA
- Extendable support: designed as both table-top and standalone, providing the possibility of hands-free operation
- Control tablet: IP65 water- and dust-proof 8" capacitive screen, wired-connected to the probe

The mechanics of the probe is specifically conceived to ensure the best alignment between the probe and the thyroid, guaranteeing excellent crystal-to-thyroid alignment, and reducing positioning uncertainties.

The control and analysis software installed on the control tablet is designed to be simple and intuitive, yet advanced and comprehensive. This is accomplished by combining a simple and intuitive interface with advanced calculation routines, which run automatically as the measurement start, without the need of operator intervention.

Data are stored locally on the tablet internal memory, and can be analysed and downloaded with dedicated software routines.

The automatic I-131 activity calculation is given for pre-defined age groups: 1 yo, 5 yo, 10 yo, 15 yo (Adult Female), Adult Male. Counts-to-activity conversion coefficients are calculated by dedicated Monte Carlo simulations based on detailed detector and thyroid numerical models. The simulations are always validated for the specific system through experimental tests performed with reference radioactive sources.

The activity is compared to 2 User-defined threshold levels, each defined per each age group, following the two Action Levels logic.

MDA as low as about 100 Bq can be achieved in 2 min screenings. The MDA can be further lowered by enabling the background subtraction option.

← [Back to partner](#)



Détection des radiations > Identificateurs d'isotopes portables

HERMES GSU

HERMES GSU is a portable gamma spectrometry system designed for rapid and precise in-field analysis of environmental samples. As part of the HERMES product line, it features a rugged, modular, and self-contained design housed in a high IP-rated technical case, ensuring durability and reliability in demanding conditions.



HERMES GSU quantifies isotope activity concentrations based on a rich built-in, yet fully-editable, isotope library. Its portability and autonomous operation make it ideal for both routine monitoring and emergency response scenarios.

Samples can be directly collected from the field, placed in 500 ml Marinelli beakers, and inserted into the built-in 1 cm lead-shielded well, minimizing background radiation for immediate, on-the-spot, low MDC analysis, and enhancing measurement accuracy and sensitivity. The system automatically calculates activity concentrations, making it a powerful tool for in-situ, laboratory-grade measurements.

HERMES GSU features advanced routines for gain stabilization, dead time correction, and automatic energy calibration (relying on natural background only, thus not requiring any radioactive reference source).

Efficiency calibration curves are generated using validated Monte Carlo simulations. Predefined efficiency curves are available for different sample matrices, including soil, water, and foodstuffs, across various densities. Custom calibration curves can be provided upon request.



Partner **Kromek**



Kromek Group plc est un leader mondial des technologies avancées de détection des radiations, spécialisé dans les solutions compactes et haute résolution pour les applications de sécurité, de défense, de nucléaire et de recherche. S'appuyant sur sa technologie brevetée de semi-conducteurs au tellure de cadmium-zinc (CZT), Kromek propose une gamme polyvalente comprenant des moniteurs portables, des identificateurs d'isotopes portables, des gamma-caméras CZT et des spectromètres de laboratoire.

Product offering

GR Series Gamma Spectrometers



D5 RIID



D3S ID



RayMon 10



AARM





GR Series Gamma Spectrometers

A family of small and light CZT-based Gamma detector spectrometers!



The Kromek GR family is a range of CZT-based high-performance Gamma spectrometers. They are completely self-contained, with built-in preamplifier, shaping amplifier, baseline restorer, pulse height digitizer and HV supply. The digitised pulse heights of detected Gamma signals are sent to a computer via the USB. The unit is powered entirely from the USB bus, so no external power supply is needed.

Can be used for all Gamma radiation detection needs either straight out of the box or built into your own devices. The GR Gamma detectors can be mounted side by side in an array to give you coverage of a large area.

GR1/GR1+ Gamma spectrometer

- Perfect for most uses
- Energy resolution: < 2.5% FWHM @ 662 KeV
- USB output only
- 1 cm cubed CZT detector
- The plus model is available for those that need higher resolution:
- Energy resolution: <2.0% FWHM @ 662 KeV

GR1-A/GR1-A+ Gamma spectrometer

- For those that need extra outputs channels
- Energy resolution: < 2.5% FWHM @ 662 keV
- USB output
- Three MCX connectors that provide energy and timing outputs and gate inputs
- MultiSpect Analysis spectroscopy software included in the price
- 1 cm cubed CZT detector
- The plus model is available for those that need higher resolution:
- Energy resolution: <2.0% FWHM @ 662 KeV

GR05 Gamma spectrometer

- For use in a high-flux environment
- Energy resolution: < 2.5% FWHM @ 662 keV
- Max dose rate approximately 10mSv/hr
- USB output
- Smaller 0.125 cm cubed CZT detector

- For use in high-count (high-flux) environments



← **Back to partner**



Détection des radiations > Identificateurs d'isotopes portables

D5 RIID

Le D5 RIID fournit un dispositif unique de détection de rayonnements hautes performances et polyvalent dans un boîtier portable pour le personnel militaire, de la sécurité intérieure et industriel.



Le D5 RIID est un petit dispositif d'identification de radio-isotopes (RIID) portable, léger, d'une résolution de 3,5 %, doté d'une vaste bibliothèque de radio-isotopes et d'un taux de fausses alarmes ultra faible. Il analyse en permanence et identifie avec précision les menaces radiologiques en temps réel, même dans des environnements à sources mixtes.

Le D5 RIID combine un petit format avec de puissantes performances radiométriques et une sensibilité améliorée à une résolution moyenne de 3,5 %. Le D5 RIID a une efficacité de surface 62 % supérieure à celle des RIID conventionnels.

D5 RIID Overview <https://youtu.be/yi-uvo05nFg>



**SCAN TO VIEW
VIDEO**

Le D5 RIID est le plus petit, le plus léger et offre les performances de détection ultimes. Il a une résolution de 3,5 %, avec une vaste bibliothèque de radio-isotopes et un taux de fausses alarmes ultra faible. Il analyse en permanence et identifie avec précision les menaces radiologiques en temps réel, même dans des environnements à sources mixtes.

← [Back to partner](#)



Détection des radiations > Identificateurs d'isotopes portables

D3S ID

Un détecteur gamma et neutronique portable et dissimulable qui met la puissance d'un RIID dans un boîtier de la taille d'un détecteur de rayonnement personnel (PRD). D3S ID est la nouvelle norme en matière de détecteurs de rayonnement portables.

Le D3S ID est un appareil puissant, portable, discret et mains libres qui recherche en permanence les menaces de rayonnement gamma et neutronique.



Le D3S de Kromek répond aux attentes en matière de sécurité des données des gouvernements, des services de renseignement et des autorités de sécurité. Le D3S est livré en standard avec un smartphone sécurisé (contrôle Android), qui contient le logiciel de détection Kromek exclusif et sécurisé. Le D3S est déjà fréquemment utilisé aux États-Unis, par exemple sur les camions de pompiers et les ambulances ou comme système de cartographie de zone avec 1 000 détecteurs lors d'une « chasse au trésor ». En Europe, le D3S a été déployé lors de visites d'État et de consultations de l'OTAN ces dernières années, pour détecter les menaces radioactives précoces pouvant être présentes dans les marchandises, les véhicules, les bâtiments, d'autres objets et dans l'environnement.

Caractéristiques:

Identifie 37 isotopes (17 de plus que la norme ANSI actuelle)

S'identifie plus rapidement qu'un RIID

Économique par rapport aux autres produits du marché

Petite taille, portable, s'adapte à la ceinture

Connectable en réseau



RayMon 10

RayMon 10

Un détecteur gamma portable puissant et robuste pour l'identification des isotopes radioactifs à haute résolution. Le RayMon10 est l'un des moniteurs de rayonnement portables les plus puissants et les plus robustes au monde. Il peut être utilisé pour détecter, mesurer et identifier avec précision les radionucléides émetteurs de rayons gamma, fournissant une identification isotopique à haute résolution à l'aide de la dernière technologie de détecteur à semi-conducteurs CZT. C'est une solution tout-en-un à vos besoins d'identification des radionucléides gamma

Il peut produire une variété de rapports, notamment la date/heure, l'identifiant de l'utilisateur, les notes photo et audio, le positionnement GPS, les spectres de rayonnement et l'identification des isotopes.

Les variations des conditions normales de fonctionnement peuvent souvent affecter les performances de l'identification des radio-isotopes. Le détecteur avancé à grille coplanaire CZT d'un centimètre cube du RayMon10 offre des performances plus stables que les détecteurs de type à scintillation.



← [Back to partner](#)



Détection des radiations > Identificateurs d'isotopes portables

AARM

Localisation, mesure et cartographie en temps réel de la radioactivité aérienne avec la charge utile basée sur le drone de Kromek !



Lorsqu'il est monté sur n'importe quel modèle de drone multirotor, le système de charge utile AARM de Kromek peut être utilisé pour effectuer des études radiologiques rapides et détaillées sur de vastes zones. Son système de capteurs avancé composé de capteurs de rayonnement et de position intégrés permet de collecter des empreintes isotopiques, des comptes par seconde et des données spectrales complètes, puis de les transmettre à l'utilisateur chaque seconde.

Les données sont également visualisées en temps réel sous la forme d'une carte thermique de rayonnement à résolution métrique sur l'application iOS de l'AARM. Les points chauds et les anomalies peuvent être rapidement identifiés à une distance sûre, ce qui est optimal pour les applications comprenant, sans toutefois s'y limiter, les enquêtes et la surveillance environnementales, ainsi que pour améliorer la connaissance de la situation et la réponse rapide dans les applications de sécurité nucléaire.

Des options flexibles de détection et de communication sont également disponibles, ajoutant à la polyvalence du système. Les communications basées sur le cloud permettent de visualiser les données spectrales et les comptes par seconde depuis n'importe où dans le monde. Des options non basées sur le cloud sont également disponibles, avec un stockage intégré des données également possible. La charge utile abrite les capacités éprouvées de détection des rayonnements de Kromek, avec des configurations de détecteurs simples ou doubles GR1, SIGMA 50, TN15 ou D3S. La large plage de températures de fonctionnement du système élargit encore la polyvalence des missions du système, rendant les missions possibles partout dans le monde.





Partner **Polimaster**



Polimaster est un leader mondial des solutions de détection et de surveillance des rayonnements. Il propose une gamme complète d'instruments conçus pour détecter, identifier et mesurer les rayonnements ionisants dans divers environnements. Sa gamme de produits comprend des détecteurs portables, des dosimètres électroniques personnels, des identificateurs isotopiques portables, des portiques de détection et des systèmes de détection mobiles,

tous conçus pour répondre aux exigences rigoureuses des secteurs de la sécurité, des interventions d'urgence et des applications industrielles.

Product offering

PM1401K-3M
**Multipurpose Hand-
Held Radiation
Monitor/Identifier**



PM1401K-3P
**Multipurpose Hand-
Held Radiation
Monitor/Identifier**



← Back to partner



Détection des radiations > Identificateurs d'isotopes portables

PM1401K-3M Multipurpose Hand-Held Radiation Monitor/Identifier

PM1401K-3M model is a gamma-only radiation monitor without a neutron detector which is designed for quick and reliable measurement of gamma dose rate, detection of alpha, beta, and gamma sources, measurement of alpha and beta radiation flux density, acquisition of gamma spectra, identification of radioisotopes, and measurement of food/soil contamination with ^{137}Cs

Features

- Storage of up to 10000 events and 1000 spectra
- Audible, visual and external vibration alarm
- Categorization of identified radionuclides
- Shock and water resistant IP65 case
- Adjustable radionuclide libraries
- USB communication with PC
- Built-in GPS module

Applications

- Customs and border control
- HAZMAT and CBRNe teams
- Emergency services
- Police and security
- Industrial facilities
- First responders





Détection des radiations > Identificateurs d'isotopes portables

PM1401K-3P Multipurpose Hand-Held Radiation Monitor/Identifier

Gamma-neutron model suitable for various radiation control tasks.

The **PM1401K-3 series** of radiation monitors comprises a wide range of all-in-one devices for radiation detection, dose rate, contamination measurements, spectrometry, and radionuclide identification.

The **PM1401K-3P model** is the **gamma-neutron model** suitable for various radiation control tasks, including measurement of ambient dose equivalent rate, detection of alpha, beta, gamma, and neutron sources, measurement of alpha and beta radiation flux density, acquisition of gamma spectra, identification of radioisotopes, and measurement of food/soil contamination with ^{137}Cs .



Features

- Storage of up to 10000 events and 1000 spectra
- Audible, visual, and external vibration alarm
- Categorization of identified radionuclides
- Shock and water-resistant IP65 case
- Adjustable radionuclide libraries
- USB communication with PC
- Built-in GPS module

Operation principle

The PM1401K-3P continuously measures ambient dose equivalent rate $\dot{H}^*(10)$ of photon radiation in the wide energy range, detects alpha, beta, gamma, and neutron radiation, measures alpha and beta radiation flux density, operates as a gamma radiation spectrometer and radioisotope identifier, and measures food/soil contamination with ^{137}Cs radionuclide.



Partner **GEORADIS s.r.o.**



Georadis s.r.o. est un fabricant spécialisé d'instruments avancés de détection et de surveillance des radiations, proposant une gamme complète de solutions pour les applications de terrain et de laboratoire. Sa gamme de produits comprend des moniteurs portables, des identificateurs d'isotopes portables, des appareils de surveillance environnementale et des équipements de laboratoire, tous conçus pour répondre aux exigences rigoureuses des professionnels des secteurs de la surveillance environnementale, de la sécurité industrielle et de la sécurité publique.

Product offering

RT-30 Gamma-Ray Spectrometer with Nuclide ID Capability - Georadis



← Back to partner



Détection des radiations > Identificateurs d'isotopes portables

RT-30 Gamma-Ray Spectrometer with Nuclide ID Capability - Georadis

The RT-30 Gamma-Ray Spectrometer with Nuclide ID Capability (Georadis) integrates a radiation survey meter, dose meter and radionuclide identification device in a weather protected, lightweight and easy to use instrument.



RT-30 Gamma-Ray Spectrometer with Nuclide ID Capability features:

- multiple functions; nuclide ID (isotope name), scan and search
- auto-stabilization
- protection: IP66
- single button operation
- sensitivity: Co-60: 270 cps/MBq, Cs-137: 160 cps/MBq, Am-241: 75 cps/MBq
- data interchange; Bluetooth or USB
- readout search mode; 0 - 65535 cps
- energy response: 20 keV to 3000 keV
- energy compensated doserate: 0 - 10 mSv/h (with G/M detector)
- graphic LCD display; 128 x 64 pixels
- 2GB memory

Read more about the RT-30 Gamma-Ray Spectrometer with Nuclide ID Capability on the [Georadis website](#)

SURVEILLANCE ENVIRONNEMENTALE





Partner **Else Nuclear**



ELSE NUCLEAR S.r.l. is an Italian OEM company specializing in advanced radiation-detection and environmental-monitoring systems for nuclear safety, industry and research.

Product offering

GSU - GAMMA SPECTROMETRY UNIT WITH NaI(Tl)



SP2 - SINGLE-SPHERE NEUTRON SPECTROMETER



LUPIN BF3



SATURN I, SATURN II



SATURN 5702



NAUSICAA IC-T, ICP-T



GM-1, MERCURY



NAUSICAA 2IC



MISTRAL XM



HERMES



FOOMON



THYMON



HERMES GSU





GSU - GAMMA SPECTROMETRY UNIT WITH NaI(Tl)

The GSU gamma spectrometry units employ a 3"x3" NaI(Tl) crystal coupled to a photosensitive detector (either PMT or SiPM) and an MCA. The detector is installed in a 5 cm thick lead shielding well, with additional inner layers of tin and copper for enhanced background reduction.

GSU is designed to perform gamma spectrometry analyses of small samples, such as foundry casting samples, air particulate filters, environmental samples (rocks, soil, biological samples), positioned in sample holders which can be tailored to meet specific measurement requirements, or Marinelli beakers.



The User can manage the system through the proprietary ELSE NUCLEAR GSU system software, calculating the specific activity and the Minimum Detectable Concentration (MDC) of the sample expressed in Bq/kg, Bq/l, Bq/m³, etc. The built-in background subtraction subroutine improves the MDC without increasing the measurement time. The software includes fully-customisable isotope libraries as well as User-settable isotope-specific activity alarm thresholds, available through password-protected functions.

The GSU-NORM is a special version of system specifically conceived to perform Naturally Occurring Radioactive Material (NORM) analysis of environmental samples, such as rocks, sediments or soils. Through its MCA and its dedicated software, the GSU-NORM system allows determining the specific activity of NORM isotopes, i.e. K-40, Th-232 and U-238, expressed in Bq/g, %K, ppm eU and ppm eTh.

The sample holders are custom-made supports that fit directly on the detector's head, used to hold casting samples, test sources or other similar objects.

The Marinelli beakers are used to contain geological samples or other similar materials. Several volumes are available, from 250 ml up to 1 l, with different geometrical features.

Each GSU system includes efficiency curves and coefficients implemented in the analysis software, calculated through Monte Carlo simulations for each specific configuration, acquisition chain and measurement geometry. The simulations are always validated through experimental tests performed with reference radioactive sources.



Détection des radiations > Équipement de laboratoire

SP2 - SINGLE-SPHERE NEUTRON SPECTROMETER

The single-sphere neutron spectrometer SP2 is a unique device that allows performing active neutron spectrometry measurements by employing a single instrument instead of the usual multi-sphere BSS.



SP2 is characterized by the same high sensitivity and precision as BSS in determining the neutron flux over the entire energy range, while removing any reproducibility uncertainty. When employed with the on-line unfolding tool, SP2 can also perform real time measurements.

SP2 is equipped with 32 active ^6LiF -covered Silicon neutron detectors installed over six concentric layers inside the moderating assembly, so that they reproduce the spectrometric performance of a six-sphere BSS. The signals are acquired by the built-in electronics and can be either analysed on-line by the built-in unfolding algorithm, or saved as raw data for off-line analysis.

SP2 can be used in a great number of activities in scientific research: homeland security, cargo inspections, calibration laboratories, characterization of stray radiation fields for radiation protection purposes, periodical quality check of the neutron stray radiation field, all applications involving the need of a fast and precise measurement of the neutron spectrum.

A SP2 LITE version is also available, featuring a lighter build and a narrower energy range, suitable for all the applications that do not require to detect neutrons with energy above 20 MeV.

The response function of the device, calculated via Monte Carlo simulations, is available for either on-line and off-line analysis. The response function and unfolding algorithm have been validated after thoroughly testing with reference radioactive sources.

SP2 is the ideal device for performing active neutron spectrum measurements in every radiation environment, including mixed stray radiation fields, workplaces characterized by high gamma background and reference calibration laboratories.



LUPIN BF3

LUPIN BF3 is an environmental monitoring unit for neutron $H^*(10)$ measurements, with unique excellent performance for neutron detection in pulsed fields.

The rem counter is composed of:

- BF_3 proportional counter
- Cylindrical moderating assembly
- Built-in power supply, signal management and control electronics



The electronics processes the signal coming from the detector and elaborates the instantaneous $H^*(10)$ rate value every second.

If required, the radiation sensitive electronics can be housed in a separate rack. An accessory IP54 version is also available

Data are sent to the connected SATURN ratemeter acquisition and control unit, which locally displays the instantaneous $H^*(10)$ rate and the integrated values and compares them to the pre-set alarm thresholds.

A LUPIN BF3 LITE version is also available, featuring a lighter build and a narrower energy range, suitable for all the applications that do not require to detect neutrons with energy above 20 MeV.

Papers published in international scientific journals:

- M. Caresana, M. Ferrarini, G.P. Manessi, M. Silari and V. Varoli, LUPIN, a new instrument for pulsed neutron fields, Nuclear Instruments and Methods in Physics Research Section A 712 (2013) 15-26.
- M. Caresana, C. Cassell, M. Ferrarini, E. Hohmann, G.P. Manessi, S. Mayer, M. Silari and V. Varoli, A new version of the LUPIN detector: improvements and latest experimental verification, Review of Scientific Instruments 85 (2014) 065102.



Détection des radiations > Équipement de laboratoire

SATURN I, SATURN II

The SATURN ratemeter is a compact acquisition and control unit, designed for managing and processing signals from any ELSE NUCLEAR connected detector.

- SATURN I: standard wall-mounted version
- SATURN II: wall-mounting version compliant with “Good Manufacturing Practice” requirements (no external cable or connectors)



All the ratemeter versions feature local function buttons with status LEDs, internal acoustic buzzer and a relay connector, used to manage external alarm columns or interlocks.

The SATURN ratemeter continuously acquires and processes the data coming from the connected detector, and compares results with user-defined alarm thresholds.

Two user-selected measurements can be displayed at the same time on the display, such as instantaneous or average count rate, dose rate, activity concentration, counts, dose or activity integrated values.

The user interface is accessible through an external keyboard, which allows local interaction with the full range of parameters (advanced setting is password protected). Measurements, thresholds and operating parameters are stored into an internal, non-volatile memory.

The ratemeter can communicate to and be remotely managed by a host PC through an Ethernet or RS485 network.



SATURN 5702

SATURN 5702 is a mobile station equipped with two detectors for gamma and neutron dose rate monitoring. The station includes:

- Ion-chamber-based gamma radiation monitoring unit: ICP-T or ICP-T-PF
- Neutron rem counter for pulsed fields: LUPIN BF3



The detectors and the electronics are housed in a trolley-mounted mechanical structure. The height of the trolley can be customized according to the customer needs, for example to centre the detectors with the beam line height.

Each detector can be removed from the trolley to be employed remotely, up to 20 m. An ALU alarm column is mounted on the top, providing luminous and acoustic warning signals related to the status of the mobile station (good functioning, pre-alarm and alarm). SATURN 5702 stations can also manage external devices through 4 sets of relay contacts.

The detectors are connected via external cables to a standard 19" electronics rack equipped with two dedicated SATURN ratemeter units (rack version). Each ratemeter features a display, 3 function keys with status LEDs, and a connector for TOUCHKEY2 external keyboard.

SATURN 5702 can be connected to a remote host PC running a data management software (5700 sMON) through ETH or RS485/422 connection.



NAUSICAA IC-T, ICP-T

NAUSICAA is an ion-chamber-based gamma radiation monitoring unit, available in two versions:

- IC-T for environmental measurements (9 decades electrometer)
- IC-T-PF for pulsed field measurements (7 decades electrometer)

Both versions include an ion chamber detector, an electrometer and a CPU-based acquisition and control unit.

The display visualises the dose rate value and status messages, while a built-in buzzer and coloured LEDs provide additional status indications.

The alarm thresholds, the operational parameters and the measurement data are saved in the internal memory. The user can set the parameters through the external keyboard or 5700 sMON software (if provided).



The standard NAUSICAA configuration, suitable for indoor use, is composed by a 3U 63HP table box housing the electronics modules, and the ion chamber directly installed on top of it. Wall mounting accessory and trolley kit are also available, as well as an IP54 enclosure.

It is possible to connect one or more units to a host PC (running 5700 sMON software) through Ethernet or serial communication.

The ICP-T detector is identical to NAUSICAA, but it does not include the CPU, being connected to and managed by a SATURN ratemeter.

The DISCOVERY IC-T unit is a special version of NAUSICAA, assembled in a IP65 housing, designed to operate outdoor; data can be transmitted through a wireless connection or downloaded through a dedicated utility.



GM-1, MERCURY

According to the measurement requirements, different versions of Geiger-Müller detectors are available:

- GM-1: single-Geiger detector (up to 1 mSv/h)
- MERCURY: double-Geiger detector (up to 1 Sv/h)

All models employ energy-compensated tubes, lodged in high-protection aluminium cylinders, together with a built-in HV board.



MERCURY detectors are equipped with 2 Geiger-Müller tubes to reach a wider measurement range. An internal electronics automatically switches to the suitable GM tube according to the count rate level.

Both the GM-1 and the MERCURY detectors are connected to and managed by a SATURN ratemeter, which provides power supply, signal processing and data visualization. Each detector-ratemeter couple forms a monitoring unit, which can be connected in a network to a central host PC running 5700 sMON management software.

Among the special versions and accessories available, we mention in particular:

- Stand-alone version of GM detectors for direct connection to PC
- IP65 housing for MERCURY for outdoor installations
- PS-ZB accessory for MERCURY, providing battery-operated power supply and ZigBee Wireless communication, and ZB-TC receiver connected to the ratemeter to acquire the data
- GPS locator for PS-ZB



NAUSICAA 2IC

The NAUSICAA 2IC system is designed to quantify the beta activity in air or gas streams, due to the presence of tritium or other noble gases, while compensating for the environmental gamma background.

NAUSICAA 2IC can be used in activities involving air sampling from rooms, stacks, hoods, or other effluent passages, process piping, glove boxes, and similar.

NAUSICAA 2IC is composed of:

- two identical, cylindrical, 10 litres, stainless-steel ion chambers
- a pneumatic sampling system
- an electrometer to amplify and manage the (typically very weak) ionisation current
- a local control unit with display and software



Ambient air is sampled in the upper chamber, while the lower one is sealed and filled with clean reference air. Ionizations occurring in the upper chamber are due to both environmental gamma background and beta contamination, whereas inside the lower chambers only gamma background interactions occur. The two chambers are provided with an opposite-polarity HV: the resulting output current is thus the difference of the two single outputs, i.e. the net beta contamination of the sampled air, expressed in activity concentration. An accessory equipment for filtering and drying the sampled air helps limiting as much as possible any spurious signals.

The NAUSICAA 2IC control unit manages data acquisition, processing and visualization. A touch-screen display allows parameters' setting and data visualization. A built-in acoustic and luminous alarm column provides proper warnings in case of alarm or malfunctioning.

NAUSICAA 2IC can be connected to a host PC through RS485 or ETH connection for remote data visualization.

With a 600 V value each camera can generate currents up to 10^{-8} A, with a saturation error < 20%.



MISTRAL XM

MISTRAL XM is a system designed to sample and monitor the gamma activity concentration resulting from air activation, in Marinelli geometry.

In particular, MISTRAL XM Rooms is designed for free air monitoring, whereas MISTRAL XM Stack is used to monitor the air expelled from a chimney or a stack. In both cases, "X" indicates the number of sampling points: up to 5 (Rooms) or 1 (Stack).



The system is composed of:

- acquisition and processing unit: APU
- sampling and detection unit: SDU-XM

The APU is the main user interface with the system, and it consists in a command and control console including: a panel PC, the system electronics, a control flow meter for the pump, and an array of electrovalves (if needed). The SDU-XM includes the NaI(Tl) detector with MCA, a lead shielding well, and a pump for air sampling. The system also manages the expulsion of the monitored air.

The Stack version includes a flow rate meter (STACK-DFM), to calculate the specific activity of the expelled air volume.

The software installed on the PC displays in real time the measurement, controls the system status, and allows to set the operative parameters, such as the alarm thresholds. The user can define specific regions of interest (ROIs) and thus determine the specific activity (Bq/g) of the sampled air.



HERMES

HERMES systems are rugged, portable units for radiation detection, designed and tailored for a wide range of operational scenarios such as gamma and neutron detection, dose rate measurement, gamma spectroscopy and more. HERMES systems are suited for emergency response activities, as they are mounted inside robust and high-IP technical cases, which can be handheld or vehicle-mounted.



The HERMES product line includes customisable configurations, such as:

- HERMES NAI or CSI, with NaI(Tl) or CsI(Tl) detector and MCA to perform gamma spectrometry
- HERMES GMT or PLA, with Geiger-Muller or plastic detector for high-sensitivity gamma monitoring
- HERMES NEU, with $^{10}\text{BZnS}$ neutron detector and plastic moderator for artificial neutron source detection
- HERMES SENTINEL, combining NaI(Tl), GM tubes and neutron detector for comprehensive radiation surveillance

HERMES units support remote operation via LAN or Wi-Fi through a smartphone or a tablet. According to the configuration, the proprietary software provides real-time dose rate data, nuclide identification, alarms, and interactive heat mapping. Scan results, GPS coordinates and events are automatically logged into the local memory for off-line processing.

HERMES units incorporate advanced gain stabilization, dead time correction, and automatic energy calibration based exclusively on natural background radiation (no source needed to calibrate).



FOOMON

FOOMON is a portable fully-integrated instrument specifically conceived for screening of I-131, Cs-134 and Cs-137 accumulated in food samples. Its “on-the-field” design allows deploying the device in any kind of situation, such as routine campaigns or emergency procedures.



The whole device is self-contained in a portable high-IP-grade technical case, for an overall weight < 25 kg. The food samples are to be placed in 500 ml Marinelli beakers, which then are lodged inside a 1 cm thick lead shielding well upon the detector’s end cap. The complete setup and deployment of the system requires less than 5 minutes.

The User can manage FOOMON through the user-friendly control and analysis software installed on the embedded panel PC, automatically calculating the specific activity and the Minimum Detectable Concentration (MDC) of the sample (in Bq/kg). Data are stored locally and can be analysed and downloaded with dedicated software routines.

The measured activity concentration is compared with isotope-specific and food-group-specific alarms. In the case of an alarm, the measurement output is clearly labelled and the alarm status is clearly displayed on the software, which also activates the acoustic alarm.

The counts-to-activity-concentration conversion coefficients are calculated by means of dedicated Monte Carlo calculations.

The MDC achievable in 1 minute, with an average indoor background (150 nSv/h), is as low as about 150 Bq/kg for Cs-137 and Cs-134, and about 90 Bq/kg for I-131. Under the same conditions, MDC as low as about 30 Bq/kg for I-131, and about 40 Bq/kg for Cs-134 and Cs-137, can be achieved in about 10 minutes.

If enabled, the automatic background subtraction subroutine allows further lowering MDC and measurement uncertainty without increasing the counting time.



Détection des radiations > Identificateurs d'isotopes portables

THYMON

THYMON is a compact NaI(Tl)-based detector specifically conceived to fast, yet reliably, measure I-131 contamination in thyroid. Its compactness, ruggedness, light-weight, together with its simple and intuitive built-in software interface, make the device perfectly suited for emergency screening applications. The instrument can be used either hand-held or hands-free. The instrument is composed by three main subparts:



- Detector probe: a 1.5" x 1.5" collimated NaI(Tl) crystal coupled to a SiPM matrix and extremely compact readout electronics and MCA
- Extendable support: designed as both table-top and standalone, providing the possibility of hands-free operation
- Control tablet: IP65 water- and dust-proof 8" capacitive screen, wired-connected to the probe

The mechanics of the probe is specifically conceived to ensure the best alignment between the probe and the thyroid, guaranteeing excellent crystal-to-thyroid alignment, and reducing positioning uncertainties.

The control and analysis software installed on the control tablet is designed to be simple and intuitive, yet advanced and comprehensive. This is accomplished by combining a simple and intuitive interface with advanced calculation routines, which run automatically as the measurement start, without the need of operator intervention.

Data are stored locally on the tablet internal memory, and can be analysed and downloaded with dedicated software routines.

The automatic I-131 activity calculation is given for pre-defined age groups: 1 yo, 5 yo, 10 yo, 15 yo (Adult Female), Adult Male. Counts-to-activity conversion coefficients are calculated by dedicated Monte Carlo simulations based on detailed detector and thyroid numerical models. The simulations are always validated for the specific system through experimental tests performed with reference radioactive sources.

The activity is compared to 2 User-defined threshold levels, each defined per each age group, following the two Action Levels logic.

MDA as low as about 100 Bq can be achieved in 2 min screenings. The MDA can be further lowered by enabling the background subtraction option.



HERMES GSU

HERMES GSU is a portable gamma spectrometry system designed for rapid and precise in-field analysis of environmental samples. As part of the HERMES product line, it features a rugged, modular, and self-contained design housed in a high IP-rated technical case, ensuring durability and reliability in demanding conditions.



HERMES GSU quantifies isotope activity concentrations based on a rich built-in, yet fully-editable, isotope library. Its portability and autonomous operation make it ideal for both routine monitoring and emergency response scenarios.

Samples can be directly collected from the field, placed in 500 ml Marinelli beakers, and inserted into the built-in 1 cm lead-shielded well, minimizing background radiation for immediate, on-the-spot, low MDC analysis, and enhancing measurement accuracy and sensitivity. The system automatically calculates activity concentrations, making it a powerful tool for in-situ, laboratory-grade measurements.

HERMES GSU features advanced routines for gain stabilization, dead time correction, and automatic energy calibration (relying on natural background only, thus not requiring any radioactive reference source).

Efficiency calibration curves are generated using validated Monte Carlo simulations. Predefined efficiency curves are available for different sample matrices, including soil, water, and foodstuffs, across various densities. Custom calibration curves can be provided upon request.



Partner **BSI**




Baltic Scientific Instruments (BSI) is an OEM manufacturer based in Riga, Latvia, dedicated to the development and production of advanced spectrometric and detection equipment. With decades of experience and roots in the former Research Institute for Radioisotope Apparatus (RNIIRP), BSI provides cutting-edge technologies for nuclear power, environmental monitoring, security, medicine, and scientific research.

The company specializes in HPGe, Si, CdZnTe/CdTe, and scintillation detector systems, known for their accuracy, stability, and performance in demanding analytical environments.


Through continuous innovation, strict quality assurance (ISO 9001:2015), and strong international collaboration, BSI supports customers worldwide in achieving precise and reliable radiation measurement and analysis.

Product offering


Gamma analysis software SpectraLineGP




Calibration software EffMaker




Calibration software MCC-MT




Nuclide Master Plus



Quality Assurance package



Alpha analysis software SpectraLineADA



AirTrack Aerosol Monitoring Station



AirTrack-i Iodine Monitoring Station



**WaterTrack Online
Water Monitoring
Station**



**Spectrometer
WaterSPEC**



Spectrometer AirSPEC



**Mobile Radiation
Monitor GammaCART**



**Alpha analysis
software AlphaPRO**




**SpectraLineGIS
software package**



**Gamma analysis
software GammaPRO**



**Radiation Analysis
and Visualization
Environment Network
RAVEN software**




**Hybrid cooling for the
HPGe detector Nicole**





Gamma analysis software SpectraLineGP

SpectraLineGP has been developed for spectrometry measurements and precision processing of gamma spectra. Spectra processing includes calibration, peaks parameters determination, nuclides identification, activities calculation and using the true-coincident factors for the gamma emission intensity correction. External programs can be used in SpectraLineGP as an additional instrument for user methods realization for solving of the specific spectrometric tasks.



Features


- algorithms of peaks search and multiplets separation;
- calibrations by energy, FWHM, peak pattern, detection efficiency, secondary peaks with quantitative and visual control;
- calculation of the peak parameters (position, half-width, area), with storing the results in a text file;
- different methods of activity calculation;
- storing the measured spectra and results of processing in the database in order to repeated analyze for convergence in accordance with the given criteria (the quality estimation);
- connection of an arbitrary number of measuring channels;
- independent control, start, stop, spectra storage and visualization in all measuring channels;
- additional stop conditions: on activity uncertainty values, peak area, peak area uncertainty, peak MDA, ROI integral count;
- account for cascade summation effect, correction to high count rates and accidental summation.



Détection des radiations > Surveillance Environnementale

Calibration software EffMaker

EffMaker software package has been developed for calculation of detection efficiency and modeling of gamma-spectra in different measuring geometries using Monte-Carlo method. EffMaker can be used for measurements of objects activity by gamma-spectrometric methods when the spectrometer calibration can be hardly done by reference standards, e.g. for measurements of transport containers, packages with radioactive wastes, others wastes. Objects with arbitrary distribution of activity, which includes nonuniform distribution, can be modeled using this software package. So it can be used for analysis of how radionuclides distribution in the sample affects the activity measurements results. This function presents the promising way of EffMaker using for development and testing of software and methodological support.



Features

The response function is modeled for the detector to the increase of the calculations speed. This function is a set of spectra for monochromatic radiation in the prescribed range. The response function is transformed to the response matrix which takes into account number of channels of the spectrometer and its resolution. The gamma spectrum of the object (the physical spectrum of the source) in the point of the detector's location is modeled independently. The detector spectrum of the source is obtained as a convolution of the physical spectrum with the detector's response matrix.

A modeled object is a dissymmetric structure consisting of embedded cylinders, parallelepipeds, spheres. So objects with sophisticated parameters and arbitrary distribution of activity can be modeled: with surface (internal and external), volume distribution etc.

The built-in set of patterns in EffMaker simplifies the creation of complex geometrical objects with nonuniform activity distribution. The following patterns are included:

- a truncated cone, with one-layer or two-layer walls;
- an empty or filled tube, open sidelong test tube with internal or external surface contamination;
- cylinder, profile, top or bottom view, with one layer of the source;
- a box for the air tubes modeling with external contamination, activity can be distributed in internal or external layers;
- spherical objects with internal contamination like pipe closers
- angle bar and double tee with random orientation, with the contaminated surface;
- circular and rectangular plates.

The main functions:

- fine adjustment of relative position of the detector and the object, including the option of the detector placing inside the object;


- calculation of spectrum and detection efficiency for the selected geometry;
- batch calculation of detection efficiency for different detectors and objects;
- energy spectrum calculation using energy grid or by setting of activities of radionuclides taking into account the decay chain;
- radionuclides database on the basis of ENSDF compatible with Nuclide Master;
- the database of cross-sections of interaction of gamma rays with matter for setting of arbitrary material of the object;
- the database with models and calculation results;
- integration of calculation results with SpectraLine software package.



Calibration software MCC-MT

Application

- Monte Carlo simulation spectra of gamma, beta and radiation;
- Characterization detectors and detection systems;
- Calibration of instruments used for ionizing radiation detection and measurements without using the hazardous ionizing radiation for human health;
- Obtaining clear picture of the internal processes of radiation transfer in order to optimize the design of the measuring devices and their protection;
- Acceleration, simplification and reduction in the cost of design and optimization of ionizing radiation detection systems;



Features

- High accuracy of calculations
- Detailed 3D-scene based on Open GL graphics technology providing maximum representation and visibility of modeling
- Availability of replenished database of sources and materials
- Possibility of creating the maximally complex measuring systems
- Forming multidetector systems and schemes of coincidence
- Display of the results in the form of an ideal and real spectrum
- Tracing and drawing trajectories of particles during calculation process
- Availability of the ready and test projects in the distributive package (HPGe, scintillation detectors, protective lead shielding, volumetric sources and samples, etc.)
- Accounting cascade summation ('Full cascade' source type)

← Back to partner




Détection des radiations > Surveillance Environnementale Nuclide Master Plus

Application

Nuclide Master Plus is an extended version of Nuclide Master software. It is intended for calculation of detection efficiency, spectra and true coincidence factors.

Features

The calculation is based on Monte-Carlo method using parameters of the required nuclides from the library of evaluated nuclear structure data ENSDF (Evaluated Nuclear Structure Data File).



The calculations can be performed in point, cylindrical geometries and in Marinelly for different detectors types (semiconductor and scintillation) which are saved in database compatible with EffMaker software.

Functions:

- detectors and measurement geometries parameters setting and saving in database;
- lines and radionuclides lists creation;
- calculation of detection efficiency and correction factors for true coincidence using Monte-Carlo method;
- data filtering;
- creation and addition of correction factors for true coincidence library;
- data viewing and saving in detection efficiency library;
- batch processing possibility for several geometries and energy ranges.

If a file with correction factors is included into processing software SpectraLine, the true coincidence effect is corrected at the activity calculation.

← Back to partner



Détection des radiations > Équipement de laboratoire Quality Assurance package

Gamma or Alpha analysis software SpectraLine can be extended with Quality Assurance package in order to provide monitoring of the spectrometer channel for the parameters of the full energy peak (position, FWHM and detection efficiency) for the specified energy and the background count rate.




The reference sample and the background are measured in semi-automatic mode for quality control. As the scenarios are used the measurement parameters can be flexibly adjusted and the monitoring results can be displayed depending on the date and time of the measurement start.

The control limits determined by the alarm and warning levels are displayed on the graph, so the parameters deviation from the specified intervals can be easily found.



Alpha analysis software SpectraLineADA

The SpectraLineADA (Alpha Decay Analysis) software package has been developed for alpha-spectrometric analysis with spectrometers based on either semiconductor detectors or ionization chambers.



- processing of alpha-spectra of both «thin» and «thick» sources
- consideration of thin structure of alpha-spectra, parametrical description of the line shape
- consideration of the contribution of conversion electrons, which is required if the ratio of detectors parameters to the distance between source and detector is small
- registration efficiency calculation
- activity calculation by the inserted label. It allows to take into account the a priori information for results specification
- calculation of the radiochemical yield (radiochemical yield is calculated as the ratio between the amount of the nuclide material in the measured sample and the amount of this nuclide material, added to the probe)

The demonstration configuration and calibration scenario are included in SpectraLineADA installation package.



Détection des radiations > Surveillance Environnementale

AirTrack Aerosol Monitoring Station

The Aerosol Monitoring Station is a breakthrough in autonomous radiation surveillance, utilizing silicone, high purity germanium or scintillation detectors for alpha, beta, and gamma monitoring in the air. With unparalleled precision, this cutting-edge system ensures swift and accurate detection of radioactive aerosols. Operating autonomously, it offers real-time data, making it ideal for industrial, research, or emergency scenarios. The advantages of high purity germanium and scintillation detectors make this station a reliable guardian, providing continuous and precise radiation monitoring to safeguard diverse environments.



MAIN OPERATING FUNCTIONS

- acquiring alpha-beta and gamma spectra in real-time;
- calculating activity of radionuclides on the filter [Bq] and concentration of radionuclides in the air [Bq/m³];
- indication of the concentration of Radon in the ambient air and automatic compensation its progenies;
- two programmable thresholds (notification and alarm) for radiological events in each measurement chain (alpha, beta and gamma emitters);
- automatic filter replacement depending on its contamination degree, integrity damage, or after measurement time;
- automatic control of filter condition, including measurement of differences in the air pressure Δp at the inlet and outlet of the filter;
- measurement of the flow rate of the incoming air;
- data transfer via LAN, USB and 4G interfaces in the ANSI 42.42/EURDEP format to the end-user;
- control of all AirTrack operations from a remote computer.



Détection des radiations > Surveillance Environnementale

AirTrack-i Iodine Monitoring Station

The Aerosol Monitoring Station, tailored for gamma radiation monitoring in the air, is a specialized tool designed for in-depth analysis of airborne iodine. Utilizing the advantages of a scintillation detector, specifically Srl, and employing unique filters crafted for iodine analysis, this autonomous system ensures unparalleled accuracy. Ideal for situations requiring precise detection, such as nuclear incidents, the station stands as a reliable guardian, providing real-time data for swift response and safeguarding against potential threats associated with airborne iodine.



Features

MAIN OPERATING FUNCTIONS

- acquiring gamma spectra in real-time;
- measuring the activity of I-131 on the filter [Bq] and calculating the concentration of I-131 in the air [Bq/m³];
- automatic filter replacement depending on its contamination degree, integrity damage, or after the expiration of the specified measurement time;
- automatic control of filter condition, including measurement of differences in the air pressure Δp at the inlet and outlet of the filter;
- measurement of the flow rate of the incoming air;
- ambient air temperature measurement;
- two programmable thresholds (notification and alarm) for radiological events;
- audio and color alarm signals about operation modes and exceeding threshold values;
- data transfer via LAN, USB and 4G interfaces in the ANSI 42.42/EURDEP format to the end-user;
- control of all AirTrack operations from a remote computer.



WaterTrack Online Water Monitoring Station

WaterTrack Online Water Monitoring Station is designed for continuous monitoring of the specific activity content of Cs-137 and/or other radioactive elements in Bq/l in running water. Utilizing a high-sensitivity scintillator, it enables real-time detection and quantification of radioactive elements in liquids. The system is ideal for environmental surveillance, industrial discharge monitoring, and water treatment facilities, offering low detection limits and precise measurements. Its robust design ensures consistent performance in diverse conditions, while user-friendly interfaces simplify operation and data analysis.



Features

- Sealed metal cabinet with pipes for connecting to the water supply system, including a stainless steel tank with a capacity >15 liters;
- 5 cm lead shield installed around the tank;
- Ø2×2" scintillation detector Srl2(Eu) with <3.5% energy resolution installed inside the tank with (NaI(Tl), CeBr3 - optionally);
- 4096 channels MCA for gamma spectrometry;
- Evaluation of measurement results according to ISO 11929;
- Automatic stabilization of gamma spectrometric channel by K-40 peak;
- Continuous self-testing procedures with an alarm signal and messages.



Spectrometer WaterSPEC

Application

WaterSPEC is designed for indoor or outdoor use in aquatic environments. The waterproof housing has IP68 degree of protection: dust-tight (full protection against dust and other particulates) and protected against extended immersion in water to a maximum depth of 2 meters.

Features

- online gamma spectrum acquisition and readout;
- ambient equivalent dose rate $H^*(10)$ calculation [mkSv/h];
- automatic radionuclide identification;
- radionuclide concentration indication [Bq/m³];
- operation and settings control via GammaSPEC software;
- data transfer via RS-485 interface;



WaterSpec is a monoblock unit, comprising scintillation crystal, photoelectronic multiplier, HV converter, amplifier, multichannel pulses analyzer and processor unit.

WaterSpec measurement system is autonomous, automated and provides calculation of the ambient equivalent dose rate $H^*(10)$ in real time, as well as identification of the most common natural and artificial gamma radionuclides. The results of the identification and dose rate are then transmitted to the upper-level computer via exchange protocol.

WaterSpec has automatic stabilization of the spectrometry channels by means of tracking the position of the K-40 1460.8 keV full energy peak provided by the potassium salt located in the cartridge near scintillation crystal.

WaterSpec is designed for indoor or outdoor use in aquatic environments. The waterproof housing has IP68 degree of protection: dust-tight (full protection against dust and other particulates) and protected against extended immersion in water to a maximum depth of 2 meters.



Spectrometer AirSPEC

Application

Scintillation gamma-ray spectrometer AirSPEC is intended for measuring scintillation spectra and also for determination of activities and specific activities of radionuclides in prepared and natural samples in 2π and 4π geometries. Spectrometer can be used for radiation monitoring and various tasks like definition of specific effective activity of naturally occurring radionuclides (NORM) in building materials (granite, crushed stone, gravel, etc.), raw materials, products, waste industrial production and rocks without sampling. In addition, AirSPEC is applicable for measurement of surface activity of the radionuclide ^{137}Cs (and other), mass fraction of NORM in rocks and resins the conditions of their natural occurrence on a surface, in boreholes and in warehouses and transport containers. Moreover, AirSPEC can analyze surface contamination of soil, as well as prospecting and exploration of mineral deposits. The spectrometer can be used for operating in laboratory and in the field conditions.



Features

- online gamma spectrum acquisition and readout;
- ambient equivalent dose rate $H^*(10)$ calculation [mkSv/h];
- automatic radionuclide identification;
- radionuclide concentration indication [Bq/m³];
- operation and settings control via GammaSPEC software;
- data transfer via RS-485 interface.

AirSPEC is a monoblock unit, comprising scintillation crystal, photoelectronic multiplier, HV converter, amplifier, multichannel pulses analyzer and processor unit.

AirSPEC measurement system is autonomous, automated and provides calculation of the ambient equivalent dose rate $H^*(10)$ in real time, as well as identification of the most common natural and artificial gamma radionuclides. The results of the identification and dose rate are then transmitted to the upper-level computer via exchange protocol.

AirSPEC has automatic stabilization of the spectrometry channels by means of tracking the position of the K-40 1460.8 keV full energy peak provided by the potassium salt located in the cartridge near scintillation crystal.

AirSPEC provides an additional feature of thermostabilizing housing to provide a wider range of operating temperatures. The housing provides both high degree of thermal insulation and automatic control and active adjustment of the temperature inside the device. The IP67 degree of protection allows to use AirSpec in severe weather conditions.



Mobile Radiation Monitor GammaCART

Application

Mobile spectrometric system Mobile Radiation Monitor is designed to measure gamma radiation energy distribution, identify gamma emitting radionuclides, as well as calculate specific and surface activity of gamma emitting radionuclides under conditions of their natural occurrence and at nuclear industry premises. In addition, the system can be used for radiation monitoring, e.g., for examination of large areas, searching lost or stolen gamma radiation sources, study of radionuclide precipitation near radiation hazardous sites without preliminary sampling.



COMPLETE SET

- Electric vehicle as a mobile platform
- Gamma radiation spectrometer containing:
 - Gamma radiation detector(s);
 - Multichannel channel analyzer Polynom;
- Thermostabilization system (for NaI(Tl) or LaBr₃(Ce) detectors) containing:
 - Thermostabilizing housing with a built-in heat exchanger
 - Cooling and heating system box;
 - Hoses for circulation of the cooling liquid;
- Navigation system including a external antenna;
- Shockproof toughbook operable in harsh conditions;
- Router with antenna which provides connection between the analyzer, navigation system and toughbook;
- Fixation and positioning system for the detection units;
- Charger for the electric vehicle.



Alpha analysis software AlphaPRO

The program AlphaPRO is the continuation of the program GammaPRO with some limitations, but focuses on the tasks of alpha spectrometry. AlphaPRO employs different algorithms for determining activity in samples (ROI-method with overdetermined matrix, individual peaks analysis method, superposition method). For the analysis of high resolution spectra (spectra received on semiconductor spectrometers) there separate tools (search peaks, Gaussian approximation, identification, plotting efficiency curves, etc.).



Application

The software is intended to control the alpha spectrometer Amber and analyze the alpha spectra acquired using SIID alpha detectors.

Features

- supported Amber models: Amber-2, 4, 8, 12.
- visualization of spectra and spectrum acquisition progress;
- peak search and fit by Gaussian;
- identification of radionuclides;
- Energy, FWHM and peak shape calibration;
- calculation of efficiency curves and sensitivities;
- calculation of activity by peak method;
- calculation of activity by matrix (ROI) method;
- calculation of MDA according ISO 11929;
- simple and easy to use report editor;
- library of radionuclides and library editor;
- mathematical operations (sum, subtraction, normalization etc);
- batch spectra processing;
- simple and easy to use report editor;
- library of radionuclides and library editor;
- quality assurance control;
- database MS Access which provides transfer and storage of measurement results in a database;
- log which provides automatic registration and storage of measurement and quality assurance results;
- support for the main spectrum formats: SPE, N42, CNF, CHN, SPC, ASW, TXT etc.


← [Back to partner](#)



Détection des radiations > Surveillance Environnementale **SpectraLineGIS software package**

Application

SpectraLineGIS software package is intended for radiation monitoring of territories with gamma-spectrometers and dosimetry sensors, for determination of the radionuclides present, and for mapping results to contamination maps of the territories. The contamination maps can be created using the software: the functions of collecting, analyzing and storing of the gridded pollution information are supported. The user can emulate the pollution from certain activities using the spectra database and identify the source location on the basis of the spectrum supported by SpectraLine.



Features

The Integrated Geographic Information System (GIS) is developed on the basis of DataGIS components and provides the following functionality:

- Creation of maps by importing from MIF and MP formats using a specific application
- Displaying and visualization of the selected thematic map layers
- Varying the map scaling
- Searching for objects on the map
- Display of contamination data according to the color settings and thresholds

← [Back to partner](#)



Détection des radiations > Équipement de laboratoire

Gamma analysis software GammaPRO

The software is intended to

- Control the spectrometric multichannel analyzer;
- Analyze the spectra acquired using scintillation and semiconductor gamma and beta detectors;
- Work with spectra modeled by the Monte Carlo simulation.



The matrix method enables automatic calculation of activity of a sample provided its radionuclide composition is known. The method is used for routine measurements of food, building materials, water and other substances subject for permanent radiological control.

The superposition method is mainly used for control of correctness of activity calculations in case of hard-to-analyse (multiple peak) low-resolution spectra (acquired by scintillation detectors). Such a tool enables visual estimate of the degree of similarity between an acquired and calculated spectrum. Additionally, calculation data can be adjusted until the spectra completely coincide.

The Software features an integrated system for report generation which provides automatic creation of measurement results. The settings for report generation can be adjusted by user.



Détection des radiations > Surveillance Environnementale

Radiation Analysis and Visualization Environment Network RAVEN software


Application

The Radiation Analysis and Visualization Environment Network RAVEN software package was developed for the following purposes:

- Comprehensive environmental radiation surveillance at multiple monitoring points
- Visual tools for data analysis and rapid operator response
- Centralized storage of measurements and technical data for quality assurance

Features

- Multi-layered network: stationary, mobile, and laboratory stations;
- Real-time monitoring with intervals based on air and water radiation levels;
- Using a map of any area: site, city, region, country;



The software package is built on several blocks, like:

- Main dashboard with general information,
- A map with location of all Stations and key current values,
- Measurement results is a block with displays detailed flow of data from each Station,
- Summary report.

The current status of each monitor at every measurement station can be tracked in the Dashboard. The Dashboard does not display measurement results; only technical data related to each Monitor. This allows the operator to maintain a comprehensive overview and respond promptly if any monitor requires attention (filters are running low or a measurement has stopped due to a malfunction).

Measurement results for each monitor are available in a dedicated window, presented in tabular format in compliance with ISO 11929. The measurement result window also provides access to monitor technical parameters and the alpha/beta or gamma radiation spectra. The radiation spectrum registered by each monitor can be accessed at any time. This option helps assess detector's performance and, together with valid technical parameters, supports quality assurance of the measurement results.

The software generates a summary report for a chosen alpha/beta/gamma radionuclide concentration in one table, presenting all monitors measuring this radionuclide. Ambient dose equivalent rate values are also shown in a table format: both from GDRM and (if presented) AirSpec/WaterSpec/WaterTrack multifunctional spectrometers.

All measurement results are stored in a database and can be displayed for any selected time period. Data can be averaged over 1, 3, 6, 12, or 24 hours, or by month. The operator can add multiple blocks for display as time series charts or tables. The resulting report can be downloaded as a DOC or PDF files.

The Software has two access levels: operator and administrator. The administrator mode provides full access to all functions, while the operator mode is limited to monitoring only.

The Software provides a station maintenance history, automatically logs all changes made by the administrator to the station configuration, and records all messages from the monitors.

← [Back to partner](#)



Détection des radiations > Équipement de laboratoire

Hybrid cooling for the HPGe detector Nicole

The NICOLE hybrid cooling system combines liquid nitrogen and electro-mechanical cooling. The merge of this two cooling systems provide detection unit non-stop operation for months without having liquid nitrogen to refill.

The NICOLE hybrid cooling system comprises Stirling-cycle cryocooler, cryocooler controller, Dewar vessel, pressure sensor and indicator, liquid nitrogen sensor and level monitor.



Application

Nicole hybrid cooling system for the HPGe detector allows you to keep your detector cold without filling with Liquid Nitrogen for months and years.

Features

One of the biggest advantages of Nicole hybrid cooling system is that it is extremely easy to perform maintenance and service. The user is given USB interface to get access to all parameters of the system. Majority of main parameters are displayed of the LCD display. And I case of maintenance, repair or replacement of the cooler is needed, it takes only 15 minutes to dismantle the cooling unit. It means the user can continue measurements by only using liquid nitrogen. It can be extremely important when routine measurements can't be terminated.



Partner Bertin Instruments



Bertin Instruments est un fournisseur mondial de solutions avancées de détection des radiations et de surveillance environnementale, spécialisé dans les détecteurs portables, les dosimètres électroniques personnels, les systèmes de surveillance environnementale et les technologies de gestion des déchets et du recyclage. Ses instruments sont conçus pour répondre aux exigences rigoureuses des installations nucléaires, des équipes d'intervention d'urgence et des agences environnementales.

Product offering

GammaTRACER Spider Autonomous Gamma Monitor for Emergencies - Saphymo



AlphaGUARD-Radon Monitor - Bertin Instruments



ShortLINK Short-Range Environmental Radiation Monitoring Network - Bertin/Saphymo



GammaTRACER Autonomous Radiation Monitoring Probe - Saphymo



BAB E Air Monitoring Beacon



SkyLINK Wide-Range Environmental Radiation Monitoring Network - Bertin/Saphymo



AlphaE - Bertin Instruments



SpectroTRACER Environmental Radiation Monitor - Saphymo



**Skydose Dosimetry
System - Bertin
Instruments**



**Coriolis RECON -
Bertin Instruments**



**Coriolis Micro - Bertin
Instruments**



← Back to partner



Détection des radiations > Surveillance Environnementale

GammaTRACER Spider Autonomous Gamma Monitor for Emergencies - Saphymo

The GammaTRACER Spider Autonomous Gamma Monitor (Saphymo) has been designed to cover the needs of first responders in an emergency scenario. Based on the proven GammaTRACER design, the probe provides reliably the measurement of the gamma dose rate and wireless data transmission to the crisis center by means of [SkyLINK](#) radio or Iridium satellite modem.



GammaTRACER Spider Autonomous Gamma Monitor for Emergencies features:

- built-in battery for up to 5 years operation
- innovative self-erecting design, very fast deployment
- ultra compact design
- emergency proof communication options
- SkyLINK radio modem (up to 100 km/60 mi)
- satellite modem (Iridium)
- hermetically sealed weatherproof housing
- wide measurement range: 20 nSv/h up to 10 Sv/h
- can be used to quickly enhance density of existing monitoring networks

GammaTRACER Spider demo

← Back to partner



Détection des radiations > Surveillance Environnementale

AlphaGUARD-Radon Monitor - Bertin Instruments


Overview:

The complete product line provides all accessories for radon in air, water, soil, building materials, progeny, thoron and calibration equipment to perform air, water, soil, exhalation measurements. The collected data can be linked to the DataVIEW software, allowing data download and storage as well as professional data analysis and reporting. With AlphaGUARD, bring your Radon Lab everywhere.

AlphaGUARD incorporates a pulse-counting ionization chamber (alpha spectroscopy).

Based on optimal chamber geometry and intelligent signal evaluation, this radon monitor is suitable for continuous monitoring of radon concentrations between 2 – 2 000 000 Bq/m³.

The DSP (Digital Signal Processing) technology provides highly effective differentiation ability between “real” radon data and all kinds of artefacts.



Features:

- 0.62 L pulsed ionization chamber
- Measuring range of 2 to 2,000,000 Bq/m³,
- Instrument calibrator error of 3%
- Storage capacity of up to 60,000 measurement points
- Storage of:
 - 400 days at 10 min measuring cycle
 - 2,500 days at 60 min measuring cycle
- Battery life of 10 days (40 days with external battery)
- 329 mm x 355 mm x 123 mm and weighs 6,2 kg (13,7 lbs)

Your Radon Lab - Everywhere:

- AquaKIT
- Soil gas Probe
- AlphaPM
- AlphaPUMP / LabPUMP
- Emanation / Calibration Container
- Exhalation Box
- On line Radon in water monitoring
- Valve Selector

Benefits:

- Quality at the highest level
- Long-term stable calibration factor (guaranteed 5 years)
- Calibration traceable to different national standards (PTB, NIST, NPL)
- Inbuilt quality assurance system for permanent validation of system operation and data
- Fast transient response

- DataVIEW PRO software

- Automatic background correction
- No sensitivity to high air humidity

Reasons to choose ALPHAGUARD - RADON MONITOR:

✓ Reference instrument with high sensitivity

✓ Calibration stability guaranteed for 5 years

✓ High performance for versatile applications

✓ Maintenance-free operation

Gallery:



AlphaGUARD - Your Radon lab everywhere

<https://youtu.be/oJaaYf9-Pbl>



SCAN TO VIEW VIDEO

← [Back to partner](#)



Détection des radiations > Surveillance Environnementale

ShortLINK Short-Range Environmental Radiation Monitoring Network - Bertin/Saphymo

The ShortLINK Wireless Communication System is a short-range, fully autonomous and private wireless network. You can use this system to transmit online data from connected low-power sensors or instruments to a central station. Unlike public cellular communication system standards (like GSM), this system is not dependant on the existence of an area covering cellular infrastructure. ShortLINK is generally installed in combination with a radiological network, like [GammaTRACER](#) and [DataExpert supervision software](#).



If you want to know more about Bertin data transmission systems, take a look at [our partner's website](#)!

SHORTLINK WIRELESS COMMUNICATION SYSTEM FEATURES AND BENEFITS

- Very low power consumption
- Operating distance up to 5 km (3 mi)
- Turnkey installation
- Long-term maintenance-free operation
- Can withstand temperatures from -40°C to 60°C (-40°F to 140°F)



Détection des radiations > Surveillance Environnementale

GammaTRACER Autonomous Radiation Monitoring Probe - Saphymo

The GammaTracer Autonomous Radiation Monitoring Probe from Bertin is designed to continuously measure, record, and transmit the environmental gamma dose rate. The probes continuously measure the gamma radiation dose.

Worldwide, there are more than 4.000 GammaTRACERs in operation.

The probes also offer a new dimension in wireless data collection. This is possible because the probes are equipped with a radio module, so you can use them with [SkyLINK](#) and [ShortLINK](#) for wireless data collection. GammaTRACER can store up to 12.800 data sets, depending on the probe type and measurement cycle.

The probe is available in four types: Basic, Wide, High and XL2.




UNLIMITED AUTONOMY

The GammaTRACER is an autonomous radiation monitoring probe. The monitor's batteries allow maintenance-free, non-stop operation for up to five years, and with an extended battery pack, it will even last up to ten years! This is possible because of the energy-saving chip technology.

But, if you choose the internal solar panel, the autonomy can be unlimited!

They can also resist extreme climatic and environmental conditions because the probes are independent of any physical connections.



GAMMATRACER TYPES

GammaTRACER covers a broad range of radiation monitoring applications because there are multiple types available. The probes are deployable for multiple applications, for example nationwide monitoring, perimeter monitoring, and monitoring for nuclear facilities. The probes are not only suitable for routine, but also for emergency applications.

BASIC

The GammaTRACER Basic has a dose rate measurement range of 20 nSv/h to 10 mSv/h and an energy range of 45keV to 3MeV.

WIDE

The GammaTRACER Wide has a dose rate measurement range of 20 nSv/h to 10 Sv/h and just like the BASIC, also an energy range of 45 keV to 3 MeV.

HIGH

The GammaTRACER High has a dose rate measurement range of 1 mSv/h to 10 Sv/h and an energy range of 80 keV to 4,4 MeV.

XL2

The GammaTRACER XL2 has a dose rate measurement range of 10 nSv/h to 10 Sv/h and an energy range of 45 keV to 2 MeV. The XL2 type also has fast a response mode of 1 second.

ADDITIONAL OPTIONS

Even though the four GammaTRACE options already have a lot of features, there are also options you can choose from. All types can operate in temperatures ranging from -20°C (-4°F) to 50°C (122°F), but you can also choose for the option of -40°C (-40°F) to 60°C (140°F). Furthermore, you can choose additional sensors (rain, wind and weather), power supply by solar panels or a seismic qualified version.



BENEFITS & FEATURES

- Measures x-radiation and gamma radiation
- Measurement cycle, adjustable from 1 second to 120 minutes
- Battery lifetime up to ten years or even unlimited with solar panels
- Can store up to 12.800 data sets
- Type approval in several countries
- Maintenance-free
- Non-stop operation
- Easy to install

If you want to read more about GammaTRACER, take a look at [our partner's website!](#)

<https://youtu.be/59D0HZs64zw>



SCAN TO VIEW
VIDEO

If you have any questions...

Contact PEO!



BAB E Air Monitoring Beacon

The BAB-E fixed beacon is used for continuous monitoring of artificial Alpha and Beta aerosols, in Gamma environments as well as in the presence of natural Radon descendants. It has a double cover that allows it to withstand the most extreme climatic conditions for uninterrupted use outdoors (territorial surveillance, nuclear infrastructures, etc.). The data collected by the BAB-E can be accessed remotely and in real time on the DataEXPERT supervision software.

Features

- Can be used in controlled areas with high gamma background
- Compensation of radon progenies
- Use of standard sources for efficiency controls
- Ruggedized, can be used on dismantling and purification sites
- Available as stationary or mobile version
- Can be connected to a central monitoring network and trigger a general alarm

Technology

- The radioactive dust is deposited by air suction on a filter paper placed in the BAB beacons.
- The suction flow rate is about 5 m³/h (it depends on dustiness and type of filter paper).
- The flow rate is calculated from the depression measured between the filter and the pump. This allows to detect any tear or dust clogging.
- Placed one centimeter above the sample, the detection system is based on two 300 µm thick silicon diodes with a surface of 360 mm².
- The analog signal from the two diodes is amplified by a preamplifier with an output range of about 30mV/MeV.
- An amplifier increases the signal amplitude to 0.7V/MeV, and the signal is then used to produce the energy spectrum via an amplitude analyzer that encodes information to 512 channels.



← Back to partner



Détection des radiations > Surveillance Environnementale

SkyLINK Wide-Range Environmental Radiation Monitoring Network - Bertin/ Saphymo

The SkyLINK Wireless Communication System is a wide-range, fully autonomous and private wireless network. You can use this system to transmit online data from connected low-power sensors or instruments to a central station. Unlike public cellular communication system standards (like GSM), this system is not dependant on the existence of an area covering cellular infrastructure. The system generally includes a radiological network like GammaTRACER probes and the DataExpert supervision software.



For more information about Bertin Data Transmission systems, take a look at [our partner's website!](#)

The system structure allows its use in every situations, even in the most accidental ones (private wireless communication network and easy-to-install autonomous probes).

SKYLINK WIRELESS COMMUNICATION SYSTEM FEATURES

- Very low power consumption
- Operating distance up to 100 km (60 mi)
- Private network, so no regular transmission fees
- Easy interface to external instruments or host processors
- Turnkey system installation
- Long-term maintenance-free operation

<https://youtu.be/59D0HZs64zw>



SCAN TO VIEW
VIDEO

← **Back to partner**



Détection des radiations > Moniteurs portables

AlphaE - Bertin Instruments

AlphaE is an electronic handheld device for fast and time-resolved radon monitoring in buildings, outdoors and mines. Typically, 80 % of the final result is achieved after 2 hours (faster response for higher values). Due to its ultra-lightweight design and sophisticated features, AlphaE is highly suitable also for surveying the personal radon exposure and dose at workplaces.



The AlphaE's favourable price-performance ratio makes it also interesting for service companies engaged in radon assessment and mitigation as well as for users in private homes. Up to 6 months battery life allows long-term measurement without mains power. Permanent operations via mains supply are possible via USB port.

Advantages AlphaE

- ultra-lightweight design
- sophisticated features
- wide measuring range for professional use
- up to 6 months autonomy
- suitable software included

Download the datasheet or contact our product specialist.



SpectroTRACER Environmental Radiation Monitor - Saphymo

SpectroTRACER is a continuous environmental radiation monitor for spectroscopy to measure very low gamma contamination (water: SpectroTRACER AQUA).



The SpectroTRACER produces a spectroscopic analysis of the detected nuclides identification. The SpectroTRACER is used for the measurement of radioactivity when a standard gamma dose rate monitor is not efficient enough and when it is necessary to discover the nature of the gamma radiation.

SpectroTRACER Environmental Monitor features:

- working temperature: -20 ° C to + 50 ° C. / option: -30 ° C to + 60 ° C
- max. 100 meters under water (SpectroTRACER -AQUA)
- IP68 certified
- relative humidity: 100%
- integrated sensors for temperature and humidity



Détection des radiations > Surveillance Environnementale

Skydose Dosimetry System - Bertin Instruments

Skydose is an operational dosimetry system, designed to measure & monitor, in real time, the ambient dose level received by response teams in high exposure areas.



The operational dosimetry system Skydose consists in eight Saphydose γ RT teledosimeters, one Personal Digital Assistant (PDA), one Easydose configuration software, one Saphyr portable reader, as well as one to three RT-ZB05 routers.

The Skydose system is part of an ongoing approach based on the reduction of both collective and individual doses, in compliance with the ALARA principle (As Low As Reasonably Achievable). By optimizing the exposition to ionizing radiation, it aims at improving the operators' conditions of intervention, who will thus be able to focus safely on the objectives of their mission. The Skydose system only takes a **few minutes to install**. Thanks to the PDA, it ensures the in-field monitoring of an eight-person team equipped with Saphydose γ RT teledosimeters using mesh networking.

Flexible & robust, the Skydose system can reliably cover an entire infrastructure (a nuclear power plant, for example), thanks to one or more RT-ZB05 dedicated routers.

Fast & easy to deploy, the Skydose system can be used by operators, first-responders & non-specialists, inside & outside the risk areas.

Features

- easy and quick setting even by non-specialized staff
- automatic network synchronization
- suitable for indoor and outdoor use including reactor buildings
- suitable for emergency situations (sturdy - high dose and dose rate range)
- real-time hotspots detection to reduce the mission dose received by workers
- compliant with use in nuclear facilities (CEI 61526)
- low maintenance costs
- real-time, remote & simultaneous monitoring of the Saphydose γ RT dosimeters, for the team to react immediately in case of emergency
- the Skydose system can be installed and configured in a few minutes, and be safely stored in a ruggedized pelicase - several systems can operate simultaneously, without interference

Specifications

- detector: 2 energy-compensated silicon diodes
- energy range: **from 50 keV. to 7 MeV!**
- dose rate measurement range: 0.5 μ Sv. to 9,999.99 mSv
- dose measurement range: 1 μ Sv. to 9,999.99 mSv
- alarms: sound & visual
- battery lifetime in operation: 4,000 hours
- radio range: 300 m



Détection des radiations > Surveillance Environnementale

Coriolis RECON - Bertin Instruments

Le Coriolis RECON est un échantillonneur bio-air portable, léger et robuste pour la détection d'agents de guerre biologique, dédié aux équipes CBRN ou aux premiers intervenants, avec un déploiement rapide en cas de suspicion d'attaque biologique. Les Coriolis RECON ont été conçus pour collecter de grandes concentrations d'aérosols dans la plage respirable de 0,5 à 10 µm avec un débit d'air de 600 L/min, étant ainsi plus représentatifs de l'environnement que les échantillonneurs de bio-aérosols traditionnels. Grâce à sa capacité à collecter des particules de bioaérosols sous forme liquide, ce système peut être utilisé avec des techniques d'identification rapide d'agents biologiques (immunodosage, PCR, etc.) pour fournir une alerte précoce sur les agents de guerre biologique aérosolisés.



Vidéo de présentation

Avantages Coriolis RECON

- la concentration la plus efficace d'agent de guerre biologique
- débit d'air élevé
- compatible avec toutes les expériences en aval pour une identification rapide
- biosurveillance avec surveillance de longue durée – jusqu'à 6 heures
- déploiement rapide dans un contexte militaire/premier intervenant

Téléchargez la fiche technique ou contactez notre spécialiste produit.



Détection des radiations > Surveillance Environnementale

Coriolis Micro - Bertin Instruments

Coriolis μ est un échantillonneur d'air biologique innovant pour l'évaluation de la biocontamination, principalement dédié au contrôle et à la surveillance de la qualité de l'air dans la recherche sur l'environnement et la pollution, les industries pharmaceutique, alimentaire et vétérinaire, l'environnement biomédical et sanitaire...

Basé sur une technologie cyclonique, combinée à un débit d'air élevé, Coriolis μ offre la collecte de particules la plus efficace en 10 minutes. Les particules biologiques telles que toxines, virus, bactéries, moisissures, pollens, spores sont collectées et concentrées dans un liquide prêt à être analysé avec des méthodes microbiologiques et de biologie cellulaire et moléculaire.



Vidéo de présentation

Avantages Coriolis Micro

- la concentration la plus efficace de particules biologiques
- Débit d'air élevé et option de surveillance longue durée - jusqu'à 6 heures
- compatible avec toutes les expériences en aval - échantillons divisibles pour plusieurs analyses en parallèle
- sortie d'échantillon liquide flexible
- pas de saturation des supports de collecte pour environnement chargé

Téléchargez la fiche technique ou contactez notre spécialiste produit.



Partner **Ludlum Measurements**



Ludlum Measurements, Inc. conçoit et fabrique des instruments et des technologies de détection des rayonnements. Fondée en 1962, elle propose une large gamme d'instruments de détection de rayonnements, développés pour aider à surveiller la sécurité du personnel et de l'environnement. Les instruments sont utilisés dans des applications telles que la surveillance de routine du personnel et du matériel, la sécurité des frontières et les situations d'intervention d'urgence.

Product offering

**Model 3101 Portable
Tritium in Air Monitor**



**Model 334AB-G
Alpha-Beta
Particulate Monitor**



**Model 334A Alpha Air
Monitor**



**Model 3100 Portable
Tritium in Air Monitor**





Détection des radiations > Surveillance Environnementale

Model 3101 Portable Tritium in Air Monitor

The Model 3101 Tritium in Air Monitor features ruggedized and flexible operation. It is powered by rechargeable internal NiMH batteries and/or an external +12 Vdc power supply. It features a maintenance-free diaphragm air pump to pull air through the 250 cc tritium chamber, and the air flow is measured internally with a mass-air flow sensor. A second 250 cc chamber is used to provide gamma compensation, allowing operation in higher gamma fields. Other internal sensors measure temperature and ambient pressure and provide compensation for these effects.



The heart of the tritium detection is the sealed electrometer chamber, using the latest low-noise electrometer chip. This electrometer can reliably measure the femtoamperes of current resulting from tritium within the chamber and does not require the user to adjust an offset or zero knob. The pixelated digital display provides feedback on the tritium concentration, as well as showing status on several important conditions: temperature, pressure, power, airflow, chamber bias, and alarm or failure status.

The Model 3101 is easy to use, having only a few simple controls, and can be used while wearing gloves. It has a large easy-to-read display with a backlight control for increasing contrast in low-light conditions. In addition to the tritium level, the display simultaneously shows the user the battery/power condition, the temperature, the pressure, the status condition, and the airflow through the chamber.

The Model 3101 is built for ruggedness and reliability. Two airflow pumps were tested and shown to last over 10,000 hours of continuous use. The Model 3101 shares many of the characteristics and design of the Model 3100, which was built and tested for the U.S. military. Testing was done in accordance with ANSI N42.30, MIL-STD-810G, MIL-STD-461G, MIL-STD-901D, and MIL-STD-1399-300B standards which test instrument operation under various conditions including temperature, blowing rain, salt fog, vibration, mechanical shock, RF susceptibility, and RF emissions. The commercial user of the Model 3101 benefits from this design and testing history.

Features

- No Zero Adjust Control Needed
- Easily Calibrated with ^{137}Cs Gamma Range

- Temperature and Altitude Compensation
- “Check Mode” Self-Test Feature Determines Instrument State of Health
- Digital Backlit Display with Status, Airflow Readout, and Diagnostic Information
- Internal Heater Element Purge Mode to Dry Ion Chamber
- Readout in $\mu\text{Ci}/\text{m}^3$ or MBq/m^3



Model 334AB-G Alpha-Beta Particulate Monitor

The Model 334AB-G (a replacement for the Model 334AB) is a lightweight, battery-powered, alpha-beta air monitor that can be used as a portable workplace monitor or a portable CAM (continuous air monitor) for emergency-response assessments. Its design provides workers with an early warning of an airborne release of alpha- or beta-emitting particulates. The instrument can monitor up to two alpha isotopes of interest simultaneously with beta monitoring.

The Model 334AB-G has an internal 7-LPM pump. (An external pump with a higher flow rate is available as an option.) The integrated LCD and touchscreen displays information on instrument status and readings during operation. The estimated dose of the isotope(s) of interest and the instrument status are displayed at all times. A visual/audio alarm stack also indicates instrument status. An ion-implanted silicon detector and 1024-channel multi-channel analyzer feed data to the embedded processor board to perform beta detection and alpha spectral analysis for radon background compensation.



Background Subtraction Using Peak Shape Fitting

State-of-the-art alpha peak fitting quantifies the alpha and beta counts from radon and thoron progeny. This technique uses the profiles of multiple alpha isotope peaks to create a composite curve which best fits the actual alpha spectrum. Because the individual radon peaks are independently determined, the beta background compensation is impervious to radon equilibrium changes and contributes to low probability of false alarms.

Guard Detector

An internal guard detector provides real-time beta compensation for changing gamma background levels. An adjustable gamma subtraction factor allows for correction of slight differences in beta and guard count rate in a fixed gamma field to produce proper energy response.

Sensitivity and Response Time

The Model 334AB-G's sensitivity varies primarily as a function of the window time. The longer Chronic Window has improved sensitivities over the shorter Acute Window time. Sensitivity is reported in Minimum Detectable Concentration (MDC) in Bq/m³ (DAC) and Minimum Detectable Dose (MDD) in Bq-

h/m^3 (DAC-h).

Features

- Integrated LCD and Touch Screen Display
- Acute and Chronic Dose, Concentration, and Flow Logging Measurements
- Radon Compensation
- Built-In Gamma Guard Detector
- American or SI Units of Measurement
- 8-Hour Battery Life



Model 334A Alpha Air Monitor

The Model 334A is a compact, lightweight, and portable alpha air monitor designed to function both as a workplace monitor and a Continuous Air Monitor (CAM) for measurements in emergency response situations. Its functionality is enhanced by its splash- and dust-proof enclosure with splash-proof electronics.

Spectral analysis is conducted via a 1024-channel analyzer that feeds data to the embedded processor. Factory configuration provides either special nuclear materials (SNM) or radon progeny measurements of potential alpha energy concentration (PAEC).

Measurements may be taken in both fast-responding (Acute) or high-sensitivity (Chronic) assessments, and report in English or SI units. The Model 334A stores acquired data in comma-separated-variable (.csv) format that is recognized by most spreadsheet and database software. Data may be saved in the instrument's internal memory, or alternately may be written to an SD card for later retrieval and review.

Independent determination of nuclide peaks means they are impervious to radon equilibrium changes, thereby contributing to low probabilities of error and false alarms. Precise fitting of the ^{218}Po tail results in excellent sensitivity.

This Model 334A features an integrated LCD and touch screen that displays information on instrument status and readings during operation. The estimated dose of the isotope(s) of interest and instrument status is displayed at all times. A window below may be switched from showing historical readings and battery status, or displaying the current spectrum.

Factory-configurable Radon Mode allows the instrument to monitor potential-alpha-energy-concentration (PAEC) of radon progeny.

Features

- Easy Setup and Use
- Integrated LCD and Touch Screen Display
- English or SI Units of Measurement
- Acute and Chronic Dose Modes
- Significantly Reduced False Alarms Using Peak Shape Fitting Capability
- 8-Hour Battery Life



- Radon Mode Option



Détection des radiations > Surveillance Environnementale

Model 3100 Portable Tritium in Air Monitor

Le modèle 3100 Tritium in Air Monitor offre un fonctionnement robuste et flexible. Il peut être alimenté soit par 115 Vca, 50/60 Hz, soit par des batteries NiMH internes rechargeables. Il dispose d'une pompe à air à membrane sans entretien pour aspirer l'air à travers la chambre au tritium de 250 cc, et le débit d'air est mesuré en interne avec un capteur de débit massique d'air. Une deuxième chambre de 250 cc est utilisée pour fournir une compensation gamma, permettant un fonctionnement dans des champs gamma plus élevés. D'autres capteurs internes mesurent la température et la pression ambiante et compensent ces effets.



Caractéristiques

- Aucun contrôle de réglage du zéro n'est nécessaire
- Facilement calibré avec la plage gamma 137Cs
- Compensation de température et d'altitude
- La fonction d'auto-test « Mode vérification » détermine l'état de santé de l'instrument
- Écran numérique rétroéclairé avec état, lecture du débit d'air et informations de diagnostic
- Mode Purge pour sécher la chambre à ions
- Chambre interne avec déshydratant remplaçable
- Tests militaires américains réussis, notamment : MIL-STD-810G, MIL-STD-461G, MIL-STD-901D, MIL-STD-1399-300B
- Lecture en $\mu\text{Ci}/\text{m}^3$ ou MBq/m^3

Le cœur de la détection du tritium est la chambre électrométrique scellée, utilisant la dernière puce électrométrique à faible bruit. Cet électromètre peut mesurer de manière fiable les femtoampères de courant résultant du tritium dans la chambre et ne nécessite pas que l'utilisateur ajuste un bouton de décalage ou de zéro. L'affichage numérique pixelisé fournit des informations sur la concentration de tritium, ainsi que l'état de plusieurs conditions importantes : température, pression, puissance, débit d'air, polarisation de la chambre et état d'alarme ou de panne.

Le modèle 3100 est facile à utiliser, ne disposant que de quelques commandes simples et peut être utilisé avec des gants. Une fenêtre transparente permet à l'utilisateur de voir l'état du déshydratant dans la chambre déshydratante intégrée. Un interrupteur à bascule permet à l'utilisateur de mettre la chambre de dessiccation en ligne avec l'air entrant. L'instrument est livré dans un étui commercial robuste à coque rigide avec des supports de montage mural. Le modèle 3100 a passé avec succès les tests militaires américains concernant la sensibilité et les émissions RF, les chocs et vibrations, la température et la pluie battante, ainsi que d'autres tests.



Partner **SDEC France**



SDEC France est un fabricant spécialisé d'équipements de surveillance environnementale et de laboratoire. Il propose des solutions complètes pour la gestion des déchets et du recyclage, la surveillance environnementale et les applications de laboratoire. Forte de plus de 30 ans d'expérience, l'entreprise conçoit et fabrique des instruments de haute qualité pour les professionnels des sciences de l'environnement, de l'agronomie et de la radioprotection.

Product offering

AM 3000 N - Air Sampler for Asbestos Diagnosis in Nuclear Environments - NF43-050 version 2021 , NF X43-269, NF EN ISO 13137



AM 3000 - Air Sampler for Asbestos Diagnosis - NF43-050 version 2021, NF X43-269, NF EN ISO 13137



Battery Operated Field Electric Vacuum Pump PAV 2000 : For soil sampling



AS 5000 Aerosol & Iodine Sampler - SDEC



AS 3000 AEROSOL & IODINE SAMPLER - SDEC





Détection des radiations > Surveillance Environnementale

AM 3000 N - Air Sampler for Asbestos Diagnosis in Nuclear Environments - NF43-050 version 2021 , NF X43-269, NF EN ISO 13137

- **AUTONOMOUS SAMPLING:** The AM 3000N ensures consistent and reliable air sampling without manual intervention.
- **HIGH PRECISION:** Equipped with a pump automatically regulated by a microcontroller and a mass flow meter for increased accuracy.
- **REMOTE CONTROL:** Controllable remotely via an infrared remote control for user convenience.
- **ROBUST & WATERPROOF:** Stackable device with an IP65 protection rating, resistant to harsh environments.
- **PROTECTION AGAINST NUCLEAR CONTAMINATION:** H13 white glass fiber THE filters at intake and exhaust to prevent contamination.
- **CERTIFIED COMPLIANCE:** Complies with NF43-050 version 2021, NF X43-269, NF EN ISO 13137 standards, ensuring reliability and adherence to standards.





AM 3000 - Air Sampler for Asbestos Diagnosis - NF43-050 version 2021, NF X43-269, NF EN ISO 13137

- **AUTONOMOUS SAMPLING:** The AM 3000 is an autonomous air sampler, ensuring consistent and reliable sampling without manual intervention.
- **HIGH PRECISION:** Equipped with a pump whose flow rate is automatically regulated by a microcontroller and a mass flow meter.
- **REMOTE CONTROL:** Can be remotely operated using an infrared remote control, enhancing user convenience.
- **ROBUST & WATERPROOF:** The device is robust, stackable, and has an IP65 protection rating, ensuring its durability and resistance to environmental factors.
- **CERTIFIED COMPLIANCE:** Meets the strict requirements of NF43-050, NF X43-269, and NF EN ISO 13137 standards, ensuring its reliability and adherence to industrial norms.





Battery Operated Field Electric Vacuum Pump PAV 2000 : For soil sampling

- **RAPID VACUUM CREATION:** Achieves a vacuum of -750 mbar in less than 15 seconds, significantly speeding up soil sampling.
- **HIGH AUTONOMY & PORTABILITY:** Offers 5 hours of continuous operation with a lightweight and durable aluminum design for convenience in the field.
- **INTEGRATED SMART CHARGING SYSTEM:** Includes a maintenance-free 12V, 5A/hour battery with a smart charger for easy recharging.
- **PRECISION & PROTECTION:** Equipped with an accurate Bourdon-type manometer and a Gore-Tex filter to guard against water ingress.
- **COMPACT & EASY TO USE:** Compact dimensions (200mm x 130mm x 240mm) with a simple three-position operational switch.





AS 5000 Aerosol & Iodine Sampler - SDEC

L'AS 5000 Aerosol & Iodine Sampler (SDEC) est un équipement stationnaire conçu pour l'échantillonnage d'aérosols et d'iode en suspension dans l'air à haut débit sur filtres en papier et cartouches. Il est particulièrement adapté au prélèvement en continu en cheminées selon la norme ISO 2889.



Caractéristiques de l'échantillonneur d'aérosols et d'iode AS 5000 :

- régulation automatique du débit d'air jusqu'à 100 litres par minute (6 Nm³/h)
- débitmètre massique avec compensation de pression et de température : affichage du débit d'air en Nm³
- compartiment d'échantillonnage et séparation électrique
- détection de colmatage de filtre ou de fuites accidentelles
- sécurité : porte d'accès à la tête de prélèvement avec serrure à clé, disjoncteur différentiel
- rapport d'alarme via sortie relais, (sortie Ethernet en option)
- réglage des paramètres d'échantillonnage et seuil de niveau de colmatage protégé par code d'accès
- installation fixe (support mural) ou installation mobile sur chariot

En savoir plus sur l'échantillonneur d'aérosols et d'iode AS 5000 sur le site Web du SDEC



Détection des radiations > Surveillance Environnementale

AS 3000 AEROSOL & IODINE SAMPLER - SDEC

L'AS 3000 Aerosol & Iodine Sampler (SDEC) a été conçu pour réaliser des prélèvements d'aérosols et d'iode sur papiers filtres et/ou cartouches de charbon. Il dispose de nombreuses innovations technologiques comme la régulation automatique du débit d'air et le rapport des données sur clé USB.



Caractéristiques de l'échantillonneur d'aérosols et d'iode AS 3000 :

- régulation automatique du débit d'air de 10 à 50 LPM
- pompe à membrane (sans entretien)
- compatible avec tous les filtres en papier et cartouches
- reconnaissance automatique du papier filtre ou de la cartouche par option de scanner de lecteur
- pompe indépendante (démontage facile en cas de contamination)
- installation du porte filtre par système rapide sur axe horizontal ou vertical
- fonctionnant sur secteur ou sur batterie
- clavier étanche

En savoir plus sur l'échantillonneur d'aérosols et d'iode AS 3000 sur le site Web du SDEC



Partner **GEORADIS s.r.o.**



Georadis s.r.o. est un fabricant spécialisé d'instruments avancés de détection et de surveillance des radiations, proposant une gamme complète de solutions pour les applications de terrain et de laboratoire. Sa gamme de produits comprend des moniteurs portables, des identificateurs d'isotopes portables, des appareils de surveillance environnementale et des équipements de laboratoire, tous conçus pour répondre aux exigences rigoureuses des professionnels des secteurs de la surveillance environnementale, de la sécurité industrielle et de la sécurité publique.

Product offering

GT-40 Gamma Ray Spectrometer





Détection des radiations > Surveillance Environnementale

GT-40 Gamma Ray Spectrometer

A multifunctional gamma ray spectrometer for rapid determination of activities of gamma emitters in field surveys or samplings. A wide range of applications in the field of monitoring heterogeneous substances, contamination of sites, buildings, objects, water and food. Application in geology in field surveys for raw material sources. Proven performance in harsh environment applications. Survey data is stored in the memory, including the GPS coordinates. Up to 6 different calibrations.

Properties

Portable digital gamma ray spectrometer with a built-in computer for complex analysis of the measured data. Bluetooth, Wi-Fi and GPS are an added advantage. Transreflective colour display.

Use

Applicable wherever it is necessary to quickly and accurately determine the activities/content of gamma emitters. Suitable for field survey measurements, but also to be incorporated into shielding.

Modification

The GT-40 series is provided with a NaI/Tl scintillator with a 3" base diameter and 3" height. A GT-40S model is also manufactured, which is fitted with either a NaI/Tl or BGO detector with a 2" base diameter and 2" height at the customer's request. The GT-40S model has a built-in 1 cm thick Pb collimator. The collimator is easily removable.

Specification

Two basic working modes: Survey, for terrain scanning, and Assay, for determining concentrations of precalibrated radionuclides, i.e. components. Energy calibration of the analyzer is carried out continuously throughout the operating time, and only natural background sources are used for the set-up. Monitoring and analysis results are displayed on a color graphic display in a well-arranged manner. All acquired data is stored in the unit's memory and can be exported to other devices via USB, Wi-Fi or Bluetooth. Field observations can be recorded and stored along with each measurement using a built-in voice recorder.



Alternatives - Options - Special applications

Alternative models for special applications have been designed. GT-40-B profits of BGO detector 3" base diameter and 3" height. GT-40 - L is a model with extended length of body for scanning of small spots on earth surface. Support for high precision external GPS, build in calibration and protocol for fast core logging.



Partner **Centronic Nuclear**



Centronic, leader britannique des technologies de détection des radiations, propose une gamme de détecteurs adaptés à la surveillance environnementale en milieu nucléaire et industriel. Fort de plus de 70 ans d'expertise, Centronic propose des solutions fiables pour la surveillance des niveaux de radiation dans divers environnements.

Product offering



[← Back to partner](#)



Détection des radiations > Surveillance Environnementale

Alpha, Beta & Gamma Detectors - Centronic

The Alpha, Beta & Gamma Detectors (Centronic) are used for the detection of radiation at low dose rates. This range of mica-window tubes is used for monitoring all types of radiation in a wide variety of environments.



Alpha, Beta & Gamma Detectors features:

- circuitry simple
- robust build
- available with compensating filter

Contact our product specialist or download the datasheet below.

← [Back to partner](#)



Détection des radiations > Surveillance Environnementale

Beta & Gamma Detectors - Centronic

The Beta & Gamma Detectors (Centronic) are used for the detection of radiation at low, intermediate and high dose rates. These types have a wide range of applications e.g. personal dosimetry, military and defence equipments.



Beta & Gamma Detectors features:

- robust construction
- simple circuitry

Contact our product specialist or download the datasheet below.



Partner **Ultra Electronics**



Ultra Electronics acquired Lab Impex Systems on July 17th, 2014. This is a known specialized manufacturer in radiation detection solutions and services for use in the global nuclear industry. Founded in 1976, Laboratory Impex Systems Ltd (LIS) is a leader in designing, developing and manufacturing health physics and radiation protection measurement instrumentation focusing on stack monitoring.

Product offering





CMS Gamma - Lab Impex

The CMS Gamma (Lab Impex) is an advanced continuous monitoring station for the measurement of gamma radiation (dose-rate of activity) in the environment or workplace. The system provides essential, reliable information to personnel when radiation levels are above normal. The versatile unit can provide interlock control in hot areas such as fuel stores, caves, glove boxes and hot cells as required.



CMS Gamma features:

- installed, transportable or trolley mounted
- internal back up battery which enables full operation for up to 1 hour in the event of mains failure
- the detector arrangement can be installed at distances of up to 1000m (3,280ft) from the CMS station
- wide range of detectors available

Read more about the CMS Gamma on the [Lab Impex website](#)

HPGE PORTABLE





Partner **BSI**



Baltic Scientific Instruments (BSI) is an OEM manufacturer based in Riga, Latvia, dedicated to the development and production of advanced spectrometric and detection equipment. With decades of experience and roots in the former Research Institute for Radioisotope Apparatus (RNIIRP), BSI provides cutting-edge technologies for nuclear power, environmental monitoring, security, medicine, and scientific research.

The company specializes in HPGe, Si, CdZnTe/CdTe, and scintillation detector systems, known for their accuracy, stability, and performance in demanding analytical environments.

Through continuous innovation, strict quality assurance (ISO 9001:2015), and strong international collaboration, BSI supports customers worldwide in achieving precise and reliable radiation measurement and analysis.

Product offering


MONOLITH Gamma & X-ray HPGe Spectrometer



HPGe Spectrometer with Lead Shield



Portable HPGe Gamma- & X-ray Spectrometer



Robotic Gamma Spectrometer



Ultra Low-background HPGe Detectors





MONOLITH Gamma & X-ray HPGe Spectrometer

Detection unit Monolith consist from the following integrated components:

- HPGe detector
- Preamplifier
- Autonomous cooling system for the detector based on electrical machinery cooler EMC
- Controller for controlling the operation of EMC
- Fans (2-4) for EMC cooling



Features

- 10% - 160% efficiency HPGe p-type coaxial detectors are available;
- Energy range from 40 keV to 10 MeV for GCD model;
- Energy range from 3 keV to 10 MeV for GCDX/GCDX-OS models;
- High efficiency of radiation detection;
- High energy rate up to 200000 MeV/sec;
- Excellent peak symmetry;
- Detection of radiation in any spatial orientation depending on cryostat modification;
- Manufacture in a portable cryostat is possible;
- Low background and Ultra - low background materials are available;
- Doesn't require a full thermal cycle after an unexpected shutdown.



HPGe Spectrometer with Lead Shield

Application

Coaxial HPGe Detector with Lead Shield is used to measure the specific gamma radiation of radionuclides from various types of environmental objects such as rocks, minerals, sludge, slag, soil, plant, sediment and particulate matter in air and water.

Features

- Adopting precision gamma-spectrometry methods
- Radionuclide identification and determination of their specific activity
- Low level of instrumental background
- Low threshold for radionuclide detection
- Separate and simultaneous measurement of activity of 100 radionuclides



DESCRIPTION

Coaxial HPGe Detector with Lead Shield is used to measure the specific gamma radiation of radionuclides from various types of environmental objects such as rocks, minerals, sludge, slag, soil, plant, sediment and particulate matter in air and water.

Ordering information

For LN2 cooled dipstick HPGe detection units:

- N100 - 100mm thick lead.
- N150 - 150mm thick lead.

For electrically cooled HPGe detection units (Monolith):

- M100 - 100mm thick lead.
- M150 - 150mm thick lead.

For hybrid cooled dipstick HPGe detection units (Nicole):

- H100 - 100mm thick lead.
- H150 - 150mm thick lead.

← [Back to partner](#)




Détection des radiations > HPGE portable

Portable HPGe Gamma- & X-ray Spectrometer

Application

Detection, accumulation, processing and analysis of gamma spectra in field and industry conditions where small dimension and weight of spectrometer are important.



Features

- Ultra-light cryostat fabrication for minimum gamma absorption;
- Light weight aluminum construction;
- Detection of radiation in any spatial orientation;
- Compact low consuming electronics;
- Available with HPGe coaxial or planar detector;
- Transportation and storage without cooling.

Detection, accumulation, processing and analysis of gamma spectra in field and industry conditions where small dimension and weight of spectrometer are important.




Détection des radiations > Équipement de laboratoire

Robotic Gamma Spectrometer

Application

The Automated Spectrometer is intended for the detection and analysis of radio nuclides from various types of environmental objects such as rocks, minerals, sludge, slag, soil, plant, sediment and particulate matter in air and water. The spectrometric system is able to determine the composition of a sample based on the photon energy and the activity based on the photon flux. The low-background lead shielding together with the highly pure germanium (HPGe) p-type detector gives precise results even for low activity materials. The fully automated sample changer enables the user to measure more than 40 samples, without having to interact with the Robotic Gamma Spectrometer. This reliable robotic sample changer increases the productivity and reduces the possibility of health risks for the operator.



The Automated Spectrometer is intended for the detection and analysis of radio nuclides from various types of environmental objects such as rocks, minerals, sludge, slag, soil, plant, sediment and particulate matter in air and water. The spectrometric system is able to determine the composition of a sample based on the photon energy and the activity based on the photon flux. The low-background lead shielding together with the highly pure germanium (HPGe) p-type detector gives precise results even for low activity materials.

The fully automated sample changer enables the user to measure more than 40 samples, without having to interact with the Robotic Gamma Spectrometer. This reliable robotic sample changer increases the productivity and reduces the possibility of health risks for the operator.

Automatic Sample Changer

The seven-axis robot handles a payload of up to 3kg and with, practically, unlimited reach, the robot is able to carry out a series of operations using flexible rather than hard automated solutions. In addition to a horizontal reach, the robot has the ability to reach below its base. Furthermore, the robot has a very compact turning radius, which is enabled by the robots symmetric architecture, without offset on axis 2. This ensures the robot can be mounted close to other equipment.

Basic characteristics of Robot arm:

- Seven-axis manipulator
- Machine vision
- Payload: 3 kg
- Reach: per request
- Fastest 7-axis robot
- Accuracy: ± 0.01 mm
- Weight: 25 kg
- IP30 protected

- All motors and cablings enclosed
- Compact controller
- Sample holder tool for vessels with diameter in range 40 - 110 mm.
- Barcode Reader and Writer

To assure the correct processing of all data during the measurement and analysis process, the samples are marked by using a barcode printer that is connected to the workstation. Here all necessary information about the sample is stored in a database. Using the bar code reader, the information stored in the database is retrieved for each sample before the measurement process is started. This fully automated process delivers all necessary information for the measurement and analysis process.



Ultra Low-background HPGe Detectors

Application

Ultra low-background HPGe detectors are widely used in underground laboratories for determination of radionuclides activities in environmental or industrial samples at $\mu\text{Bq/kg}$ levels and in scientific experiments such as investigation of magnetic moment of neutrino, dark matter search, etc.



Design

- Task related design (U-type, vertical, down-looking or portable cryostat)
- Remote not cooled part of preamplifier
- Zeolite is placed near not cooled part of preamplifier in order to be outside measuring chamber

Cryostat materials

- Certified materials with low radiation impurities
- Ultrapure aluminium-silicon alloy with U + Th content $< 1, 0.5$ or 0.2 ppb for detector holder and endcap
- Freshly produced electrolytic copper for coldfinger and pedestal
- Tested on radiopurity selected stainless steel screws and sapphire insulators

Technology

- Transportation of HPGe crystal and cryostat materials by surface freight
- Minimization of fabrication time (location of materials above ground)
- Assembly in a cleanroom
- Cleaning and passivation of copper surfaces
- Storage of crystal and cryostat materials in a container made from materials effectively slowing down and absorbing neutrons (water and Cd)

Design features

- Fabrication of large volume HPGe detectors without bulletization
- Front end electronics made on low-background Teflon substrate
- Passive screen between front end electronics and HPGe crystal made from Pb with Bi-210 radioactivity < 0.1 Bq/kg
- Double-crystal HPGe detector design
- Multi-crystal HPGe detector design



Partner **PHDS**



PHDS Co. est spécialisée dans le développement de détecteurs de rayons gamma portables au germanium haute pureté (HPGe), offrant des capacités de spectroscopie et d'imagerie haute résolution pour des applications en sécurité nucléaire, en intervention d'urgence et en recherche scientifique. Ses instruments sont conçus pour une identification et une quantification précises des isotopes dans des formats déployables sur le terrain.

Product offering

GeGI: Imaging HPGe Detector



NP Radiochemistry Imager



Fulcrum: HPGe Detector



Fulcrum-40h: 40% HPGe Detector



LoPro HPGe Detector



← Back to partner



Détection des radiations > HPGE portable

GeGI: Imaging HPGe Detector

- HPGe gamma-ray spectroscopy and isotope identification
- Real-time exposure rate calculation
- Fully capable of imaging Special Nuclear Materials (^{235}U and ^{239}Pu)
- Fast cool-down to operating temperature
- Long-life mechanical cooler
- Compact and hand-portable
- Hot-swappable batteries for continuous field operation
- User-friendly tablet operation
- Reachback File: ANSI N42.42 format





NP Radiochemistry Imager

The NP Imager is specifically designed to measure the dynamics of radiochemical separation processes in real time. Developed under a Small Business Innovation Research (SBIR) grant from the Department of Energy Office of Nuclear Physics (NP), the NP Imager focuses on the unique needs of radiochemists and technicians separating radioisotopes for radio-pharmaceuticals and other applications.



The NP Imager monitors the locations and distributions of multiple isotopes over time, allowing the radiochemist and technician to monitor separation processes in real time. In the process shown here, NP Imager measured Lu-177 and Yb-175 separation on a column over the course of 3 ½ hours using 10-minute exposures. Note that it's clear when the Yb-175 has been removed from the column, allowing the radiochemist to know when to collect the desired Lu-177.

Applications

- Radiopharmaceutical Process Monitoring
- Radiochemical Separation Research and Development
- Nuclear Physics Isotope Production
- Nuclear Materials Management
- Waste Management
- Decontamination and Decommissioning



Fulcrum: HPGe Detector



Overview:

The Fulcrum is a next-generation HPGe gamma ray detector engineered for rapid, accurate isotope identification in a compact, field-ready design. Weighing just 8 lbs, it is the lightest and most portable detector of its kind, making it ideal for mobile and emergency response scenarios. Equipped with the user-friendly PHDS OMNI software, the Fulcrum offers real-time exposure rate calculation and intuitive, color-coded isotope identification—all accessible through a simple touchscreen interface. With fast cool-down, wireless capability, and extended field operation features, the Fulcrum sets a new standard for high-performance gamma spectroscopy in any environment.

Features:

- HPGe gamma-ray spectroscopy and isotope identification
- Ultra-fast cool-down to operating temperature (2 hours)
- Most compact and lightweight HPGe detector (8 lbs)
- Relative efficiency: 12% at 1333 keV
- Real-time exposure rate calculation
- Compact, hand-portable design
- User-friendly Android app interface
- Wireless capability for remote operation
- Long-life mechanical cooler
- Bridge battery option for uninterrupted field use
- User-defined timed data acquisition with auto file save
- Reachback file output in ANSI N42.42 format



← **Back to partner**



Détection des radiations > HPGE portable

Fulcrum-40h: 40% HPGe Detector

- HPGe gamma-ray spectroscopy and isotope identification
- Relative efficiency of 40% (at 1332 keV)
- Fast cool-down to operating temperature (5 hours)
- Long-life mechanical cooler
- ISOTAC activity calculator
- Configurable with 1 or 2 onboard batteries and optional neutron detector
- Real-time exposure rate calculation
- User-specified timed data acquisition and auto file save
- Reachback File: ANSI N42.42 format





Détection des radiations > HPGE portable

LoPro HPGe Detector

The LoPro is a lightweight, low-profile HPGe gamma ray detector used by U.S. military operators around the world. The LoPro provides unmatched field reliability and gamma-ray spectroscopy for mission-critical applications. The unique form factor allows inconspicuous measurements for missions in which discretion is a must, while not sacrificing the spectroscopic performance expected from an HPGe detector.

Features

HPGe gamma-ray spectroscopy and isotope identification	Fast cool-down to operating temperature (3 hours)	Compact and hand-portable (8 lbs)
Integrated GADRAS isotope identification	Relative efficiency: 12% (at 1333 keV)	Real-time exposure rate calculation
User-friendly Android app, including TAK compatibility	Reachback File: ANSI N42.42 format	Long-life mechanical cooler
Long battery life (up to 15 hours per battery)	Wireless capable for remote operation	User-specified timed data acquisition and auto file save





Partner **Autre**

Product offering

**Spectromètre
d'analyse rapide par
activation
neutronique gamma
(PGNAA)**





Spectromètre d'analyse rapide par activation neutronique gamma (PGNAA)

Application

Le spectromètre PGNAA est destiné à :

- L'analyse de la composition radionucléidique d'échantillons contenant des traces de radionucléides ;
- La recherche de produits de désintégration de radionucléides d'origine anthropique ou naturelle ;
- Il permet d'obtenir des rendements d'enregistrement élevés et des limites de détection faibles grâce à :
- La réduction des niveaux de fond naturels grâce à l'utilisation de matériaux purifiés des radionucléides ;
- Augmentation du contraste des pics grâce à la suppression active des quanta de diffusion Compton.

Le spectromètre PGNAA est applicable dans les domaines suivants :

- Exploitation minière et exploration minérale : pour une analyse élémentaire précise et rapide des minerais et des minéraux.
- Surveillance environnementale : détection et quantification des polluants dans le sol et l'eau.
- Agriculture : analyse de la composition du sol afin d'optimiser l'utilisation des engrais et le rendement des cultures.
- Industrie pétrochimique : surveillance de la composition élémentaire du pétrole brut et de ses dérivés.
- Recherche géologique : étude d'échantillons de roches et de sédiments à des fins de recherche scientifique.
- Industrie pharmaceutique : garantie de la pureté et de la composition des matières premières et des produits finis.
- Institutions universitaires et de recherche : recherche avancée dans divers domaines scientifiques.



ÉQUIPEMENT DE LABORATOIRE





Partner **BSI**



Baltic Scientific Instruments (BSI) is an OEM manufacturer based in Riga, Latvia, dedicated to the development and production of advanced spectrometric and detection equipment. With decades of experience and roots in the former Research Institute for Radioisotope Apparatus (RNIIRP), BSI provides cutting-edge technologies for nuclear power, environmental monitoring, security, medicine, and scientific research.

The company specializes in HPG_e, Si, CdZnTe/CdTe, and scintillation detector systems, known for their accuracy, stability, and performance in demanding analytical environments.

Through continuous innovation, strict quality assurance (ISO 9001:2015), and strong international collaboration, BSI supports customers worldwide in achieving precise and reliable radiation measurement and analysis.

Product offering

<p>Gamma analysis software GammaPRO</p> 	<p>MONOLITH Gamma & X-ray HPG_e Spectrometer</p> 	<p>HPGe Spectrometer with Lead Shield</p> 	<p>Hybrid cooling for the HPG_e detector Nicole</p> 
<p>Robotic Gamma Spectrometer</p> 	<p>HPGe Spectrometer with Shield</p> 	<p>Flowing HPG_e Spectrometer</p> 	<p>HPGe Infrared Detectors</p> 

**Ultra Low-background
HPGe Detectors**



**LN2 storage and
transfer system**




**Multi Channel
Analyzer BOSON**



**Digital Miniature
Multi Channel
Analyzer MCA 527**



**Quality Assurance
package**



**Free Release Monitor
HERCULES-FRM**



**Gamma-, beta- and
alpha-
spectrometer-radiometer TRIO**



← [Back to partner](#)



Détection des radiations > Équipement de laboratoire

Gamma analysis software GammaPRO

The software is intended to

- Control the spectrometric multichannel analyzer;
- Analyze the spectra acquired using scintillation and semiconductor gamma and beta detectors;
- Work with spectra modeled by the Monte Carlo simulation.



The matrix method enables automatic calculation of activity of a sample provided its radionuclide composition is known. The method is used for routine measurements of food, building materials, water and other substances subject for permanent radiological control.

The superposition method is mainly used for control of correctness of activity calculations in case of hard-to-analyse (multiple peak) low-resolution spectra (acquired by scintillation detectors). Such a tool enables visual estimate of the degree of similarity between an acquired and calculated spectrum. Additionally, calculation data can be adjusted until the spectra completely coincide.

The Software features an integrated system for report generation which provides automatic creation of measurement results. The settings for report generation can be adjusted by user.



MONOLITH Gamma & X-ray HPGe Spectrometer

Detection unit Monolith consist from the following integrated components:

- HPGe detector
- Preamplifier
- Autonomous cooling system for the detector based on electrical machinery cooler EMC
- Controller for controlling the operation of EMC
- Fans (2-4) for EMC cooling



Features

- 10% - 160% efficiency HPGe p-type coaxial detectors are available;
- Energy range from 40 keV to 10 MeV for GCD model;
- Energy range from 3 keV to 10 MeV for GCDX/GCDX-OS models;
- High efficiency of radiation detection;
- High energy rate up to 200000 MeV/sec;
- Excellent peak symmetry;
- Detection of radiation in any spatial orientation depending on cryostat modification;
- Manufacture in a portable cryostat is possible;
- Low background and Ultra - low background materials are available;
- Doesn't require a full thermal cycle after an unexpected shutdown.



HPGe Spectrometer with Lead Shield

Application

Coaxial HPGe Detector with Lead Shield is used to measure the specific gamma radiation of radionuclides from various types of environmental objects such as rocks, minerals, sludge, slag, soil, plant, sediment and particulate matter in air and water.

Features

- Adopting precision gamma-spectrometry methods
- Radionuclide identification and determination of their specific activity
- Low level of instrumental background
- Low threshold for radionuclide detection
- Separate and simultaneous measurement of activity of 100 radionuclides



DESCRIPTION

Coaxial HPGe Detector with Lead Shield is used to measure the specific gamma radiation of radionuclides from various types of environmental objects such as rocks, minerals, sludge, slag, soil, plant, sediment and particulate matter in air and water.

Ordering information

For LN2 cooled dipstick HPGe detection units:

- N100 - 100mm thick lead.
- N150 - 150mm thick lead.

For electrically cooled HPGe detection units (Monolith):

- M100 - 100mm thick lead.
- M150 - 150mm thick lead.

For hybrid cooled dipstick HPGe detection units (Nicole):

- H100 - 100mm thick lead.
- H150 - 150mm thick lead.

← [Back to partner](#)



Détection des radiations > Équipement de laboratoire

Hybrid cooling for the HPGe detector Nicole

The NICOLE hybrid cooling system combines liquid nitrogen and electro-mechanical cooling. The merge of this two cooling systems provide detection unit non-stop operation for months without having liquid nitrogen to refill.

The NICOLE hybrid cooling system comprises Stirling-cycle cryocooler, cryocooler controller, Dewar vessel, pressure sensor and indicator, liquid nitrogen sensor and level monitor.



Application

Nicole hybrid cooling system for the HPGe detector allows you to keep your detector cold without filling with Liquid Nitrogen for months and years.

Features

One of the biggest advantages of Nicole hybrid cooling system is that it is extremely easy to perform maintenance and service. The user is given USB interface to get access to all parameters of the system. Majority of main parameters are displayed of the LCD display. And I case of maintenance, repair or replacement of the cooler is needed, it takes only 15 minutes to dismantle the cooling unit. It means the user can continue measurements by only using liquid nitrogen. It can be extremely important when routine measurements can't be terminated.



Détection des radiations > Équipement de laboratoire

Robotic Gamma Spectrometer

Application

The Automated Spectrometer is intended for the detection and analysis of radio nuclides from various types of environmental objects such as rocks, minerals, sludge, slag, soil, plant, sediment and particulate matter in air and water. The spectrometric system is able to determine the composition of a sample based on the photon energy and the activity based on the photon flux. The low-background lead shielding together with the highly pure germanium (HPGe) p-type detector gives precise results even for low activity materials. The fully automated sample changer enables the user to measure more than 40 samples, without having to interact with the Robotic Gamma Spectrometer. This reliable robotic sample changer increases the productivity and reduces the possibility of health risks for the operator.



The Automated Spectrometer is intended for the detection and analysis of radio nuclides from various types of environmental objects such as rocks, minerals, sludge, slag, soil, plant, sediment and particulate matter in air and water. The spectrometric system is able to determine the composition of a sample based on the photon energy and the activity based on the photon flux. The low-background lead shielding together with the highly pure germanium (HPGe) p-type detector gives precise results even for low activity materials.

The fully automated sample changer enables the user to measure more than 40 samples, without having to interact with the Robotic Gamma Spectrometer. This reliable robotic sample changer increases the productivity and reduces the possibility of health risks for the operator.

Automatic Sample Changer

The seven-axis robot handles a payload of up to 3kg and with, practically, unlimited reach, the robot is able to carry out a series of operations using flexible rather than hard automated solutions. In addition to a horizontal reach, the robot has the ability to reach below its base. Furthermore, the robot has a very compact turning radius, which is enabled by the robots symmetric architecture, without offset on axis 2. This ensures the robot can be mounted close to other equipment.

Basic characteristics of Robot arm:

- Seven-axis manipulator
- Machine vision
- Payload: 3 kg
- Reach: per request
- Fastest 7-axis robot
- Accuracy: ± 0.01 mm
- Weight: 25 kg
- IP30 protected

- All motors and cablings enclosed
- Compact controller
- Sample holder tool for vessels with diameter in range 40 - 110 mm.
- Barcode Reader and Writer

To assure the correct processing of all data during the measurement and analysis process, the samples are marked by using a barcode printer that is connected to the workstation. Here all necessary information about the sample is stored in a database. Using the bar code reader, the information stored in the database is retrieved for each sample before the measurement process is started. This fully automated process delivers all necessary information for the measurement and analysis process.



Détection des radiations > Équipement de laboratoire

HPGe Spectrometer with Shield

Application

The spectrometer with shield is designed for defining the composition and activity of radionuclides in the flow of liquids and gases in automated technological processes in the nuclear power industry, environmental monitoring and in industrial applications involving radionuclides. The Spectrometer can be used for radiation monitoring and various tasks like definition of activity of naturally occurring radionuclides (NORM) in building materials, raw materials, foodstuff, industrial waste monitoring and technological radionuclide production and processing without sampling. The Spectrometer allows pre-setting algorithm of continuous and autonomous measurement in advanced to avoid interaction of employees with the Spectrometer and samples in case of remote installation or installation in restricted area. Complete control, monitoring, calibration and preventive maintenance of the Spectrometer is performed remotely by means of Ethernet interface or other available interfaces..



Features

- Definition of composition and activity levels of radionuclides in real time mode
- Display of current values for specific activity of controlled radionuclides
- High registration efficiency
- Wide range of measured activities
- Operation rates in fully-automatic mode: measurement, washing, purging, pre - starting

The spectrometer with shield is designed for defining the composition and activity of radionuclides in the flow of liquids and gases in automated technological processes in the nuclear power industry, environmental monitoring and in industrial applications involving radionuclides. The Spectrometer can be used for radiation monitoring and various tasks like definition of activity of naturally occurring radionuclides (NORM) in building materials, raw materials, foodstuff, industrial waste monitoring and technological radionuclide production and processing without sampling. The Spectrometer allows pre-setting algorithm of continuous and autonomous measurement in advanced to avoid interaction of employees with the Spectrometer and samples in case of remote installation or installation in restricted area. Complete control, monitoring, calibration and preventive maintenance of the Spectrometer is performed remotely by means of Ethernet interface or other available interfaces.

- Low activity samples

To get more statistics, the system is equipped with large diameter tube and might have several loops around the detector in order bigger amount of the sample was located around the detector for measurement.

The system is also capable to perform not only continuous measurement of sample flow but also to perform

sampling by stopping the flow for certain amount of time to get more time for acquisition.

- Low and middle activity samples

One loop tube can be used of sampling. Material of the tube can be acryl or glass.

- High activity samples

High activity samples can be brought the detector by using metal tube of relatively small diameter. Such kind of tubes can be used for measurement of hot liquid samples and high pressurized gas samples within reasonable limits.

Diameter and material of the tube is carefully determined during technical discussion with the user in order to consider of parameters of technological line and environmental conditions.

Depending on the application, other sample vessels are available to be used instead of sample tube. Acryl or metal Marinelli-type vessels. Example is below:

← Back to partner



Détection des radiations > Équipement de laboratoire Flowing HPGe Spectrometer

Application


Highly efficient control of radionuclide materials with low activity.

Features

Detection unit performs 4π geometry measurements as measuring product is moving inside germanium detector. Radionuclide efficiency registration is more than an order of magnitude higher than efficiency registration of standard coaxial detection unit of the same dimensions.



HPGe detector flowing geometry can be developed based on the crystal with equivalent efficiency from 10 to 100%.



Absolute efficiency registration comparison curves during gamma-ray emission with sample positioning inside and outside detector.

← [Back to partner](#)



Détection des radiations > Équipement de laboratoire

HPGe Infrared Detectors

Application

High sensitive HPGe infrared detectors are intended for NIR Fluorescence or Raman spectroscopy and similar applications in spectral region from 850 nm to 1.7 μm .



Features

- Highest sensitivity
- Low noise level
- Frequency range up to 300 Hz
- LN2 cooled electronic input stage (FET and feedback resistor)
- RG 850 window with antireflective coating
- Preamplifier with temperature monitor
- Various types of Dewar vessel are available

HPGe infrared detectors are intended for NIR Fluorescence or Raman spectroscopy and similar applications in spectral region from 850 nm to 1.7 μm .



Ultra Low-background HPGe Detectors

Application

Ultra low-background HPGe detectors are widely used in underground laboratories for determination of radionuclides activities in environmental or industrial samples at $\mu\text{Bq/kg}$ levels and in scientific experiments such as investigation of magnetic moment of neutrino, dark matter search, etc.



Design

- Task related design (U-type, vertical, down-looking or portable cryostat)
- Remote not cooled part of preamplifier
- Zeolite is placed near not cooled part of preamplifier in order to be outside measuring chamber

Cryostat materials

- Certified materials with low radiation impurities
- Ultrapure aluminium-silicon alloy with U + Th content < 1, 0.5 or 0.2 ppb for detector holder and endcap
- Freshly produced electrolytic copper for coldfinger and pedestal
- Tested on radiopurity selected stainless steel screws and sapphire insulators

Technology

- Transportation of HPGe crystal and cryostat materials by surface freight
- Minimization of fabrication time (location of materials above ground)
- Assembly in a cleanroom
- Cleaning and passivation of copper surfaces
- Storage of crystal and cryostat materials in a container made from materials effectively slowing down and absorbing neutrons (water and Cd)

Design features

- Fabrication of large volume HPGe detectors without bulletization
- Front end electronics made on low-background Teflon substrate
- Passive screen between front end electronics and HPGe crystal made from Pb with Bi-210 radioactivity < 0.1 Bq/kg
- Double-crystal HPGe detector design
- Multi-crystal HPGe detector design

← [Back to partner](#)



Détection des radiations > Équipement de laboratoire **LN2 storage and transfer system**

Application

The system for storage and transportation of liquid nitrogen in the following areas of application: Industrial, laboratories, life sciences, medical, etc.



Features

- Direct liquid nitrogen supply with the decanting valve
- The LN2 System can fit easily under a laboratory bench or workstation
- A hand rail can be easily attached to protect the operating head and make it easier to move the vessel
- Easy to dispense liquid nitrogen
- Double valve option for liquid use
- Capacity of 35 to 100 litres
- Self-pressurized vessel
- Delivered with or without the operating head
- Static holding time up to 75 days
- 6 year guarantee on the vacuum



Détection des radiations > Équipement de laboratoire

Multi Channel Analyzer BOSON

Features

- Boson MCA acquires and displays spectra with overlapping by energy range up to 1000 times
- No resolution deterioration at operation in the beginning of spectrum energy range
- Stable operation with preamplifiers of TPR type with output voltage swing up to +/- 10 V and reset duration up to 250 us
- Automated P/Z adjustment
- Improved dead time correction
- Spectrum stabilization
- Setting and control of all parameters using colour LCD display with touch screen
- Complete remote control of Boson MCA via software from PC
- Dead time correction
- Base Line Restorer (BLR)
- Operation with preamplifier TPR



All settings are saved in spectrometer memory in case of power supply disconnection.

Basic settings:

- HV ON and OFF
- HV polarity switching
- HV value setting
- Input signal polarity switching
- Amplification coefficient setting coarse (in analogue section)
- Amplification coefficient setting smooth (in analogue section)
- P/Z compensation adjustment with optimal adjustment indication
- ADC capacity switching 1024 / 2048 / 4096 / 8192 / 16384
- Discrimination threshold value setting of "fast" channel (CRM) in conventional unit, in the range of 0 - 30% of dynamic range (by amplitude of output signal on "LIN OUT")
- Discrimination threshold value setting of low signal level (LLD) in the channels, in the range of 0 - 50% of dynamic range (by amplitude of output signal on "LIN OUT")
- Discrimination threshold level setting of high signal level (HLD) in the channels, in the range of 50 - 100% of dynamic range (by amplitude of output signal on "LIN OUT")
- Shaping time constant switching
- Basic line restoration time switching (8 values)
- Dead time correction
- Spectrum acquisition time setting
- Spectrum acquisition ON and OFF
- Switching of communication port with the outer computer: USB, LAN, RS-232



Détection des radiations > Équipement de laboratoire

Digital Miniature Multi Channel Analyzer MCA 527

The MCA527 is a battery powered high performance 16K Multi-Channel Analyzer/Multi-Channel Scaler module with the performance of a laboratory grade MCA. High voltage supply for detector and preamplifier power supply are integrated as well as an internal coarse amplifier and digital filtering and analysis. Together with a detector it forms a small-size gamma spectroscopy system, which is well suited to the demands of field measurements for international safeguards, environmental monitoring, nuclear waste treatment facilities, radioactive transport control and similar applications.



- Automated base line restorer and threshold adjustment
- Automated or manual pole zero adjustment without oscilloscope
- System dead time and count rate indication
- Dead time correction
- Automated spectrum recording
- Peak stabilization
- Basic analysis functions (energy calibration, FWHM, peak area and integral calculations, spectrum stripping and smoothing)
- File menu: write/read functions with drive/path – and file pick list functions
- Setup menu: ADC, Amplifier, Presets, Memory splitting, MCA mode, MCS mode, Multi spectral recording mode, automated instrument configuration using setup file
- Analysis menu: Energy calibration und further analysis functions defined according the purpose. Energy calibration with linear calibration curve using 2 peaks or energy channel pairs
- Acquire control: Start, Stop, Erase, Presets Incorporated Help texts Print screen for print via system printer (Windows) quick documentation
- Display functions: Automated vertical full scale (VFS), manual and logarithmic VFS, cursor functions, expand and unexpand, ROI setting
- Detection limit formalism: more than 17

← Back to partner



Détection des radiations > Équipement de laboratoire Quality Assurance package

Gamma or Alpha analysis software SpectraLine can be extended with Quality Assurance package in order to provide monitoring of the spectrometer channel for the parameters of the full energy peak (position, FWHM and detection efficiency) for the specified energy and the background count rate.



The reference sample and the background are measured in semi-automatic mode for quality control. As the scenarios are used the measurement parameters can be flexibly adjusted and the monitoring results can be displayed depending on the date and time of the measurement start.

The control limits determined by the alarm and warning levels are displayed on the graph, so the parameters deviation from the specified intervals can be easily found.



Free Release Monitor HERCULES-FRM

Application

Free Release Monitor HERCULES-FRM main working principle can be described the following way. Any loading mechanism like forklift or a crane gently puts measuring object to the movable platform on the front roller-based conveyor. Scales which are inbuilt in the front conveyor are determining weight of the measuring object and automatically transfers information for the analytical software. Further actions are performed totally automatically or in manual mode. Measuring chamber opens front doors and movable platform slides inside of measuring chamber. Doors are closed and measurement starts. The FRM is equipped with 16 plastic scintillators surrounding the measuring object from all sides. Plastic scintillators are connected to digital multichannel analysers located in the control box. Analytical and control software packages guarantee total remote control and data acquisition from all plastic scintillators simultaneously. All analytical performance of the FRM is set up previously by inputting all information concerning measuring object, geometry, sizes, weights, filling of containers, etc. in the software package. After measurement is finished, operator is alarmed, record is stored in the database and report can be printed any time. In order to change the measuring object, the FRM opens the front doors and slides the platform out for further unload by the forklift or a crane. In case the operator needs to measure specific object, it is possible to open back doors to load the measuring object from the back. The whole measuring chamber is securely covered with stainless-steel for easy decontamination.



Features

General

- Overall dimensions of the FRM: 5000x2300x2100mm (LxWxH)
- Overall weight of the FRM: 10000kg
- Operation temperature: +10...+35°C
- Ready to accommodate object with size 1.2m x 0.8m x 1.0m (L x W x H)
- Lead walls not less than 50mm thick
- Stain-less steel protection
- External and internal automatic conveyor
- Inbuilt scales

Plastic scintillators (HPGe detectors optional)

- 16 or 24 or more plastic scintillators equipped with PMTs
- Energy range from 100 to 3000 keV
- Detection limit for Co-60 is less than 300 Bq

Software

- Total activity calculation
- Visualization of measurement and diagnostic information
- Storage of measurement data, controlled parameters and fixed constants in internal memory
- Control of all mechanically movable mechanisms
- Control and reset of the FRM in case of failure of automation
- Self-diagnostics control
- Visual and audible alarm in case of failure or exceed of previously set levels
- Alarm in case of fixed level activity exceed for separately chosen radionuclide
- 3D visualization interface for measurement object monitoring and setting geometrical parameters in order to decrease measurement uncertainties
- Visualization of inhomogeneities in activity distribution
- Automatic change of measurement parameters depending on measurement geometry (Geometry must be set up preliminary)
- All software packages run under Windows operation system

Control box Control box of the FRM includes the following components:

- Set of MCAs for reading and transforming signals from PMTs of plastic scintillators
- Set of power supplies for different modules of the FRM
- Set of controllers to manage all components of automation process
- Indicators for operator
- Control panel with colour LCD display and touchscreen
- An emergency stop button is provided on the control box and the measuring chamber



Gamma-, beta- and alpha-spectrometer-radiometer TRIO

Application

Spectrometer TRIO is designed for registration of gamma-, beta- and alpha radiation and for measuring activity (specific and volumetric activity) of natural radionuclides (for example Ra-226, Th-232, K-40, Rn-222), technogenic radionuclides (for example Cs-137, Cs-134, Co-60, mTc-99, Sr-90 and etc.) in water, food, vegetation, building materials, soil samples, radiopharmaceuticals, rocks, chemical industry materials, alloys, scrap metal and other technological products. Also, it is used for measuring gross specific activity of beta- and alpha-emitting radionuclides in water.



Features

- Ability to manage several channels simultaneously
- Intuitive and user-friendly software
- Low Power Consumption
- Compact size of each chamber
- Free to choose channels of your interest depending on application
- Easy extension of channel quantity
- 100% remote control of the spectrometer TRIO via software package



Partner **Else Nuclear**



ELSE NUCLEAR S.r.l. is an Italian OEM company specializing in advanced radiation-detection and environmental-monitoring systems for nuclear safety, industry and research.

Product offering

**BSS - BONNER
SPHERE
SPECTROMETER**



**SP2 - SINGLE-SPHERE
NEUTRON
SPECTROMETER**



**W-PIE - WIDE ENERGY
ACTIVE NEUTRON
SPECTROMETER**




**GSU - GAMMA
SPECTROMETRY UNIT
WITH NaI(Tl)**



SATURN I, SATURN II



WDMS NT-VK



**LEM - LIQUID
EFFLUENT
MONITORING SYSTEM**





BSS - BONNER SPHERE SPECTROMETER

The Bonner Sphere Spectrometer consists of an array of He-3 proportional counter thermal neutron detectors, each housed in a spherical HDPE moderator of different diameters.

BSS is proposed in two main configurations, adjustable according to the requirements, for single or multiple detectors.

An unfolding software (RUFUS), used to calculate the neutron spectrum, is also available for both configurations.



Each proportional counter is connected to a compact electronic module (2.5 cm diam. x 7.6 cm), providing:

- Precision wide-band charge-sensitive pre-amplifier and amplifier
- Discriminator circuit
- High voltage adjustment 0-2200 V
- Amplifier gain and discriminator threshold adjustment
- Analogue test points for shaped signals and HV

A user-friendly dedicated acquisition software can be installed on the PC managing the BSS, allowing the user to start and stop the measurements, to modify the parameters and to visualize the saved data.

The BSS standard set, designed to cover the neutron energy range from 1 meV to < 100 MeV, includes the following HDPE moderators: Ø 3", Ø 3.5", Ø 4", Ø 4.5", Ø 5", Ø 6", Ø 7", Ø 8", Ø 10", Ø 12", Ø 15", Ø 18".

The available configurations of BSS are:

- Single detector: includes only one He-3 proportional counter, to be inserted in one moderator sphere at a time. The detector is managed by a Counter Module and the user interface is the "Single counter" software.
- Multiple detectors: includes up to 16 He-3 proportional counters, and up to 16 moderator spheres (12 standard + 4 accessory), to be employed at the same time. The detectors are managed by a Datalogger and the user interface is the "DLOG" software.



Détection des radiations > Équipement de laboratoire

SP2 - SINGLE-SPHERE NEUTRON SPECTROMETER

The single-sphere neutron spectrometer SP2 is a unique device that allows performing active neutron spectrometry measurements by employing a single instrument instead of the usual multi-sphere BSS.



SP2 is characterized by the same high sensitivity and precision as BSS in determining the neutron flux over the entire energy range, while removing any reproducibility uncertainty. When employed with the on-line unfolding tool, SP2 can also perform real time measurements.

SP2 is equipped with 32 active ^6LiF -covered Silicon neutron detectors installed over six concentric layers inside the moderating assembly, so that they reproduce the spectrometric performance of a six-sphere BSS. The signals are acquired by the built-in electronics and can be either analysed on-line by the built-in unfolding algorithm, or saved as raw data for off-line analysis.

SP2 can be used in a great number of activities in scientific research: homeland security, cargo inspections, calibration laboratories, characterization of stray radiation fields for radiation protection purposes, periodical quality check of the neutron stray radiation field, all applications involving the need of a fast and precise measurement of the neutron spectrum.

A SP2 LITE version is also available, featuring a lighter build and a narrower energy range, suitable for all the applications that do not require to detect neutrons with energy above 20 MeV.

The response function of the device, calculated via Monte Carlo simulations, is available for either on-line and off-line analysis. The response function and unfolding algorithm have been validated after thoroughly testing with reference radioactive sources.

SP2 is the ideal device for performing active neutron spectrum measurements in every radiation environment, including mixed stray radiation fields, workplaces characterized by high gamma background and reference calibration laboratories.



Détection des radiations > Équipement de laboratoire

W-PIE - WIDE ENERGY ACTIVE NEUTRON SPECTROMETER

The W-PIE neutron spectrometer is a unique device designed for on-line neutron spectrometry measurements. The system features an extremely high counting efficiency, making it suitable to perform neutron spectrometry and absolute flux measurement for applications such as:

- homeland security
- cargo inspections
- calibration laboratories
- background suppression in high-energy physics experiments
- cosmic ray neutron sensing (CRNS) in agriculture
- snow water equivalent (SWE) measurements in hydrology



W-PIE employs ${}^6\text{Li}$ as neutron converter, ${}^4\text{He}$ as scintillating medium, and 24 independent low-voltage SiPMs as photosensitive components. The detector is surrounded by increasingly thick moderating assemblies, defining 4 detection sub-volumes each optimised for a specific spectral region. Signals are acquired and analysed by the built-in electronics and unfolding algorithm, or they can be saved as raw data for off-line analysis.

The response function of W-PIE, calculated via Monte Carlo simulations, is available for either on-line and off-line analysis. The response function and unfolding algorithm have been validated after thoroughly testing with reference radioactive sources, with quasi-monoenergetic neutron fields, and in the high-energy reference neutron field facility CERF at CERN.

The device is available in two configurations:

- W-PIE - standard, high-energy version, with Cd and Pb inserts, designed to be sensitive to neutrons up to 10 GeV
- HERMES W-PIE - lightweight and standalone low energy version, without high-Z inserts, designed to be sensitive to neutrons up to about 100 MeV

The W-PIE version is powered over Ethernet and communicates with a PC through Ethernet connection.

The HERMES W-PIE version is a standalone unit featuring a single board computer, a 4G router, a GPS and a dual-SIM system allowing remote control.



GSU - GAMMA SPECTROMETRY UNIT WITH NaI(Tl)

The GSU gamma spectrometry units employ a 3"x3" NaI(Tl) crystal coupled to a photosensitive detector (either PMT or SiPM) and an MCA. The detector is installed in a 5 cm thick lead shielding well, with additional inner layers of tin and copper for enhanced background reduction.

GSU is designed to perform gamma spectrometry analyses of small samples, such as foundry casting samples, air particulate filters, environmental samples (rocks, soil, biological samples), positioned in sample holders which can be tailored to meet specific measurement requirements, or Marinelli beakers.



The User can manage the system through the proprietary ELSE NUCLEAR GSU system software, calculating the specific activity and the Minimum Detectable Concentration (MDC) of the sample expressed in Bq/kg, Bq/l, Bq/m³, etc. The built-in background subtraction subroutine improves the MDC without increasing the measurement time. The software includes fully-customisable isotope libraries as well as User-settable isotope-specific activity alarm thresholds, available through password-protected functions.

The GSU-NORM is a special version of system specifically conceived to perform Naturally Occurring Radioactive Material (NORM) analysis of environmental samples, such as rocks, sediments or soils. Through its MCA and its dedicated software, the GSU-NORM system allows determining the specific activity of NORM isotopes, i.e. K-40, Th-232 and U-238, expressed in Bq/g, %K, ppm eU and ppm eTh.

The sample holders are custom-made supports that fit directly on the detector's head, used to hold casting samples, test sources or other similar objects.

The Marinelli beakers are used to contain geological samples or other similar materials. Several volumes are available, from 250 ml up to 1 l, with different geometrical features.

Each GSU system includes efficiency curves and coefficients implemented in the analysis software, calculated through Monte Carlo simulations for each specific configuration, acquisition chain and measurement geometry. The simulations are always validated through experimental tests performed with reference radioactive sources.



Détection des radiations > Équipement de laboratoire **SATURN I, SATURN II**

The SATURN ratemeter is a compact acquisition and control unit, designed for managing and processing signals from any ELSE NUCLEAR connected detector.

- SATURN I: standard wall-mounted version
- SATURN II: wall-mounting version compliant with “Good Manufacturing Practice” requirements (no external cable or connectors)



All the ratemeter versions feature local function buttons with status LEDs, internal acoustic buzzer and a relay connector, used to manage external alarm columns or interlocks.

The SATURN ratemeter continuously acquires and processes the data coming from the connected detector, and compares results with user-defined alarm thresholds.

Two user-selected measurements can be displayed at the same time on the display, such as instantaneous or average count rate, dose rate, activity concentration, counts, dose or activity integrated values.


The user interface is accessible through an external keyboard, which allows local interaction with the full range of parameters (advanced setting is password protected). Measurements, thresholds and operating parameters are stored into an internal, non-volatile memory.

The ratemeter can communicate to and be remotely managed by a host PC through an Ethernet or RS485 network.



WDMS NT-VK

The WDMS NT-VK system is designed to collect and monitor radioactive wastewaters, which can be released only after their radioactivity drops below a defined value. The main application of such a system is related to diagnostic and therapeutic procedures involving radioactive substances, and their partial elimination through the patient's metabolism.



The WDMS NT-VK system is designed to collect and monitor radioactive wastewaters, which can be released only after their radioactivity drops below a defined value. The main application of such a system is related to diagnostic and therapeutic procedures involving radioactive substances, and their partial elimination through the patient's metabolism.

The WDMS NT-VK main components are:

- Purification group: Imhoff tanks designed to collect the wastewaters and to separate liquid from solid waste
- Sorting group: pumps and conduits pouring the wastewaters in the decay tanks
- Decay group: tanks array where the wastewaters are poured and stocked until their radioactive level drops below a defined value
- Sampling system: valves and pumps used by the system to wash the sampling circuit and to sample the stocked wastewaters, allowing the measurement in Marinelli geometry
- Release group: pumps and conduits releasing the wastewaters in the sewers, if allowed by the monitoring results
- Safety groups and devices: level and pump sensors installed in all the system critical stages, stopping the wastewaters flow in case of detected anomaly, and safety flooding well which can collect and stock wastewaters potentially overflowing from any system group

The entire system is locally managed by a PLC, which is commanded by a remote management software installed on a PC.

Through the interactive synoptic interface of the software the operator can activate the system automatic cycles, set the measurement parameters, visualize the alarms and release archives, and monitor the system's status (filling levels, pump stages, measurements, alarms). Depending on the measurement results, and as defined by the procedures in force, the operator can also activate the monitored wastewaters release in the sewers.

← **Back to partner**



Détection des radiations > Équipement de laboratoire

LEM - LIQUID EFFLUENT MONITORING SYSTEM

The LEM system is designed to sample the liquid effluents and to perform a spectroscopic analysis in Marinelli geometry.

LEM system is composed of the following main parts:

- Stainless steel frame
- Electrical and command board with touch-screen panel PC
- NaI(Tl) detector, 1 l Marinelli, 5 cm thick lead shielding well
- Self-priming pump (*)
- Software for system management, data acquisition and processing



The measurements are visualised in real time by the software, expressed in terms of specific/total activity through spectroscopic analysis.

LEM status and parameters are managed by the ELSE NUCLEAR software. The system provides also I/O contacts through dedicated connectors:

- Good functioning status output
- Alarm status output
- Pump activation input from customer PLC (*)
- Spare available I/O contacts (to be defined when necessary)

The software provides a calibration routine, to be used with a Marinelli calibration source (available as accessory).

A test program is also available, separate from the main application, to be used for maintenance or periodical quality controls.

(*) If not available in the sampling/hydraulic equipment which LEM shall be connected to



Partner Ludlum Measurements



Ludlum Measurements, Inc. conçoit et fabrique des instruments et des technologies de détection des rayonnements. Fondée en 1962, elle propose une large gamme d'instruments de détection de rayonnements, développés pour aider à surveiller la sécurité du personnel et de l'environnement. Les instruments sont utilisés dans des applications telles que la surveillance de routine du personnel et du matériel, la sécurité des frontières et les situations d'intervention d'urgence.

Product offering

Model 3030E Alpha-Beta Scaler



Model 2000 General Purpose Scaler



Model 2200 Scaler-Ratemeter



Model 2100-1 Sample Counter



Model 2100 Conveyorized Sample Counter



Model 3030E with 43-10-1 Alpha-Beta Sample Counter



Model 3030-2 Simultaneous Alpha-Beta Sample Counter



Model 3030 Alpha-Beta Sample Counter



Model 3030P Alpha-Beta Sample Counter



Probes (Ludlum)





Détection des radiations > Équipement de laboratoire Model 3030E Alpha-Beta Scaler

- Dual Channel Scaler with Independent Readouts
- Connects to External Sample Head/Detector
- CPM & DPM Modes
- Background Subtraction
- Alpha/Beta Alarms
- QC Check
- 8 Hour Battery Operation
- Real Time Clock
- RS-232 Interface
- Includes PC Software



The Model 3030E is a dual channel, scaler-type, sample counter electronics package that will accommodate many detector inputs from external sample head/detectors. This design represents a significant improvement over older analog type scalers by providing greater utility and functionality.

The system incorporates independent backlit LCD readouts to support discriminated alpha and beta sample counting. The system features background subtraction, crosstalk correction, separate alpha/beta alarms, cpm/dpm operating modes, and a pre-scripted QC function with an automatic reminder timer.

The instrument supports both 110 and 220 Vac operation and includes a trickle-charged gel-cell battery for portable offsite use up to eight hours. A wide-range, high-voltage power supply supports virtually any detector.

Status indicators located along the front panel inform the operator when another QC check is required, if the detector is nonfunctional, if it is operating in DPM or CPM mode, and if either an alpha or beta alarm setpoint has been exceeded. The count time is selected via a front panel rotary switch that enables count times ranging from 0.1 to 60 minutes or some other prescribed value as set up via a link to a PC. Other controls include a start count button, audio volume rotary adjustment, and instrument on/off switch.

An RS-232 output from the rear panel supports connection to either a printer or PC. Included in the price is PC control software, which is a Windows application that supports setup of the system, as well as collecting and logging all count results from the 3030E.



Model 2000 General Purpose Scaler

- General Purpose Scaler
- Supports Wide Range of External Detectors
- 95 to 250 Vac Power Input
- Portable Battery Operation
- RS-232 Interface to Printer or PC

The Model 2000 is a general purpose scaler typically used for counting samples. Rugged design and construction accommodates both benchtop and portable applications. The wide-ranging AC power supply and internal batteries are capable of powering the instrument upwards of 120 hours. The Model 2000 supports GM, proportional, and scintillator type detectors, and provides fine adjustment controls for setting the high-voltage and threshold settings.

The scaler reading is presented on a digital, six-digit readout LED that can be set to count from 0.1 to 999 minutes via a front-panel dip switch. An internal switch facilitates counting in seconds rather than minutes, if desired. Other front-panel controls include a start-count button, an HV/Bat switch for displaying the current value on the accompanying analog meter, and a three-way switch for selecting Power Off, Battery, or Line Power.

An RS-232 port on the rear panel allows connection to a PC or printer as set by a rear mounted switch (a RS-232 to USB adapter cable is included). When connected to a PC, the counting may be controlled and results recorded via application software.





Model 2200 Scaler-Ratemeter

- General Purpose Scaler/Ratemeter
- Single Channel Analyzer
- Supports Wide Range of External Detectors
- 95 to 250 Vac Power Input
- Portable Battery Operation
- RS-232 Interface to Printer or PC

The Model 2200 is a general purpose scaler with an accompanying ratemeter, and is typically used for counting samples. Its rugged design and construction allow both benchtop and portable applications. The wide-ranging AC power supply and internal batteries are capable of powering the instrument upwards of 120 hours. The Model 2200 supports GM, proportional, and scintillator-type detectors, and provides fine adjustment controls for setting the high-voltage and threshold settings.

An adjustable discriminator and an adjustable window allow the user to count pulses within a user specified energy range. This portable unit can be powered by wall current or by four "D" cell batteries. The latter allows for continued operations during power interruptions. An optional printer (Model 4167-386) is available for hard copy archival of wipe test results.

The Ludlum Model 2200 Scaler/Ratemeter is the ideal economic solution for routine sample counting, single channel analyzing and routine radiopharmaceutical related procedures, when used with the [Model 243](#) well scintillator (NaI) detector. The well counter's 4π geometry and 1.3 cm (0.5 in.) shielding provides excellent sensitivity to higher energy isotopes like ^{131}I .



← **Back to partner**



Détection des radiations > Équipement de laboratoire

Model 2100-1 Sample Counter

The Model 2100-1 manually operated sample counting system processes sample steel slugs to determine whether any radioactive impurities exist. The gamma radiation counting system is a table-mounted, fully integrated design that includes a gamma detector, sample tray, and controller.

The counting electronics incorporates two channels to distinguish between low and high energy gamma isotopes. All parameters, such as alarm point and count time are user-adjustable from the front panel LCD touch screen via a simple menu selection.

Measurement results for each sample are displayed on the backlit LCD. An Ethernet port reports all results and system status in real time for remote data logging and alarm annunciation. Visual and audible alarms are annunciated via the system's LCD and rear panel mounted buzzer respectively. A built-in relay provides a method for driving an external horn/strobe (available as an option).

One rear panel mounted USB port enables connection to either a keyboard or barcode reader device for the purpose of entering sample IDs.

Features

- High Sensitivity Gamma Detector
- Separate High & Low Gamma Energy Sampling
- User-Adjustable Parameters
- Color LCD Touch Screen
- Ethernet Connectivity
- Remote Alarm Output
- USB Ports for ID Input Devices





Model 2100 ConveyORIZED Sample Counter

The Model 2100 automated sample counting system processes sample steel slugs to determine whether any radioactive impurities exist. The gamma radiation counting system is a table-mounted, fully integrated design that includes a gamma detector, sample conveyor, and controller to facilitate automated processing.

Once the sample has been positioned on the conveyor, an infrared sensor automatically initiates conveyance of the sample into the lead shielded detector where it is counted for a predetermined time. Once the count is completed, the conveyor again advances until the sample drops into a discard container.

The counting electronics incorporates two channels to distinguish between low and high energy gamma isotopes. All parameters, such as alarm point and count time are user-adjustable from the front panel LCD touch screen via a simple menu selection.

Measurement results for each sample are displayed on the backlit LCD. An Ethernet port reports all results and system status in real time for remote data logging and alarm annunciation. Visual and audible alarms are annunciated via the system's LCD and rear panel mounted buzzer respectively. A built-in relay provides a method for driving an external horn/strobe (available as an option).

One rear panel mounted USB port enables connection to either a keyboard or barcode reader device for the purpose of entering sample IDs.





Détection des radiations > Équipement de laboratoire

Model 3030E with 43-10-1 Alpha-Beta Sample Counter

- Alpha-Beta Dual Channel Sample Counter
- Simultaneous Alpha & Beta Counting
- 5.1 cm (2 in.) Diameter Sample Tray
- Independent Readouts
- CPM & DPM Modes
- Background Subtraction
- Alpha/Beta Alarms
- QC Check
- 8-Hour Battery Operation
- Real Time Clock
- RS-232 Interface
- Includes PC Software



This system joins Ludlum's Model 3030E dual channel scaler and the [Model 43-10-1](#) dual phosphor detector with a 5.1 cm (2 in.) diameter sample tray to produce a complete alpha beta sample counting system. The 3030E electronics incorporates independent backlit LCD readouts to support discriminated alpha and beta sample counting. The system features background subtraction, crosstalk correction, separate alpha/beta alarms, CPM/DPM operating modes, and a pre-scripted QC function with automatic reminder timer.

The instrument supports both 110 and 220 Vac operation and includes a trickle-charged gel-cell battery for portable offsite use for up to eight hours. A wide-range high-voltage power supply supports virtually any detector. Status indicators located along the front panel inform the operator when another QC check is required, if the detector is nonfunctional, if it is operating in DPM or CPM mode, and if either an alpha or beta alarm setpoint has been exceeded.



Model 3030-2 Simultaneous Alpha-Beta Sample Counter

- Fully Integrated Alpha-Beta Sample Counter
- Simultaneous Alpha and Beta Counting
- Shielded 5.1 cm (2 in.) Diameter Sample Tray
- Independent Readouts
- CPM, Bq, & CPS Modes
- Background Subtraction
- Alpha/Beta Alarms
- QC Check
- 8 Hour Battery Operation
- Real Time Clock
- RS-232 Interface



The Model 3030-2 Simultaneous Alpha-Beta Sample Counter is a dual-channel counter designed for simultaneous alpha and beta sample measurement.

The counts per minute (CPM), Becquerel (Bq), or counts per second (CPS) modes may be enabled to allow the count to be automatically, and in real time, in CPM, Bq, or CPS. While in Bq and CPS display modes the display will show the count with two decimal places.

The counter incorporates an internally housed ZnS(Ag) plastic scintillator detector with shielded 5.1 cm (2 in.) diameter stainless steel sample tray. This system supplies independent backlit LCD readouts to support alpha and beta sample counting.



Model 3030 Alpha-Beta Sample Counter

- Fully Integrated Alpha-Beta Sample Counter
- Simultaneous Alpha and Beta Counting
- Shielded 5.1 cm (2 in.) Diameter Sample Tray
- Independent Readouts
- CPM & DPM Modes
- Background Subtraction
- Alpha/Beta Alarms
- QC Check
- 8 Hour Battery Operation
- Real Time Clock
- RS-232 Interface
- Includes PC Software



The Model 3030 Alpha-Beta Sample Counter incorporates an internally housed ZnS(Ag) plastic scintillator detector with shielded 5.1 cm (2 in.) diameter stainless steel sample tray into the Ludlum Model 3030 Scaler. This combined system supplies independent backlit LCD readouts to support discriminated alpha and beta sample counting. Key features include background subtraction, crosstalk correction, separate alpha/beta alarms, cpm/dpm operating modes, and a pre-scripted QC function with automatic reminder timer.

The instrument supports both 110 and 220 Vac operation, and includes a trickle charged gel-cell battery for portable offsite use for up to eight hours. A wide-range high voltage power supply supports virtually any detector. Status indicators located along the front panel inform the operator when a QC check is required, if the detector is non-functional, if it is operating in dpm or cpm mode, and if either an alpha or beta alarm setpoint has been exceeded.

The count time is selected via a front-panel rotary switch that enables count times ranging from 0.1 to 60 minutes, or some other prescribed value as set up via a link to a PC. Other controls include a start count button, audio volume rotary adjustment, and instrument on/off switch. An RS-232 output from the rear panel supports connection to either a printer or PC. Included in the price is PC-control software, which is a Windows application that supports setup of the system, as well as collecting and logging all count results from the 3030.



Model 3030P Alpha-Beta Sample Counter

- Fully Integrated Alpha-Beta Sample Counter
- Simultaneous Alpha and Beta Counting
- Employs PIPS™ Detector
- Ultra Low A/B Crossover & Backgrounds
- Adjustable Alpha Window for Radon Rejection
- Data Logging with USB Connectivity
- 48-Hour Battery Operation
- Includes PC Software



The 3030P with a solid state PIPS™ detector facilitates efficient and cost-effective, simultaneous alpha and beta sample counting for air filters, smears, and swipes. This instrument meets the newer Electric Power Research Institute (EPRI) guideline for detecting a few disintegrations per minute of alpha amidst several hundred-thousand disintegrations per minute beta background. All data are automatically logged and easily retrievable via a USB connection. The light weight and battery operability afford convenient use in the field. With the optional detector shield, the Model 3030P can be used virtually anywhere.

The instrument comes with PC control software that allows the user to set all parameters, view QC check settings, change alpha and beta window and threshold values, perform MDA (Minimum Detectable Activity), and retrieve the sample data saved to the logging memory.

← Back to partner



Détection des radiations > Équipement de laboratoire Probes (Ludlum)

For any application Ludlum offers a wide range of probes. The probes can be used with all Ludlum models which require an external detector.



Ludlum models with external detector a.o.:

- [Model 3000 Digital Survey Meter](#)
- [Model 3001 Multi-Detector Survey Meter](#)
- [Model 375 Area Monitor Controller](#)
- [Model 375/9 Digital Area Monitor](#)
- [Model 30 Digital Survey Meter](#)



Partner **SDEC France**



SDEC France est un fabricant spécialisé d'équipements de surveillance environnementale et de laboratoire. Il propose des solutions complètes pour la gestion des déchets et du recyclage, la surveillance environnementale et les applications de laboratoire. Forte de plus de 30 ans d'expérience, l'entreprise conçoit et fabrique des instruments de haute qualité pour les professionnels des sciences de l'environnement, de l'agronomie et de la radioprotection.

Product offering

EDP 9002 - Double Mast Electrodeposition Equipment



PRC 14: Maintenance Pump - For Cleaning Pipes for HAGUE 7000 CARBON 14 Bubbler



MARC 7000 - Tritium Bubbler: Atmospheric Monitoring System with 4 Pots (With Oven)



Aerosol and Iodine Sampling Heads



AS 5000 Portable Aerosol & Iodine Sampler DPRC Type for Air Flow Regulation - Maintenance-Free Design



EDP 7000 - Electrodeposition Equipment - Monostation



DPM 7001 Liquid Scintillation Counter - SDEC



H3R 7000 Airborne Tritium Condenser - SDEC



**Single Mast
Electrodeposition
Equipment - EDP
7000 - SDEC**



**Tritium sampler 4
vials MARC 7000 -
SDEC**





EDP 9002 - Double Mast Electrodeposition Equipment

- **SPACE-SAVING & ECONOMICAL DESIGN:** Two measurement stations on a single base, ideal for laboratories with limited workspace. The EDP 9002 is more affordable than purchasing two EDP 7000 devices.
- **TIME EFFICIENCY:** Significant time savings when conducting multiple analyses.
- **SYNTHETIC MATERIALS:** The EDP is made solely from synthetic materials that perfectly resist the sometimes highly corrosive environments of research laboratories, thus ensuring a very long lifespan for the device.
- **HIGH PRECISION:** Ensures optimal trapping efficiency with regulated and constant direct current. The EDP is equipped with a polarity reverser for electrochemical stripping of the stainless steel pellet intended to receive the deposit, thereby ensuring perfect purity of the support.
- **COOLING SYSTEM:** Features high-flow air convection, preventing solution evaporation thanks to a solution cooling system with high-flow air convection.
- **VERSATILE SETTINGS:** Adjust the current intensity up to 5 Amperes and the electrode rotation speed with precision potentiometers and three sizes for solution containers.
- **DIGITAL TIMER:** Set the exact duration of electrodeposition with a digital display timer and an audible alarm.
- **EASY TO USE:** Quick assembly/disassembly of bottles and an internal container for accidental spills. Easy user maintenance of the device. Almost instantaneous assembly/disassembly of bottles.
- **COLLABORATION WITH COGEMA:** Designed in association with the leading French nuclear institute.



← Back to partner



Détection des radiations > Équipement de laboratoire

PRC 14: Maintenance Pump - For Cleaning Pipes for HAGUE 7000 CARBON 14 Bubbler


- **RELIABILITY:** PRC 14 self-priming centrifugal pump with a 150-hour motor life, operates continuously without cooling.
- **VERSATILITY:** Specifically designed for HAGUE 7000 bubblers using a diluted acid solution. This operation dissolves and evacuates the solid deposits that have accumulated inside the Ø 3 mm stainless steel pipes and in the drilled block, mainly between pots 1 and 2. It is ideal for various applications, ensuring efficient capture of atmospheric ^{14}C .
- **DURABLE CONSTRUCTION:** Equipped with an ABS impeller, stainless steel motor shaft, and nitrile seal, ensuring longevity and resilience with a constant flow rate of 10l/h.
- **ENERGY EFFICIENCY:** Maximum consumption of 60 Watts, operates ideally at 12-15 volts DC, compatible with 12V battery.
- **ECONOMICAL SOLUTION:** Offers reliability and performance at an attractive price.





MARC 7000 - Tritium Bubbler: Atmospheric Monitoring System with 4 Pots (With Oven)

- **EFFICIENCY:** The MARC 7000 monitors atmospheric tritium, capturing vapor and gas, with oxidation in an oven.
- **PERFORMANCE:** 99% HTO trapping efficiency and 98% oven conversion efficiency for precise tritium monitoring.
- **INTEGRATED ADVANCED FUNCTIONS:** Offers adjustable airflow, real-time display of various parameters, automatic regulation, and default data storage. Designed for user-friendly operation and accurate readings.
- **PERFORMANCE:** Automatic air flow regulation, durable diaphragm pump, and 316L stainless steel circuit.
- **INTEGRATED ADVANCED FUNCTIONS:** Adjustable air flow, automatic regulation, real-time display, and anomaly storage.
- **OPTIONS FOR ENHANCED FUNCTIONALITY:** Cooling circuit, Ethernet connectivity, and alarms.
- **VERSATILE APPLICATIONS:** Suitable for the nuclear industry, research centers, waste storage, and laboratories.
- **SUPPLIER CONFIDENCE:** Officially supplied to major organizations such as IRSN, the French Navy, EDF, ANDRA, CEA, and internationally to IAEA and various nuclear power plants.
- **CERTIFICATION:** NF ISO 20045 & NF ISO 20041-1



← [Back to partner](#)



Détection des radiations > Équipement de laboratoire

Aerosol and Iodine Sampling Heads

These holders are used for sampling aerosols and volatile compounds on filter paper and cartridge(s). They can be used for ambient sampling or connected to a line (e.g., type DPRC). They are made of anodised aluminium or stainless steel (on request) for various diameters of filter paper and cartridge(s):



← Back to partner



Détection des radiations > Équipement de laboratoire

AS 5000 Portable Aerosol & Iodine Sampler DPRC Type for Air Flow Regulation - Maintenance-Free Design

- **HIGH-QUALITY SAMPLING:** The AS 5000 excels in aerosol and iodine sampling, fully compliant with NF ISO 2889 standards.
- **ADJUSTABLE AIR FLOW:** Microprocessor for airflow setting from 30 to 100 liters/minute, customizable options.
- **EASY FILTER HANDLING:** TPHP head for easy installation and retrieval of filters, without interrupting the air circuit.
- **EASY DATA TRANSFER:** Transmits data via Ethernet, an available option.
- **PRECISE MONITORING:** Tracks sampled air volume and alerts for clogging and leaks, with audible and written reports.
- **CERTIFICATION:** NF ISO 2889





EDP 7000 - Electrodeposition Equipment - Monostation

- **SYNTHETIC MATERIALS:** Made from synthetic materials resistant to the corrosive environments of laboratories, ensuring longevity of the EDP.
- **HIGH PRECISION:** Ensures optimal trapping efficiency with a regulated and constant direct current. The EDP is equipped with a polarity reverser for electrochemical stripping of the stainless steel pellet intended to receive the deposit, thereby ensuring perfect purity of the support.
- **COOLING SYSTEM:** High-flow air convection to prevent solution evaporation, thanks to a cooling ventilation system.
- **VERSATILE SETTINGS:** Precise settings for current intensity up to 5 Amperes and electrode rotation speed.
- **DIGITAL TIMER:** Timer with digital display and audible alarm for exact duration of electrodeposition.
- **INTUITIVE USE:** Quick installation of bottles, internal container for spills, easy maintenance.
- **COLLABORATION WITH COGEMA:** Designed in partnership with COGEMA, a leading French nuclear institute.



← [Back to partner](#)



Détection des radiations > Équipement de laboratoire

DPM 7001 Liquid Scintillation Counter - SDEC

Le compteur à scintillation liquide (SDEC) DPM 7001 est un compteur à scintillation liquide mobile équipé de deux photomultiplicateurs, lui conférant une efficacité de comptage élevée et un faible bruit de fond. Il est spécialement conçu pour le comptage du tritium et du carbone-14. De par sa petite taille et son poids léger (16kg), il peut être transporté facilement sur les sites de surveillance pour des mesures rapides.



Caractéristiques du compteur à scintillation liquide DPM 7001 :

- efficacité de comptage élevée (H3 > 37 %, C14 > 94 %)
- faible bruit de fond (< 40 CPM)
- poids léger : 16 kg
- contrôle et lecture sur afficheur LCD ou sur PC (logiciel en option)
- export des données au format Excel
- deux voies de comptage pour deux comptages simultanés

En savoir plus sur le compteur à scintillation liquide DPM 7001 sur le site Web du SDEC

← Back to partner



Détection des radiations > Équipement de laboratoire

H3R 7000 Airborne Tritium Condenser - SDEC

Le condenseur de tritium aéroporté H3R 7000 (SDEC) est un instrument innovant dans le domaine du tritium dans l'échantillonnage de l'air. Il collecte des échantillons de tritium sous forme de vapeur et produit des résultats en moins de 40 minutes. L'échantillon obtenu peut être mesuré jusqu'à une limite de détection de 0,01 Bq/m³ par mesure différée par scintillation liquide.



Caractéristiques du condensateur aéroporté au tritium H3R 7000 :

- mode de démarrage rapide
- mesure et calcul en temps réel de l'humidité absolue de l'air ambiant en g/m³
- calcul automatique du temps de piégeage en fonction de la quantité d'eau requise
- séchage automatique sous haute température du circuit de piégeage pour éviter une contamination croisée
- sélection du temps de séchage
- Sortie USB : récupération des données sur clé USB
- imprimante thermique intégrée : impression des données sur autocollant à placer sur le flacon d'échantillon

En savoir plus sur le condenseur aéroporté au tritium H3R 7000 sur le site Web du SDEC



Détection des radiations > Équipement de laboratoire

Single Mast Electrodeposition Equipment - EDP 7000 - SDEC

La mesure des radio-isotopes est utilisée en médecine nucléaire pour contrôler et suivre le niveau de contamination d'un patient ayant manipulé des radio-isotopes. Habituellement, lorsqu'on mesure un radio-isotope, la première chose à faire est de le piéger et de le faire déposer sur un support.



Le système Single Mast Electrodeposition Equipment - EDP 7000 est le principe le plus efficace pour piéger un radio-élément en solution liquide. Ce principe permet de déposer les radio-isotopes contenus dans une solution sur une plaque métallique. Pour mesurer la quantité de radioélément piégé, la plaque métallique est ensuite placée dans un appareil adapté (spectromètre ou autre).

équipement d'électrodéposition à mât unique - caractéristiques de l'EDP 7000 :

- matériaux synthétiques.
- contrôle de la température de la solution.
- trois tailles de récipients de solution.
- visser/dévisser rapidement.
- entretien facile par l'opérateur.
- interrupteur de polarité inversée.
- minuterie indépendante.

En savoir plus sur l'équipement d'électrodéposition à mât unique sur le site Web du SDEC



Tritium sampler 4 vials MARC 7000 - SDEC

L'équipement Tritium sampler 4 flacons (MARC 7000) est conçu pour échantillonner le tritium contenu dans un volume d'air (gaz H₃, eau tritiée HTO ou organiquement combiné). La vapeur d'eau tritiée est piégée dans les deux premiers biberons grâce au principe du bullage. Pour piéger le tritium qui s'associe aux matières organiques, une réaction d'oxydation est créée dans le four. Un catalyseur est utilisé pour abaisser le niveau de combustion. Cela provoque une réaction chimique du tritium pour former de la vapeur d'eau tritiée qui est piégée dans les biberons n°3 & 4. Au bout d'un certain temps, l'eau tritiée contenue dans les biberons est mesurée en laboratoire. La quantité de tritium mesurée est liée au volume d'air ayant traversé l'équipement.



Caractéristiques de l'échantillonneur de tritium 4 flacons :

- excellente efficacité de piégeage (près de 99%)
- système de refroidissement pour augmenter la longueur d'échantillonnage (option)
- bon prix
- évolution constante du produit
- facile à utiliser
- connectable à toutes les lignes d'échantillonnage

En savoir plus sur l'échantillonneur Tritium 4 flacons (MARC 7000) sur le site SDEC



Partner **Spectrum Techniques**

Spectrum Techniques Spectrum Techniques est un fournisseur leader de solutions de détection et de mesure des rayonnements, spécialisé dans les équipements de laboratoire et les sources radioactives. Son offre comprend une gamme d'instruments et de détecteurs conçus pour les applications éducatives, de recherche et industrielles.

Product offering

<p>Advanced Spectroscopy System</p> 	<p>SCINTILLATION WELL COUNTING SYSTEM</p> 	<p>Intermediate Nuclear Laboratory System</p> 
--	---	--

← [Back to partner](#)



Détection des radiations > Équipement de laboratoire

Advanced Spectroscopy System

The Advanced Spectroscopy System, your comprehensive solution for advanced nuclear experimentation and analysis.

Sophisticated Capabilities: Our cutting-edge systems are engineered to meet the demands of diverse applications, from academic research and industrial quality control to environmental monitoring and nuclear medicine. They empower users with the tools needed to delve deep into the intricacies of radiation spectroscopy.

Tailored Solutions: Offering a range of models and configurations, these systems are highly customizable to align perfectly with your specific requirements. Whether you need energy resolution, peak analysis, or nuclide identification, our systems are designed to adapt.

Superior Detector Technology: At the heart of our spectroscopy systems lies advanced detector technology, delivering unparalleled sensitivity and accuracy. From scintillation detectors to high-purity germanium detectors, our instruments are optimized for peak performance.

User-Friendly Interface: Navigating the complexities of radiation analysis has never been easier. Our intuitive software interfaces simplify data acquisition and analysis, allowing users of all skill levels to achieve precise results.

Reliability and Support: Backed by Spectrum Techniques' decades of expertise, these systems are built for longevity and backed by top-notch technical support. We're committed to ensuring your success in radiation spectroscopy.

Elevate your research, enhance your quality control, and make breakthroughs in nuclear science with Spectrum Techniques' Advanced Spectroscopy Systems. Explore the limitless possibilities today.

The System is built around the UCS-30 and a 1.5" x 1.5" NaI(Tl) detector; it is designed for conducting a wide selection of spectroscopy experiments.



← [Back to partner](#)



Détection des radiations > Équipement de laboratoire

SCINTILLATION WELL COUNTING SYSTEM

The Wipe System - a state-of-the-art solution for the precise and efficient collection of radioactive contamination.

Effortless Contamination Detection: Our Wipe System is designed to simplify and enhance the process of identifying and quantifying radioactive contamination. With meticulous attention to detail, it enables you to maintain the highest standards of safety and environmental protection.

Comprehensive Solution: This system comprises user-friendly software and specialized wiping materials, ensuring a comprehensive approach to contamination monitoring. It empowers users across various industries, including nuclear facilities, healthcare, and environmental laboratories.

Accurate and Reliable: Spectrum Techniques' Wipe System is built on cutting-edge technology, offering unparalleled accuracy and reliability. It allows you to confidently detect and measure radioactive contaminants, safeguarding your personnel and the environment.

Customizable for Your Needs: We understand that different applications have unique requirements. Our Wipe System is customizable to meet your specific needs, offering flexibility in terms of sample size, detection thresholds, and reporting options.

Exceptional Support: As with all Spectrum Techniques products, our Wipe System is backed by a team of experts dedicated to ensuring your success. Our technical support and training resources are available to assist you every step of the way.

Upgrade your contamination monitoring process with Spectrum Techniques' Wipe System. Stay compliant, protect your environment, and mitigate risks with precision and confidence.



← [Back to partner](#)



Détection des radiations > Équipement de laboratoire

Intermediate Nuclear Laboratory System

The Intermediate Plus Nuclear Laboratory System, your comprehensive solution for advanced nuclear experimentation and analysis.

Unparalleled Versatility: This cutting-edge system is meticulously crafted to cater to the evolving needs of educational institutions, research facilities, and nuclear science enthusiasts. With its versatile design, it's perfectly suited for a wide range of applications, including teaching, advanced research, and radiation safety studies.

Precise Data Acquisition: Equipped with state-of-the-art technology, the Intermediate Plus Nuclear Laboratory System ensures precise data acquisition. It empowers users to conduct experiments with confidence, facilitating a deeper understanding of nuclear phenomena.

Seamless Integration: Our system seamlessly integrates with an array of detectors, amplifiers, and software, providing a comprehensive toolkit to explore and analyze radiation sources effectively. It's engineered for ease of use, making it accessible to both novice and experienced users.

Enhanced Features: The Intermediate Plus Nuclear Laboratory System boasts an array of enhanced features, including user-friendly software for data analysis, adaptable detector options, and flexible connectivity options, allowing you to tailor your experiments to your specific requirements.

Reliability and Support: Backed by Spectrum Techniques' commitment to quality and customer satisfaction, this system is built to last and comes with exceptional technical support to ensure your research and educational objectives are met with ease.

Unlock the potential of nuclear science with confidence, precision, and versatility using the Spectrum Techniques Intermediate Plus Nuclear Laboratory System. Elevate your experiments and research to new heights with this comprehensive solution.





Partner **GEORADIS s.r.o.**



Georadis s.r.o. est un fabricant spécialisé d'instruments avancés de détection et de surveillance des radiations, proposant une gamme complète de solutions pour les applications de terrain et de laboratoire. Sa gamme de produits comprend des moniteurs portables, des identificateurs d'isotopes portables, des appareils de surveillance environnementale et des équipements de laboratoire, tous conçus pour répondre aux exigences rigoureuses des professionnels des secteurs de la surveillance environnementale, de la sécurité industrielle et de la sécurité publique.

Product offering

**RT-50 Laboratory
Gamma-Ray
Spectrometer -
Georadis**



← Back to partner



Détection des radiations > Équipement de laboratoire

RT-50 Laboratory Gamma-Ray Spectrometer - Georadis

The RT-50 (Georadis) is a state of the art gamma spectrum analyzer to monitor and detect the presence of radiation in metals, metals by-products, geological samples, construction materials, environmental commodities, food and many other materials. Floor standing and easy to operate, the RT-50 spectrum analyzer is an indispensable part of any analytical laboratory, it rapidly detects and accurately measures extremely low levels of radioactive contamination.



RT-50 Laboratory Gamma-Ray Spectrometer features:

- full sample analysis in less than 5 min
- sensitivity; 0.02 Bq/g
- energy range: 20 keV - 3,0 MeV
- 1024 channel pulse amplitude analyzer
- short calibration times
- NaI(Tl) volume 0.35 l, 76 x 76 mm (3"x3") detector

Read more about the RT-50 Laboratory Gamma-Ray Spectrometer on the [Georadis website](#)



Partner **Kromek**



Kromek Group plc est un leader mondial des technologies avancées de détection des radiations, spécialisé dans les solutions compactes et haute résolution pour les applications de sécurité, de défense, de nucléaire et de recherche. S'appuyant sur sa technologie brevetée de semi-conducteurs au tellure de cadmium-zinc (CZT), Kromek propose une gamme polyvalente comprenant des moniteurs portables, des identificateurs d'isotopes portables, des gamma-caméras CZT et des spectromètres de laboratoire.

Product offering



[← Back to partner](#)



Détection des radiations > Caméras CZT et Gamma

Quant GR1

The Quant GR1 is a complete mobile or benchtop solution for quantifying doses of Gamma radiation released by radionuclides. Its high resolution of <math><2\%</math> and count spectrum range of 4096 channels enables any isotope to be identified and its associated dose quantified, even from complex mixtures.

The ability to quantify radiation doses in real time eliminates the need for further analysis in the lab, as data can both be collected and processed on site, saving time and costs.





Partner **Ultra Electronics**



Ultra Electronics acquired Lab Impex Systems on July 17th, 2014. This is a known specialized manufacturer in radiation detection solutions and services for use in the global nuclear industry. Founded in 1976, Laboratory Impex Systems Ltd (LIS) is a leader in designing, developing and manufacturing health physics and radiation protection measurement instrumentation focusing on stack monitoring.

Product offering

**CMS Iodine Monitor -
Lab Impex Systems**





CMS Iodine Monitor - Lab Impex Systems

Le CMS Iodine Monitor (Lab Impex Systems) est un système avancé de surveillance de la concentration atmosphérique d'iode radioactif sur le lieu de travail et dans d'autres zones d'intérêt (cheminées, cellules et boîtes à gants).

Le moniteur est disponible dans des configurations isotopiques spécifiques, notamment I-124, I-125, I-129 et I-131, et offre une mesure en temps réel des formes moléculaires et organiques de l'iode.

De plus, le système est disponible dans une configuration montée sur châssis, boîtier ou chariot.

L'élément capteur du moniteur d'iode est un détecteur breveté appelé CGADC (Continuous Gas Analysis and Detection Chamber). Le CGADC associe un détecteur sensible à scintillation à une chambre de mesure en acier inoxydable abritant une cartouche de filtration de l'iode radioactif. Le CGADC est présenté sous forme de dispositif intégré, avec blindage, pompe, capteur de débit et processeur CMS, et est disponible dans une configuration fixe ou transportable.

Caractéristiques du moniteur d'iode CMS :

- le mécanisme de filtration capture toutes les formes d'iode radioactif
- atteint de faibles MDL grâce à une conception de détecteur unique avec bouclier Brehmstrahlung
- compensation automatique de l'arrière-plan
la stabilisation du spectre de température réduit les
- mesures inexactes dues à la dérive du spectre
L'algorithme d'analyse CMS fournit une mesure
- faiblement stable en arrière-plan, mais garantit une réponse rapide aux niveaux de concentration croissants.

En savoir plus sur le moniteur d'iode CMS sur le site Web de Lab Impex Systems.



SIMULATEURS DE FORMATION





Partner **Argon Electronics**


ARGON™ Argon Electronics propose des solutions de formation sur simulateur haute fidélité pour les interventions en cas d'incident chimique, biologique, radiologique, nucléaire et explosif (NRBC) et de matières dangereuses (HazMat). Leur technologie permet des formations réalistes et pratiques, sur le terrain comme en salle de classe, sans les risques liés aux agents réels.

Product offering

RADSIM 44-9-SIM
Radiation Safety
Training Probe
Simulator



PlumeSIM®



PlumeSIM-SMART



RS340 Back Pack



UDR-13 & UDR-14 SIM



Radsim DS3 Mini 900



Nuvia CoMo 170
Contamination
Training Simulator



AN/PDR 77 ALPHA & BETA SIM PROBES



GMP-11 Radiation Safety Training Simulator Probe



M4A1 JCAD Chemical Hazard Detection Simulator



6150AD-K Contamination Simulator



RADSIM GS4



MultiGAS SIM



RDS Beta Photon Probe Simulator



Ludlum 133-6 and 44-2 Radiation Simulation Probes



RDS-100 / PDR-77 / CDV 718 SIM Probes



AN/VDR 2 DT616-SIM Radiation Safety Training Simulator



ADM300A-SIM Radiation Training Simulator



GID-3 Chemical Warfare Detection Simulator



MCAD-SIM Chemical Warfare Detection Simulator



CAMSIM Chemical Hazard Detection Simulator



AccuRad PRD Simulator



Nuvia DoImo Radiation Hazard Detection Simulator



HRM Radiation Hazard Simulator



SP4E Chemical Hazard Detection Simulator



AP4C-SIM Chemical Detector Simulator



D-tect SYSTEMS RDS Radiation Training Simulator



SVG-2 Radiation Hazard Detection Simulator



RadEye GF-10 SIM



RADSIM-SS3



LCD3.3-SIM Chemical Hazard Detection Simulator



FH 40 GSIM Survey Meter Simulator



Raid-100M Training Simulator



Dräger X-am Series Simulator



Tracerco PED+ Simulator





RADSIM 44-9-SIM Radiation Safety Training Probe Simulator

The RADSIM 44-9-SIM is a cutting-edge simulation probe designed for use with Ludlum's 44-9 GM pancake-type detector.

This versatile training system offers a realistic alternative to traditional methods, eliminating the need for ionising radiation sources while delivering high-fidelity functionality for instructors and students alike.

Key Features

- **Accurate Simulation:** Replicates the functionality of Ludlum's 44-9 GM pancake-type detector, responding to safe magnetic sources simulating short-range Alpha and Beta radiation.
- **Adaptable Training Design:** Compatible with an extensive range of Ludlum survey meters, rate meters, and scalars. Includes an Instructor Remote Controller (IRC) for managing partial or full decontamination and probe functionality scenarios.
- **Integrated Training Capabilities:** Offers virtual Alpha, Beta, and Gamma simulation when used with Argon's Plume SIM system. Enables simultaneous, multi-detector, and multi-isotope training scenarios.






PlumeSIM®

Plume SIM is the ultimate tool for preparing teams to respond to complex chemical, biological, radiological, and nuclear (CBRNe) threats. This innovative wide area training system creates realistic hazard plumes and hotspots, allowing instructors to manage a variety of threat scenarios in real time.

Ideal for counterterrorism and nuclear emergency exercises, Plume SIM adapts seamlessly from classroom tabletop mode to full scale field operations, enhancing team preparedness through powerful, scenario-based training.

Key Features

- Versatile Training Modes: Use Plume SIM in tabletop mode for classroom exercises or field mode for outdoor training with GPS enabled units.
- Customizable Scenarios: Create user defined scenarios with single or multiple threat sources, environmental factors, and release characteristics like duration, direction, and persistence.
- RealTime Monitoring & Mapping: Supports GIS mapping and real time adjustments to simulate wind changes and other environmental variables, making every session unique.
- Multiplatform Compatibility: Integrates with a range of Argon simulators, including the M4 JCADSIM, CAMSIM, AP2CSIM, and others, allowing simultaneous, multi threat exercises.



← Back to partner



Détection des radiations > Simulateurs de formation

PlumeSIM-SMART

Our App-based training system provides you with the capability to deliver practical, highly engaging Command Officer and survey operative tabletop and live field CBRNe / HazMat and offsite release exercises incorporating gaseous, radioactive, Hazardous Material (HazMat) and Chemical Warfare Agent (CWA) threats and releases.

PlumeSIM-SMART Simulates:

- Single or multiple threats / releases including Radioactivity, Radioactive compounds, TICs / TIMs and CWA
- Real-time chemical or radiation plume variation to changes in wind direction and velocity and evaporation, deposition, persistency, radioactive fallout and decay
- Hot spots, static emissions, hidden / activated radiological dispersion devices, puffs and plumes and placement of water barriers to restrict plume from sensitive areas
- Sources comprising Individual or multiple radionuclides and foot, fixed or vehicle based survey / monitoring / reconnaissance



← [Back to partner](#)



Détection des radiations > Simulateurs de formation

RS340 Back Pack

Based upon the Lawrence Livermore National Laboratory RaFTS Gamma Spectrometry simulation technology and developed in collaboration with Radiation Solutions Inc., the RaFTS-RS340 Gamma simulation module enables you to temporarily convert your operational RSI RS340 back pack into a powerful training system.

Substituting the RS340 detector, the RaFTS module responds to our GS Series simulation Gamma Sources which can be programmed to represent a variety of Industrial, Nuclear, Medical and even Specialist Nuclear Material (SNM) radionuclides and can be discretely hidden within buildings, open field, vehicles and even body worn rucksacks for specialist search and threat identification exercises.

For larger area exercises multiple GS series sources can be deployed or PlumeSIM provides the perfect solution.

Multi-Device Compatibility

The RS340 back pack responds in exactly the same way as it would for real radionuclides with count rate a spectra faithfully reproduced in real time with all standard user alarms and visual alerts including spectra displays presented on you Bluetooth linked RS340 mobile App.

Compatibility with all Argon Electronics survey, Personal Radiation Detector (PRD) and personal dosimeter simulators provides you with a powerful multi detector search team exercise capability so that you can ensure your teams maintain optimal operational readiness.





UDR-13 & UDR-14 SIM

Thanks to a combination of Argon's wealth of simulation experience and our relationship with Mirion, the look, feel and response of the UDR-13 and UDR-14 radiation training simulators is extremely close to that of actual detectors.

The simulators respond to RADSIM electromagnetic sources that safely simulate ionizing radiation eliminating regulatory, environmental, and health and safety concerns for you and your students.

Key Features

- Simulated Science: Inverse square law ($1/r^2$) response within real detector tolerance and accurate representation of different shielding effects.
- Unmatched Realism: Has the same human interface and dose rate alarm settings as the real detector.
- Comprehensive Training: Optional units of measurement available include Gy/hr, Sv/hr, Rem, and CPM.
- Cost Effective: Uses the same commercial batteries as real detector and doesn't require regular calibration or maintenance.





Radsim DS3 Mini 900

The Radsim DS3 Mini 900 Simulator revolutionizes radiation safety training by replicating the detection capabilities of the Thermo Mini Monitor 900 EP15. Designed with photon based fluorescent simulation technology, this powerful training tool allows users to detect Alpha and Beta particles without any environmental or safety risks.

From educational institutions and hospitals to nuclear facilities and emergency response units, the Radsim DS3 provides a safe, hands on learning experience, equipping trainees to respond effectively in contamination scenarios.

Key Features

- **Realistic Simulation Technology:** Detects safe, coloured powder, liquid, and cream simulants on various surfaces—including protective gloves, food, and even simulated contaminated water.
- **Customizable Detection Modes:** Easily configure the Radsim DS3 for Alpha, Beta, or combined Alpha Beta detection, simulating varied particle detection for an authentic hands on experience.
- **Scenario Adaptability:** Adjustable settings for background noise, mute, and alarm thresholds allow instructors to align the simulation environment with specific training objectives, enhancing immersion.
- **Environmentally Safe Simulants:** Made from common dyes, food additives, and cosmetic grade bases, all simulants are nontoxic, with full ingredient transparency for uncompromised safety.





Nuvia CoMo 170 Contamination Training Simulator

The Nuvia CoMo 170 simulator replicates the operational features of the operational CoMo 170 contamination detector, enabling safe and effective radiation training. By eliminating the need for ionising radiation sources, this system ensures regulatory, environmental, and health safety compliance while offering unparalleled realism.

Key Features

- **Advanced Simulation Technology:** Accurate replication of the CoMo 170 detector with fully functional alarm, language, and configuration options.
- **Dynamic Training Scenarios:** Supports training for survey, location, and decontamination tasks.
- **Integrated Training Solutions:** Compatible with Argon's Plume SIM system for wide-area emergency response exercises. Allows simultaneous multi-detector and multi-hazard training with Argon simulators.





AN/PDR 77 ALPHA & BETA SIM PROBES

The RADSIM A-SIM-P and B-SIM-P radiation training simulator probes are for use with the Mirion / Canberra AN/PDR-77 and RDS100 survey meters. These probes provide you with a training system that enables your students to experience the operational features of the real detector without the need for real radiation sources or radioactive materials.



Key Features

- Operational Realism: Compatible with Mirion/Canberra meters including AN/VDR-2, PDR-77, and RDS100 with identical functionality and readings as the real probes.
- Dynamic Training Scenarios: Supports training for search, reconnaissance, survey, location, and decontamination procedures.
- Instructional Ease: Instructor remote control for simulating partial/full decontamination and probe failure at the push of a button.
- Advanced Simulation Capabilities: Simulates radiation hazards with realistic response and shielding effects.



GMP-11 Radiation Safety Training Simulator Probe

The GMP-11-SIM is an advanced Beta radiation contamination training simulator designed for the Mirion GMP-11 probe. This simulator seamlessly connects to your Mirion RDS-200 or Argon RDS-200-SIM, providing an authentic training experience without the need for ionising radiation sources or radioactive materials.

Key Features

- **Accurate Simulation:** Responds to safe, inexpensive fluorescent powder and liquid materials that simulate beta radiation. Automatically detected by the RDS-200-SIM for seamless operation.
- **Training Versatility:** Compatible with both real RDS-200 and RDS-200-SIM survey meters.
- **User-Friendly Design:** Logarithmic analogue bar graph and numeric dose rate display.



← [Back to partner](#)



Détection des radiations > Simulateurs de formation

M4A1 JCAD Chemical Hazard Detection Simulator

The M4A1 JCAD-SIM is a high-fidelity simulator for the Smiths Detection M4A1 JCAD, enabling safe, effective, and environmentally friendly training for chemical warfare and hazardous material scenarios.

Designed to preserve operational readiness and reduce costs, this simulator ensures your team is prepared for real-world challenges while extending the lifespan of your actual detection equipment.

Key Features

- True-to-Life Interface: Perfectly mimics the actual detector, supporting a seamless transition from training to real-world response.
- Comprehensive Threat Simulation: Detects and simulates a wide array of agents, including nerve, blister, and blood agents, toxic industrial chemicals (TICs) and false positives.
- Environmental Adaptability: Simulate varied conditions like wind direction, temperature shifts, and night vision
- Enhanced Control for Instructors: With a dedicated remote, instructors can set decontamination effectiveness, persistency, and contamination levels



← [Back to partner](#)



Détection des radiations > Simulateurs de formation

6150AD-K Contamination Simulator

Radiation Hazard Detection Simulator

- Large area contamination simulation 6150AD-K probe for Automess 6150AD
- Responds to safe simulation radiation sources
- Simulation of partial and full decontamination
- Simulation of detector cover plate
- Simulation of contamination of sensor face
- Perfect for radiation, HazMat and CBRN training, exercises and scenarios.



← Back to partner



Détection des radiations > Simulateurs de formation

RADSIM GS4

The RADSIM series of highly realistic simulation gamma radiological sources overcome the regulatory, financial and administrative burden of live radiological source based training scenarios in an entirely safe, environmentally friendly and cost effective manner.

What truly sets the RADSIM series apart is the realism of the simulation – hide the simulation detector training label and the “Pucker Factor” is as real as it gets!

Key Features

- Dose rate and Dose readings and alarms indicating potentially hazardous radiation levels.
- Inverse square law ($1/r^2$) response and shielding effects of different materials.
- Consistent readings across instruments each time the student revisits the same location within the exercise.





MultiGAS SIM

MultiGAS-SIM supports from one to a total of six different simulation sensor types, including O₂, CL₂, SO₂ and LEL. Instructors can configure the MultiGAS-SIM to incorporate specific simulation sensors as required to represent fielded single or multiple sensor MultiGAS detectors. You can even configure the visual layout of the sensors on the display screen to accurately replicate the sensor layout configuration of your operational detectors.

The **MultiGAS-SIM** system delivers a highly realistic and versatile training solution through our **Long Range Vapour Source (LRVS)** technology. Designed for both open environments and confined spaces, the system can be programmed to replicate a wide range of hazardous gases and oxygen-depleted scenarios with unmatched precision.



Key Features

- **Realistic Training:** Mimics the operation of real gas detectors, providing trainees with practical, hands-on experience.
- **Customizable Scenarios:** Enables tailored training for a wide range of hazardous environments and operational conditions.
- **Enhanced Learning:** Real-time feedback through instructor monitoring ensures trainees learn from their mistakes in a controlled, safe environment.
- **Advanced Simulation Features:** Features realistic O₂ readings and LRVS simulation gas emitters detected up to 25 meters (80 feet).





Détection des radiations > Simulateurs de formation

RDS Beta Photon Probe Simulator

The D-tect SYSTEMS Beta Photon radiation simulator probe has been designed to work with Argon's simulation RDS base unit.

The simulation Beta Photon Probe can be connected directly to the Simulation RDS base unit by flexible cable, or can be mounted on the Telepole enabling you to practice remotely monitoring high level radiation sources from a safe distance.

You can "hot connect" and disconnect the simulation Beta Photon Probe just like the real instrument - no need to turn the simulation RDS base unit off and most impressively the base unit display screen splits just like real providing real time simulated reading from both base unit and remote Beta Photon Probe enabling your trainees to experience the higher reading obtained due to the Beta Photon Probe while monitoring the base unit reading which represent the hazard at their personal location.

Inverse square law response is extremely realistic; even the effect of shielding between the probe and base unit to determine source position is realistically simulated enabling you to ensure survey teams understand what to do when that emergency comes.

Key features:

- Inverse square law ($1/r^2$) response within real detector tolerance.
- Simulation of user body shielding for source location.
- Realistic representation of different shielding effects.
- Responds to Simulation check source.
- No regular calibration.
- No preventative maintenance.
- PlumeSIM compatible.
- Compatible with other Argon radiological simulators.





Ludlum 133-6 and 44-2 Radiation Simulation Probes

The Ludlum 133-6-SIM and 44-2-SIM are advanced radiation simulator probes designed to replicate the operational features of the Ludlum 133-6 Gamma detector and the 44-2 scintillation detector.

These simulators provide unmatched realism and usability, enabling trainees to master radiation search, survey, and localisation skills without the need for real radioactive sources. Compatible with Ludlum meters, these probes offer a versatile and cost-effective solution for comprehensive radiation safety training.



Key Features

- **Expertly Designed:** Identical user interface and operational characteristics to the real 133-6 and 44-2 detectors.
- **Incredible Realism:** Response speeds closely mimic real detectors, supporting realistic source search and localisation exercises.
- **Effortless Integration and Versatility:** Compatible with any Ludlum meter supporting 133-6 or 44-2 probes. o Fully compatible with PlumeSIM and other Argon simulation systems.
- **Simulated Science:** Inverse square law ($1/r^2$) response within real detector tolerance.

← [Back to partner](#)



Détection des radiations > Simulateurs de formation

RDS-100 / PDR-77 / CDV 718 SIM Probes

The RDS-100-SIM 3-Probe simulator set offers a cutting-edge training system that replicates the operational features of an operational Canberra RDS-100, AN/PDR-77, and CDV 718 probes.



Designed to simulate Alpha, Beta, and Gamma radiation without the need for real radioactive sources, this system provides a safe, practical, and environmentally friendly solution for mastering radiation safety skills.

Key Features

- BG-SIM-P: Simulates the Beta/Gamma probe, compatible with the RDS-100, AN/PDR-77, and M-243/VDR-2 meters.
- A-SIM-P: Simulates the Alpha probe for contamination and decontamination training.
- B-SIM-P: Simulates the Beta probe for Pancake detector functions



AN/VDR 2 DT616-SIM Radiation Safety Training Simulator

The DT616-SIM is a high-fidelity Beta/Gamma radiation training simulator designed for use with Mirion/Canberra AN/VDR-2, PDR-77, RDS100, and CDV 718 survey meters.

This innovative simulator allows trainees to experience the full operational functionality of the DT616 probe without the need for live radiation sources, ensuring safe, compliant, and practical training for critical radiological scenarios.



Key Features

- **Advanced Simulation Capabilities:** Simulates both Beta and Gamma radiation hazards with realistic inverse square law ($1/r^2$) response and shielding effects.
- **Operational Realism:** Compatible with Mirion/Canberra meters including AN/VDR-2, PDR-77, and RDS100 with identical functionality and readings as the real DT616 probe.
- **Dynamic Training Scenarios:** Supports training for search, reconnaissance, survey, location, and decontamination procedures with encoded signals simulate specific Gamma emitting radionuclides.
- **Instructional Ease:** Instructor remote control for simulating partial/full decontamination and probe failure at the push of a button.

← Back to partner



Détection des radiations > Simulateurs de formation

ADM300A-SIM Radiation Training Simulator

The ADM300ASIM is a cutting-edge radiation training simulator, designed in collaboration with Mirion to replicate the functionality of the ADM300A radiation survey meter.

Providing seamless compatibility with your operational equipment, this simulator ensures safe, realistic, and comprehensive training without the need for ionising radiation sources.

Key Features

- Unparalleled Realism: Accurately simulates dose, dose rate, accumulated dose, and alarm thresholds using safe Beta and Gamma simulation sources.
- Simulated Science: Excellent simulation of inverse square law and body shielding effects.
- User-Friendly Design: Identical menu structure, software processing, and interface to the real ADM300A V1b meter, with visual and audible alarms fully configurable to match your operational equipment.
- Advanced Compatibility: Fully integrated with Argon's PlumeSIM and supports multi-detector and multi-threat scenarios with other Argon simulators.





GID-3 Chemical Warfare Detection Simulator

Présentation :

Le GID-3-SIM est un système de simulation de pointe conçu pour reproduire les caractéristiques et les fonctionnalités des systèmes GID-3 et ACADA de Smiths Detection. Conçu pour les intervenants militaires et civils dans le domaine CBRNe, cet outil avancé offre une expérience de formation sûre, complète et réaliste.

En éliminant le besoin de simulants et de consommables nocifs, le GID-3-SIM permet aux étudiants d'acquérir une expérience pratique essentielle en matière de détection et d'intervention en cas de risque chimique.



Caractéristiques

- Simulation réaliste des risques : simule avec précision les alarmes CW et les défaillances des détecteurs.
- Formation complète : simule le processus de configuration complet, y compris les tests d'alarme et le positionnement des capuchons anti-pluie. Propose une formation simulée au testeur de confiance afin de reproduire les procédures réelles.
- Télécommande avancée : la télécommande de l'instructeur prend en charge jusqu'à 8 simulateurs à plus de 750 mètres de distance.
- Kit complet : système fourni avec un testeur de confiance de simulation, un capuchon d'entrée et de sortie, des capuchons anti-pluie de simulation, un pack de batteries de formation avec des piles « D » commerciales et une mallette de transport.



MCAD-SIM Chemical Warfare Detection Simulator

Présentation :

Le MCAD-SIM est un système de simulation de pointe conçu pour reproduire les fonctionnalités du détecteur d'agents chimiques portable (MCAD) de Smiths Detection. Cet outil avancé offre une expérience de formation inégalée, permettant aux utilisateurs de maîtriser l'utilisation des systèmes MCAD de manière sûre, écologique et rentable.

Grâce à des simulations réalistes et à de puissantes capacités de contrôle à distance, le MCAD-SIM prépare les intervenants aux exigences de la détection chimique dans le monde réel.

Caractéristiques:

- Simulation réaliste des dangers : simule tous les agents chimiques détectés, y compris le mode myosis.
- Contrôle complet : la télécommande de l'instructeur prend en charge jusqu'à 8 simulateurs à plus de 750 mètres de distance.
- Formation avancée : simule le processus de configuration complet, y compris les tests d'alarme et le positionnement des capuchons anti-pluie. Propose une formation simulée au testeur de confiance pour reproduire les procédures réelles.
- Conception efficace et pratique : alimenté par des piles commerciales standard, y compris des options rechargeables, et livré avec un testeur de confiance de simulation, des capuchons et des packs de formation.





CAMSIM Chemical Hazard Detection Simulator

Présentation :

Le simulateur CAMSIM CAM offre une solution révolutionnaire pour la formation à la détection des risques chimiques. Conçu pour le détecteur d'agents chimiques (CAM) de Smiths Detection, CAMSIM utilise des sources électroniques pour simuler des vapeurs chimiques, des substances industrielles toxiques et des faux positifs, offrant ainsi un environnement de formation sûr et réaliste sans simulants nocifs.

Ce système portable et adaptable peut être utilisé à l'intérieur, y compris dans les bâtiments publics, et s'installe en quelques minutes, ce qui en fait un outil polyvalent pour la formation à la contamination, à la décontamination et à la persistance dans des scénarios réels.

Caractéristiques:

- Simulation de menaces diverses : émulez les agents neurotoxiques, vésicants, hématoxiques et suffocants, ainsi que les faux positifs, les effets de la contamination et les impacts du vent et de la température.
- Contrôle par l'instructeur et réinitialisation instantanée du scénario : les formateurs peuvent ajuster les facteurs environnementaux, les niveaux de contamination et la persistance de l'exercice, ce qui permet de réinitialiser rapidement le scénario pour une formation continue.
- Compatibilité multi-appareils : s'intègre au système Plume SIM d'Argon et est compatible avec d'autres simulateurs Argon, prenant en charge des exercices multi-détecteurs et multi-menaces dans un seul scénario.
- Rapport d'erreurs intégré : suit et enregistre les erreurs des utilisateurs, permettant aux instructeurs d'afficher des rapports d'erreurs détaillés après l'exercice.





AccuRad PRD Simulator

Présentation :

Le simulateur de formation à la détection des rayonnements AccuRad™ PRD est une solution de formation de pointe conçue pour offrir la formation la plus réaliste possible en matière de détection des rayonnements. Développé en collaboration avec Mirion Technologies, le simulateur AccuRad™ PRD reproduit l'apparence, le toucher et la réactivité du véritable AccuRad™ PRD de Mirion.



Ce simulateur avancé offre une formation pratique et sûre à la détection des rayonnements sans les risques liés aux sources radioactives réelles. Que la formation se déroule en intérieur ou en extérieur, le simulateur AccuRad™ PRD garantit à vos étudiants l'acquisition de l'expérience pratique dont ils ont besoin dans des scénarios de détection des rayonnements à fort impact.

Caractéristiques:

- Interface utilisateur authentique : l'interface humaine du simulateur, qui comprend les écrans avant et supérieur, la sirène, le vibreur et le panneau de commutation, reproduit le Mirion AccuRad PRD pour une formation sans faille.
- Sensibilité réaliste : le simulateur AccuRad™ PRD peut détecter les sources gamma de simulation Radsim GS4 jusqu'à une distance de 60 mètres, offrant une directionnalité précise et des capacités de recherche de sources.
- Simulation de la protection corporelle : le simulateur reproduit avec précision les effets de la protection corporelle, permettant aux utilisateurs de s'entraîner à interpréter les lectures et les alarmes dans des scénarios réels.
- Unités de mesure sélectionnables : les utilisateurs peuvent choisir entre des unités telles que Sv/h, Rem et CPS, tout comme ils le peuvent sur le Mirion AccuRad™ PRD.



Nuvia DolMo Radiation Hazard Detection Simulator

Présentation :

Le Nuvia DolMo-SIM est un simulateur de pointe conçu pour reproduire avec une précision remarquable le dosimètre Nuvia DolMo Gamma. Offrant une solution de formation sûre et respectueuse de l'environnement, ce simulateur élimine le besoin de sources de rayonnements ionisants, ce qui le rend idéal pour les exercices de détection des rayonnements dans le monde réel, quel que soit l'environnement.

Caractéristiques:

- Précision de simulation inégalée : affichage analogique linéaire et logarithmique sous forme de graphique à barres, lectures numériques du débit de dose avec des vitesses de réponse réalistes et effets de blindage simulés.
- Interface utilisateur authentique : reproduit intégralement toutes les fonctionnalités opérationnelles du détecteur réel avec un affichage, un panneau de commutation, un avertisseur sonore et un vibreur identiques.
- Capacités de formation dynamiques : répond aux sources gamma Radsim GS4 codées jusqu'à 60 mètres (200 pieds) en ligne droite et permet de démontrer la loi de l'inverse du carré, la cartographie du débit d'isodose et la délimitation de sécurité.

Compatible avec PlumeSIM : à utiliser avec PlumeSIM pour les exercices tactiques sur le terrain et les exercices d'intervention d'urgence à grande échelle.





Détection des radiations > Simulateurs de formation

HRM Radiation Hazard Simulator

Présentation :

Le HRM-SIM est un simulateur avancé de détection des rayonnements conçu pour reproduire le détecteur HRM de Sensor Technology Engineering.

Développé pour l'interception et la localisation de matières nucléaires, ce simulateur offre un réalisme inégalé, garantissant que vos équipes d'inspection sont prêtes à réagir efficacement dans des scénarios critiques. Alimenté par des piles standard disponibles dans le commerce, le HRM-SIM offre jusqu'à 160 heures de formation ininterrompue.



Caractéristiques:

- Précision de simulation exceptionnelle : détecte les sources gamma, neutroniques et gamma + neutroniques avec une sensibilité précise. Réponse réaliste à la loi de l'inverse du carré ($1/r^2$) dans les limites de tolérance du détecteur.
- Blindage précis : simulation du blindage corporel de l'utilisateur pour la localisation de la source et représentation réaliste des différents effets de blindage.
- Interface utilisateur réaliste : avec des composants identiques à ceux du détecteur HRM réel, il reproduit parfaitement le comportement opérationnel du détecteur réel.
- Capacités de formation dynamiques : entièrement compatible avec PlumeSIM pour les exercices CBRN sur le terrain et sur table.



SP4E Chemical Hazard Detection Simulator

Présentation :

Le simulateur de détection des risques chimiques S4PE est un outil de formation de pointe qui reproduit les fonctionnalités réelles de l'échantillonneur de surface et du testeur de fiabilité Proengin S4PE.

Conçu pour s'intégrer parfaitement à l'AP4C-SIM d'Argon, ce simulateur offre une expérience de formation inégalée en émulant les vapeurs chimiques, les substances industrielles toxiques et les faux positifs. Que vous vous entraîniez dans des environnements contrôlés ou dans des bâtiments publics, le S4PE-SIM garantit une préparation sûre, pratique et efficace aux scénarios de risques chimiques.



Caractéristiques:

- Fonctions d'échantillonnage réalistes : test de fiabilité et échantillonnage de surface. Collecte d'échantillons de surface avec cycles de préchauffage. Simule des scénarios de contamination, de décontamination et de persistance.
- Compatibilité : fonctionne avec le tuyau d'échantillonnage de simulation AP4C-SIM et est compatible avec PlumeSIM pour une formation tactique à grande échelle.



AP4C-SIM Chemical Detector Simulator

The AP4C-SIM is a state-of-the-art simulation training system designed collaboratively between Argon and Proengin to replicate the operational capabilities of Proengin's AP4C chemical hazard detector. Provide your security force, first responder, and industrial safety teams with a realistic and comprehensive training experience—without the risks associated with live chemical agents.

The AP4C-SIM allows your team to practice detecting chemical vapours, toxic industrial substances (TICs), and even false positives in various environments, all while using safe, electronic simulation sources.



Key Features

- **Realistic Simulation:** Responds to electronic sources simulating CWAs, TICs, and explosive atmospheres
- **Safe and Environmentally Friendly:** Eliminates the need for harmful simulants, allowing realistic training without environmental impact or safety compromise..
- **Instructor Control:** A remote control provides instructors with full control over scenario management in real-time, allowing trainers to adjust contamination levels, wind direction, and temperature effects.
- **Simulation Tools:** The system includes simulation sources, hydrogen cells, error reporting cards, survey nozzles, and a carry case for easy transport. The simulator is ready to go from the box with minimum set up required.



D-tect SYSTEMS RDS Radiation Training Simulator

Présentation :

Dans un monde où les menaces radiologiques constituent un danger invisible mais grave, il est essentiel de former les premiers intervenants à gérer les incidents de manière sûre et efficace. Le simulateur de formation aux radiations RDS-SIM offre l'expérience de formation la plus fidèle qui soit.

Il reproduit fidèlement le RDS AN/PDR-83 approuvé par le ministère américain de la Défense, permettant aux équipes de s'entraîner sans utiliser de sources ionisantes nocives. Les stagiaires découvrent toutes les fonctionnalités du RDS, ce qui les prépare à faire face à de réelles menaces radiologiques avec compétence et confiance.

Caractéristiques:

- Fonctionnalités fidèles à l'appareil : reproduction exacte de l'interface RDS réelle, y compris les alarmes visuelles et sonores, les unités de mesure (Rem, Sv/h) et la navigation dans les menus.
- Simulation gamma et bêta : réagit aux sources gamma et bêta sûres, permettant une formation authentique aux risques radiologiques sans risques environnementaux.
- Adaptabilité à l'environnement : démontre les effets de blindage à l'aide de matériaux tels que le bois, le verre ou le béton, donnant aux équipes des connaissances pratiques sur les principes de radioprotection.
- Contrôle par l'instructeur : contrôle simple et flexible des niveaux de contamination et de décontamination, avec des réglages de décontamination partielle ou totale par simple pression sur un bouton.





SVG-2 Radiation Hazard Detection Simulator

The SVG-2 SIM is an advanced simulator designed to replicate the Thermo Fischer Scientific SVG-2 Radiac Meter with exceptional accuracy.

Offering a safe, practical, and cost-effective training solution, this simulator eliminates the need for ionising radiation sources, ensuring students can safely learn essential survey and reconnaissance skills in any environment.

No preventative maintenance, calibration or consumables (except batteries) are required ensuring whole life cost of ownership is minimal, expensive damage to real detectors is avoided and operational readiness is maintained.

Additionally, the SVG-2 SIM eliminates the regulatory, health, and environmental concerns of real radiation sources.

Key Features

- **Advanced Simulation Capabilities:** Simulated external Alpha, Beta, Gamma probe for contamination monitoring and decontamination exercises. Dose and dose rate indications with analogue and digital backlit displays.
- **Operational Realism:** Identical interface as the real SVG-2 detector, inverse square law ($1/r^2$) response, and realistic shielding effects.
- **Flexible Training Applications:** Compatible with PlumeSIM for wide-area tactical field and emergency response exercises. Multi-detector, multi-isotope capability for comprehensive scenario development.





RadEye GF-10 SIM

Présentation :

Le simulateur RadEye™ GF-10 est une solution de formation ultra-réaliste conçue pour reproduire les fonctionnalités et les réactions du RadEye™ GF-10 de Thermo Fisher.

Conçu pour des exercices de détection des rayonnements haute fidélité, ce simulateur élimine les risques associés aux rayonnements ionisants, garantissant un environnement de formation sûr, efficace et respectueux de l'environnement. Équipez votre équipe des outils nécessaires pour maîtriser la détection et la réponse aux rayonnements dans des conditions réelles.

Caractéristiques:

- Précision de simulation inégalée : réponse réaliste à la loi de l'inverse du carré de la distance dans les limites de tolérance réelles du détecteur. Simule les effets du blindage corporel de l'utilisateur et des matériaux de blindage pour une formation précise à la localisation des sources.
- Fidélité de l'interface utilisateur : affichage, panneau de commande, sonnerie et vibreur identiques à ceux du RadEye™ GF-10 opérationnel. Options de menu configurables, notamment les unités de mesure (Sv/h, Rem, CPS), la sélection de la langue et les alarmes de dose et de débit de dose avec des paramètres personnalisables.
- Intégration transparente : entièrement compatible avec Plume SIM d'Argon pour les exercices CBRN et HazMat à grande échelle et multi-appareils.



Overview:

The RadEye™ GF-10 Simulator offers realistic, risk-free training for radiation detection, mirroring the functionality of the Thermo Fisher RadEye™ GF-10. It's a safe, effective solution for hands-on exercises—without exposure to ionizing radiation.





Features:

- **Unmatched Simulation Accuracy:** Realistic inverse square law response within actual detector tolerances. Simulates user body shielding and shielding material effects for precise source location training.
- **User Interface Fidelity:** Identical display, switch panel, sounder, and vibrator as the operational RadEye™ GF-10. Configurable menu options, including measurement units (Sv/hr, Rem, CPS), language selection and dose and dose rate alarms with customisable settings.
- **Seamless Integration:** Fully compatible with Argon's Plume SIM for wide-area, multi-device CBRN and HazMat exercises.

High impact radiation training

The RadEye™ GF-10 Simulator delivers a true-to-life training experience by replicating the real detector's interface, audio/visual signals, and response speed. It supports realistic source search exercises with detection of the Radsim GS4 simulation source at distances up to 60 meters.

With accurate simulation of sensitivity and inverse square law behavior, it allows trainers to demonstrate and teach critical radiation protection principles such as time, distance, and shielding without the safety, regulatory, or environmental concerns of using live sources.

Consistent, Repeatable Performance

Powerful proprietary signal processing ensures consistent, repeatable readings every time a scenario is revisited. Simulated responses across multiple units remain within the tolerances of real detectors, delivering high-quality, realistic training that meets professional standards.

Train Smarter, Train Safer

RadEye™ simulators are fully compatible with Argon's PlumeSIM system—used by leading training facilities worldwide for live field and tabletop CBRN exercises. PlumeSIM enables real-time, wide-area emergency response training with multiple simulated devices reacting to virtual hazards.



RADSIM-SS3

Présentation :

Le RADSIM-SS3 est un simulateur de radiamètre gamma haute fidélité, conçu pour reproduire les fonctionnalités des radiamètres réels sans avoir recours à des sources de rayonnement ionisant.

Offrant des expériences de formation précises et réalistes, le RADSIM-SS3 est idéal pour développer des compétences essentielles en matière de radioprotection de manière sûre, économique et respectueuse de l'environnement.

Caractéristiques:

- Sûr et respectueux de l'environnement : réagit à des sources électroniques sûres de simulation gamma et peut démontrer les effets de blindage de matériaux tels que la brique, le bois et le verre.
- Précision scientifique : simule la réponse de la loi de l'inverse du carré ($1/r^2$) pour une détection précise des sources.
- Technologie de simulation avancée : affiche la dose et le débit de dose en Sv/h ou Rem/h via des écrans LCD numériques et à barres combinés.
- Solutions de formation intégrées : entièrement compatible avec Plume SIM d'Argon et prend en charge des scénarios simultanés à détecteurs multiples et isotopes multiples avec d'autres simulateurs Argon.





LCD3.3-SIM Chemical Hazard Detection Simulator

Présentation :

Entrez dans une nouvelle ère de formation CBRNe avec le LCD3.3-SIM, le simulateur ultime pour la détection des risques chimiques, conçu pour que chaque exercice donne l'impression d'être réel. Avec une conception réaliste reflétant le LCD3.3 de Smiths Detection, ce simulateur présente aux intervenants des scénarios authentiques sans exposition à des matières dangereuses. Qu'il s'agisse de simulations d'agents neurotoxiques, de toxines industrielles ou de guerre chimique, cet appareil est conçu pour renforcer la préparation de votre équipe à toute menace.



Caractéristiques:

- Interface réaliste : imite parfaitement le détecteur réel, permettant une transition transparente entre la formation et l'intervention dans le monde réel.
- Simulation complète des menaces : détecte et simule un large éventail d'agents, notamment les agents neurotoxiques, vésicants et hémotoxiques, les produits chimiques industriels toxiques (TIC) et les faux positifs.
- Adaptabilité à l'environnement : simule diverses conditions telles que la direction du vent, les changements de température et la vision nocturne.
- Contrôle amélioré pour les instructeurs : grâce à une télécommande dédiée, les instructeurs peuvent régler l'efficacité de la décontamination, la persistance et les niveaux de contamination.



FH 40 GSIM Survey Meter Simulator

Présentation :

Le simulateur de radiamètre FH 40 G SIM offre une formation réaliste et percutante sur les risques liés aux rayonnements, sans les dangers liés aux sources ionisantes. Ce simulateur avancé reproduit les fonctionnalités opérationnelles du Thermo FH 40 G, permettant aux stagiaires d'acquérir une expérience pratique en matière de détection des rayonnements, de reconnaissance et de délimitation sécurisée.

Réagissant à des sources électroniques sûres, le FH 40 G SIM permet de comprendre parfaitement le comportement des rayonnements, le blindage et la gestion des doses de manière contrôlée et respectueuse de l'environnement.

Caractéristiques:

- Simulation de détection authentique : reproduit le graphique à barres analogique et les affichages numériques du débit de dose, les alarmes de dose et de débit de dose, ainsi que l'avertisseur sonore sélectionnable.
- Effets de blindage réalistes : réagit aux sources de simulation sur des distances allant jusqu'à 60 mètres, en modélisant les effets du blindage à travers les murs, les sols et les plafonds.
- Prise en charge de plusieurs appareils : fonctionne avec les simulateurs de dosimètre, de radiamètre et de spectromètre d'Argon, ainsi qu'avec les détecteurs HazMat en option, permettant des scénarios multi-isotopes et multi-détecteurs.
- Options de formation améliorées : compatible avec la sonde ThermoFisher FH 40 TG Teleprobe, la sonde de rayonnement d'extension FTZ612-SIM d'Argon et le système PlumeSIM.





Raid-100M Training Simulator

The RAID-M100 Chemical Hazard Detection Simulator is an advanced training tool designed for military and civil CBRNE responders. Specifically engineered to emulate the Bruker Daltonics RAID-M100, this simulator replicates its features, responses, and operations to deliver unmatched realism in training.

Whether preparing for chemical warfare agents (CWAs) or toxic industrial chemicals (TICs), the RAID-M100-SIM provides a safe, practical, and cost-effective solution for mastering critical detection skills.

Key Features

- **Versatile Hazard Simulation:** Identifies CWAs, TICs, and false positives and simulates persistent and non-persistent substances. Replicates contamination and decontamination scenarios, including probe contamination.
- **Realistic Instrument Interaction:** Functional sieve pack and filter replacement and monitoring of user errors such as missed confidence tests or procedural oversights.
- **Rapid Deployment:** Set up scenarios in under 10 minutes for maximum training flexibility.
- **Sustainability & Cost Efficiency:** Requires no ionizing radiation, calibration, or preventative maintenance. Operates with electronic simulation sources that are safe and environmentally friendly.





Dräger X-am Series Simulator

Developed in cooperation with Dräger, the Argon Electronics X-am 2x00/5x00 SIM replicates the full functionality of the Dräger X-am 2x00 and 5x00 series gas detectors, offering a powerful, engaging, risk-free training experience. Responding to Argon's safe, environmentally friendly simulation long range vapour sources (LRVS), instructors can quickly implement a wide variety of confined space and open area training scenarios.

Perfect for confined space, open area and gas leak detection and management training, the Dräger X-am series simulator helps ensure responders have the confidence to conduct gas monitoring, interpret readings, and respond to alarms without exposure to real gas hazards, depleted oxygen or explosive atmosphere.



Key Features

- Realistic Gas Detection Training: accurate replicates detection and alarm responses
- Seamless Compatibility: Works with Dräger's standard configuration software
- Data-Driven Training: Compatible with Dräger Gas Detection Connect for live data transmission.
- Multi Detector Exercises: Compatibility with Argon's CWA / TIC detector simulators for specialist team multi detector response exercises.
- Flexible Multi-Scenario Training: Integrates with Argon's simulation vapour sources and PlumeSIM for dynamic scenarios.

← Back to partner



Détection des radiations > Simulateurs de formation

Tracerco PED+ Simulator



Grâce à la combinaison de la richesse de l'expérience de simulation d'Argon et de notre relation avec Tracerco, l'apparence, la sensation et la réponse du simulateur de dosimètre électronique personnel (PED+) sont extrêmement proches de celles du détecteur réel.

PED+SIM répond aux sources électromagnétiques Radsim qui simulent en toute sécurité les rayonnements ionisants, éliminant ainsi les problèmes de réglementation, d'environnement, de santé et de sécurité pour vous et vos étudiants. Vous pouvez utiliser les sources de simulation à l'air libre ou à l'intérieur des bâtiments.



Formation aux rayonnements à fort impact

Pour garantir une expérience de formation ultime, tous les composants de l'interface utilisateur (écran,

indicateurs, panneau de commande, sirène et vibreur) sont exactement les mêmes que le détecteur réel.

La vitesse de réponse et les caractéristiques lors de l'approche et du retrait de la source de simulation sont identiques à celles du détecteur réel, ce qui vous permet de fournir une formation de recherche/trouver une source très réaliste.

La sensibilité simulée permet au Tracerco PED+SIM de détecter la source gamma de simulation Radsim GS4 à une distance en espace libre généralement de 200 pieds (60 mètres) en ligne de mire.

Performances constantes et reproductibles

Un puissant traitement du signal exclusif garantit que les lectures simulées sont reproductibles chaque fois que les étudiants revisitent le même emplacement de scénario tout en garantissant que les lectures observées sur différents simulateurs se situent dans les tolérances acceptées des détecteurs réels ; tous contribuant à fournir une formation réaliste et de haute qualité.

Même l'effet de la protection corporelle de l'utilisateur pour déterminer la position de la source est simulé de manière réaliste afin que vous puissiez être certain que vos équipes d'enquête comprennent comment utiliser et interpréter efficacement les lectures et les alarmes de leurs détecteurs.

Principales caractéristiques:

- Réponse de la loi du carré inverse ($1/r^2$) dans les limites de la tolérance réelle du détecteur.
- Simulation du blindage corporel de l'utilisateur pour l'emplacement de la source.
- Représentation réaliste de différents effets de blindage.
- Unités de mesure sélectionnables (Sv/h, Rem, CPS).
- Même interface humaine que le vrai Tracerco PED+.
- Paramètres de menu configurables.
- Paramètres d'alarme de dose et de débit de dose.
- Sélection de la langue.
- Même batterie que le détecteur réel (environ 36 heures de fonctionnement standard, 150 heures de fonctionnement en mode économiseur d'écran).
- Pas d'étalonnage régulier.
- Aucun entretien préventif.



Blindage temps-distance

Le simulateur de formation PED+ permet d'enseigner et de démontrer facilement l'importance du blindage temps/distance ; l'activité de la source simulée est réduite de manière réaliste en fonction du matériau situé entre la source de simulation et le détecteur simulé.

La réponse extrêmement réaliste de la loi du carré inverse permet de démontrer la puissante combinaison

de protection de la distance et du blindage, permettant ainsi aux étudiants de pratiquer la communication des recommandations et des procédures de sécurité sans les restrictions réglementaires, de sécurité, environnementales et de coûts associées aux sources réelles.

Formation réaliste et rentable

Aucun entretien préventif, étalonnage ou consommable (à l'exception des piles) n'est requis, garantissant que le coût de possession sur toute la durée de vie est minime, que des dommages coûteux aux détecteurs réels sont évités et que la préparation opérationnelle est maintenue.

Compatible PlumeSIM

PED+SIM est compatible avec PlumeSIM, le système d'exercices CBRN Live Field et Tabletop éprouvé d'Argon. Utilisé par de nombreuses installations de formation parmi les plus importantes au monde, PlumeSIM permet de mener en temps réel des exercices tactiques instrumentés sur une vaste zone et des interventions d'urgence nucléaires / HazMat / Guerre chimique à l'aide d'un ou de plusieurs types de dispositifs de simulation qui répondent en temps réel aux dangers simulés.

PED est une marque déposée de Tracerco. Tracerco est une marque déposée de Johnson Matthey.

MONITEURS CORPORELS





Partner Ludlum Measurements



Ludlum Measurements, Inc. conçoit et fabrique des instruments et des technologies de détection des rayonnements. Fondée en 1962, elle propose une large gamme d'instruments de détection de rayonnements, développés pour aider à surveiller la sécurité du personnel et de l'environnement. Les instruments sont utilisés dans des applications telles que la surveillance de routine du personnel et du matériel, la sécurité des frontières et les situations d'intervention d'urgence.

Product offering

Model 215 Alpha Frisker Station



Model 177HFM Low Cost Hand & Foot Monitor



Model HFC-8 Hand, Foot, and Clothing Monitor



Model 4906P Alpha-Beta-Gamma Hand & Foot Monitor

Shown with
Optional Light Tower



Model 4906AB Alpha-Beta Hand & Foot Monitor



Model 4906A Alpha Hand & Foot Monitor



Model 4901P Beta-Gamma Hand & Foot Monitor



Model 3276HFM Low Cost Hand & Foot Monitor



Model 3277HFM Compact Alpha-Beta Hand & Foot Monitor



Model 53 Gamma Portal Monitor



Model 52-1, 52-5 & 52-6 Series Portable Portal Monitors



Model 52 Portable Portal Monitor



Model HBP-22 Body Contamination Monitor



Model HBP-29 Body Contamination Monitor



Model 375P-1000 Outdoor Radiation Contamination Monitor - Ludlum





Détection des radiations > Moniteurs corporels

Model 215 Alpha Frisker Station

Ludlum Model 215 is a unique dual-purpose alpha contamination detection system that can be used as both a stationary detector and a mobile frisker. When alongside a glovebox, the operator can use this innovative device as a stationary hand frisker, then simply remove it from the charging stand for use as any other mobile alpha frisker.

This convenient, integrated detector design requires no batteries, P-10 counting gas, or cables, giving the user complete freedom in performing frisking duties. The large area, air proportional detector has built-in electronics, display, and capacitors that allow it to be operated for at least 10 minutes, typically 15 minutes, before needing to be recharged. Fully discharged, the detector is ready for stationary operation within five minutes of being placed into the charger stand, and ready for mobile frisking within 30 minutes. The charging stand interfaces to a PC to facilitate setting parameters and running high voltage plateaus via an optional application program.



Features

- Dual Purpose Alpha Frisker & Hand Monitor Station
- Detector Operates Independent of Its Stand
- Simple to Use
- No Batteries, Cables, or Gas Required

← [Back to partner](#)



Détection des radiations > Moniteurs corporels

Model 177HFM Low Cost Hand & Foot Monitor

This setup offers a low-cost alpha/beta/gamma contamination monitoring system for checking hands and feet.

To build this system, order the following items:

- **Model 177** Benchtop Meter (PN: 48-1632)
- **Model 44-25** Hand Detector (PN: 47-1508)
- **Model 44-26** Foot Detector (PN: 47-1509)
- Connection Tee (PN: 13-7788)
- 1.5 m (5 ft.) Cable (PN: 40-1004-5)

Features

- Detects alpha, beta, and gamma
- Low cost
- Easy to set up





Détection des radiations > Moniteurs corporels

Model HFC-8 Hand, Foot, and Clothing Monitor

Robust and Portable Hand-Foot-Clothing Monitor with Touch-Screen Display

The HFC-8 is a compact hand, foot, and clothing monitor to measure personnel leaving controlled areas. With a removable probe and spring-loaded hand detectors, the HFC-8 has been developed for portability between different areas. Featuring a detector arrangement to measure the hands and feet in one measurement step, the HFC-8 integrates the latest technology and design, while meeting official standards.

Various detector options are available, including:

- Beta detectors (plastic scintillator)
- Beta-Gamma detectors (plastic scintillator)
- Alpha/Beta detectors (plastic scintillator or gas-flow proportional)

The standard unit consists of:

- 8 detectors with semiconductor readout, one of them as removable hand probe
- Robust stainless-steel housing
- Ergonomic detector positioning
- Integrated 12 in. touch-screen display
- Fully automated measurement process with audiovisual operator guidance
- Latest industry controller technology
- Power provided by UPS for several measurements during mains power outage

Features

- Intuitive User-Friendly Software
- Spring-Loaded Hand Detectors for Reliable Contact with the Hand Surfaces
- Compact Footprint with Easy Access to the Service Cabinet
- Modern Touch-Screen Display
- Stainless Steel Housing for Easy Cleaning and Durability
- Access to Historical Measurement Data via Integrated Database
- Export of Measurement/Parameter Data in XML Format via USB





Détection des radiations > Moniteurs corporels

Model 4906P Alpha-Beta-Gamma Hand & Foot Monitor

The Model 4906P is a low cost, industrial duty, alpha-beta-gamma contamination monitoring system that uses six pancake cluster detectors for checking personnel. A large color LCD presents users with the system status and points out any potential contamination in an easy-to-use manner. Alarms are annunciated locally and can be augmented with optional relays for signaling remote devices or a light stack mounted on top.

All maintenance can be performed from the front of the instrument. Detector access for quick replacement or repair is facilitated by hinged top covers. The unit is equipped with rear-mounted wheels to facilitate transporting the instrument from one location to the next.

Features

- GM Pancake Detectors
- Large LCD User Interface
- Automatic Routines for Detector Setup & Alarm Calculations
- Customizable Voice Prompts
- Single-Hand Operational Mode
- Front Access to All Components for Repair/Calibration





Détection des radiations > Moniteurs corporels

Model 4906AB Alpha-Beta Hand & Foot Monitor

The Model 4906AB is a low cost, industrial duty, alpha and beta contamination monitoring system for checking personnel hands and feet. A large color LCD presents users with the system status and points out any potential contamination in an easy-to-use manner.

The system employs six gas flow proportional type detectors with counting activated by optical switches. Alarms are annunciated locally and can be augmented with optional relays for signaling remote devices or a light stack mounted on top. The built-in Ethernet interface supports connection to a network for gathering all count cycles and remote monitoring of the status.

All maintenance can be performed from the front of the instrument. Detector access for quick replacement or repair is facilitated by hinged top covers. The unit is equipped with rear-mounted wheels to facilitate transporting the instrument from one location to another.

Features

- Alpha-Beta Gas Flow Proportional Probes
- Large LCD User Interface
- Automatic Routines for Detector Setup and Alarm Calculations
- Voice Prompts
- Built-in Ethernet Interface
- Single-Hand Operational Mode
- Front Access to All Components for Repair/Calibration





Model 4906A Alpha Hand & Foot Monitor

The Model 4906A is an industrial-duty, low-cost, alpha-only contamination monitoring system for the hands and shoes of personnel. System status and areas of possible contamination are presented in a large color LCD making the process simple and user-friendly.

Counting is initiated by optical switches that activate six air-proportional-type detectors. Alarms annunciate locally and can be augmented with optional relays that will signal remote devices or a high-visibility alert light mounted on top of the unit. The built-in Ethernet interface supports connection to a network for gathering all count cycles along with permitting remote monitoring of the status of the instrument.

All maintenance can be performed from the front of the instrument. Hinged top covers make accessing detectors for repair or replacement convenient. Rear-mounted wheels allow the instrument to be transported from one location to another with relative ease.

Features

- Alpha Air Proportional Probes
- Large LCD User Interface
- Automatic Routines for Detector Setup and Alarm Calculations
- Voice Prompts
- Built-in Ethernet Interface
- Single-Hand Operational Mode
- Front Access to All Components for Repair/Calibration





Détection des radiations > Moniteurs corporels

Model 4901P Beta-Gamma Hand & Foot Monitor

The Model 4901P Beta-Gamma Hand & Foot Monitor is intended for use as a medium-level beta and gamma contamination monitor. Four count channels are in the standard configuration for monitoring the palm of each hand and the sole of each foot. The Model 4901P employs a total of twenty-two pancake Geiger-Mueller (GM) type detectors, five in each hand detector (palm side only) and six in each foot detector. LED indicators show status and alarm location. The Model 4901P allows parameter updating by viewing the built-in, 16-character LCD display. Detector counts, background, alarm set points, and all parameters may be viewed on the LCD display. Switches at each hand detector initiate an interrogation (both switches must activate). Audible alarm and status change indications are standard.



Features

- Affordable
- Simple to Use
- Automatic Background Subtract
- Password-Protected Parameters
- Alarm Audio Volume Adjustment
- Non-Volatile Memory Requires No Battery Backup



Détection des radiations > Moniteurs corporels

Model 3276HFM Low Cost Hand & Foot Monitor

The Model 3276 is a versatile instrument that can be used for multiple radiation detection or measurement purposes. In this configuration, the Model 3276 is connected to both a Model 44-25 hand monitor detector and Model 44-26 foot monitor detector to monitor personnel for alpha, beta, and gamma contamination. An optional Model 44-9 detector can also be included for frisking.

The Model 3276 features a large, backlit, easy-to-read LCD screen and audible alarms and is controlled using a simple four-button interface. The unit body is made of lightweight, rugged aluminum. It is not intended for outdoor use and should be protected from splashing water.

The Model 3276 can measure radiation in count rate, exposure rate, exposure rate/dose, activity rate, integrated exposure/dose, time-averaged rates, and scaler counts. In this configuration, three modes of operation are available - RATE, MAX, and COUNT - which can be selected by pressing the MODE button. Measurements can be collected in two sets of units (primary and secondary) for RATE and MAX modes in cps, cpm, Bq, dpm, R/hr, or Sv/h units. The user can switch between the two sets of units by pressing the UNITS button.

Instrument setup can be done either through the front-panel controls or via the Lumeric Calibration Kit (PN: 4498-1018). Power is supplied by either four alkaline "AA" batteries or a 9 Vdc wall mount transformer. The Model 3276HFM is shipped ready to use with batteries, a wall transformer, and a calibration certificate.





Détection des radiations > Moniteurs corporels

Model 3277HFM Compact Alpha-Beta Hand & Foot Monitor

The Model 3277HFM Hand & Foot Monitor is intended for checking low-level alpha and beta contamination on personnel. The gasless system incorporates two scintillation detectors, one for the hand and one for the foot. An optional frisker scintillation detector can be included as well.

Measurement is a two-step process, measuring the hand and foot on one side at a time. To begin an automatic count, both the hand and foot must be placed on the respective detectors, activating the infrared (IR) sensor on each detector. User-friendly instructions and the status of each detector is clearly displayed on the large, color touch-screen. The instrument uses a minimum count time mode to automatically determine the count time based on background, alarm setpoints, and other factors. When the count is completed, either a “Clean” or “Alarm” message will be displayed, depending on the configured alarm set-points.

In “Idle” mode, the screen will display the current detector count rates (default) or the accumulated background rate.

If the system includes a frisker, the status of all three detectors are displayed in “Idle” mode, but only the active detector(s) (either both the hand and foot, or the frisker) are displayed when a count is performed. The frisk state is activated when the frisker is removed from the cradle, and the automatic hand and foot count is activated as described above. A lockout prevents the instrument from toggling the display between the frisker and the hand and foot detectors, so that whichever detector is activated first remains active until the sensor is no longer triggered.

The system can communicate through a standard Ethernet connection for remote monitoring. It is powered by a 100 – 240 Vac wall transformer. An optional battery backup is available to ensure constant power. Instrument setup can be done through the touch-screen display or via Ludlum’s Lumic Calibration Software.

Features

- 7-inch Color LCD Display Shows All Readings Simultaneously in a Large, Simple Layout
- Audible & Visual Alert Signals
- Easy to Operate Two-Step System



- Gasless - Uses Dual-Phosphor Scintillation Detectors
- Optional Rechargeable Battery Backup
- Automatic Start of Count
- Minimum Count Time
- Automatic Background Subtraction During Measurements



Détection des radiations > Moniteurs corporels

Model 53 Gamma Portal Monitor

The Model 53 Gamma Personnel Portal detects gamma radiation in or on personnel passing through the portal from either direction. This highly sensitive portal uses eight large plastic scintillation detectors. Shielding is accomplished with either the standard 2.5 cm (1 in.) or optional 5.1 cm (2 in.) thickness of lead. A user-friendly interface guides personnel through the portal monitor via automated voice prompts, and is accompanied with 25.7 cm (10.1 in.) color LCD articulating screens presenting the instrument readiness and status at the ingress and egress. Alarms are manifested both audibly and visually, and can be silenced and acknowledged via control buttons located on either side of the instrument.



Three statistical counting modes are available to maximize throughput, maximize sensitivity, or fix the count time. Several modifiable parameters adjust the alarm set point, including the false alarm probability, detection probability, background sigma coefficient (K_b), and the composite sigma coefficient (K_{S+B}). Fast alarm and clean options provide the ability to quickly determine if personnel are contaminated or clean before the entire count cycle has ended.

There are also four user modes to choose from that include a walk-through mode, a pause mode, a pause-and-turn mode, and a front-and-back mode. Voice prompts may be customized in any language for each of these modes. These prompts can, for example, dictate in-house procedures to follow. Instrument technicians have password-protected access to set up the instrument, and to the advanced automated routines for calibrating and verifying operation.

Easily accessible USB ports facilitate connecting a keyboard to implement changes, input user ID, or upload revised software. The system also includes an Ethernet link. Ludlum's optional Universal Network Software can be used to log instrument status, user activity, and other information from one or more instruments connected to the network. This software broadcasts emails whenever radiological alarms or instrument failures occur, and has the ability to capture images from network cameras that can be stored along with the user ID (if implemented). See the "Options" tab for more information and other available options.



Détection des radiations > Moniteurs corporels

Model 52-1, 52-5 & 52-6 Series Portable Portal Monitors

The Model 52-1, 52-5, and 52-6 Series Portable Portal Monitors are used for beta-gamma contamination monitoring on personnel and meet the FEMA standard for Emergency Response Portal Monitoring (FEMA-REP-21). They are designed to be disassembled for ease of transportation and storage, and can be set up in five minutes or less without any tools.

Each instrument's non-volatile parameters are preset at the factory to detect a 1.0 μCi ^{137}Cs source in a 10 $\mu\text{R/hr}$ background field. Microprocessor-based electronics provide ease of setup and reliability. Status LEDs indicate count-cycle status and audible signals accompany the LEDs for additional indication. Detector counts, background, and all parameters may be viewed on the instrument display. All setup is accomplished by way of pushbuttons located below the display.

These portal monitors can be operated in a walk-through mode with a quick scan occurring while a person is positioned within the portal. In this mode, checking is performed every 200 milliseconds while the portal is occupied, and 600 milliseconds before and 600 milliseconds after the portal is occupied. The portal monitor can also monitor in a stop-and-count mode, allowing for a more sensitive scan. In stop-and-count mode, the fixed count time may be set from 1 to 20 seconds.

These instruments have automatic background update and dynamic alarm setting capabilities. On startup, the instrument will take a background count and calculate alarm levels for each detector. Self-diagnostic routines check the background count and warn if the background becomes either too high or too low.

Alarms are calculated with a user-adjustable sigma parameter and the current background count. During setup, the user can also specify individual alarms only, sum alarm only, or both individual and sum alarm. The sum alarm groups upper detectors and lower detectors.

Included with each instrument are a wheeled transport case and a clear polypropylene sleeve to protect against wet weather conditions.



These instruments are able to operate from 85 to 250 Vac, 50/60 Hz without a voltage selector switch. They may also be powered from the supplied vehicle cigarette lighter adapter, or three or six “D” cell batteries.

Water-Resistant Versions

Ludlum also offers some water-resistant versions: Models 52-1W (PN 48-4300), 52-1-1W (PN 48-3516) and 52-6-1W (PN 48-4312). Note that these water-resistant versions can only be used for gamma contamination monitoring.

Vehicle Monitoring

The Model 52-1, 52-5, and 52-6 Series can also be used as vehicle monitors using the optional vehicle conversion kit (PN 4215-374 for standard models, PN 4215-1099 for water-resistant models). The kit includes two stands to support the side detectors and a 6.1 m (20 ft.) cable. See Options tab for more information.



Détection des radiations > Moniteurs corporels

Model 52 Portable Portal Monitor

The Model 52 Portal Monitor is used for Beta-Gamma personnel contamination monitoring and meets the FEMA standard for Emergency Response Portal Monitoring (FEMA-REP-21). It is designed to be assembled in five minutes or less without tools, and can be quickly disassembled for ease of transportation and storage. All parameters are stored in non-volatile memory, which requires no battery backup. These parameters allow easy operation with minimal setup by minimally trained personnel. The parameters are preset at the factory to detect a 1 μCi ^{137}Cs beta window source in a 10 $\mu\text{R/hr}$ background field, in accordance with the FEMA standard. The Model 52 can be powered by 120 Vac, six "D" cell batteries, or 220 Vac-powered units, which are available as a special order.



The instrument has a "person-counter" integrated into the electronics that increments by one every time a count is completed. It is a four-digit number normally displayed on the LCD display, next to the "READY" message. It also has an RS-232 port that can be used to print out parameter setpoints, background counts, and counts above background.

The portal frame incorporates an array of 18 Geiger-Mueller (GM) detectors positioned around the frame and base. Fourteen GM pancake detectors are located in the frame for monitoring the head and body. Four cylindrical GM detectors are utilized in the base for monitoring the feet. The electronics are microprocessor-based for ease of setup and reliability. Individual LEDs (Light Emitting Diodes) mounted in the frame and also on the electronics front panel indicate the specific alarm location. LEDs in the front panel indicate count cycle status. Audible signals accompany the LEDs for additional indication. Detector counts, background, and all parameters may be viewed on the LCD display. All setup is accomplished via pushbuttons on the electronics assembly.

The Model 52 incorporates a summing alarm in addition to the individual channel alarms. This increases the system sensitivity to widespread contamination. If two or more channels have a noticeable increase in counts but do not exceed their alarm threshold, the sum of their counts could exceed the summing alarm.

The Model 52 also has background update and subtract capabilities. The instrument will take a background count and

subtract it from the current count. This function helps compensate for fluctuations in background. Background subtract can be turned on or off, the background count time is adjustable, and the background interval time is adjustable. The operator can force the instrument to stop and take a background count at a different interval if desired.

The Model 52 is supplied with a polypropylene weather sleeve to protect against wet weather conditions. Units are also supplied with a rugged, wheeled, and padded transport/storage case for rapid deployment.



Model HBP-22 Body Contamination Monitor

Robust, Ergonomically Designed Body Contamination Pre-Monitor

The Model HBP-22 is a body contamination monitor that utilizes beta plastic detectors to measure personnel as a pre-monitor. Robust, with a modern design that integrates the latest available industrial technology, the system is optimized for users of all sizes.



The key features include:

- 22 beta plastic detectors with semiconductor readout
- Whole body measurement in 2 easy steps
- Automated measurement process with audio-visual user guidance
- Integrated 12 in. touch-screen display
- Intuitive user-friendly software
- Hand-detector on the side
- Latest industry-controller technology
- Energy filter settings to optimize discrimination of background radiation
- Power provided by internal UPS for several measurements during power loss
- Intuitive User-Friendly Software
- Large Service Space in a Footprint of 900 x 840 mm (35.4 x 33.1 in.) (W x D) with Easy Access to the Service Cabinet
- Modern 12 in. Touch-Screen Display
- Stainless Steel Housing for Easy Cleaning and Durability
- Access to Ludlum's Test Tool Software for Detector Analysis
- Export of Measurement/Parameter Data in XML Format via USB
- Access to Historical Measurement Data via Integrated Database
- Network Capability for Remote Monitoring

← [Back to partner](#)



Détection des radiations > Moniteurs corporels

Model HBP-29 Body Contamination Monitor

The Model HBP-29 is a whole-body contamination monitor designed to measure personnel leaving controlled areas.



Features:

- Intuitive User-Friendly Software
- Large Service Space in a Footprint of 900 x 840 mm (35.4 x 33.1 in.) (W x D) with Easy Access to the Service Cabinet
- Modern Touch-Screen Display
- Access to Ludlum's Test Tool Software for Detector Analysis
- Export of Measurement/Parameter Data in XML Format via USB
- Access to Historical Measurement Data via Integrated Database
- Remote Access via Web Browser Interface

Standard features include:

- 29 beta plastic detectors with semiconductor readout
- Stainless steel housing for easy cleaning and durability
- Ergonomic detector positioning
- Hand-detector on the side
- Integrated 17 in. touch-screen display
- Automated measurement process with audio-visual guidance
- Latest industry-controller technology
- Energy filter settings to optimize discrimination of background radiation
- Power provided by UPS for several measurements during power loss
- Designed to meet industry and regulatory standards



Détection des radiations > Moniteurs corporels

Model 375P-1000 Outdoor Radiation Contamination Monitor - Ludlum

The Model 375P-1000 Outdoor Radiation Contamination Monitor (Ludlum) is a Digital Model 375 controller coupled to 2 shielded 7866 cm² plastic scintillator detectors. The detectors are covered in weathertight enclosures applicable for the outside environment. The Model 375P-1000 Outdoor Radiation Contamination Monitor is perfect for examine outgoing trash and/or medical waste for possible low-level radioisotope contamination.



Model 375P-1000 Outdoor Radiation Contamination Monitor features:

- indicates status, sum alarm, sigma alarm, low battery, det fail and overrange
- 4-digit LED display with 2 cm (0.8 in.) digits
- range: 0.0 to 9999 kcps
- battery backup
- programmable alarms
- network cable
- data output: 9-pin connector providing RS-232 output, signal ground connection, FAIL and ALARM signals and direct connection to battery and ground
- relay output: mains (120 or 240 Vac) output on alarm

Read more about the Model 375P-1000 Outdoor Radiation Contamination Monitor on the [Ludlum website](#)



Partner **Helgeson Scientific Services (HSS)**



Helgeson Scientific Services (HSS) conçoit et fabrique des systèmes avancés de surveillance des radiations axés sur la sécurité du personnel, la protection des installations et le contrôle des déchets. Sa gamme comprend des moniteurs corporels, des systèmes de détection par portique et des solutions de gestion des déchets, tous développés pour garantir la manipulation sûre des matières radiologiques dans des environnements critiques.

Product offering


HS-BEXA - Alpha Beta hand feet monitor



HS-BEX - Beta gamma hand feet monitor



DIYS - Bed type whole body counter for internal dosimetry



HS-ABOMO - Alpha beta gamma portal for personnel monitoring



HS-BOMO - Beta gamma portal for personnel monitoring



HS-RAM - Gamma portal for personnel monitoring



QUICKY - Whole body counter for internal dosimetry



[← Back to partner](#)



Détection des radiations > Moniteurs corporels

HS-BEXA - Alpha Beta hand feet monitor

The HS-BEX monitors are multitasking equipment designed for the detection and measurement of radiation ALPHA and BETA on the hands and feet of potentially exposed personnel through a fully automatic operation.

The system can be configured to have 3, 4, 6 or 7 detectors depending on the application and budget. An equipment that complies with the highest quality standards, designed and assembled in Spain.



[← Back to partner](#)



Détection des radiations > Moniteurs corporels

HS-BEX - Beta gamma hand feet monitor

The HS-BEX monitors are multitasking equipment designed for the detection and measurement of radiation BETA and GAMMA on the hands and feet of potentially exposed personnel through a fully automatic operation.

The system can be configured to have 3, 4, 6 or 7 detectors depending on the application and budget. An equipment that complies with the highest quality standards, designed and assembled in Spain.






Détection des radiations > Moniteurs corporels

DIYS - Bed type whole body counter for internal dosimetry

Présentation :

Compact et facile à utiliser, le « compteur corporel complet à monter soi-même » Helgeson offre un moyen peu coûteux d'assurer la sécurité du personnel des installations nucléaires, des laboratoires ou des hôpitaux. Le « compteur corporel complet à monter soi-même » mesure la charge corporelle totale des émetteurs gamma et estime également l'emplacement approximatif des émetteurs dans le corps. Le « compteur corporel complet à monter soi-même » Helgeson utilise une géométrie de balayage reconnue depuis longtemps comme celle qui produit le moins d'erreurs en raison de la distribution non uniforme des sources. Sa réponse positionnelle est bien supérieure à celle de n'importe quel compteur de chaise ou d'organe. Helgeson fournit un logiciel d'analyse, dont la supériorité a été prouvée au fil des ans, qui permet une analyse qualitative et quantitative des dépôts radioactifs.



Caractéristiques :

- Géométrie de balayage haute précision - Utilise une conception de balayage éprouvée qui minimise les erreurs causées par une distribution non uniforme des sources, garantissant une mesure très précise des émetteurs gamma dans tout le corps.
- Logiciel d'analyse complet - Fourni avec un logiciel d'analyse avancé qui fournit une évaluation qualitative et quantitative des dépôts radioactifs, soutenue par une représentation graphique claire des données pour une interprétation précise.
- Conception compacte et conviviale - Conçu pour être facile à utiliser et à installer, il offre une solution rentable pour surveiller la sécurité du personnel dans les installations nucléaires, les laboratoires et les hôpitaux.

← [Back to partner](#)



Détection des radiations > Moniteurs corporels

HS-ABOMO - Alpha beta gamma portal for personnel monitoring

Multitasking two-step device

The HS-ABOMO unit is a multitasking two-step device designed for the detection and measurement of radioactive contamination, ALPHA, BETA and GAMMA, on potentially exposed personnel.

It has been specifically designed for controlled areas. It includes up to 31 detectors, which work autonomously and independently, allowing to perform simultaneous measurements with different alarm levels.

The user can identify exactly in a different channel the beta cps and gamma cps since the detectors are different for each type of radiation. Its operation is fully automated. The equipment has sensors that detect when a person enters the portal, interrupting the background acquisition and initiating automatically a thorough examination of the subject.



← [Back to partner](#)



Détection des radiations > Moniteurs corporels

HS-BOMO - Beta gamma portal for personnel monitoring

Multitasking two-step device

The HS-BOMO unit is a multitasking two-step device designed for the detection and measurement of radioactive contamination, BETA and GAMMA, on potentially exposed personnel.

It has been specifically designed for controlled areas. It includes up to 31 detectors, which work autonomously and independently, allowing to perform simultaneous measurements with different alarm levels.

The user can identify exactly in a different channel the beta cps and gamma cps since the detectors are different for each type of radiation. Its operation is fully automated. The equipment has sensors that detect when a person enters the portal, interrupting the background acquisition and initiating automatically a thorough examination of the subject.



[← Back to partner](#)



Détection des radiations > Moniteurs corporels

HS-RAM - Gamma portal for personnel monitoring

Completely autonomous equipment

The HS-RAM monitors are completely autonomous equipment designed for the detection and measurement of gamma radiation on exposed workers.

They are designed to perform high speed measurements, allowing fast counting of a high volume of nuclear power plant workers. With different versions that customize the number of detectors, size, barriers, etc. the HS-RAM is without doubts the most flexible gamma portal for fast screening of personnel.





QUICKY - Whole body counter for internal dosimetry

Helgeson “Quicky” In-Vivo Counter is designed to complement any health physics program which includes routine whole body counting.

The “Quicky” is used to rapidly screen personnel or it can be used with a fixed counting time to obtain more precise results. The printed results provide the documentation for subject identification, counting time and date. Results are reported in Becquerel or Nano curies. The “Quicky” can reduce your regular counting requirements and costs significantly.

User-friendly software

Software for the “Quicky” is “user-friendly” with a menu format which provides a variety of standard and optional operating programs. System performance software includes a Quality Assurance program which checks the electronics of system, reporting any errors to the operator. An Energy Calibration program allows the gains of the individual detector-amplifier systems to be adjusted to uniformity and conformity to the design parameters.

- Data Acquisition, continuous spectral display.
- Data Analysis with graphs of original data and residuals.
- Calibrations: Energy vs. Channel and Efficiency, FWHM vs Channel.
- Parameter Modification for complete control: acquisition, analysis & miscellaneous parameters.
- File Maintenance.
- Dose calculating software based on ICRP recommendations and approved by the Spanish Nuclear Council.



MONITEURS DE PORTAIL





Partner **Polimaster**



Polimaster est un leader mondial des solutions de détection et de surveillance des rayonnements. Il propose une gamme complète d'instruments conçus pour détecter, identifier et mesurer les rayonnements ionisants dans divers environnements. Sa gamme de produits comprend des détecteurs portables, des dosimètres électroniques personnels, des identificateurs isotopiques portables, des portiques de détection et des systèmes de détection mobiles, tous conçus pour répondre aux exigences rigoureuses des secteurs de la sécurité, des interventions d'urgence et des applications industrielles.

Product offering

<p>Poligate Light G1 RPM</p>	<p>PoliGate™ Vehicle G4 RPM</p>	<p>PoliGate™ Pedestrian G1 RPM</p>	<p>PoliGate™ Pedestrian GN2 RPM</p>
<p>Poligate Light G2 RPM</p>	<p>Poligate Light G4 RPM</p>	<p>Poligate Pedestrian GN1 RPM</p>	<p>Poligate Deployable RPM</p>

**Poligate Pedestrian
G2 RPM**



**Poligate Vehicle G4N4
RPM**



**Poligate Vehicle G2
RPM**





Poligate Light G1 RPM

Lightweight one-sided model equipped with one gamma detector.

The **PoliGate™ Light G1** is a one-sided **gamma-only** Radiation Portal Monitor (RPM) equipped with one detector and is a **high-sensitive fixed system** designed for permanent installation and providing continuous radiation detection and monitoring of vehicles, people, or packages.

The **PoliGate™ Light series** is a simplified series of Polimaster RPMs that is available in a **more compact and lightweight design** and its detection blocks can be mounted on a frame or wall.

Features

- Lightweight design
- Control zone up to 1.5 m x 2 m (W x H)
- Wide gamma energy range from 20 keV to 3 MeV
- No stop of an object is required for the inspection
- Lead shielding for natural background rejection
- Ingress protection IP55
- Local and remote light and audible alarm annunciators
- Back-up battery providing at least 8 hours of operation
- Presence detection system (occupancy sensors)
- Adjustable sensitivity parameters for specific applications
- Optional video surveillance system





Détection des radiations > Moniteurs de portail

PoliGate™ Vehicle G4 RPM

Double-sided gamma model equipped with four gamma detectors.

The **PoliGate™ Vehicle G4** is a double-sided **gamma-only** Radiation Portal Monitor (RPM) equipped with four 11L-gamma detectors and is a **high-sensitive fixed system** designed for permanent installation and providing continuous radiation detection and monitoring of moving objects.

The **PoliGate™ Vehicle series** is an essential tool for safeguarding against the potential threat of nuclear materials entering secure areas and can be used for screening **trains, trucks, vehicles, cargo containers, luggage, and people**.



Features

- IEC 62244:2019 compliance
- Control zone up to 6 x 4.5 (W x H)
- Wide gamma energy range from 20 keV to 3 MeV
- No stop of an object is required for the inspection
- Lead shielding for natural background rejection
- Ingress protection IP65
- Local and remote light and audible alarm annunciators
- Back-up battery providing at least 8 hours of operation
- Presence detection system (occupancy sensors)
- Adjustable sensitivity parameters for specific applications
- Optional video surveillance system

← [Back to partner](#)



Détection des radiations > Moniteurs de portail

PoliGate™ Pedestrian G1 RPM

One-sided gamma model equipped with one (11L) gamma detector.

The **PoliGate™ Pedestrian G1** is a one-sided **gamma-only** Radiation Portal Monitor (RPM) equipped with one 11L-gamma detector and one neutron detector and is a **high-sensitive fixed system** designed for permanent installation and monitoring of people or packages for the presence of radioactive materials.

The **PoliGate™ Pedestrian series** is an essential component of any facility that requires strict security measures, including government buildings, research facilities, and nuclear power plants. The compact and ergonomic design of the RPM makes it a convenient solution for use in various applications for screening **people, luggage, and cargo**.



Features

- IEC 62244:2019 compliance
- Control zone up to 1.5 x 2 (W x H)
- Wide gamma energy range from 20 keV to 3 MeV
- No stop of an object is required for the inspection
- Lead shielding for natural background rejection
- Ingress protection IP65
- Local and remote light and audible alarm annunciators
- Back-up battery providing at least 8 hours of operation
- Presence detection system (occupancy sensors)
- Adjustable sensitivity parameters for specific applications
- Optional video surveillance system

← [Back to partner](#)



Détection des radiations > Moniteurs de portail

PoliGate™ Pedestrian GN2 RPM

Double-sided gamma-neutron model equipped with two gamma (6.6L each) and two neutron detectors.

The **PoliGate™ Pedestrian GN2** is a double-sided **gamma-neutron** Radiation Portal Monitor (RPM) equipped with two 6.6L-gamma and one neutron detector and is a **high-sensitive fixed system** designed for permanent installation and monitoring of people or packages for the presence of radioactive materials.

The **PoliGate™ Pedestrian series** is an essential component of any facility that requires strict security measures, including government buildings, research facilities, and nuclear power plants. The compact and ergonomic design of the RPM makes it a convenient solution for use in various applications for screening **people, luggage, and cargo**.



Features

- IEC 62244:2019 compliance
- Control zone up to 1.5 x 2 (W x H)
- Wide gamma energy range from 20 keV to 3 MeV
- No stop of an object is required for the inspection
- Lead shielding for natural background rejection
- Ingress protection IP65
- Local and remote light and audible alarm annunciators
- Back-up battery providing at least 8 hours of operation
- Presence detection system (occupancy sensors)
- Adjustable sensitivity parameters for specific applications
- Optional video surveillance system



Poligate Light G2 RPM

Lightweight double-sided model equipped with two gamma detectors.

The **PoliGate™ Light G2** is a double-sided **gamma-only** Radiation Portal Monitor (RPM) equipped with two detectors and is a high-sensitive fixed system designed for permanent installation and providing continuous radiation detection and monitoring of vehicles, cargo containers, people, or packages.

The **PoliGate™ Light series** is a simplified series of Polimaster RPMs that is available in a **more compact and lightweight design** and its detection blocks can be mounted on a frame or wall.

Features

- Lightweight design
- Control zone up to 6 m x 2 m (W x H)
- Wide gamma energy range from 20 keV to 3 MeV
- No stop of an object is required for the inspection
- Lead shielding for natural background rejection
- Ingress protection IP55
- Local and remote light and audible alarm annunciators
- Back-up battery providing at least 8 hours of operation
- Presence detection system (occupancy sensors)
- Adjustable sensitivity parameters for specific applications
- Optional video surveillance system





Poligate Light G4 RPM

Lightweight double-sided model equipped with four gamma detectors.

The **PoliGate™ Light G4** is a double-sided **gamma-only** Radiation Portal Monitor (RPM) equipped with four detectors and is a high-sensitive fixed system designed for permanent installation and providing continuous radiation detection and monitoring of vehicles, cargo containers, people, or packages.

The **PoliGate™ Light series** is a simplified series of Polimaster RPMs that is available in a **more compact and lightweight design** and its detection blocks can be mounted on a frame or wall.

Features

- Lightweight design
- Control zone up to 6 m x 4.5 m (W x H)
- Wide gamma energy range from 20 keV to 3 MeV
- No stop of an object is required for the inspection
- Lead shielding for natural background rejection
- Ingress protection IP55
- Local and remote light and audible alarm annunciators
- Back-up battery providing at least 8 hours of operation
- Presence detection system (occupancy sensors)
- Adjustable sensitivity parameters for specific applications
- Optional video surveillance system



← [Back to partner](#)



Détection des radiations > Moniteurs de portail

Poligate Pedestrian GN1 RPM

One-sided gamma-neutron model equipped with one gamma (6.6L) and one neutron detector.

The **PoliGate™ Pedestrian GN1** is a one-sided **gamma-neutron** Radiation Portal Monitor (RPM) equipped with one 6.6L-gamma and one neutron detector and is a **high-sensitive fixed system** designed for permanent installation and monitoring of people or packages for the presence of radioactive materials.

The **PoliGate™ Pedestrian series** is an essential component of any facility that requires strict security measures, including government buildings, research facilities, and nuclear power plants. The compact and ergonomic design of the RPM makes it a convenient solution for use in various applications for screening **people, luggage, and cargo**.



Features

- IEC 62244:2019 compliance
- Control zone up to 1.5 x 2 (W x H)
- Wide gamma energy range from 20 keV to 3 MeV
- No stop of an object is required for the inspection
- Lead shielding for natural background rejection
- Ingress protection IP65
- Local and remote light and audible alarm annunciators
- Back-up battery providing at least 8 hours of operation
- Presence detection system (occupancy sensors)
- Adjustable sensitivity parameters for specific applications
- Optional video surveillance system

← [Back to partner](#)



Détection des radiations > Moniteurs de portail

Poligate Deployable RPM

Gamma-only model transported in plastic protective cases and designed for fast deployment.

The **PoliGate™ Deployable** is a **gamma-only** Radiation Portal Monitor (RPM) highly sensitive **deployable radiation monitor** designed to detect radioactive and nuclear materials transported through a controlled area.

This fast deployable RPM is designed to provide high mobility and flexibility, allowing it to be used in various settings to **screen individuals, vehicles, or cargo at the scene of an incident or in temporary screening situations** such as at major public mass events.



Features

- No stop of an object is required for the inspection
- Lead shielding for natural background rejection
- Wide gamma energy range from 30 keV to 3 MeV
- Local and remote light and audible alarm annunciators
- Back-up battery providing at least 8 hours of operation
- Presence detection system (occupancy sensors)
- Adjustable sensitivity parameters for specific applications
- Optional video surveillance system
- Optional Ethernet / Wi-Fi connection



Poligate Pedestrian G2 RPM

Double-sided gamma model equipped with two (11L each) gamma detectors.

The **PoliGate™ Pedestrian G2** is a double-sided **gamma-only** Radiation Portal Monitor (RPM) equipped with two 11L-gamma detectors and is a **high-sensitive fixed system** designed for permanent installation and monitoring of people or packages for the presence of radioactive materials.

The **PoliGate™ Pedestrian series** is an essential component of any facility that requires strict security measures, including government buildings, research facilities, and nuclear power plants. The compact and ergonomic design of the RPM makes it a convenient solution for use in various applications for screening **people, luggage, and cargo**.



Features

- IEC 62244:2019 compliance
- Control zone up to 1.5 x 2 (W x H)
- Wide gamma energy range from 20 keV to 3 MeV
- No stop of an object is required for the inspection
- Lead shielding for natural background rejection
- Ingress protection IP65
- Local and remote light and audible alarm annunciators
- Back-up battery providing at least 8 hours of operation
- Presence detection system (occupancy sensors)
- Adjustable sensitivity parameters for specific applications
- Optional video surveillance system

← [Back to partner](#)



Détection des radiations > Moniteurs de portail

Poligate Vehicle G4N4 RPM

Double-sided gamma-neutron model equipped with four gamma and four neutron detectors.

The **PoliGate™ Vehicle G4N4** is a double-sided **gamma-neutron** Radiation Portal Monitor (RPM) equipped with four 11L-gamma and four neutron detectors and is a **high-sensitive fixed system** designed for permanent installation and providing continuous radiation detection and monitoring of moving objects.

The **PoliGate™ Vehicle series** is an essential tool for safeguarding against the potential threat of nuclear materials entering secure areas and can be used for screening **trains, trucks, vehicles, cargo containers, luggage, and people**.

Features

- IEC 62244:2019 compliance
- Control zone up to 6 x 4.5 (W x H)
- Wide gamma energy range from 20 keV to 3 MeV
- No stop of an object is required for the inspection
- Lead shielding for natural background rejection
- Ingress protection IP65
- Local and remote light and audible alarm annunciators
- Back-up battery providing at least 8 hours of operation
- Presence detection system (occupancy sensors)
- Adjustable sensitivity parameters for specific applications
- Optional video surveillance system





Poligate Vehicle G2 RPM

Double-sided gamma model equipped with two gamma detectors.

The **PoliGate™ Vehicle G2** is a double-sided **gamma-only** Radiation Portal Monitor (RPM) equipped with two 11L-gamma detectors and is a **high-sensitive fixed system** designed for permanent installation and providing continuous radiation detection and monitoring of moving objects.

The **PoliGate™ Vehicle series** is an essential tool for safeguarding against the potential threat of nuclear materials entering secure areas and can be used for screening **trucks, vehicles, cargo containers, luggage, and people**.

Features

- IEC 62244:2019 compliance
- Control zone up to 6 x 2 (W x H)
- Wide gamma energy range from 20 keV to 3 MeV
- No stop of an object is required for the inspection
- Lead shielding for natural background rejection
- Ingress protection IP65
- Local and remote light and audible alarm annunciators
- Back-up battery providing at least 8 hours of operation
- Presence detection system (occupancy sensors)
- Adjustable sensitivity parameters for specific applications
- Optional video surveillance system





Partner **Radiation Solutions Inc.**



Radiation Solutions Inc. (RSI) est une entreprise canadienne spécialisée dans les systèmes avancés de détection et de surveillance des rayonnements, notamment les portiques de surveillance pour diverses applications. Ses technologies sont conçues pour garantir la sécurité et la conformité dans des secteurs tels que l'acier, la ferraille, le recyclage et la sécurité frontalière.

Product offering


**RS-200 / 3000
Radiation Portal
Monitoring Systems
(Radiation Solutions)**



**RS-200 / 6000
Radiation Portal
Monitoring Systems
(Radiation Solutions)**



**RS-200 / 10000
Radiation Portal
Monitoring Systems
(Radiation Solutions)**



**RS-300 Radiation
Portal Monitoring
Systems (Radiation
Solutions)**



**RS-400 Radiation
Portal Monitoring
Systems (Radiation
Solutions)**





Détection des radiations > Moniteurs de portail

RS-200 / 3000 Radiation Portal Monitoring Systems (Radiation Solutions)

Les systèmes RS-200 (Radiation Solutions) sont 2 systèmes entièrement numériques basés sur PMT spécialement conçus pour les conditions de fonctionnement difficiles des usines de traitement de la ferraille et de l'aluminium. Ces systèmes combinent des performances exceptionnelles avec un minimum de fausses et de fausses alarmes grâce à une conception numérique avancée et à une analyse spectrale.



Le système est entièrement modulaire, ce qui le rend facilement configurable pour s'adapter à la logistique locale et permet une maintenance rapide et facile. Le système fonctionne de manière indépendante et dispose d'une connectivité Ethernet directe aux réseaux de l'usine. Cette connectivité permet une conception d'usine entièrement intégrée avec la possibilité d'une vue d'ensemble RSO sur tous les systèmes installés.

Caractéristiques des systèmes de surveillance du portail de rayonnement RS-200/3000 :

- volume du détecteur : 1 512 po3 (23,5 L) – maximum 16 détecteurs
- conception du système entièrement numérique – aucun ajustement par l'utilisateur
- 2 Technologie PMT pour une sensibilité élevée + rejet élevé du bruit Taux d'échantillonnage des données de 10/s pour une analyse optimale des données
- système avancé de spectromètre à 4096/128 canaux pour une analyse améliorée
- l'analyse spectrale permet de rejeter la majorité des fausses alarmes, de pluie et de vide répandues dans la plupart des systèmes sans réduire la sensibilité du système
- classification des alarmes pour trier les alarmes en catégories de rebuts et de non-rebuts pour un meilleur contrôle
alarmes intempestives minimales grâce au filtrage avancé des signaux et à la reconnaissance des formes
- analyse de sensibilité du système et correction automatique pour minimiser la perte de signal sans aucune source
- radioactive requise pour tester les performances du système
- Écran tactile couleur 15" pour une interface utilisateur facile
- imprimante locale pour l'impression des alarmes
- Connexion GPS pour une localisation et un timing précis
- connexion directe au réseau de l'usine permettant une vue d'ensemble RSO de toutes les alarmes sur tous les systèmes
rapport d'erreurs en temps réel (1/sec) au service RSI via Internet pour une assistance rapide et une vue d'ensemble du système
- Fonctionnement 48 V pour minimiser les chutes de tension sur les longs câbles
- conception de système modulaire pour un service facile sur site par le personnel local pour un

support de service « instantané »

- Assistance technique 24h/24 et 7j/7 pour une assistance rapide et réactive de la part de techniciens si nécessaire



Détection des radiations > Moniteurs de portail

RS-200 / 6000 Radiation Portal Monitoring Systems (Radiation Solutions)

Les systèmes RS-200 sont des systèmes entièrement numériques basés sur 2 PMT spécialement conçus pour les conditions de fonctionnement difficiles des usines de traitement de la ferraille et de l'aluminium. Ces systèmes combinent des performances exceptionnelles avec un minimum de fausses et de fausses alarmes grâce à une conception numérique avancée et à une analyse spectrale.

Le système est entièrement modulaire, ce qui le rend facilement configurable pour s'adapter à la logistique locale et permet une maintenance rapide et facile. Le système fonctionne de manière indépendante et dispose d'une connectivité Ethernet directe aux réseaux de l'usine. Cette connectivité permet une conception d'usine entièrement intégrée avec la possibilité d'une vue d'ensemble RSO sur tous les systèmes installés.



Caractéristiques des systèmes de surveillance du portail de rayonnement RS-200/6000 :

- volume du détecteur : 3 000 po³ (24 L) – maximum 16 détecteurs
- conception du système entièrement numérique – aucun ajustement par l'utilisateur
- 2 Technologie PMT pour une sensibilité élevée + rejet élevé du bruit Taux d'échantillonnage des données de 10/s pour une analyse optimale des données
- système avancé de spectromètre à 4096/128 canaux pour une analyse améliorée
- l'analyse spectrale permet de rejeter la majorité des fausses alarmes, de pluie et de vide répandues dans la plupart des systèmes sans réduire la sensibilité du système
- classification des alarmes pour trier les alarmes en catégories de rebuts et de non-rebuts pour un meilleur contrôle
- alarmes intempestives minimales grâce au filtrage avancé des signaux et à la reconnaissance des formes
- analyse de sensibilité du système et correction automatique pour minimiser la perte de signal sans aucune source
- radioactive requise pour tester les performances du système
- Écran tactile couleur 15" pour une interface utilisateur facile
- imprimante locale pour l'impression des alarmes
- Connexion GPS pour une localisation et un timing précis
- connexion directe au réseau de l'usine permettant une vue d'ensemble RSO de toutes les alarmes sur tous les systèmes
- rapport d'erreurs en temps réel (1/sec) au service RSI via Internet pour une assistance rapide et une vue d'ensemble du système
- Fonctionnement 48 V pour minimiser les chutes de tension sur les longs câbles


- conception de système modulaire pour un service facile sur site par le personnel local pour un support de service « instantané »
- Assistance technique 24h/24 et 7j/7 pour une assistance rapide et réactive de la part de techniciens si nécessaire



Détection des radiations > Moniteurs de portail

RS-200 / 10000 Radiation Portal Monitoring Systems (Radiation Solutions)

Les systèmes RS-200 sont des systèmes entièrement numériques basés sur 2 PMT spécialement conçus pour les conditions de fonctionnement difficiles des usines de traitement de la ferraille et de l'aluminium. Ces systèmes combinent des performances exceptionnelles avec un minimum de fausses et de fausses alarmes grâce à une conception numérique avancée et à une analyse spectrale.



Le système est entièrement modulaire, ce qui le rend facilement configurable pour s'adapter à la logistique locale et permet une maintenance rapide et facile. Le système fonctionne de manière indépendante et dispose d'une connectivité Ethernet directe aux réseaux de l'usine. Cette connectivité permet une conception d'usine entièrement intégrée avec la possibilité d'une vue d'ensemble RSO sur tous les systèmes installés.

Caractéristiques des systèmes de surveillance du portail de rayonnement RS-200/10000 :

- volume du détecteur : 5 000 po3 (73 L) - maximum 16 détecteurs
- conception du système entièrement numérique - aucun ajustement par l'utilisateur
- 2 Technologie PMT pour une sensibilité élevée + rejet élevé du bruit Taux d'échantillonnage des données de 10/s pour une analyse optimale des données
- système avancé de spectromètre à 4096/128 canaux pour une analyse améliorée
- l'analyse spectrale permet de rejeter la majorité des fausses alarmes, de pluie et de vide répandues dans la plupart des systèmes sans réduire la sensibilité du système
- classification des alarmes pour trier les alarmes en catégories de rebuts et de non-rebuts pour un meilleur contrôle
- alarmes intempestives minimales grâce au filtrage avancé des signaux et à la reconnaissance des formes
- analyse de sensibilité du système et correction automatique pour minimiser la perte de signal sans aucune source
- radioactive requise pour tester les performances du système
- Écran tactile couleur 15" pour une interface utilisateur facile
- imprimante locale pour l'impression des alarmes
- Connexion GPS pour une localisation et un timing précis

- connexion directe au réseau de l'usine permettant une vue d'ensemble RSO de toutes les alarmes sur tous les systèmes
- rapport d'erreurs en temps réel (1/sec) au service RSI via Internet pour une assistance rapide et une vue d'ensemble du système
- Fonctionnement 48 V pour minimiser les chutes de tension sur les longs câbles
- conception de système modulaire pour un service facile sur site par le personnel local pour un support de service « instantané »
- Assistance technique 24h/24 et 7j/7 pour une assistance rapide et réactive de la part de techniciens si nécessaire



Détection des radiations > Moniteurs de portail

RS-300 Radiation Portal Monitoring Systems (Radiation Solutions)

Le système RS-300 est un système entièrement numérique à super-coïncidence basé sur 3PMT, spécialement conçu pour les conditions de fonctionnement difficiles de nombreuses usines de traitement de l'acier et de la ferraille. Ce système utilise des détecteurs de volume moyen pour une bonne couverture du véhicule. De plus, afin de permettre un remplacement et des mises à niveau faciles, les détecteurs sont identiques en termes de taille aux détecteurs les plus couramment utilisés sur le terrain aujourd'hui.



Le système est entièrement MODULAIRE pour le rendre facilement configurable en fonction de la logistique locale. Le système fonctionne de manière indépendante mais dispose d'une connectivité Ethernet directe aux réseaux de l'usine, ce qui permet une conception d'usine entièrement intégrée avec une vue d'ensemble RSO sur tous les systèmes installés. La connectivité USB/série permet également une configuration du système adaptée aux besoins des utilisateurs en matière d'écrans locaux, d'imprimantes locales ou réseau, d'intégration informatique à grande échelle, etc.

Caractéristiques des systèmes de surveillance du portail de rayonnement RS-300 :

- Assemblages de détecteurs de 3 000 pouces cubes (3 024 pouces cubes réels) – maximum 16 détecteurs
- conception du système entièrement numérique – pas de réglages utilisateur compliqués
- Technologie 3 PMT pour une sensibilité élevée + un rejet de bruit élevé
- Taux d'échantillonnage des données de 10/s pour une analyse optimale des données
- système avancé de spectromètre à 128 canaux
- analyse NASVD spectrale complète pour une sensibilité élevée avec pratiquement aucune fausse alarme
- essentiellement aucune alarme de vide et de pluie grâce à une analyse spectrale avancée
- mise en réseau entièrement intégrée pour l'intégration dans le réseau de l'usine
- capteurs optiques quadruples avec échantillonnage de données à 500 Hz pour une détection précise du véhicule
- Écran tactile couleur de 12" ou 15" pour une interface utilisateur facile
- classification des alarmes si nécessaire pour trier les alarmes en rebuts et non-rebuts
- Fonctionnement 48 V pour minimiser les chutes de tension sur les longs câbles
- connexion automatique au centre de service RSI via Internet pour une assistance rapide
- Logiciel RSO fourni pour l'analyse des alarmes directement depuis le bureau RSO
- rapport d'erreurs en temps réel (1/sec) au service RSI via Internet pour une assistance rapide
- surveillance automatique de la sensibilité du système avec correction automatique du gain
- conception de système modulaire pour un entretien facile

Modèles disponibles :

- RS-300/6000 = système à 2 détecteurs
- RS-300/9000 = système à 3 détecteurs
- RS-300/12000 = système à 4 détecteurs
- RS-300/15000 = système à 5 détecteurs
- RS-300/18000 = système à 6 détecteurs
- RS-300/21000 = système à 7 détecteurs
- RS-300/24000 = système à 8 détecteurs



Détection des radiations > Moniteurs de portail

RS-400 Radiation Portal Monitoring Systems (Radiation Solutions)

Le système RS-400 est un système entièrement numérique à super-coïncidence basé sur 4PMT, spécialement conçu pour les conditions de fonctionnement difficiles de nombreuses usines de traitement de l'acier et de la ferraille. Ce système utilise des détecteurs de grand volume pour une couverture optimale du véhicule. Ces longs détecteurs souffrent considérablement de perte de signal en utilisant la technologie conventionnelle, c'est pourquoi RSI a développé une technologie 4PMT utilisant des PMT aux DEUX extrémités du détecteur pour une collecte de signal et une forme spectrale considérablement améliorées.



Le système est entièrement MODULAIRE pour le rendre facilement configurable en fonction de la logistique locale. Le système fonctionne de manière indépendante mais dispose d'une connectivité Ethernet directe aux réseaux de l'usine, ce qui permet une conception d'usine entièrement intégrée avec une vue d'ensemble RSO sur tous les systèmes installés. La connectivité USB/série permet également la configuration du système pour répondre aux besoins des utilisateurs en matière d'écrans locaux, d'imprimantes locales ou réseau, d'intégration informatique à grande échelle, etc.

Caractéristiques des systèmes de surveillance du portail de rayonnement RS-400 :

- Assemblages de détecteurs de 5 000 pouces cubes (4 698 pouces cubes réels) – maximum 16 détecteurs
- conception du système entièrement numérique – pas de réglages utilisateur compliqués
- Technologie 4 PMT pour une sensibilité élevée + un rejet de bruit élevé sur les détecteurs longs
- Taux d'échantillonnage des données de 10/s pour une analyse optimale des données
- système avancé de spectromètre à 128 canaux
- analyse NASVD spectrale complète pour une sensibilité élevée avec pratiquement aucune fausse alarme
- essentiellement aucune alarme de vide et de pluie grâce à une analyse spectrale avancée
- mise en réseau entièrement intégrée pour l'intégration dans le réseau de l'usine
- capteurs optiques quadruples avec échantillonnage de données à 500 Hz pour une détection précise du véhicule
- Écran tactile couleur de 12" ou 15" pour une interface utilisateur facile
- classification des alarmes si nécessaire pour trier les alarmes en rebuts et non-rebuts
- Fonctionnement 48 V pour minimiser les chutes de tension sur les longs câbles
- connexion automatique au centre de service RSI via Internet pour une assistance rapide
- Logiciel RSO fourni pour l'analyse des alarmes directement depuis le bureau RSO
- rapport d'erreurs en temps réel (1/sec) au service RSI via Internet pour une assistance rapide

- surveillance automatique de la sensibilité du système avec correction automatique du gain
- conception de système modulaire pour un entretien facile

Modèles disponibles :

- RS-400/10000 = système à 2 détecteurs
- RS-400/15000 = système à 3 détecteurs
- RS-400/20000 = système à 4 détecteurs
- RS-400/25000 = système à 5 détecteurs
- RS-400/30000 = système à 6 détecteurs
- RS-400/35000 = système à 7 détecteurs
- RS-400/40000 = système à 8 détecteurs



Partner **Ludlum Measurements**



Ludlum Measurements, Inc. conçoit et fabrique des instruments et des technologies de détection des rayonnements. Fondée en 1962, elle propose une large gamme d'instruments de détection de rayonnements, développés pour aider à surveiller la sécurité du personnel et de l'environnement. Les instruments sont utilisés dans des applications telles que la surveillance de routine du personnel et du matériel, la sécurité des frontières et les situations d'intervention d'urgence.

Product offering

**Model 4525 Series
Radiation Portal
Monitor**



**Model 4525-5000
Radiation Portal
Monitor - Ludlum**



**Model 4525-7000
Radiation Portal
Monitor - Ludlum**



**Model 4530 Series
Radiation Portal
Monitor**



**Model 375P-3500
Conveyor Monitor -
Ludlum**



**Model 52-8 Series
Outdoor Portal
Monitor**



← **Back to partner**



Détection des radiations > Moniteurs de portail

Model 4525 Series Radiation Portal Monitor

All Model 4525 systems with 57 L (3500 in³) detectors now come with new 5th generation NEMA 4 enclosures.

The new enclosures are manufactured with a 14-gauge carbon steel body and a 2 mm (0.080 in.) aluminum door for increased sensitivity. Using stainless steel concealed hinges and quarter turn latches for easy accessibility, they are 70 mm (2.75 in.) slimmer than the previous generation, reducing waste and cost.

Ask about our NEMA 4X stainless steel upgrade option for increased corrosion protection!

The Model 4525 Series of Radiation Portal Monitors (RPMs) represents state-of-the-art technology for detecting low levels of radiation, such as orphan radiation sources and NORM (naturally occurring radioactive materials), at facilities including scrap yards, recycling companies, landfills, and foundries. These systems are composed of ruggedized, large plastic scintillation detectors optimally arranged to monitor items passing through. Each system can be configured with two to six large detectors, with individual detector volumes of 9.8 L (600 in³), 41 L (2500 in³), or 57 L (3500 in³).

Real-time data acquisition and analysis is performed directly at each detector system and then reported to a central PC for logging, reporting, and alarm notification. Up to four detector systems (lanes) can be networked together via Ethernet or wirelessly to a central PC so that vehicles entering from either direction can be monitored in real time. An optional remote control/annunciator panel is available to support operator awareness, alarm acknowledgement, and if necessary, backup operation in the event the central PC is unavailable.

Data from all the system sensors are acquired and checked by powerful, field-tested, and time-proven algorithms designed to check each load vigorously in a multi-dimensional and multi-layered manner before declaring any load as clean. Any abnormality is immediately indicated via both local and remote alarms. An optional camera system can capture an image of the offending vehicle and store the image with the logged data for permanent record keeping. Alarms can also be configured to automatically notify shift supervisors directly by e-mail if desired.



The system is designed for ease of use and can be customized to accommodate a wide variety of site and application specific criteria. Intuitive menus and controls combined with pre-defined automatic event handlers ensure each situation is handled properly and consistently.

Features


- Use to Monitor Trucks, Rail Cars, Personal Vehicles, etc.
- Large, Highly Sensitive, Industrial Duty Plastic Scintillation Detectors
- Reliable Operation with Very Low False Positives
- Flexible Configurations Accommodate Up to Four Lanes, Each with Two to Six Detectors
- Real-time Central Data Logging, Reporting, and Alarm Notification
- Bi-Directional Entry
- User-Friendly Operation
- Excellent Service and 24-Hour Tech Support
- 8-hour Battery Backup in Event of Power Loss
- Modular and Upgradeable
- Variety of Options to Customize the System to Meet Your Needs
- Made in USA



Détection des radiations > Moniteurs de portail

Model 4525-5000 Radiation Portal Monitor - Ludlum

La série Ludlum 4525-Generation IV de moniteurs de portail de rayonnement (RPM) récemment reconfigurée représente une technologie de pointe pour détecter les sources de rayonnement orphelines et les NORM. Les systèmes révisés sont évolutifs, avec un coût de possession inférieur et représentent un prix d'achat initial inférieur.



La série Gen IV de systèmes RPM est constituée de grands systèmes de scintillation en plastique robustes qui peuvent être disposés de manière optimale pour surveiller les véhicules en mouvement entrant dans le système. Chaque système de détecteurs peut être configuré avec deux à six grands détecteurs.

Caractéristiques du moniteur de portail de rayonnement modèle 4525-5000 :

- Enregistrement central des données en temps réel, notification d'alarme et reporting
- fonctionnement convivial
- Détecteurs industriels de grande taille et haute sensibilité
- système évolutif et modulaire
- 2 systèmes de détection
- entrée bidirectionnelle
- enregistre les images du véhicule et les captures de caméra (facultatif)
- Scintillateur en plastique EJ-200

En savoir plus sur le moniteur de portail de rayonnement modèle 4525-5000 sur le site Web de Ludlum



Détection des radiations > Moniteurs de portail

Model 4525-7000 Radiation Portal Monitor - Ludlum

Le moniteur de portail de rayonnement (RPM) Ludlum 4525-7000 représente une technologie de pointe pour détecter les sources de rayonnement orphelines. Ludlum a vendu plus de 800 de ces types de systèmes à travers le monde à des casses, des entreprises de recyclage, des décharges et des fonderies. Les détecteurs de la série modèle 4525 sont de grands systèmes à scintillation en plastique robustes qui peuvent être disposés de manière optimale pour surveiller les véhicules en mouvement entrant dans le système.



Caractéristiques du moniteur de portail de rayonnement modèle 4525-7000 :

- Enregistrement et reporting centralisés des données en temps réel
- Câble CAT 5e de 76,2 m (250 pieds)
- double capteurs de présence/vitesse
- panneau annonciateur à distance
- entrée bidirectionnelle
- capture d'image de la caméra et stockage dB (en option)
- mode wagon
- deux détecteurs à scintillateurs en plastique protégés contre les intempéries

En savoir plus sur le moniteur à portail de rayonnement modèle 4525-7000 sur le site Web de Ludlum



Détection des radiations > Moniteurs de portail

Model 4530 Series Radiation Portal Monitor



The Model 4530 Series of Radiation Portal Monitors (RPMs) represents state-of-the-art technology for detecting low levels of radiation, such as orphan radiation sources and NORM (naturally occurring radioactive materials), at facilities including scrap yards, recycling companies, landfills, and foundries. These systems are composed of ruggedized, large plastic scintillation detectors optimally arranged to monitor items passing through. Each system can be configured with one to six large detectors, with individual detector volumes of 39.7 L (2117 in³) or 57 L (3500 in³).

Real-time data acquisition and analysis is performed directly at each detector system and then reported to the internal PC for logging, reporting, and alarm notification. Up to four detector systems (lanes) can be networked together via Ethernet or wirelessly to a central PC so that vehicles entering from either direction can be monitored in real time. An optional remote control/annunciator panel is available to support operator awareness, alarm acknowledgement, and if necessary, backup operation in the event the internal PC is unavailable.

Data from all the system sensors are acquired and checked by powerful, field-tested, and time-proven algorithms designed to check each load vigorously in a multi-dimensional and multi-layered manner before declaring any load as clean. Any abnormality is immediately indicated via both local and remote alarms. An optional camera system can capture an image of the offending vehicle and store the image with the logged data for permanent record keeping. Alarms can also be configured to automatically notify shift supervisors directly by e-mail if desired.

The system is designed for ease of use and can be customized to accommodate a wide variety of site and application specific criteria. Intuitive menus and controls combined with pre-defined automatic event handlers ensure each situation is handled properly and consistently.

All of the main components of these systems are manufactured in-house in the USA.

Features

- Made in USA
- Monitor Trucks, Rail Cars, Personal Vehicles, etc.

- Large, Highly Sensitive, Industrial Duty Plastic Scintillation Detectors
- Reliable Operation with Very Low False Positives
- Flexible Configurations Accommodate Up to Four Lanes, Each with One to Six Detectors
- Real-time Central Data Logging, Reporting, and Alarm Notification
- Bi-Directional Entry
- User-Friendly Operation
- Excellent Factory Service and 24-Hour Tech Support
- Modular and Upgradeable
- Variety of Options to Customize the System to Meet Your Needs

Retrofit Option

Ludlum Measurements offers the option to retrofit existing portal monitor systems with the electronics and software used in our Model 4530 Series Radiation Portal Monitors, including systems manufactured by our competitors. Retrofitting allows you to upgrade an aging system without having to purchase new detector housings and stands. Besides our own systems, Ludlum has experience retrofitting systems manufactured by Exploranium, RadComm, SAIC, Mirion/Canberra, and Thermo. Retrofits are customized to your needs, and can also include replacing the plastic scintillator detectors if necessary.

← **Back to partner**



Détection des radiations > Moniteurs de portail

Model 375P-3500 Conveyor Monitor - Ludlum

The Model 375P-3500 Conveyor Monitor (Ludlum) is a radiation detector system to inspect materials at contamination on a conveyor.



Model 375P-3500 Conveyor Monitor features:

- detector delivers superior sensitivity
- controller can operate totally independently or connected to an ethernet network or wired for remote annunciation
- 57.4 L (3500 in²) plastic detector with 15.2 m cable
- 24-Hour battery backup
- check source (10 μ Ci)
- electronics housed in a NEMA 4X enclosure with external reset button
- see-through viewing window
- weathertight, lead-shielded enclosure

Read more about the Model 375P-3500 Conveyor Monitor on the [Ludlum website](#)

← [Back to partner](#)



Détection des radiations > Moniteurs de portail

Model 52-8 Series Outdoor Portal Monitor

The Model 52-8 is a weather-resistant portable scintillation portal monitor used for beta-gamma radiation monitoring of vehicles, as well as monitoring of personnel. Two plastic scintillation detectors, one per side, are housed in weatherproof, dust-tight, impact-resistant cases with wheels and tow handles. Microprocessor-based electronics are housed in a third case with matching characteristics, plus a mounted On/Off toggle switch and an optional red/green strobe light. The system provides high sensitivity for detecting very low levels of radiation coming from personnel or vehicles that move through the portal.



Ease of setup, adjustable audio signals, and user-friendly LCD display that provides detector counts, background levels, and system parameters, and the ability to operate via vehicle cigarette lighter plug or batteries, keep the Model 52-8 applicable to a variety of different situations. This instrument meets the Federal Emergency Management Agency (FEMA) standard for Emergency Management Response Portal Monitoring (FEMA-REP-21).

Features

- Portable Weatherproof Monitor
- Deploys in 5 Minutes
- Vehicle or Personnel Screen Compatibility
- Audible & Visual Alert Signals
- Two Sizes: 15.7 L (960 in³) or 32.7 L (2000 in³)



Partner **Helgeson Scientific Services (HSS)**



Helgeson Scientific Services (HSS) conçoit et fabrique des systèmes avancés de surveillance des radiations axés sur la sécurité du personnel, la protection des installations et le contrôle des déchets. Sa gamme comprend des moniteurs corporels, des systèmes de détection par portique et des solutions de gestion des déchets, tous développés pour garantir la manipulation sûre des matières radiologiques dans des environnements critiques.

Product offering

**HS-VGAM - Portal
vehicle for scrap
yards**



**HS-PORT - Portable
Gamma Portal
monitor for personnel
and vehicles**



HS-PoNaI



[← Back to partner](#)



Détection des radiations > Moniteurs de portail

HS-VGAM - Portal vehicle for scrap yards

The HS-VGAM unit is an automated multitasking device, designed for the detection and measurement of gamma radiation on potentially exposed material, transported in vehicles.

It is particularly suitable for the detection of radioactive sources in loads of raw materials, scrap and waste materials.



[← Back to partner](#)



Détection des radiations > Moniteurs de portail

HS-PORT - Portable Gamma Portal monitor for personnel and vehicles

The HS-PORT has been designed for the detection and measurement of gamma radiation on potentially contaminated personnel, vehicles, etc.

It has a very fast deployment (one person in 2 minutes) and can be used in several applications like emergency response, monitoring of critical facilities, monitoring of events like concerts, sport events, etc. The system is operated remotely with a mobile phone or laptop without any additional cable connection.





Détection des radiations > Moniteurs de portail

HS-PoNaI

- Detectors:
 - NaI scintillation detector (can be customized: CsI, LaBr, CeBr, etc.)
 - Number of detectors: 1 detector (can be upgraded to 2 detectors)
 - Detector size: 4x4x16 inches (3x5x16" also available)
 - Energy range: 40 keV - 3 MeV
- Electronics:
 - Plug-in MCA with 2048 channels
 - Automatic gain stabilization
- Other features:
 - PC with Windows 11
 - Software for isotope identification and quantification
 - Spectrums displayed in real time, can be saved to be analyzed later
 - GPS
 - Hard disk memory up to 125 Gb
 - Remote connection with tablets, PCs, etc.
 - Dimensions: 730 x 160 x 170 mm approx.
 - Weight: 25 kg
 - Power: 220 - 115 V , 10 - 36 VDC
 - Battery bank to work autonomously
 - IP67



HS-PoNaI is a fantastic solution for a quick and efficient **in-situ isotope identification** in different applications. It is a strong and customizable equipment with a very simple and intuitive operation thanks to its automatic isotope identification and quantification software. It is equipped with a 4 liters NaI detector (4x4x16"), and all electronics are installed inside a PeliCase providing IP67 protection. Communication can be done remotely via tablet or another device.

SYSTÈMES DE DÉTECTION MOBILE DES RAYONNEMENTS





Partner **Else Nuclear**



ELSE NUCLEAR S.r.l. is an Italian OEM company specializing in advanced radiation-detection and environmental-monitoring systems for nuclear safety, industry and research.

Product offering





SATURN 5702

SATURN 5702 is a mobile station equipped with two detectors for gamma and neutron dose rate monitoring. The station includes:

- Ion-chamber-based gamma radiation monitoring unit: ICP-T or ICP-T-PF
- Neutron rem counter for pulsed fields: LUPIN BF3



The detectors and the electronics are housed in a trolley-mounted mechanical structure. The height of the trolley can be customized according to the customer needs, for example to centre the detectors with the beam line height.

Each detector can be removed from the trolley to be employed remotely, up to 20 m. An ALU alarm column is mounted on the top, providing luminous and acoustic warning signals related to the status of the mobile station (good functioning, pre-alarm and alarm). SATURN 5702 stations can also manage external devices through 4 sets of relay contacts.

The detectors are connected via external cables to a standard 19" electronics rack equipped with two dedicated SATURN ratemeter units (rack version). Each ratemeter features a display, 3 function keys with status LEDs, and a connector for TOUCHKEY2 external keyboard.

SATURN 5702 can be connected to a remote host PC running a data management software (5700 sMON) through ETH or RS485/422 connection.



Partner **Polimaster**



Polimaster est un leader mondial des solutions de détection et de surveillance des rayonnements. Il propose une gamme complète d'instruments conçus pour détecter, identifier et mesurer les rayonnements ionisants dans divers environnements. Sa gamme de produits comprend des détecteurs portables, des dosimètres électroniques personnels, des identificateurs isotopiques portables, des portiques de détection et des systèmes de détection mobiles, tous conçus pour répondre aux exigences rigoureuses des secteurs de la sécurité, des interventions d'urgence et des applications industrielles.

Product offering

**PoliGate™ Mobile
MDS**



**PoliPack® G-S
Backpack Radiation
Detector**



**PoliPack® GN
Backpack Radiation
Detector**



**PoliPack® G
Backpack Radiation
Detector**



**PoliPack® GN-S
Backpack Radiation
Detector**





PoliGate™ Mobile MDS

Vehicle-based radiation portal monitors for detection on the go.

The **PoliGate™ Mobile MDS** is a complex solution designed for the **automatic scanning of fixed or mobile objects** to detect illicit trafficking of radioactive substances and materials. The vehicle-integrated system is highly customizable and available in numerous modifications to cater to the specific requirements of the customers. The vehicle model used for the MDS can differ depending on the needs of the user.

When it comes to securing borders, emergency response, and any situation where rapid response is vital, the PoliGate™ Mobile is a game-changer. Its mobile design allows for **quick deployment at strategic locations**, enabling an efficient inspection (detection, localization, measurement, and identification) of vehicles, cargo, and pedestrians for potential radioactive threats in any place.



← [Back to partner](#)



Détection des radiations > Moniteurs portables

PoliPack® G-S Backpack Radiation Detector

Spectroscopic Gamma-only Backpack Radiation Detector.

The **PoliPack® G-S** is a **gamma-only** Backpack-Based Radiation Detection System (BRD) equipped with spectroscopic gamma detectors for identifying radionuclides. It is carried in a compact backpack and controlled remotely via the wired control unit or a smartphone with the free Polismart® iOS and Android App.

The **PoliPack® BRDs** are rugged, lightweight, and fast-deploying devices that provide prompt and reliable detection, location, and identification of multiple and masked isotopes. The device is ideal for undercover radiation surveys in crowded areas, addressing the problems of orphaned and maliciously introduced sources and ensuring security before and during mass events. Radionuclides libraries are uploaded in the BRD and can be customized by users.



← [Back to partner](#)



Détection des radiations > Moniteurs portables

PoliPack® GN Backpack Radiation Detector

Gamma-Neutron Backpack Radiation Detector.

The **PoliPack® GN** is a **gamma-neutron** Backpack-Based Radiation Detection System (BRD) equipped with a highly sensitive portable radiation monitor carried in a compact backpack and controlled remotely via the wired control unit or a smartphone with the free Polismart® iOS and Android App.

The **PoliPack® BRDs** are rugged, lightweight, and fast deployable devices that provide prompt and reliable detection, location, and identification of multiple and masked isotopes. The device is ideal for undercover radiation surveys in crowded areas, addressing the problems of orphaned and maliciously introduced sources and ensuring security before and during mass events.



← [Back to partner](#)



Détection des radiations > Moniteurs portables

PoliPack® G Backpack Radiation Detector

Gamma-only Backpack Radiation Detector.

The **PoliPack® G** is a **gamma-only** Backpack-Based Radiation Detection System (BRD) equipped with a highly sensitive portable radiation monitor carried in a compact backpack and controlled remotely via the wired control unit or a smartphone with the free Polismart® iOS and Android App.

The **PoliPack® BRDs** are rugged, lightweight, and fast-deploying devices that provide prompt and reliable detection, location, and identification of multiple and masked isotopes. The device is ideal for undercover radiation surveys in crowded areas, addressing the problems of orphaned and maliciously introduced sources and ensuring security before and during mass events.



← [Back to partner](#)



Détection des radiations > Moniteurs portables

PoliPack® GN-S Backpack Radiation Detector

Spectroscopic Gamma-Neutron Backpack Radiation Detector.

The **PoliPack® GN-S** is a **gamma-neutron** Backpack-Based Radiation Detection System (BRD) equipped with **spectroscopic** gamma detectors for identifying radionuclides. It is carried in a compact backpack and controlled remotely via the wired control unit or a smartphone with the free Polismart® iOS and Android App.

The **PoliPack® BRDs** are rugged, lightweight, and fast deployable devices that provide prompt and reliable detection, location, and identification of multiple and masked isotopes. The device is ideal for undercover radiation surveys in crowded areas, addressing the problems of orphaned and maliciously introduced sources and ensuring security before and during mass events. Radionuclides libraries are uploaded in the BRD and can be customized by users.



ÉQUIPEMENT DE RADIOPROTECTION






Partner **RADsafe**

 Les vêtements de radioprotection individuelle RADsafe établissent de nouvelles normes en matière de protection innovante et fiable pour les professionnels de santé du monde entier. Fabriqués selon des normes exceptionnellement élevées, les tabliers RADsafe sont disponibles dans une variété de modèles ergonomiques et unisexes pour une flexibilité et un confort optimaux. Ainsi, si nécessaire, les tabliers RADsafe peuvent être portés plus fréquemment ou plus longtemps en toute sécurité et confortablement.

Product offering

<p>Comfortwear Aprons</p> 	<p>Urology Aprons</p> 	<p>Surgical Drop-Away Aprons</p> 	<p>Maternity Aprons</p> 
<p>RadShield - Apex Series</p> 	<p>RadShield - Zenith Series</p> 	<p>RadShield - Zenith - X Base</p> 	<p>RadShield - Zenith - H Base</p> 

[← Back to partner](#)



Détection des radiations > Équipement de radioprotection

Comfortwear Aprons

The Comfortwear Apron is a flexible fit. Please refer to our apron size measurements to choose your size preference for the required use.

At RadSafe we strive to make our protective aprons simple to apply and remove. Fitting and storage time are critical in the medical industry. The Comfortwear Apron's application time from removing the apron off the storage rack to placing it on the wearer for use is approximately 25 seconds. Additionally, the time from removing the apron off the wearer after use to storing the garment on the storage rack is approximately 20 seconds.

The Comfortwear Apron is ideal for use during short periods of time, particularly for radiology and minor surgeries in addition to nurses and vets.



[← Back to partner](#)



Détection des radiations > Équipement de radioprotection

Urology Aprons

The apron's two vital protective contact points are the shoulders and waist. The Urology Apron is a flexible fit. Please refer to our apron size measurements to choose your size preference for the required use.

At RadSafe we strive to make our protective aprons simple to apply and remove. Fitting and storage time are critical in the medical industry. The application time from removing the apron off the storage rack to placing it on the wearer for use is approximately 25 seconds. Additionally, the time from removing the apron off the wearer after use to storing the garment on the storage rack is approximately 20 seconds.

The Urology Apron is typically worn for urological surgeries or procedures.



← [Back to partner](#)



Détection des radiations > Équipement de radioprotection

Surgical Drop-Away Aprons

The apron's two vital protective contact points are the shoulders and waist. The Surgical Drop-Away Apron is a flexible fit. Please refer to our apron size measurements to choose your size preference for the required use.

At RadSafe we strive to make our protective aprons simple to apply and remove. Fitting and storage time are critical in the medical industry. The application time from removing the apron off the storage rack to placing it on the wearer for use is approximately 25 seconds. Additionally, the time from removing the apron off the wearer after use to storing the garment on the storage rack is approximately 20 seconds.

The Surgical Drop-Away Apron is typically worn for short periods of time. Most suitably worn for radiology and minor surgeries in addition to vets and more.



← [Back to partner](#)



Détection des radiations > Équipement de radioprotection

Maternity Aprons

The apron's three vital protective contact points are the shoulders, underarm and waist. The Maternity Apron is a flexible fit. Please refer to our apron size measurements to choose your size preference for the required use.

At RadSafe we strive to make our protective aprons simple to apply and remove. Fitting and storage time are critical in the medical industry. The application time from removing the apron off the storage rack to placing it on the wearer for use is approximately 50 seconds. Additionally, the time from removing the apron off the wearer after use to storing the garment on the storage rack is approximately 35 seconds.

The Maternity Apron is used during long or short periods of time for procedures in operating theatres, catheter laboratories and more.



← [Back to partner](#)




Détection des radiations > Équipement de radioprotection

RadShield - Apex Series

Mobile radiation protective screens with lead glass viewing panel. Suitable for any environment. Lead equivalence is 2.1 Pb. Height 1990 mm, Depth 650mm.

Screen Types:

- **Type 1:** Width 600mm (310×1000 window) (Narrows to 450mm at top)
- **Type 2:** Width 600mm (460×1000 window)
- **Type 3:** Width 1200mm (1000×500 window)
- **Type 4:** Width 1200mm (1000×1000 window)
- **Type 5:** Width 600mm (no window)
- **Type 6:** Width 1200mm (no window)



← [Back to partner](#)




Détection des radiations > Équipement de radioprotection

RadShield - Zenith Series

Powder coated steel frames, precision TIG welded for years of trouble-free service completely enclosing the leaded glass panel for increased durability and safety. Includes extra support around base unlike competing models.

Screen Types:

- **Type 1:** 1100mm x 1975mm leadlined Radiation Screen
Viewing panel 1000mm x 1800mm.
- **Type 2:** 1100mm x 1975mm leadlined Radiation Screen
Viewing panel 1000 x 1330mm.
- **Type 3:** 1100mm x 1975mm leadlined Radiation Screen
Viewing panel 1000 x 1000mm.
- **Type 4:** 1300mm x 1975mm leadlined Radiation Screen
Viewing panel 1200 x 1000mm.
- **Type 5:** 760mm x 1775mm leadlined Radiation Screen
Viewing panel 660 x 1000mm.



← [Back to partner](#)



Détection des radiations > Équipement de radioprotection

RadShield - Zenith - X Base

Height adjustable mobile personal shield, featuring a RadSafe protective panel supported by a powder coated steel frame with precision TIG welds and medical grade wheels for years of trouble-free service.

Unique shield design for todays users, featuring:

- Stable X Base giving increased usability and handling
- Centralised height adjustment allowing no obstructions above the shield
- Middle mount support allowing ease of left hand, right hand or both
- Medical grade castors (wheels) as standard
- RadSafe lead protective panel as standard

Specifications:

- Shield Size: 1200x500mm
- Shield Protection: 0.5mmPb RadSafe Non-Lead Core
- Frame Width: 840mm at user side, 240mm at patient side
- Frame Depth: 520mm
- Frame Height: 1350mm at lowest, 2000mm at highest
- Height Adjust: Manual pull pin, release, lift and lock



← [Back to partner](#)



Détection des radiations > Équipement de radioprotection

RadShield - Zenith - H Base

Height adjustable mobile personal shield, featuring a RadSafe protective panel supported by a powder coated steel frame with precision TIG welds and medical grade wheels for years of trouble-free service.

Unique shield design for todays users, featuring:

- Angled H Base improving usability and handling
- Centralised height adjustment allowing no obstructions above the shield
- Middle mount support allowing ease of left hand, right hand or both
- Medical grade castors (wheels) as standard
- RadSafe lead protective panel as standard

Specifications:

- Shield Size: 1200x500mm
- Shield Protection: 0.5mmPb RadSafe Non-Lead Core
- Frame Width: 840mm at user side, 240mm at patient side
- Frame Depth: 520mm
- Frame Height: 1350mm at lowest, 2000mm at highest
- Height Adjust: Manual pull pin, release, lift and lock



SOURCES






Partner Spectrum Techniques

Spectrum Techniques Spectrum Techniques est un fournisseur leader de solutions de détection et de mesure des rayonnements, spécialisé dans les équipements de laboratoire et les sources radioactives. Son offre comprend une gamme d'instruments et de détecteurs conçus pour les applications éducatives, de recherche et industrielles.

Product offering

<p>RSS3 Source Set - Spectrum Techniques</p> 	<p>RSS-5 Source Set - Spectrum Techniques</p> 	<p>RSS-8 Source Set - Spectrum Techniques</p> 	<p>Laminated Sources - Spectrum Techniques</p> 
<p>Disc Sources - Spectrum Techniques</p> 	<p>Isotope Generator - Spectrum Techniques</p> 	<p>Tube Sources - Spectrum Techniques</p> 	<p>Needle Sources - Spectrum Techniques</p> 

← [Back to partner](#)



Détection des radiations > Sources

RSS3 Source Set - Spectrum Techniques

The RSS-3 contains 1 each Po-210, Sr-90 and Co-60 emitting a range of alpha, beta and gamma radiation's. This set is ideal for demonstration and introductory nuclear labs covering basic characteristics of radiation. The Co-60 is 1.0 uCi and the Po-210 and Sr-90 are 0.1 uCi activity.

Contact one of our product specialists.



← [Back to partner](#)



Détection des radiations > Sources

RSS-5 Source Set - Spectrum Techniques

Containing 1 each Cs-137, Co-60, Sr-90, Tl-204 and Po-210, the RSS-5 provides a wide of alpha, beta and gamma emissions making it a popular choice for nuclear science instruction. The set contains two beta emitters, two beta/gamma emitters and one alpha source for in-depth studies of radiation. The Cs-137 is 5 uCi, the Po-210 and Sr-90 are 0.1 uCi activity and the Co-60 and Tl-204 are both 1 uCi.

Contact one of our product specialists.



← [Back to partner](#)



Détection des radiations > Sources

RSS-8 Source Set - Spectrum Techniques

Designed for gamma spectroscopy, the RSS-8 contains eight different gamma emitting isotopes covering the entire energy range from 32 to 1333 keV. Also included in the set is a mixed source of Cs-137 and Zn-65 which students may use to identify an “unknown” isotope. The set consists of Ba-133, Cd-109, Co-57, Co-60, Cs-137, Mn-54, Na-22 and Cs/Zn. Source activities are all 1 uCi, except the Cs/Zn source, which is 0.5 uCi Cs and 1 uCi Zn.

Contact one of our product specialists.





Détection des radiations > Sources

Laminated Sources - Spectrum Techniques

Laminate credit card sources are designed to offer a convenient alternative packaging - easy to handle and store - in various industries including, but not limited to:

- **Laboratories:** They are ideal for performing functional checks on gamma counters or spectrometers.
- **Radiation Protection:** Laminate credit card sources can be used for functional checks and periodic verifications of radiation protection probes and systems.
- **Training and Education:** Laminate credit card sources can be used to illustrate fundamental concepts in nuclear physics and radiation science. Students can observe and study radioactive decay, half-life, energy spectra, and interactions of radiation with matter.
- **Security:** Laminate credit card sources are also useful for functional checks and periodic verifications of portable devices used to identify radiological threats and for conducting emergency exercises.



AVAILABLE SIZES

Each credit card source is constructed using 7.5 mil, heavy-weight card stock and is available in one standard size:

- 3.75 x 2.25 inches (95.3 mm x 57.2 mm)

The source material deposit will be 2-3 mm in diameter located at the center of the radiation trefoil.

CALIBRATION OPTIONS

Credit card sources are not available for calibration. The maximum deviation of the delivered activity from the nominal values listed is $\pm 20\%$.

REGULATORY COMPLIANCE

Activities provided will not exceed the U.S. NRC Exempt Quantity limit.

Plastic laminates provide a convenient alternative packaging being easy to handle and store. The standard laminates have a transmission window of 0.005" and produce minimum attenuation for photons and higher energy beta particles.

Two sizes are available, 3.75"x2.25", and a 1" diameter circular disc. Other sizes are available; just let us know and we will send you a quote. Low energy x-ray, beta and alpha sources can be produced with a 80

$\mu\text{g}/\text{cm}^2$ aluminized Mylar window offering excellent transmission for Fe-55, C-14 and Po-210.

Contact one of our product specialists.

← [Back to partner](#)



Détection des radiations > Sources

Disc Sources - Spectrum Techniques

Disc sources are available in 1" and 2" diameter plastic disc with the 1" being standard and other sizes on special order.

The Po-210 alpha source is of open window construction with the source material bonded to the surface of a silver foil mounted in the recess of the plastic disc. This design yields excellent emission of alpha particles without window losses.

Contact one of our product specialists.



← [Back to partner](#)



Détection des radiations > Sources

Isotope Generator - Spectrum Techniques

This Cs-137/Ba-137m Isotope Generator is used to conduct experiment in schools and universities to demonstrate the properties of radioactive decay. Based on the original Union Carbide patented design, it offers exceptional performance combined with ease of use and safe operation.

Contact one of our product specialists.

If you prefer to continue your search for additional information, try this [link](#).



[← Back to partner](#)



Détection des radiations > Sources

Tube Sources - Spectrum Techniques

We now offer a selection of exempt quantity gamma sources encapsulated in standard size test tubes or rods for use with well type radiation detectors. These sources are exempt sources and of nominal activity. The isotope is deposited as a point source in the bottom of the tube and is then sealed with epoxy.

Contact one of our product specialists.



← [Back to partner](#)



Détection des radiations > Sources

Needle Sources - Spectrum Techniques

Needle sources are used to generate a point source of radiation inside cloud chambers for demonstrating alpha and beta radiation tracks. Three different types of isotopes are offered, a pure alpha emitter, a pure beta emitter and a combined alpha /beta emitter.

The sources are constructed by depositing a small, license exempt quantity of radioactive isotope onto the eye of a standard sewing needle which is mounted on a test tube stopper for insertion into the cloud chamber. The needle and stopper are placed into a test tube for protection during shipping and storage.

Contact one of our product specialists.



GESTION DES DÉCHETS ET DU RECYCLAGE





Partner **Else Nuclear**




ELSE NUCLEAR S.r.l. is an Italian OEM company specializing in advanced radiation-detection and environmental-monitoring systems for nuclear safety, industry and research.

Product offering

**LEM - LIQUID
EFFLUENT
MONITORING SYSTEM**



WDMS NT-VK



← **Back to partner**



Détection des radiations > Équipement de laboratoire

LEM - LIQUID EFFLUENT MONITORING SYSTEM

The LEM system is designed to sample the liquid effluents and to perform a spectroscopic analysis in Marinelli geometry.

LEM system is composed of the following main parts:

- Stainless steel frame
- Electrical and command board with touch-screen panel PC
- NaI(Tl) detector, 1 l Marinelli, 5 cm thick lead shielding well
- Self-priming pump (*)
- Software for system management, data acquisition and processing



The measurements are visualised in real time by the software, expressed in terms of specific/total activity through spectroscopic analysis.

LEM status and parameters are managed by the ELSE NUCLEAR software. The system provides also I/O contacts through dedicated connectors:

- Good functioning status output
- Alarm status output
- Pump activation input from customer PLC (*)
- Spare available I/O contacts (to be defined when necessary)

The software provides a calibration routine, to be used with a Marinelli calibration source (available as accessory).

A test program is also available, separate from the main application, to be used for maintenance or periodical quality controls.


(*) If not available in the sampling/hydraulic equipment which LEM shall be connected to



Détection des radiations > Équipement de laboratoire

WDMS NT-VK

The WDMS NT-VK system is designed to collect and monitor radioactive wastewaters, which can be released only after their radioactivity drops below a defined value. The main application of such a system is related to diagnostic and therapeutic procedures involving radioactive substances, and their partial elimination through the patient's metabolism.



The WDMS NT-VK system is designed to collect and monitor radioactive wastewaters, which can be released only after their radioactivity drops below a defined value. The main application of such a system is related to diagnostic and therapeutic procedures involving radioactive substances, and their partial elimination through the patient's metabolism.

The WDMS NT-VK main components are:

- Purification group: Imhoff tanks designed to collect the wastewaters and to separate liquid from solid waste
- Sorting group: pumps and conduits pouring the wastewaters in the decay tanks
- Decay group: tanks array where the wastewaters are poured and stocked until their radioactive level drops below a defined value
- Sampling system: valves and pumps used by the system to wash the sampling circuit and to sample the stocked wastewaters, allowing the measurement in Marinelli geometry
- Release group: pumps and conduits releasing the wastewaters in the sewers, if allowed by the monitoring results
- Safety groups and devices: level and pump sensors installed in all the system critical stages, stopping the wastewaters flow in case of detected anomaly, and safety flooding well which can collect and stock wastewaters potentially overflowing from any system group

The entire system is locally managed by a PLC, which is commanded by a remote management software installed on a PC.

Through the interactive synoptic interface of the software the operator can activate the system automatic cycles, set the measurement parameters, visualize the alarms and release archives, and monitor the system's status (filling levels, pump stages, measurements, alarms). Depending on the measurement results, and as defined by the procedures in force, the operator can also activate the monitored wastewaters release in the sewers.



Partner **BSI**



Baltic Scientific Instruments (BSI) is an OEM manufacturer based in Riga, Latvia, dedicated to the development and production of advanced spectrometric and detection equipment. With decades of experience and roots in the former Research Institute for Radioisotope Apparatus (RNIIRP), BSI provides cutting-edge technologies for nuclear power, environmental monitoring, security, medicine, and scientific research.

The company specializes in HPGe, Si, CdZnTe/CdTe, and scintillation detector systems, known for their accuracy, stability, and performance in demanding analytical environments.

Through continuous innovation, strict quality assurance (ISO 9001:2015), and strong international collaboration, BSI supports customers worldwide in achieving precise and reliable radiation measurement and analysis.

Product offering

**Free Release Monitor
HERCULES-FRM**



**Hybrid cooling for the
HPGe detector Nicole**





Free Release Monitor HERCULES-FRM

Application

Free Release Monitor HERCULES-FRM main working principle can be described the following way. Any loading mechanism like forklift or a crane gently puts measuring object to the movable platform on the front roller-based conveyor. Scales which are inbuilt in the front conveyor are determining weight of the measuring object and automatically transfers information for the analytical software. Further actions are performed totally automatically or in manual mode. Measuring chamber opens front doors and movable platform slides inside of measuring chamber. Doors are closed and measurement starts. The FRM is equipped with 16 plastic scintillators surrounding the measuring object from all sides. Plastic scintillators are connected to digital multichannel analysers located in the control box. Analytical and control software packages guarantee total remote control and data acquisition from all plastic scintillators simultaneously. All analytical performance of the FRM is set up previously by inputting all information concerning measuring object, geometry, sizes, weights, filling of containers, etc. in the software package. After measurement is finished, operator is alarmed, record is stored in the database and report can be printed any time. In order to change the measuring object, the FRM opens the front doors and slides the platform out for further unload by the forklift or a crane. In case the operator needs to measure specific object, it is possible to open back doors to load the measuring object from the back. The whole measuring chamber is securely covered with stainless-steel for easy decontamination.



Features

General

- Overall dimensions of the FRM: 5000x2300x2100mm (LxWxH)
- Overall weight of the FRM: 10000kg
- Operation temperature: +10...+35°C
- Ready to accommodate object with size 1.2m x 0.8m x 1.0m (L x W x H)
- Lead walls not less than 50mm thick
- Stain-less steel protection
- External and internal automatic conveyor
- Inbuilt scales

Plastic scintillators (HPGe detectors optional)

- 16 or 24 or more plastic scintillators equipped with PMTs
- Energy range from 100 to 3000 keV
- Detection limit for Co-60 is less than 300 Bq

Software

- Total activity calculation
- Visualization of measurement and diagnostic information
- Storage of measurement data, controlled parameters and fixed constants in internal memory
- Control of all mechanically movable mechanisms
- Control and reset of the FRM in case of failure of automation
- Self-diagnostics control
- Visual and audible alarm in case of failure or exceed of previously set levels
- Alarm in case of fixed level activity exceed for separately chosen radionuclide
- 3D visualization interface for measurement object monitoring and setting geometrical parameters in order to decrease measurement uncertainties
- Visualization of inhomogeneities in activity distribution
- Automatic change of measurement parameters depending on measurement geometry (Geometry must be set up preliminary)
- All software packages run under Windows operation system

Control box Control box of the FRM includes the following components:

- Set of MCAs for reading and transforming signals from PMTs of plastic scintillators
- Set of power supplies for different modules of the FRM
- Set of controllers to manage all components of automation process
- Indicators for operator
- Control panel with colour LCD display and touchscreen
- An emergency stop button is provided on the control box and the measuring chamber

← [Back to partner](#)



Détection des radiations > Équipement de laboratoire

Hybrid cooling for the HPGe detector Nicole

The NICOLE hybrid cooling system combines liquid nitrogen and electro-mechanical cooling. The merge of this two cooling systems provide detection unit non-stop operation for months without having liquid nitrogen to refill.

The NICOLE hybrid cooling system comprises Stirling-cycle cryocooler, cryocooler controller, Dewar vessel, pressure sensor and indicator, liquid nitrogen sensor and level monitor.



Application

Nicole hybrid cooling system for the HPGe detector allows you to keep your detector cold without filling with Liquid Nitrogen for months and years.

Features

One of the biggest advantages of Nicole hybrid cooling system is that it is extremely easy to perform maintenance and service. The user is given USB interface to get access to all parameters of the system. Majority of main parameters are displayed of the LCD display. And I case of maintenance, repair or replacement of the cooler is needed, it takes only 15 minutes to dismantle the cooling unit. It means the user can continue measurements by only using liquid nitrogen. It can be extremely important when routine measurements can't be terminated.



Partner Ludlum Measurements



Ludlum Measurements, Inc. conçoit et fabrique des instruments et des technologies de détection des rayonnements. Fondée en 1962, elle propose une large gamme d'instruments de détection de rayonnements, développés pour aider à surveiller la sécurité du personnel et de l'environnement. Les instruments sont utilisés dans des applications telles que la surveillance de routine du personnel et du matériel, la sécurité des frontières et les situations d'intervention d'urgence.

Product offering

HLM-6GP Laundry Monitor



Model 375-600 Digital Area Monitor for Small Areas



Model 2100-1 Sample Counter



Model 329-32 Laundry Contamination Monitor



Model 2100 Conveyorized Sample Counter



Model 375P-3500 Conveyor Monitor



Model 375P-1000 Outdoor Monitoring System



Model 375P-2000 Outdoor Monitoring System



HLM-22, HLM-3G Laundry Monitor





HLM-6GP Laundry Monitor

Présentation :

Le moniteur de blanchisserie HLM-6GP est conçu pour mesurer et libérer les vêtements tels que les combinaisons, les serviettes et les couvre-chaussures provenant de zones contrôlées. Doté de mesures automatiques et d'un convoyeur à grille en acier inoxydable, le HLM-6GP offre une détection précise et fiable de la contamination.



Les détecteurs, positionnés de manière à réduire les zones mortes, mesurent les matériaux sur le convoyeur en mouvement à travers le tunnel, au-dessus et en dessous. Un écran tactile placé à côté de l'utilisateur sur un bras mobile permet une utilisation pratique et facile pendant les mesures et le mode service.

Caractéristiques :

- Bande de mesure de 2 m x 1 m (6,6 ft x 3,3 ft)
- Distance réglable automatiquement entre le détecteur et le matériau
- Vitesse du convoyeur variable
- Équipé de roues verrouillables robustes
- Démarrage/arrêt automatique de la mesure
- Alimentation fournie par UPS pour le PC de mesure en cas de panne de courant
- Mini-UPS intégré pour la conservation des données de l'ordinateur de mesure en cas de panne de courant de courte durée
- Revêtement en acier inoxydable pour une décontamination facile
- Exportation des données et paramètres de mesure au format XML via USB
- Accès aux données de mesure historiques via une base de données intégrée
- Capacité réseau pour la surveillance et le contrôle à distance
- Accès à l'outil d'analyse des détecteurs Ludlum
- Plateau de chargement
- GP avec détecteurs proportionnels au gaz



Model 375-600 Digital Area Monitor for Small Areas

Présentation :

Le modèle 375-600 est un système de mesure gamma hautement intégré et très sensible qui combine tous les composants dans un boîtier pratique, ce qui rend son installation plus simple et moins coûteuse. Le détecteur interne est un scintillateur en plastique de 10,3 L (630 pouces cubes) blindé sur cinq côtés avec 0,32 cm (0,125 pouce) de plomb. Le contrôleur est le contrôleur numérique populaire modèle 375 de Ludlum, situé à une extrémité de l'armoire. Un stroboscope rouge est monté sur le dessus, ainsi qu'un gros bouton-poussoir d'acquiescement d'alarme de qualité industrielle. Le détecteur est accessible depuis un panneau amovible, et l'ensemble du système repose sur une plaque qui peut être boulonnée au sol.



Caractéristiques :

- Système de mesure intégré
- Détecteur à scintillateur interne
- Paramètres d'alarme programmables par l'utilisateur
- Alerte stroboscopique rouge très visible
- Alarmes sonores et visuelles
- Connectable en réseau, nécessite une option d'interface Ethernet ou Web
- Batterie de secours de 8 heures

← **Back to partner**



Détection des radiations > Équipement de laboratoire

Model 2100-1 Sample Counter

The Model 2100-1 manually operated sample counting system processes sample steel slugs to determine whether any radioactive impurities exist. The gamma radiation counting system is a table-mounted, fully integrated design that includes a gamma detector, sample tray, and controller.

The counting electronics incorporates two channels to distinguish between low and high energy gamma isotopes. All parameters, such as alarm point and count time are user-adjustable from the front panel LCD touch screen via a simple menu selection.

Measurement results for each sample are displayed on the backlit LCD. An Ethernet port reports all results and system status in real time for remote data logging and alarm annunciation. Visual and audible alarms are annunciated via the system's LCD and rear panel mounted buzzer respectively. A built-in relay provides a method for driving an external horn/strobe (available as an option).

One rear panel mounted USB port enables connection to either a keyboard or barcode reader device for the purpose of entering sample IDs.

Features

- High Sensitivity Gamma Detector
- Separate High & Low Gamma Energy Sampling
- User-Adjustable Parameters
- Color LCD Touch Screen
- Ethernet Connectivity
- Remote Alarm Output
- USB Ports for ID Input Devices





Model 329-32 Laundry Contamination Monitor

Présentation :

Le moniteur de contamination pour linge Ludlum modèle 329-32 est destiné à la surveillance automatique de la contamination alpha et bêta-gamma sur les vêtements ou autres articles légers présumés exempts de radioactivité, ou dans les limites de rejet ou de réutilisation. Une bande transporteuse à mailles métalliques entraînée par un moteur achemine les articles entre deux réseaux de détecteurs proportionnels à gaz. Une alarme sonore retentit lorsque la contamination dépasse le seuil d'alarme défini. Une rangée de LED située au-dessus du tapis indique la position approximative de l'alarme sur le convoyeur et informe l'opérateur de l'état de la machine. Un double écran LCD affiche les comptages et les conditions de fonctionnement actuelles, telles que la vitesse du convoyeur et le débit de gaz. Un clavier à 20 touches protégé par un code de sécurité permet également de modifier les seuils d'alarme, les paramètres de fonctionnement et d'autres informations système. L'ensemble du système est mobile et équipé de roulettes verrouillables pour empêcher tout déplacement indésirable du moniteur.



Caractéristiques :

- Système hautement automatisé
- Surveillance simultanée des surfaces supérieure et inférieure
- Roulettes verrouillables
- 32 canaux alpha et 32 canaux bêta-gamma
- Alarme sonore accompagnée de voyants LED visuels indiquant l'emplacement approximatif de la contamination
- Voyants LED indiquant l'état de fonctionnement en temps réel
- Tunnel de passage réglable jusqu'à une hauteur de 17,8 cm (7 pouces)



Model 2100 ConveyORIZED Sample Counter

The Model 2100 automated sample counting system processes sample steel slugs to determine whether any radioactive impurities exist. The gamma radiation counting system is a table-mounted, fully integrated design that includes a gamma detector, sample conveyor, and controller to facilitate automated processing.

Once the sample has been positioned on the conveyor, an infrared sensor automatically initiates conveyance of the sample into the lead shielded detector where it is counted for a predetermined time. Once the count is completed, the conveyor again advances until the sample drops into a discard container.

The counting electronics incorporates two channels to distinguish between low and high energy gamma isotopes. All parameters, such as alarm point and count time are user-adjustable from the front panel LCD touch screen via a simple menu selection.

Measurement results for each sample are displayed on the backlit LCD. An Ethernet port reports all results and system status in real time for remote data logging and alarm annunciation. Visual and audible alarms are annunciated via the system's LCD and rear panel mounted buzzer respectively. A built-in relay provides a method for driving an external horn/strobe (available as an option).

One rear panel mounted USB port enables connection to either a keyboard or barcode reader device for the purpose of entering sample IDs.





Model 375P-3500 Conveyor Monitor

Présentation :

Le moniteur pour convoyeur modèle 375P-3500 est un système de détection des rayonnements à usage intensif conçu pour les applications sur convoyeurs à bande dans les environnements industriels (tels que le recyclage de ferraille, le traitement des déchets ou les installations de flux de matériaux). Il combine un grand détecteur à scintillation en plastique avec un système de contrôle robuste pour surveiller la contamination radioactive des matériaux transportés sur un convoyeur.



Caractéristiques :


- Détecteur à scintillation en plastique de grand volume (57,4 L / 3 500 pouces cubes) pour une haute sensibilité dans la surveillance des convoyeurs.
- Contrôleur robuste logé dans un boîtier NEMA 4X avec fenêtre de visualisation transparente, conçu pour les environnements industriels.
- Relais secteur intégré pour arrêter le convoyeur en cas d'alarme, réglages d'alarme ajustables par l'utilisateur et capacité réseau/télécommande.
- Batterie de secours de 24 heures (en l'absence d'alarme) pour assurer une surveillance continue en cas de fluctuations de courant.
- Boîtier de détecteur étanche et blindé au plomb, adapté aux environnements industriels difficiles tels que les parcs à ferraille ou les usines de recyclage.



Model 375P-1000 Outdoor Monitoring System

Présentation :

Le modèle 375P-1000 est un contrôleur numérique modèle 375 couplé à deux détecteurs à scintillateur en plastique blindés de 7866 cm³ (480 pouces cubes). Les détecteurs sont logés dans des boîtiers étanches adaptés à une utilisation en extérieur. Le contrôleur modèle 375 n'est pas étanche et doit être installé à l'intérieur ou dans un boîtier environnemental (disponible séparément, voir Options). Cette solution économique offre un système simple, facile à utiliser et à entretenir.



Caractéristiques :

- Vérification de la contamination de surface à l'entrée/sortie des installations
- Contrôleur numérique abordable
- Détecteurs à scintillateur en plastique blindés et résistants aux intempéries
- Alarmes programmables
- Connectable en réseau (nécessite l'option Ethernet ou interface Web)
- Batterie de secours



Model 375P-2000 Outdoor Monitoring System

Présentation :

Le modèle 375P-2000 est un contrôleur numérique modèle 375 couplé à quatre détecteurs à scintillateur plastique blindés de 7866 cm³ (480 pouces cubes). Les détecteurs sont logés dans des boîtiers étanches adaptés à une utilisation en extérieur. Le contrôleur modèle 375P n'est pas étanche et doit être installé à l'intérieur ou dans un boîtier environnemental (disponible séparément, voir Options). Cette solution économique offre un système simple, facile à utiliser et à entretenir.



Caractéristiques :

- Vérification de la contamination de surface à l'entrée/sortie des installations
Contrôleur numérique abordable
- Détecteurs à scintillateur en plastique blindés et résistants aux intempéries
- Alarmes programmables
- Connectable en réseau (nécessite l'option Ethernet ou interface Web)
- Batterie de secours



HLM-22, HLM-3G Laundry Monitor

Présentation :

Le moniteur de blanchisserie HLM-22/HLM-3G est conçu pour mesurer et libérer les vêtements tels que les combinaisons, les serviettes et les couvre-chaussures provenant de zones contrôlées. Doté de mesures automatiques et d'un convoyeur à grille en acier inoxydable, le HLM-22/HLM-3G offre une détection précise et fiable de la contamination.



Les détecteurs, positionnés de manière à réduire les zones mortes, mesurent les matériaux sur le convoyeur en mouvement à travers le tunnel, au-dessus et en dessous. Un écran tactile placé à côté de l'utilisateur sur un bras mobile permet une utilisation pratique et facile pendant les mesures et le mode service.

Caractéristiques :

- Différentes versions possibles en fonction des besoins
- Distance réglable automatiquement entre le détecteur et le matériau
- Vitesse du convoyeur variable
- Équipé de roues verrouillables robustes
- Démarrage/arrêt automatique de la mesure
- Alimentation fournie par UPS pour la mesure en cas de coupure de courant
- Revêtement en acier inoxydable pour une décontamination facile
- Exportation des données de mesure/paramètres au format XML via USB
- Accès aux données de mesure historiques via une base de données intégrée
- Capacité réseau pour la surveillance et le contrôle à distance
- Accès à l'outil d'analyse du détecteur
- Plateau de chargement



Partner **Helgeson Scientific Services (HSS)**




Helgeson Scientific Services (HSS) conçoit et fabrique des systèmes avancés de surveillance des radiations axés sur la sécurité du personnel, la protection des installations et le contrôle des déchets. Sa gamme comprend des moniteurs corporels, des systèmes de détection par portique et des solutions de gestion des déchets, tous développés pour garantir la manipulation sûre des matières radiologiques dans des environnements critiques.

Product offering

HS-DRUM - Waste characterization system for drums



HS-FRM - Free release monitor for drums, containers and big bags



HS-OTM - Object and tool monitors for objects monitoring



Complete storage and treatment plant for NORM wastes



Descaling system for NORM waste



Soil segregation unit





HS-DRUM - Waste characterization system for drums

Présentation :

Le HS-DRUM est un système spécialisé de balayage et de mesure conçu pour caractériser les déchets contenus dans des fûts, en particulier dans le cadre de la gestion des déchets radioactifs ou nucléaires. Il est conçu pour évaluer la répartition de l'activité à l'intérieur des fûts de déchets, permettant ainsi aux opérateurs de déterminer la répartition spatiale de la radioactivité dans la matrice des déchets.

Caractéristiques :

- Configuration multi-détecteurs - Équipé de détecteurs HPGe et NaI pour une spectroscopie gamma précise et d'un dosimètre pour une évaluation complète des rayonnements.
- Système de balayage à tambour rotatif - Utilise une table rotative motorisée et un convoyeur à rouleaux pour un balayage précis et uniforme des fûts de 180 à 400 litres.
- Collimateurs en plomb et mannequins d'étalonnage - Intègre des collimateurs en plomb pour une meilleure résolution spatiale et des fûts d'étalonnage standardisés pour la vérification de la précision du système.
- Logiciel d'analyse avancé - Comprend des modules pour l'analyse spectrale, l'étalonnage, l'assurance qualité et la génération de rapports, avec un étalonnage théorique basé sur Monte Carlo en option.





HS-FRM - Free release monitor for drums, containers and big bags

Présentation :

Le HS-FRM est un moniteur à libération libre destiné à être utilisé avec différents types de déchets tels que des fûts, des conteneurs et des big bags.

Il s'agit d'une chambre protégée contre l'influence des rayonnements naturels externes et composée de détecteurs situés dans chacun des 4 panneaux latéraux, au plafond et au sol.

Cela permet d'effectuer une détection et une quantification rapides et efficaces des rayonnements émis par les déchets présents à l'intérieur de la chambre.

Caractéristiques :

- Couverture complète par les détecteurs - Équipé de détecteurs sur tous les côtés, y compris en haut et en bas, assurant une surveillance 3D complète des matières radioactives contenues dans les fûts ou les conteneurs.
- Blindage en plomb épais - Dispose d'un blindage en plomb épais sur toutes les parois, le sol et le plafond afin de minimiser les interférences de fond et d'améliorer la précision des mesures.
- Détection rapide et sensible - Permet un balayage rapide avec une activité minimale détectable (MDA) très faible, offrant des résultats précis en quelques minutes seulement.
- Logiciel d'analyse avancé - Comprend un logiciel intelligent pour l'identification des isotopes, la correction du fond, la gestion de l'étalonnage et la création de rapports détaillés.





HS-OTM - Object and tool monitors for objects monitoring

Présentation :

Le HS-OTM est un système de surveillance conçu pour détecter et mesurer les rayonnements gamma (et éventuellement bêta/gamma) dans les objets et les outils susceptibles d'avoir été exposés. Il convient au contrôle de tout type d'objet, des plus petits aux plus grands (comme les fûts ou les big bags). Le système est configurable en termes de nombre de détecteurs, de blindage et de taille de la chambre, ce qui permet de l'adapter à différents flux de travail. Il est livré avec un logiciel intégré pour le contrôle, l'alarme, l'étalonnage et le traitement des données.



Caractéristiques :

- Configuration multi-détecteurs - Équipé de jusqu'à 10 détecteurs gamma ou bêta/gamma pour une efficacité de détection élevée et une surveillance complète des objets.
- Chambre et blindage personnalisables - Taille de la chambre et épaisseur du blindage en plomb réglables pour s'adapter à différents types d'objets et garantir des mesures précises.
- Système de contrôle et de sécurité intelligent - Comprend une interface à écran tactile, une synchronisation automatique des mesures, des capteurs de détection de présence et des alarmes visuelles/sonores.
- Logiciel avancé de gestion des données - Comprend des modules pour l'étalonnage, la vérification, l'enregistrement des données, le fonctionnement à distance et la génération de rapports avec des limites de détection conformes à la norme ISO.



Complete storage and treatment plant for NORM wastes

Présentation :

L'usine complète de stockage et de traitement des déchets NORM est une installation entièrement intégrée conçue pour la manipulation, le traitement et le stockage en toute sécurité des matières radioactives naturelles (NORM). Développée par Helgeson Scientific Services, cette usine offre une solution complète pour les industries telles que le pétrole et le gaz, l'exploitation minière et la fabrication, où les déchets NORM sont couramment générés.



Caractéristiques :

- Options de traitement complètes — Comprend plusieurs unités de traitement telles que le détartrage, la centrifugation des boues, l'incinération et la solidification pour traiter différentes formes de déchets NORM.
- Stockage et élimination intégrés — Outre le traitement des déchets, l'usine est conçue pour le stockage et l'élimination finale en toute sécurité des matières NORM.
- Conception d'usine sur mesure par Helgeson — L'installation est conçue et construite par Helgeson Scientific Services afin de répondre aux exigences réglementaires, de sécurité et de manipulation des matières radioactives naturelles.
- Gestion des déchets de bout en bout — De la production (industrielle, minière, pétrolière et gazière, etc.) au traitement et au stockage, l'usine prend en charge l'ensemble de la chaîne de processus pour la gestion des déchets NORM.



Descaling system for NORM waste

Présentation :

Le système de détartrage pour déchets NORM est conçu pour éliminer les dépôts radioactifs des tuyaux et des équipements métalliques généralement utilisés dans les opérations pétrolières et gazières. Il utilise de l'eau à haute pression pour nettoyer les surfaces intérieures et extérieures des tubes et autres pièces métalliques. Le système est partiellement automatisé (pour la décontamination des tuyaux) et comprend également une cabine de nettoyage manuel pour les équipements métalliques plus grands ou complexes. L'unité est transportable pour les campagnes sur site, ce qui réduit au minimum la nécessité de déplacer les gros éléments contaminés vers des installations de nettoyage centralisées.



Caractéristiques :

- Nettoyage à l'eau à haute pression – Utilise des jets d'eau pouvant atteindre 1 400 bars pour éliminer efficacement les dépôts radioactifs des surfaces internes et externes des tuyaux.
- Fonctionnement automatisé et manuel – Comprend une cabine de nettoyage entièrement automatisée pour les tubes et une cabine manuelle équipée d'un pistolet à haute pression pour les équipements de grande taille ou de forme irrégulière.
- Système de traitement de l'eau en circuit fermé – Recycle et traite l'eau usée sans additifs chimiques, transformant les déchets en une matrice solide pour une élimination sûre.
- Conception portable et personnalisable – Conçu pour une utilisation sur site avec une capacité réglable pour s'adapter à différents diamètres et longueurs de tuyaux selon les besoins.



Soil segregation unit

Présentation :

L'unité de tri des sols de Helgeson est un système compact et transportable conçu pour analyser, classer et trier les sols contaminés en fonction de leur teneur en matières radioactives. Installée dans un conteneur de 6 mètres, cette unité est idéale pour les projets de décontamination et d'assainissement sur site dans des secteurs tels que le nucléaire, l'exploitation minière et la gestion environnementale.



Elle mesure automatiquement les niveaux de rayonnement dans les échantillons de sol et les sépare en catégories de déchets appropriées (propres, à faible niveau ou contaminés), optimisant ainsi le traitement des déchets et minimisant les coûts d'élimination. Le système prend en charge plusieurs types de détecteurs et comprend des fonctions de surveillance de la sécurité pour un fonctionnement fiable et efficace sur le terrain.

Caractéristiques :

- Options de détection flexibles — Prend en charge plusieurs types de détecteurs (scintillateurs en plastique, scintillateurs inorganiques et HPGe) selon que vous surveillez les rayonnements alpha, bêta ou gamma.
- Armoire d'analyse modulaire — Construite dans un conteneur de 20 pieds pour faciliter le transport ; peut être configurée avec jusqu'à deux « trains d'analyse » pour doubler le débit.
- Criblage et tri automatisés des sols — Le système trie automatiquement les sols/matériaux dans de grands sacs en fonction de leur niveau de contamination, ce qui permet d'accélérer les processus de décontamination ou de gestion des déchets.
- Sécurité opérationnelle et surveillance — Équipé d'un système de surveillance des aérosols (pour les émetteurs alpha et bêta en suspension dans l'air) et d'un système de vidéosurveillance pour observer les processus internes, il est conçu pour être facile à installer et à utiliser.



Partner **SDEC France**



SDEC France est un fabricant spécialisé d'équipements de surveillance environnementale et de laboratoire. Il propose des solutions complètes pour la gestion des déchets et du recyclage, la surveillance environnementale et les applications de laboratoire. Forte de plus de 30 ans d'expérience, l'entreprise conçoit et fabrique des instruments de haute qualité pour les professionnels des sciences de l'environnement, de l'agronomie et de la radioprotection.

Product offering

Isokinetic Sampling Probes - SDEC



Carbon 14 Sampler with 2 Vials - SDEC



Carbon 14 Sampler with 4 Vials - SDEC



Tritium Sampler with 2 Vials - SDEC



← **Back to partner**



Détection des radiations > Gestion des déchets et du recyclage

Isokinetic Sampling Probes - SDEC

Les Sondes de Prélèvement Isocinétique (SDEC) sont reconnues dans l'industrie nucléaire et adaptées pour tout type de prélèvement en monopoint ou en multipoints.



Caractéristiques des sondes d'échantillonnage isocinétique :

- qualité et durabilité
- haut niveau de finition
- fabrication sur mesure
- le meilleur prix

En savoir plus sur les sondes d'échantillonnage isocinétique sur le site Web du SDEC

← Back to partner



Détection des radiations > Gestion des déchets et du recyclage

Carbon 14 Sampler with 2 Vials - SDEC

L'échantillonneur Carbon 14 avec 2 flacons (SDEC) a été conçu pour capturer le gaz CARBONE (CO₂ ou CO). Il peut être équipé d'un système de refroidissement qui évitera toute perte d'échantillon due à l'évaporation dans les biberons.

Caractéristiques de l'échantillonneur Carbon 14 avec 2 flacons :

- conforme à la norme nf m60-812-
- excellente efficacité de piégeage (près de 99%)
- système de refroidissement pour augmenter la
- longueur d'échantillonnage (option)
- bon prix
- évolution constante du produit
- facile à utiliser
- connectable à toutes les lignes d'échantillonnage

En savoir plus sur l'échantillonneur Carbon 14 avec 2 flacons sur le site Web SDEC



← [Back to partner](#)



Détection des radiations > Gestion des déchets et du recyclage

Carbon 14 Sampler with 4 Vials - SDEC

Le Carbon 14 Sampler with 4 Vials (SDEC) apporte des solutions originales dans l'exploitation des systèmes d'échantillonnage du gaz carbonique et de l'eau carbonée. Cet échantillonneur est principalement utilisé pour la détection des rejets de cheminée et le dégazage des déchets carbonés.



Caractéristiques de l'échantillonneur Carbon 14 avec 4 flacons :

- excellente efficacité de piégeage (près de 99%)
- système de refroidissement pour augmenter la longueur d'échantillonnage (option)
- bon prix
- évolution constante du produit
- facile à utiliser
- connectable à toutes les lignes d'échantillonnage
- conforme à la norme NF M60-812-1

En savoir plus sur l'échantillonneur Carbon 14 avec 4 flacons sur le site Web du SDEC

← [Back to partner](#)



Détection des radiations > Gestion des déchets et du recyclage

Tritium Sampler with 2 Vials - SDEC

L'Échantillonneur Tritium à 2 Flacons (SDEC) propose des solutions originales pour le fonctionnement des systèmes de collecte du tritium gazeux et de l'eau tritiée. Ce système de collecte est principalement utilisé pour la détection des déchets de cheminée et le dégazage des déchets tritiés.



Caractéristiques de l'échantillonneur de tritium avec 2 bouteilles :

- bonne efficacité de pédalage
- système de refroidissement pour augmenter la longueur d'échantillonnage (option)
- bon prix
- évolution constante du produit
- très robuste
- facile à utiliser
- peut être connecté à toutes les lignes d'échantillonnage

En savoir plus sur l'échantillonneur de tritium avec 2 flacons sur le site Web du SDEC




Partner **Bertin Instruments**



Bertin Instruments est un fournisseur mondial de solutions avancées de détection des radiations et de surveillance environnementale, spécialisé dans les détecteurs portables, les dosimètres électroniques personnels, les systèmes de surveillance environnementale et les technologies de gestion des déchets et du recyclage. Ses instruments sont conçus pour répondre aux exigences rigoureuses des installations nucléaires, des équipes d'intervention d'urgence et des agences environnementales.

Product offering

**Coriolis Consumables
- Bertin Instruments**





Coriolis Consommables - Bertin Instruments

Les consommables Coriolis font partie de la technologie cyclonique : la séparation des particules en suspension dans le flux d'air est due au débit d'air, à la géométrie d'entrée d'air, à la conception des cônes et au liquide de collecte (tensioactif en faible concentration).



Vidéo de présentation

Consommables

- cônes & capuchons : Les cônes et capuchons sont conçus spécifiquement pour être utilisés avec le Coriolis μ
- doses de liquide de collecte
- Consommables LTM : liquide de collecte en flacon et kit tubulure
- entrée d'air : en fonction de vos recherches vous pouvez adapter la prise d'air
- prise d'air standard : prise d'air compatible avec tous les Coriolis pour échantillonnage classique
- Prise d'air LTM : dédiée à la collecte de suivi longue durée (uniquement compatible avec la plateforme LTM)
- Raccord 25 mm LTM : conçu pour proposer une fixation de tuyau (enceinte d'essai, espace confiné ...)

Avantages des consommables Coriolis

- cônes dédiés pour effectuer une collecte à haute efficacité
- adaptateur pour se connecter à n'importe quel connecteur de 25 mm de diamètre
- installation facile avec une dose de liquide de collecte calibrée de 15 ml
- collecte de liquide compatible avec toute expérience en aval
- cônes disponibles stériles et non stériles

Veillez contacter notre spécialiste produits.